

SANDER VAN VUGT

# Cert Guide

Learn, prepare, and practice for exam success



## Red Hat RHCE®/RHCSA™ 7

Red Hat Enterprise Linux 7  
(EX200 and EX300)



PEARSON IT  
CERTIFICATION

FREE SAMPLE CHAPTER



SHARE WITH OTHERS

# **Red Hat® RHCSA™/RHCE® 7 Cert Guide: Red Hat Enterprise Linux 7 (EX200 and EX300)**

Sander van Vugt

**PEARSON**

800 East 96th Street  
Indianapolis, Indiana 46240 USA

<https://t.me/learningnets>

# Red Hat RHCSA/RHCE 7 Cert Guide: Red Hat Enterprise Linux 7 (EX200 and EX300)

Sander van Vugt

Copyright© 2016 Pearson Certification

Published by:

Pearson IT Certification  
800 East 96th Street  
Indianapolis, IN 46240 USA

All rights reserved. No part of this book may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, without written permission from the publisher, except for the inclusion of brief quotations in a review.

Printed in the United States of America 1 2 3 4 5 6 7 8 9 0

First Printing August 2015

Library of Congress Control Number: 2015942167

ISBN-13: 978-0-7897-5405-9

ISBN-10: 0-7897-5405-3

## Warning and Disclaimer

This book is designed to provide information about Red Hat RHCSA and Red Hat RHCE certification. Every effort has been made to make this book as complete and as accurate as possible, but no warranty or fitness is implied.

## Trademarks

All terms mentioned in this book that are known to be trademarks or service marks have been appropriately capitalized. Pearson IT Certification cannot attest to the accuracy of this information. Use of a term in this book should not be regarded as affecting the validity of any trademark or service mark.

## Warning and Disclaimer

Every effort has been made to make this book as complete and as accurate as possible, but no warranty or fitness is implied. The information provided is on an “as is” basis. The author and the publisher shall have neither liability nor responsibility to any person or entity with respect to any loss or damages arising from the information contained in this book or from the use of the companion website, DVD, or programs accompanying it.

## Special Sales

For information about buying this title in bulk quantities, or for special sales opportunities (which may include electronic versions; custom cover designs; and content particular to your business, training goals, marketing focus, or branding interests), please contact our corporate sales department at [corpsales@pearsoned.com](mailto:corpsales@pearsoned.com) or (800) 382-3419.

For government sales inquiries, please contact [governmentsales@pearsoned.com](mailto:governmentsales@pearsoned.com).

For questions about sales outside the U.S., please contact [international@pearsoned.com](mailto:international@pearsoned.com).

## Publisher

Paul Boger

## Associate Publisher

David Dusthimer

## Acquisitions Editor

Denise Lincoln

## Production Manager

Sandra Schroeder

## Development Editor

Ellie Bru

## Project Editor

Mandie Frank

## Copy Editor

Keith Cline

## Technical Editors

Frederik Vos

Ross Brunson

William “Bo” Rothwell

## Publishing Coordinator

Vanessa Evans

## Designer

Alan Clements

## Composition

Nonie Ratcliff

## Senior Indexer

Cheryl Lenser

## Proofreader

The Wordsmithery LLC

## About the Author

**Sander van Vugt** is an independent Linux trainer, author, and consultant living in the Netherlands. Sander is the author of the best-selling *Red Hat Certified System Administrator (RHCSA) Complete Video Course* and also of the *Red Hat Certified Engineer (RHCE) Complete Video Course*. He has also written numerous books about different Linux-related topics, and many articles for Linux publications around the world. Sander has been teaching Red Hat, SUSE, and LPI Linux classes since 1994. As a consultant, he specializes in Linux high-availability solutions and performance optimization. You can find more information about Sander on his website at <http://www.sandervanvugt.com>.

For more information about RHAT certification and additional resources, visit the author's Red Hat Certification page at <http://www.rhatcert.com/>.

## About the Technical Reviewers

**Frederik Vos** is a senior technical trainer in Linux training and also in several virtualization solutions, such as VMware vSphere, XenServer, and KVM. For the past 8 years Frederik has working for XTG in Gouda, a training center specializing in virtualization solutions and Linux, as a teacher and Linux evangelist, responsible for the Linux portfolio at XTG.

He has specialized in data center infrastructures (several Linux distributions), hypervisors, networking, and storage solutions and cloud computing (Cloudstack, Cloudplatform, and OpenStack). He has a lot of knowledge as a teacher and also real-world experience as a system engineer and as a long-time (1997) Linux user.

**Ross Brunson** has more than 20 years of experience as a Linux and open source trainer, training manager, and technologist and is author of the popular LPIC-1 Exam Cram (Que Publishing), as well as the Pearson LPIC-1 Certification Guide.

Ross recently spent almost 5 years as the director of member services for the Linux Professional Institute, building the member program, conducting dozens of Train-the-Trainer sessions, and providing support for the worldwide Master Affiliate network spanning 100+ countries.

Ross holds a number of key IT certifications and is also author of several successful technical books, dozens of technical courses for major organizations (including the first LPI Certification Bootcamp). He is also skilled at both contributing to and building community around IT products.

He lives in Paradise Valley, Montana, with his family and enjoys traveling far and wide, winter sports, and photography.

**William “Bo” Rothwell**, at the impressionable age of 14, crossed paths with a TRS-80 Micro Computer System (affectionately known as a Trash 80). Soon after, the adults responsible for Bo made the mistake of leaving him alone with the TSR-80. He immediately dismantled it and held his first computer class, showing his friends what made this “computer thing” work.

Since this experience, Bo’s passion for understanding how computers work and sharing this knowledge with others has resulted in a rewarding career in IT training. His experience includes Linux, UNIX, and programming languages such as Perl, Python, Tcl, and Bash. Bo owns several IT certifications, including earning his original RHCE in 2003. He is a former RHCI (Red Hat Certified Instructor) and the founder and president of One Course Source, an IT training organization.

## Dedication

*This book is dedicated to my family: Florence, Franck, and Alex. Together we've made great accomplishments over the past year.*

## Acknowledgments

This book could not have been written without the help of all the people who contributed to it. To start, I want to thank the people at Pearson, Denise Lincoln and Ellie Bru in particular. We've worked a lot together over the past year, and this book is another milestone on our road to success!

Next I want to thank my technical proofreaders. What has made this book special is that the first round of technical proofreading was completely done by volunteers. We started with 10 volunteers, but just 1 made it all the way to the end. Many thanks to Giles, the man behind the great and very useful website certdepot.net, the only one who reviewed all the chapters.

I also want to thank Jaques Weewer, Rob Morkink, and all the other volunteer technical reviewers. You made many suggestions without which the book would not have the high quality that it has right now.

## **We Want to Hear from You!**

As the reader of this book, you are our most important critic and commentator. We value your opinion and want to know what we're doing right, what we could do better, what areas you'd like to see us publish in, and any other words of wisdom you're willing to pass our way.

We welcome your comments. You can email or write to let us know what you did or didn't like about this book[md]as well as what we can do to make our books better.

Please note that we cannot help you with technical problems related to the topic of this book.

When you write, please be sure to include this book's title and author as well as your name and email address. We will carefully review your comments and share them with the author and editors who worked on the book.

Email: [feedback@pearsonitcertification.com](mailto:feedback@pearsonitcertification.com)

Mail: Pearson IT Certification  
ATTN: Reader Feedback  
800 East 96th Street  
Indianapolis, IN 46240 USA

## **Reader Services**

Visit our website and register this book at [www.pearsonitcertification.com/register](http://www.pearsonitcertification.com/register) for convenient access to any updates, downloads, or errata that might be available for this book.

# Contents at a Glance

Introduction xxxix

## Part 1: RHCSA 3

- CHAPTER 1** Installing Red Hat Enterprise Linux Server 7 7
- CHAPTER 2** Using Essential Tools 33
- CHAPTER 3** Essential File Management Tools 57
- CHAPTER 4** Working with Text Files 85
- CHAPTER 5** Connecting to Red Hat Enterprise Linux 7 103
- CHAPTER 6** User and Group Management 123
- CHAPTER 7** Configuring Permissions 151
- CHAPTER 8** Configuring Networking 177
- CHAPTER 9** Managing Processes 205
- CHAPTER 10** Working with Virtual Machines 225
- CHAPTER 11** Managing Software 249
- CHAPTER 12** Scheduling Tasks 281
- CHAPTER 13** Configuring Logging 295
- CHAPTER 14** Managing Partitions 319
- CHAPTER 15** Managing LVM Logical Volumes 349
- CHAPTER 16** Basic Kernel Management 369
- CHAPTER 17** Configuring a Basic Apache Server 389
- CHAPTER 18** Managing and Understanding the Boot Procedure 405
- CHAPTER 19** Troubleshooting the Boot Procedure 429
- CHAPTER 20** Using Kickstart 451
- CHAPTER 21** Managing SELinux 473
- CHAPTER 22** Configuring a Firewall 499
- CHAPTER 23** Configuring Remote Mounts and FTP 515
- CHAPTER 24** Configuring Time Services 539

**Part 2: RHCE 555****CHAPTER 25** Configuring External Authentication and Authorization 557**CHAPTER 26** Configuring an iSCSI SAN 577**CHAPTER 27** System Performance Reporting 607**CHAPTER 28** System Optimization Basics 627**CHAPTER 29** Configuring Advanced Log Features 641**CHAPTER 30** Configuring Routing and Advanced Networking 655**CHAPTER 31** An Introduction to Bash Shell Scripting 683**CHAPTER 32** Advanced Firewall Configuration 701**CHAPTER 33** Managing Advanced Apache Services 719**CHAPTER 34** Configuring DNS 741**CHAPTER 35** Configuring a MariaDB Database 759**CHAPTER 36** Configuring NFS 781**CHAPTER 37** Configuring Samba File Services 801**CHAPTER 38** Setting Up an SMTP Server 825**CHAPTER 39** Configuring SSH 845**CHAPTER 40** Managing Time Synchronization 859**CHAPTER 41** Final Preparation 875**CHAPTER 42** Theoretical Pre-Assessment Exams 881**RHCSA Practice Exam A** 887**RHCSA Practice Exam B** 891**RHCE Practice Exam A** 895**RHCE Practice Exam B** 899**Index** 902**Elements on DVD and Companion Website****APPENDIX A** Answers to the “Do I Know This Already” Quizzes and “Review Questions”**APPENDIX B** Memory Tables**APPENDIX C** Memory Tables Answer Key**APPENDIX D** Setting Up Identity Management**APPENDIX E** Study Planner

Glossary

# Contents

**Introduction xxxix**

## **Part 1: RHCSA 3**

### **Chapter 1 Installing Red Hat Enterprise Linux Server 7**

“Do I Know This Already?” Quiz 7

Foundation Topics 11

Preparing to Install Red Hat Enterprise Linux 11

    What Is Red Hat Enterprise Linux 7 Server? 11

    Getting the Software 12

    Using CentOS 12

    Other Distributions 13

    Understanding Access to Repositories 13

    Understanding Red Hat Enterprise Linux 7 Server Variants  
    and Add-Ons 14

    Setup Requirements 15

    Course Environment Description 16

Performing a Manual Installation 17

Summary 29

Exam Preparation Tasks 29

    Review All Key Topics 29

    Define Key Terms 30

Review Questions 30

End-of-Chapter Labs 30

    Lab 1.1 31

### **Chapter 2 Using Essential Tools 33**

“Do I Know This Already?” Quiz 33

Foundation Topics 36

Basic Shell Skills 36

    Executing Commands 36

    I/O Redirection 37

    Using Pipes 39

    History 40

    Bash Completion 42

- Editing Files with vim 42
- Understanding the Shell Environment 45
  - Understanding Variables 45
  - Environment Configuration Files 46
  - Using /etc/motd and /etc/issue 46
- Finding Help 47
  - Using --help 48
  - Using man 48
  - Finding the Right man Page 48
  - Updating mandb 50
  - Using info 51
  - Using /usr/share/doc Documentation Files 53
- Summary 53
- Exam Prep Tasks 53
  - Review All Key Topics 53
  - Complete Tables and Lists from Memory 53
  - Define Key Terms 54
- Review Questions 54
- End-of-Chapter Labs 54
  - Lab 2.1 55
- Chapter 3 Essential File Management Tools 57**
  - Do I Know This Already Quiz 57
  - Foundation Topics 60
  - Working with the File System Hierarchy 60
    - Defining the File System Hierarchy 60
    - Understanding Mounts 61
  - Managing Files 66
    - Working with Wildcards 67
    - Managing and Working with Directories 67
    - Working with Absolute and Relative Pathnames 68
    - Listing Files and Directories 69
    - Copying Files 70
    - Moving Files 71
    - Deleting Files 71

Using Links	73
Understanding Hard Links	73
Understanding Symbolic Links	74
Creating Links	74
Removing Links	75
Working with Archives and Compressed Files	76
Managing Archives with tar	77
Using Compression	78
Summary	80
Exam Preparation Tasks	80
Review All Key Topics	80
Complete Tables and Lists from Memory	81
Define Key Terms	81
Review Questions	81
End-of-Chapter Labs	82
Lab 3.1	82
<b>Chapter 4 Working with Text Files</b>	<b>85</b>
“Do I Know This Already?” Quiz	85
Foundation Topics	88
Using Common Text File-Related Tools	88
Doing More with Less	88
Showing File Contents with cat	89
Displaying the First or Last Lines of a File with head and tail	90
Filtering Specific Columns with cut	91
Sorting File Contents and Output with sort	91
Counting Lines, Words, and Characters with wc	93
A Primer to Using Regular Expressions	93
Using Line Anchors	94
Using Escaping in Regular Expressions	95
Using Wildcards and Multipliers	95
Using grep to Analyze Text	96
Working with Other Useful Text Processing Utilities	97
Summary	99
Exam Preparation Tasks	99

	Review All Key Topics	99
	Complete Tables and Lists from Memory	99
	Define Key Terms	100
	Review Questions	100
	End-of-Chapter Labs	100
	Lab 4.1	100
<b>Chapter 5</b>	<b>Connecting to Red Hat Enterprise Linux 7</b>	<b>103</b>
	“Do I Know This Already?” Quiz	103
	Foundation Topics	106
	Working on Local Consoles	106
	Logging In to a Local Console	106
	Switching Between Terminals in a Graphical Environment	107
	Working with Multiple Terminals in a Nongraphical Environment	108
	Understanding Pseudo Terminal Devices	109
	Booting, Rebooting, and Shutting Down Systems	110
	Using SSH and Related Utilities	112
	Accessing Remote Systems Using SSH	112
	Using Graphical Applications in an SSH Environment	114
	Securely Transferring Files Between Systems	115
	Configuring Key-Based Authentication for SSH	116
	Using Passphrases or Not?	117
	Using the screen Command	118
	Summary	119
	Exam Preparation Tasks	120
	Review All Key Topics	120
	Define Key Terms	120
	Review Questions	120
	End-of-Chapter Labs	121
	Lab 5.1	121
<b>Chapter 6</b>	<b>User and Group Management</b>	<b>123</b>
	“Do I Know This Already?” Quiz	123
	Foundation Topics	126

Different User Types	126
Users on Linux	126
Working as Root	126
Using su	127
sudo	128
PolicyKit	128
Managing User Accounts	129
System and Normal Accounts	129
Creating Users	132
Managing User Properties	134
Configuration Files for User Management Defaults	134
Managing Password Properties	135
Creating a User Environment	136
Creating and Managing Group Accounts	137
Understanding Linux Groups	137
Creating Groups	138
Managing Group Properties	139
Logging In Through an External Authentication Service	140
Understanding LDAP	140
Making the Authentication Platform Available	142
Configuring RHEL 7 for LDAP Authentication	142
Managing nslcd	143
Managing sssd	144
Summary	146
Exam Preparation Tasks	146
Review All Key Topics	146
Complete Tables and Lists from Memory	147
Define Key Terms	147
Review Questions	147
End-of-Chapter Labs	148
Lab 6.1	148
Lab 6.2	148

**Chapter 7 Configuring Permissions 151**

“Do I Know This Already?” Quiz	151
Foundation Topics	155
Managing File Ownership	155
Displaying Ownership	155
Changing User Ownership	156
Changing Group Ownership	156
Understanding Default Ownership	157
Managing Basic Permissions	158
Understanding Read, Write, and Execute Permissions	158
Applying Read, Write, and Execute Permissions	159
Managing Advanced Permissions	161
Understanding Advanced Permissions	161
Applying Advanced Permissions	164
Managing ACLs	165
Understanding ACLs	166
Preparing Your File System for ACLs	166
Changing and Viewing ACL Settings with setfacl and getfacl	166
Working with Default ACLs	168
Setting Default Permissions with umask	169
Working with User Extended Attributes	170
Summary	172
Exam Preparation Tasks	172
Review All Key Topics	172
Define Key Terms	173
Review Questions	173
End-of-Chapter Labs	173
Lab 7.1	173

**Chapter 8 Configuring Networking 177**

“Do I Know This Already?” Quiz	177
Foundation Topics	180
Networking Fundamentals	180
IP Addresses	180
IPv6 Addresses	181

Network Masks	181
Binary Notation	182
MAC Addresses	183
Protocol and Ports	183
Managing Network Addresses and Interfaces	183
Validating Network Configuration	184
Validating Network Address Configuration	185
Validating Routing	187
Validating the Availability of Ports and Services	187
Configuring Network Configuration with nmtui and nmcli	189
Configuring the Network with nmcli	189
Configuring the Network with nmtui	193
Working on Network Configuration Files	194
Setting Up Hostname and Name Resolution	196
Hostnames	196
DNS Resolving	198
Summary	200
Exam Prep Tasks	200
Review All Key Topics	200
Complete Tables and Lists from Memory	201
Define Key Terms	201
Review Questions	201
End-of-Chapter Labs	201
Lab 8.1	202
<b>Chapter 9 Managing Processes</b>	<b>205</b>
“Do I Know This Already?” Quiz	205
Foundation Topics	208
Introduction to Process Management	208
Managing Shell Jobs	208
Running Jobs in the Foreground and Background	208
Managing Shell Jobs	209
Managing Parent Child Relations	211

- Using Common Command-Line Tools for Process Management 211
  - Understanding Processes and Threads 211
  - Using ps to Get Process Information 212
  - Adjusting Process Priority with nice 214
  - Sending Signals to Processes with kill, killall, and pkill 216
  - Using top to Manage Processes 218
- Summary 220
- Exam Preparation Tasks 220
  - Review All Key Topics 220
  - Complete Tables and Lists from Memory 221
  - Define Key Terms 221
- Review Questions 221
- End-of-Chapter Labs 222
  - Lab 9.1 222
- Chapter 10 Working with Virtual Machines 225**
  - “Do I Know This Already?” Quiz 225
  - Foundation Topics 228
  - Understanding RHEL 7 Virtualization 228
    - Understanding KVM Virtualization 228
    - Understanding QEMU 228
    - Red Hat Beyond KVM 229
    - Understanding the Role of Libvirt 229
  - Making Your Server a KVM Host 231
    - Checking Host Requirements 231
    - Installing the KVM Software 232
    - Understanding KVM Host Networking 233
  - Managing Virtual Machines 234
    - Installing Virtual Machines 234
    - Using KVM Virtual Machines 240
    - Accessing Virtual Machines from a Text-Only Console 241
    - Managing Virtual Machine Properties 242
    - Managing Virtual Machines from the Command Line 243
    - Monitoring Virtual Machine Activity from Top 244

Summary	245
Exam Prep Tasks	245
Review All Key Topics	245
Define Key Terms	246
Review Questions	246
End-of-Chapter Labs	247
Lab 10.1	247
<b>Chapter 11 Managing Software</b>	<b>249</b>
“Do I Know This Already?” Quiz	249
Foundation Topics	252
Managing Software Packages with yum	252
Understanding the Role of Repositories	252
Specifying Which Repository to Use	253
Understanding Repository Security	256
Creating Your Own Repository	259
Using yum	260
Using yum to Find Software Packages	261
Getting More Information About Packages	262
Installing and Removing Software Packages	263
Showing Lists of Packages	265
Updating Packages	267
Working with yum Package Groups	268
Using yum History	270
Managing Software Packages with rpm	271
Understanding RPM Filenames	272
Querying the RPM Database	273
Querying RPM Package Files	273
Using repoquery	275
Summary	276
Exam Preparation Tasks	276
Review All Key Topics	276
Complete Tables and Lists from Memory	277
Define Key Terms	277

- Review Questions 277
- End-of-Chapter Labs 278
  - Lab 11.1 278

**Chapter 12 Scheduling Tasks 281**

- “Do I Know This Already?” Quiz 281
- Configuring cron to Automate Recurring Tasks 284
  - Managing the cron Service 284
  - Understanding cron Timing 285
  - Managing cron Configuration Files 286
  - Understanding the Purpose of anacron 288
  - Managing cron Security 289
- Configuring at to Schedule Future Tasks 290
- Summary 291
- Exam Preparation Tasks 291
  - Review All Key Topics 291
  - Define Key Terms 292
- Review Questions 292
- End-of-Chapter Labs 293
  - Lab 12.1 293

**Chapter 13 Configuring Logging 295**

- “Do I Know This Already?” Quiz 295
- Foundation Topics 298
- Understanding System Logging 298
  - Understanding the Role of rsyslogd and journald 298
  - Reading Log Files 300
  - Understanding Log File Contents 300
  - Live Log File Monitoring 302
  - Using logger 302
- Configuring rsyslogd 303
  - Understanding rsyslogd Configuration Files 303
  - Understanding rsyslog.conf Sections 304
  - Understanding Facilities, Priorities, and Log Destinations 304
- Rotating Log Files 308

Working with journald	310
Using journalctl to Find Events	310
Preserving the systemd Journal	314
Summary	316
Exam Prep Tasks	316
Review All Key Topics	316
Define Key Terms	316
Review Questions	317
End-of-Chapter Labs	317
Lab 13.1	317
<b>Chapter 14 Managing Partitions</b>	<b>319</b>
“Do I Know This Already?” Quiz	319
Understanding MBR and GPT Partitions	322
Understanding the MBR Partitioning Scheme	322
Understanding the Need for GPT Partitioning	323
Understanding Storage Measurement Units	324
Managing Partitions and File Systems	324
Creating MBR Partitions with fdisk	325
Using Extended and Logical Partitions on MBR	329
Creating GPT Partitions with gdisk	330
Creating File Systems	334
Changing File System Properties	336
Adding Swap Partitions	338
Adding Swap Files	339
Mounting File Systems	339
Manually Mounting File Systems	340
Using Device Names, UUIDs, or Disk Labels	340
Automating File System Mounts Through /etc/fstab	341
Summary	344
Exam Preparation Tasks	344
Review All Key Topics	344
Complete Tables and Lists from Memory	345
Define Key Terms	345

Review Questions	345
End-of-Chapter Labs	346
Lab 14.1	346
Lab 14.2	346
<b>Chapter 15 Managing LVM Logical Volumes</b>	<b>349</b>
“Do I Know This Already?” Quiz	349
Foundation Topics	352
Understanding LVM	352
LVM Architecture	352
LVM Features	353
Creating LVM Logical Volumes	354
Creating the Physical Volumes	355
Creating the Volume Groups	359
Creating the Logical Volumes and File Systems	360
Understanding LVM Device Naming	361
Resizing LVM Logical Volumes	363
Resizing Volume Groups	363
Resizing Logical Volumes and File Systems	364
Summary	366
Exam Preparation Tasks	366
Review All Key Topics	366
Define Key Terms	366
Review Questions	366
End-of-Chapter Labs	367
Lab 15.1	367
<b>Chapter 16 Basic Kernel Management</b>	<b>369</b>
“Do I Know This Already?” Quiz	369
Foundation Topics	372
Understanding the Role of the Linux Kernel	372
Understanding the use of Kernel Threads and Drivers	372
Analyzing What the Kernel Is Doing	374
Working with Kernel Modules	375
Understanding Hardware Initialization	376
Managing Kernel Modules	378

	Checking Driver Availability for Hardware Devices	381
	Managing Kernel Module Parameters	383
	Upgrading the Linux Kernel	384
	Summary	384
	Exam Preparation Tasks	384
	Review All Key Topics	384
	Define Key Terms	385
	Review Questions	385
	End-of-Chapter Labs	386
	Lab 16.1	386
<b>Chapter 17</b>	<b>Configuring a Basic Apache Server</b>	<b>389</b>
	“Do I Know This Already?” Quiz	389
	Foundation Topics	392
	Configuring a Basic Apache Server	392
	Installing the Required Software	392
	Identifying the Main Configuration File	392
	Creating Web Server Content	395
	Understanding Apache Configuration Files	397
	Creating Apache Virtual Hosts	398
	Summary	400
	Exam Preparation Tasks	401
	Review All Key Topics	401
	Define Key Terms	401
	Review Questions	401
	End-of-Chapter Labs	402
	Lab 17.1	402
<b>Chapter 18</b>	<b>Managing and Understanding the Boot Procedure</b>	<b>405</b>
	“Do I Know This Already?” Quiz	405
	Foundation Topics	408
	Working with Systemd	408
	Understanding Systemd	408
	Managing Units Through Systemd	413

- Working with GRUB 2 420
  - Understanding GRUB 2 420
  - Modifying Default GRUB 2 Boot Options 423
- Summary 424
- Exam Prep Tasks 424
  - Review All Key Topics 424
  - Complete Tables and Lists from Memory 425
  - Define Key Terms 425
- Review Questions 425
- End-of-Chapter Labs 426
  - Lab 18.1 426
  - Lab 18.2 426
- Chapter 19 Troubleshooting the Boot Procedure 429**
  - “Do I Know This Already?” Quiz 429
  - Foundation Topics 432
  - Understanding the RHEL 7 Boot Procedure 432
  - Passing Kernel Boot Arguments 434
    - Accessing the Boot Prompt 434
    - Starting a Troubleshooting Target 435
  - Using a Rescue Disk 436
    - Restoring System Access Using a Rescue Disk 436
    - Reinstalling GRUB Using a Rescue Disk 439
    - Re-Creating the Initramfs Using a Rescue Disk 439
  - Fixing Common Issues 441
    - Reinstalling GRUB 2 441
    - Fixing the Initramfs 442
    - Recovering from File System Issues 442
    - Resetting the Root Password 443
  - Recovering Access to a Virtual Machine 444
  - Summary 446
  - Exam Prep Tasks 446
    - Review All Key Topics 446
    - Complete Tables and Lists from Memory 446
    - Define Key Terms 447

Review Questions	447
End-of-Chapter Labs	448
Lab 19.1	448
<b>Chapter 20 Using Kickstart</b>	<b>451</b>
“Do I Know This Already?” Quiz	451
Foundation Topics	454
Setting Up an Installation Server	454
Configuring a Network Server as Installation Server	454
Setting Up a TFTP and DHCP Server for PXE Boot	455
Installing the TFTP Server	456
Configuring DHCP for PXE Boot	457
Creating the TFTP PXE Server Content	458
Creating a Kickstart File	462
Using a Kickstart File to Perform an Automated Installation	462
Modifying the Kickstart File with system-config-kickstart	464
Making Manual Modifications to the Kickstart File	467
Summary	469
Exam Preparation Tasks	470
Review All Key Topics	470
Define Key Terms	470
Review Questions	470
End-of-Chapter Labs	471
Lab 20.1	471
<b>Chapter 21 Managing SELinux</b>	<b>473</b>
“Do I Know This Already?” Quiz	474
Foundation Topics	477
Understanding SELinux Working and Modes	477
Understanding Context Settings and the Policy	481
Monitoring Current Context Labels	481
Setting Context Types	483
Finding the Context Type You Need	486
Restoring Default File Contexts	487
Using Boolean Settings to Modify SELinux Settings	489

- Diagnosing and Addressing SELinux Policy Violations 491
  - Making SELinux Analyzing Easier 492
- Summary 494
- Exam Prep Tasks 494
  - Review All Key Topics 494
  - Complete Tables and Lists from Memory 495
  - Define Key Terms 495
- Review Questions 495
- End-of-Chapter Labs 496
  - Lab 21.1 496
- Chapter 22 Configuring a Firewall 499**
  - “Do I Know This Already?” Quiz 499
  - Foundation Topics 502
  - Understanding Linux Firewalling 502
    - Understanding Previous Solutions 502
    - Understanding FirewallD 502
    - Understanding FirewallD Zones 503
    - Understanding FirewallD Services 504
  - Working with FirewallD 505
    - Working with Firewall-cmd 506
    - Working with **Firewall-config** 508
  - Summary 511
  - Exam Prep Tasks 511
  - Key Topics 511
    - Define Key Terms 512
    - Complete Tables and Lists from Memory 512
  - Review Questions 512
  - End-of-Chapter Labs 513
- Chapter 23 Configuring Remote Mounts and FTP 515**
  - “Do I Know This Already?” Quiz 515
  - Foundation Topics 519
  - Mounting NFS Shares 519
    - Understanding NFS Security Options 519
    - Understanding Kerberos Requirements 520

RHEL 7 NFS Support	521
Mounting the NFS Share	521
Mounting SMB File Systems	522
Discovering SMB Shares	523
Mounting SMB Shares	525
Authenticating to SMB Shares	525
Accessing Samba Shares Through the Graphical Interface	526
Mounting Remote File Systems Through fstab	528
Mounting NFS Shares Through fstab	528
Mounting SMB Shares Through fstab	529
Using Automount to Mount Remote File Systems	530
Understanding Automount	530
Configuring Automount for NFS	531
Using Wildcards in Automount	532
Using Automount to Mount SMB Shares	533
Configuring an FTP Server	533
Summary	535
Exam Preparation Tasks	535
Review All Key Topics	535
Complete Tables and Lists from Memory	536
Define Key Terms	536
Review Questions	536
End-of-Chapter Labs	537
Lab 23.1	537
<b>Chapter 24 Configuring Time Services</b>	<b>539</b>
“Do I Know This Already?” Quiz	539
Foundation Topics	542
Understanding Local Time	542
Using Network Time Protocol	543
Managing Time on Red Hat Enterprise Linux	543
Using date	544
Using hwclock	544
Using timedatectl	545
Managing Time Zone Settings	548

- Using Graphical Tools to Manage Time 550
- Summary 551
- Exam Prep Tasks 551
  - Review All Key Topics 551
  - Complete Tables and Lists from Memory 551
  - Define Key Terms 552
- Review Questions 552
- End-of-Chapter Labs 552
  - Lab 24.1 552

**Part 2 RHCE 555**

**Chapter 25 Configuring External Authentication and Authorization 557**

- “Do I Know This Already?” Quiz 557
- Foundation Topics 560
- Understanding Remote Authentication 560
- Understanding Kerberos Basics 561
  - Understanding Kerberos Authentication 561
  - Understanding Kerberos Principals 563
- Configuring LDAP Authentication with Kerberos Authorization 564
  - Using nslcd or sssd as the Authentication Backend Service 568
  - Setting Up External Authentication 569
  - Using an IPA Server or Active Directory 572
- Summary 572
- Exam Preparation Tasks 573
  - Review All Key Topics 573
  - Complete Tables and Lists from Memory 573
  - Define Key Terms 573
- Review Questions 573
- End-of-Chapter Labs 574
  - Lab 25.1 574

**Chapter 26 Configuring an iSCSI SAN 577**

- “Do I Know This Already?” Quiz 578
- Foundation Topics 581
- Understanding iSCSI 581

Comparing SAN Solutions	581
Software Versus Hardware iSCSI SAN	582
iSCSI SAN Architecture	582
iSCSI SAN Terminology	583
Setting Up the iSCSI Target	585
Opening the Firewall	594
Setting Up the iSCSI Initiator	596
Setting the iSCSI Initiatorname	596
Performing the Discovery	596
Making the Connection	598
Making iSCSI Connections Persistent	600
Troubleshooting iSCSI	602
Summary	603
Exam Preparation Tasks	603
Review All Key Topics	603
Complete Tables and Lists from Memory	603
Define Key Terms	604
Review Questions	604
End-of-Chapter Labs	604
Lab 26.1	604
Lab 26.2	605
Lab 26.3	605
<b>Chapter 27 System Performance Reporting</b>	<b>607</b>
“Do I Know This Already?” Quiz	607
Foundation Topics	610
Understanding top Performance Data	610
Understanding Load Average	610
CPU Performance Data	611
Memory Usage	612
Understanding Swap Usage	613
Process Memory Usage	615
Customizing top Display	615

Using iostat, vmstat, and pidstat	616
Using iostat	617
Using vmstat	618
Using pidstat	620
Configuring sar	621
Summary	622
Exam Preparation Tasks	622
Review All Key Topics	622
Complete Tables and Lists from Memory	623
Define Key Terms	623
Review Questions	623
End-of-Chapter Labs	624
<b>Chapter 28 System Optimization Basics</b>	<b>627</b>
“Do I Know This Already?” Quiz	627
Foundation Topics	630
Understanding System Optimization Basics	630
Understanding the /proc File System	631
Using /proc to Analyze Performance	631
Using /proc/sys to Tune Linux Performance	633
Using systemctl to Automate System Optimization Parameters	635
Summary	637
Exam Preparation Tasks	638
Review All Key Topics	638
Complete Tables and Lists from Memory	638
Define Key Terms	638
Review Questions	639
End-of-Chapter Labs	639
Lab 28.1	639
<b>Chapter 29 Configuring Advanced Log Features</b>	<b>641</b>
“Do I Know This Already?” Quiz	641
Foundation Topics	644
Understanding rsyslogd Modules	644
Understanding the Need for Modules	644
Using Modules in rsyslog Configuration	645

Connecting journald to rsyslog	646
Configuring Remote Logging	648
Understanding the Need for Remote Log Servers	648
Configuring Remote Logging	649
Summary	651
Exam Preparation Tasks	651
Review All Key Topics	651
Complete Tables and Lists from Memory	651
Define Key Terms	651
Review Questions	652
End-of-Chapter Labs	652
Lab 29.1	652
<b>Chapter 30 Configuring Routing and Advanced Networking</b>	<b>655</b>
“Do I Know This Already?” Quiz	655
Foundation Topics	658
Configuring Aggregated Network Interfaces	658
Using Bonding	658
Using Teaming	663
Configuring Network Teams	663
Looking Behind the Teaming Configuration	666
Troubleshooting Network Teaming	671
Configuring IPv6 Addresses	673
Understanding IPv6 Addresses	673
Managing IPv6 Address Configurations	675
Troubleshooting IPv6	676
Routing IP Traffic	677
Enabling Routing	677
Configuring Custom Routes	678
Summary	679
Exam Preparation Tasks	679
Review All Key Topics	679
Complete Tables and Lists from Memory	680
Define Key Terms	680

Review Questions 680

End-of-Chapter Labs 681

Lab 30.1 681

### **Chapter 31 An Introduction to Bash Shell Scripting 683**

“Do I Know This Already?” Quiz 683

Foundation Topics 686

Understanding Shell Scripting Core Elements 686

Using Variables and Input 687

Using Positional Parameters 688

Working with Variables 689

Using Conditional Loops 691

Working with if then else 692

Using || and && 693

Applying for 693

Understanding while and until 695

Understanding case 696

Bash Shell Script Debugging 697

Summary 698

Exam Preparation Tasks 698

Review All Key Topics 698

Define Key Terms 699

Review Questions 699

End-of-Chapter Labs 699

Lab 31.1 699

### **Chapter 32 Advanced Firewall Configuration 701**

“Do I Know This Already?” Quiz 701

Foundation Topics 705

Excluding Iptables Services 705

Creating Firewall Services 706

Configuring Firewall Rich Rules 708

Rich Rule Syntax 708

Ordering 709

Managing Rich Rules 709

Logging with Rich Rules 711

Configuring Network Address Translation	711
Configuring Masquerading	712
Configuring Port Forwarding	713
Summary	715
Exam Preparation Tasks	716
Review All Key Topics	716
Complete Tables and Lists from Memory	716
Define Key Terms	716
Review Questions	716
End-of-Chapter Labs	717
Lab 32.1	717
<b>Chapter 33 Managing Advanced Apache Services</b>	<b>719</b>
“Do I Know This Already?” Quiz	719
Foundation Topics	723
Revising Apache Basics	723
Essential Apache Parameters	723
Revising Apache SELinux-Related Settings	725
Configuring Write Access to the DocumentRoot	726
Configuring TLS Security	727
Understanding TLS Security	728
Configuring Apache for Using TLS Certificates	729
Deploying CGI Applications	731
Using Common Gateway Interface	731
Serving Dynamic PHP Content	732
Using Dynamic Python Content	733
Connecting to Databases	733
Configuring Private Directories	735
Summary	736
Exam Preparation Tasks	737
Review All Key Topics	737
Complete Tables and Lists from Memory	737
Define Key Terms	737

Review Questions 737

End-of-Chapter Labs 738

Lab 33.1 738

### **Chapter 34 Configuring DNS 741**

“Do I Know This Already?” Quiz 741

Foundation Topics 744

Understanding DNS 744

The DNS Hierarchy 744

DNS Terminology 745

Understanding DNS Lookups 745

Understanding Resource Records 747

Setting Up a Cache-Only DNS Server 749

Understanding the Need for DNSSEC 749

Configuring the Unbound Caching Name Server 749

Configuring Trust Anchors 751

Troubleshooting DNS Issues 752

Dumping and Changing the Unbound Cache 753

Using dig 753

Analyzing Client Issues 755

Summary 755

Exam Preparation Tasks 755

Review All Key Topics 755

Complete Tables and Lists from Memory 756

Define Key Terms 756

End-of-Chapter Labs 757

Lab 34.1 757

### **Chapter 35 Configuring a MariaDB Database 759**

“Do I Know This Already?” Quiz 759

Foundation Topics 762

MariaDB Base Configuration 762

Performing Simple Database Administration Tasks 768

Managing Users 771

MariaDB Backup and Restore 773

Summary	776
Exam Preparation Tasks	777
Review All Key Topics	777
Complete Tables and Lists from Memory	777
Define Key Terms	777
Review Questions	777
End-of-Chapter Labs	778
Lab 35.1	778
<b>Chapter 36 Configuring NFS</b>	<b>781</b>
“Do I Know This Already?” Quiz	781
Foundation Topics	785
Setting Up the Basic NFSv4 Server	785
Configuring the NFSv4 Server	785
Accessing NFS Shares	787
Testing Client Access with showmount	787
Making NFS Mounts Persistent	788
Configuring the Firewall for NFSv4	788
Configuring SELinux for NFSv4	788
Configuring NFS Kerberos Authentication	791
Understanding NFSv4 SELinux Transparency	795
Summary	796
Exam Prep Tasks	796
Review All Key Topics	796
Define Key Terms	797
Review Questions	797
End-of-Chapter Labs	798
Lab 36.1	798
<b>Chapter 37 Configuring Samba File Services</b>	<b>801</b>
“Do I Know This Already?” Quiz	801
Foundation Topics	804
Setting Up SMB File Sharing	804
Installing Samba	804
Preparing Shared Directories on Linux	804

Configuring /etc/samba/smb.conf	805
Using Samba Users	808
Securing Samba	810
Samba-Related SELinux Parameters	810
Samba Firewalling	811
Setting Up Kerberized Samba Shares	813
Accessing SMB Shares	815
Discovering Samba Shares	815
Mounting Samba Shares	816
Performing a Multiuser Samba Mount	817
Mounting Samba Shares Through automount	819
Summary	820
Exam Preparation Tasks	820
Review All Key Topics	820
Complete Tables and Lists from Memory	821
Define Key Terms	821
Review Questions	821
End-of-Chapter Labs	822
Lab 37.1	822
<b>Chapter 38 Setting Up an SMTP Server</b>	<b>825</b>
Do I Know This Already Quiz	825
Foundation Topics	828
Understanding Email Basics	828
Understanding Roles in Mail Handling	828
The Email Transmission Process	829
Mail Server Solutions on RHEL 7	830
Configuring Postfix Parameters	832
Understanding Essential Parameters	833
Configuring Postfix to Relay Mail	835
Verifying a Working Mail Configuration	838
Summary	840

Exam Preparation Tasks	840
Review All Key Topics	840
Complete Tables and Lists from Memory	841
Define Key Terms	841
Review Questions	841
End-of-Chapter Labs	842
Lab 38.1	842
<b>Chapter 39 Configuring SSH</b>	<b>845</b>
“Do I Know This Already?” Quiz	845
Foundation Topics	848
Hardening the SSH Server	848
Limiting Root Access	848
Configuring Alternative Ports	849
Modifying SELinux to Allow for Port Changes	849
Limiting User Access	850
Using Other Useful sshd Options	851
Session Options	852
Connection Keepalive Options	852
Configuring Key-Based Authentication with Passphrases	853
Configuring SSH Tunnels	854
Summary	856
Exam Preparation Tasks	856
Review All Key Topics	856
Complete Tables and Lists from Memory	856
Define Key Terms	856
Review Questions	857
End-of-Chapter Labs	857
Lab 39.1	857
<b>Chapter 40 Managing Time Synchronization</b>	<b>859</b>
“Do I Know This Already?” Quiz	859
Foundation Topics	862
Understanding the Need for Synchronized Time	862

Setting Up Time Synchronization	862
Understanding NTP	863
Configuring chrony to Synchronize Time	864
Managing and Monitoring Time Synchronization with chronyc	866
Summary	871
Exam Preparation Tasks	871
Review All Key Topics	871
Complete Tables and Lists from Memory	872
Define Key Terms	872
Review Questions	872
End-of-Chapter Labs	873
Lab 40.1	873
<b>Chapter 41 Final Preparation</b>	<b>875</b>
Generic Tips	875
Verifying Your Readiness	875
Registering for the Exam	876
On Exam Day	876
During the Exam	877
The Nondisclosure Agreement	878
<b>Chapter 42 Theoretical Pre-Assessment Exams</b>	<b>881</b>
RHCSA Theoretical Pre-Assessment Exam	881
RHCE Theoretical Pre-Assessment Exam	883
<b>RHCSA Practice Exam A</b>	<b>887</b>
<b>RHCSA Practice Exam B</b>	<b>891</b>
<b>RHCE Practice Exam A</b>	<b>895</b>
<b>RHCE Practice Exam B</b>	<b>899</b>
<b>Index</b>	<b>902</b>

**DVD and Companion Website Elements**

**Appendix A: Answers to the “Do I Know This Already” Quizzes and  
“Review Questions”**

**Appendix B: Memory Tables**

**Appendix C: Memory Tables Answer Key**

**Appendix D: Setting Up Identity Management**

**Appendix E: Study Planner**

**Glossary**

## Command Syntax Conventions

The conventions used to present command syntax in this book are the same conventions used in the IOS Command Reference. The Command Reference describes these conventions as follows:

- **Boldface** indicates commands and keywords that are entered literally as shown. In actual configuration examples and output (not general command syntax), boldface indicates commands that are manually input by the user (such as a **show** command).

## Introduction

Welcome to the Red Hat RHCSA/RHCE 7 Cert Guide. The Red Hat exams are some of the toughest in the business, and this guide will be an essential tool in helping you prepare to take both the Red Hat Certified System Administrator (RHCSA) and the Red Hat Systems Engineer (RHCE) exams.

As a Red Hat instructor with more than 20 years of experience, I have taken both the RHCSA and RHCE exams numerous times so that I can keep current on the progression of the exam, what is new, and what is different. I share my knowledge with you in this comprehensive Cert Guide so that you get the guidance you need to pass both exams.

The RHCSA and RHCE exams were recently updated for Red Hat Enterprise Linux 7. This book contains all you need to know to pass these exams. As you will see, this Cert Guide covers every objective in both exams: 42 chapters, more than 100 exercises, 4 practice exams (2 RHCSA and 2 RHCE), interactive quizzes and exercises, 4 advanced command-line interface (CLI) simulations, 3 virtual machines, and hours of video training. This Red Hat RHCSA/RHCE 7 Cert Guide is the best resource you can get to prepare for and pass the exams.

## Goals and Methods

To learn the topics described in this book, it is recommended that you create your own testing environment. You cannot become an RHCSA or RHCE without practicing a lot. Within the exercises included in every chapter of the book, you will find all the examples you need to understand what is on the exam and thoroughly learn the material needed to pass it. The exercises in the chapters provide step-by-step procedure descriptions that you can work through to find working solutions so that you can get real experience before taking the tests.

Each chapter also includes an end-of-chapter lab. These labs ask questions that are very similar to the questions that you might encounter on the exam. There are no solutions for these labs provided, and that is on purpose, because you need to train yourself to verify your work before you take the exams. On the exam, you also have to be able to verify for yourself whether the solution is working as expected.

Before you begin, you can test your knowledge by taking the theoretical pre-assessment exams in Chapter 42. These exams help you determine what you know and what you do not know so that you can better prepare your study plan. When you feel ready to take the exams, take a look at the practice exams that come with this book, two RHCSA and two RHCE. These will help you test your skills and get comfortable with the exam content and how questions might be presented in the testing facility.

This book contains everything you need to pass the exams, but if you want more guidance and practice, I have a number of video training titles available to help you study, including the following:

- Red Hat Certified System Administrator (RHCSA) Complete Video Course
- Red Hat Certified Engineer (RHCE) Complete Video Course
- Red Hat Certified System Administrator (RHCSA) Exam Prep Video Workshop
- Red Hat Certified Engineer (RHCE) Exam Prep Video Workshop

Apart from these products, you might also appreciate my website [rhatcert.com](http://rhatcert.com). Through this website, I provide updates on anything that is useful to exam candidates. I recommend that you register on the website so that I can send you messages about important updates that I've made available. Also, you'll find occasional video updates on my YouTube channel [rhatcertification.com](http://rhatcertification.com). I hope that all these resources provide you with everything you need to pass the Red Hat exams in an affordable way! Good luck!

## Who Should Read This Book?

This book is written as an RHCSA/RHCE exam preparation guide. That means that you should read it if you want to increase your chances of passing either the RHCSA or RHCE exam. A secondary use of this book is as a reference guide for Red Hat system administrators. As an administrator, you'll like the explanations and procedures that describe how to get things done on Red Hat Enterprise Linux.

So, why should you consider passing the RHCSA/RHCE exams? That question is simple to answer. Linux has become a very important operating system, and qualified professionals are sought after all over the world. If you want to work as a Linux professional, and prove your skills, the RHCSA or RHCE certificate really helps. Having these certificates dramatically increases your chances of becoming hired as a Linux professional.

## How This Book Is Organized

This book is organized as a reference guide to help you prepare for the exams. If you're new to the topics, you can just read it cover to cover. It is a smart idea, though, to distinguish between the RHCSA part and the RHCE part of this book. Finish RHCSA before starting with RHCE, because it will be too much to learn all of it at once.

You can also read the individual chapters that you need to fine-tune your skills in this book. Every chapter starts with a “Do I Know This Already?” quiz. This quiz asks questions about 10 topics that are covered in each chapter and provides a simple tool to check whether you’re already familiar with the topics covered in a chapter. Remember, though, the RHCSA and RHCE practice exams; these are an essential part of readying yourself for the real testing experience. You may be able to provide the right answer to the multiple-choice chapter questions, but that doesn’t mean that you can create the configurations when you take the tests. The companion files, included on the DVD and through the book’s companion web page, also includes more than 40 interactive exercises to help you learn and retain the knowledge needed to pass the exam and 4 simulations that take you through complex CLI exercises so that you can feel sure you’re ready not only for the exams but also to actually use Red Hat Linux.

The core chapters are organized in two parts. The first part, which includes Chapters 1 through 24, covers RHCSA topics; the second part, which consists of Chapters 25 through 40, covers RHCE objectives. All the objectives in both exams are covered in these chapters.

The following topics are covered in the chapters:

#### Part 1: RHCSA

##### Part 1-1: Performing Basic System Management Tasks

- Chapter 1: Installing Red Hat Enterprise Linux Server

In this chapter, you learn how to install Red Hat Enterprise Linux Server (RHEL). It also shows how to set up an environment that can be used for working on the labs and exercises in this book.

- Chapter 2: Using Essential Tools

This chapter covers some of the Linux basics, including working with the shell and Linux commands. This chapter is particularly important if you’re new to working with Linux.

- Chapter 3: Essential File Management Tools.

In this chapter, you learn how to work with tools to manage the Linux file system. This is an important skill because everything on Linux is very file system oriented.

- Chapter 4: Working with Text Files

In this chapter, you learn how to work with text files. The chapter teaches how to create text files, but also how to look for specific contents in the different text files.

- Chapter 5: Connecting to a Red Hat Enterprise Linux 7

This chapter teaches about the different methods that can be used to connect to RHEL 7. It explains local login as well as remote log in, and the different terminal types used for this purpose as well.

- Chapter 6: User and Group Management

On Linux, users are used as an entity that can be used by people or processes that need access to specific resources. This chapter explains how to create users and make user management easier by working with groups.

- Chapter 7: Configuring Permissions

In this chapter, you learn how to manage Linux permissions through the basic read, write, and execute permissions, but also through the special permissions and access control lists.

- Chapter 8: Configuring Networking

A server is useless if it isn't connected to a network. In this chapter, you learn the essential skills required for managing network connections.

#### Part 1-2: Operating Running Systems

- Chapter 9: Managing Processes

As an administrator, you need to know how to work with the different tasks that can be running on Linux. This chapter shows how to do this, by sending signals to processes and by changing process priority.

- Chapter 10: Working with Virtual Machines

Red Hat Enterprise Linux includes KVM, a complete solution that allows you to run virtual machines on top of RHEL. This chapter explains how to manage virtual machines.

- Chapter 11: Managing Software

Red Hat offers an advanced system for managing software packages. This chapter teaches you how it works.

- Chapter 12: Scheduling Tasks

In this chapter, you learn how to schedule a task for execution on a moment that fits you best.

- Chapter 13: Configuring Logging

As an administrator, you need to know what's happening on your server. The `rsyslogd` and `journald` services are used for this purpose. This chapter explains how to work with them.

- Chapter 14: Managing partitions

Storage management is an important skill of a Linux administrator. This chapter explains how hard disks can be organized in partitions, and how these partitions can be mounted in the file system.

- Chapter 15: Managing LVM Logical Volumes

Dividing disks in partitions isn't very flexible. If you need optimal flexibility, you need LVM logical volumes, which are used by default while installing Red Hat Enterprise Linux. This chapter shows how to create and manage those logical volumes.

### Part 1-3: Performing Advanced System Administration Tasks

- Chapter 16: Basic Kernel Management

The kernel is the part of the operating system that takes care of handling hardware. This chapter explains how that works, and what an administrator can do to analyze the current configuration and manage hardware devices in case the automated procedure doesn't work well.

- Chapter 17: Configuring a Basic Apache Server

Apache is the most commonly used service on Linux. This chapter shows how to set up Apache web services, including the configuration of Apache virtual hosts.

- Chapter 18: Managing and Understanding the Boot Procedure

Many things are happening when a Linux server boots. This chapter describes the boot procedure in detail and zooms in on vital aspects of the boot procedure, including the GRUB 2 boot loader and the `systemd` service manager.

- Chapter 19: Troubleshooting the Boot Procedure

Sometimes a misconfiguration might cause your server no longer to boot properly. This chapter teaches you some of the techniques that can be applied when normal server startup is no longer possible.

## Part 1-4: Managing Network Services

### ■ Chapter 20: Using Kickstart

If you want to install one server, you can go through a manual installation procedure. If you need to install many servers, you're better off using an installation server. This chapter teaches you how to set up such a server.

### ■ Chapter 21: Managing SELinux

Many Linux administrators only know how to switch it off, because SELinux is hard to manage and is often the reason why services cannot be accessed. In this chapter, you learn how SELinux works and what to do to configure it so that your services are still working and will be much better protected against possible abuse.

### ■ Chapter 22: Configuring a Firewall

Apart from SELinux, RHEL 7 comes with a firewall, which is implemented by the firewalld service. In this chapter, you learn how this service is organized and what you can do to block or enable access to specific services.

### ■ Chapter 23: Configuring Remote Mounts and FTP

While working in a server environment, managing remote mounts is an important skill. A remote mount allows a client computer to access a file system offered through a remote server. These remote mounts can be made through a persistent mount in `/etc/fstab`, or by using the automount service. This chapter teaches how to set up either of them, and also shows how to configure an FTP server.

### ■ Chapter 24: Configuring Time Services

For many services, such as databases and Kerberos, it is essential to have the right time. That's why as an administrator you need to be able to manage time on Linux. This chapter teaches you how.

## Part 2: RHCE

### Part 2-1: System Configuration and Management

#### ■ Chapter 25: Configuring External Authentication and Authorization

If you have multiple servers to manage, it makes sense to use an external authentication and authorization server, such as a Lightweight Directory Access Protocol (LDAP) server that uses Kerberos for authorization. This chapter teaches you how to set up a server for usage of an existing LDAP server that uses Kerberized authorization. It also explains Kerberos protocol fundamentals.

- Chapter 26: Configuring an iSCSI SAN

RHEL 7 includes everything that is needed to set up a storage-area network (SAN). This chapter explains how to set up the SAN itself, using the iSCSI target software, and how to connect to a SAN, using the iSCSI initiator software on the client server.

- Chapter 27: System Performance Reporting

Your server might sometimes have problems replying to a user request adequately. If that happens, you need to be able to find out what is wrong with it. This chapter explains performance reporting and all the different tools available to do this in an efficient way.

- Chapter 28: System Optimization Basics

If you've found that something is wrong with your server's performance, you need to optimize it. In this chapter, you learn how to optimize your server for specific workloads.

- Chapter 29: Configuring Advanced Log Features

The rsyslog service used for logging on RHEL 7 contains some advanced features, such as working with modules and setting up a remote log server. This chapter explains how to use these features.

- Chapter 30: Configuring Routing and Advanced Networking

To integrate a server in a datacenter, advanced network configurations are often needed. This chapter explains how to do so and includes configuring aggregated network interfaces using bonding or teaming, as well as routing and IPv6 configurations.

- Chapter 31: An Introduction to Bash Shell Scripting

Some tasks are complex and need to be performed repeatedly. Such tasks are ideal candidates for optimization through shell scripts. In this chapter, you learn how to use conditional structures in shell scripts to automate tasks efficiently.

## Part 2-2: System Security

- Chapter 32: Advanced Firewall Configuration

In Chapter 22, you learned how to set up a firewalld based firewall, using the default components of this firewall. This chapter zooms in on some more advanced configurations, including port forwarding and rich rules.

- **Chapter 33: Managing Advanced Apache Services**

The Apache web server offers many solutions to access web content. That includes using virtual servers, but also includes authentication and the use of Transport Layer Security (TLS) certificates. This chapter teaches you how to manage these advanced features.

- **Chapter 34: Configuring DNS**

In this chapter, you learn how to set up a caching-only DNS name server, which is useful to handle DNS requests more efficiently.

- **Chapter 35: Configuring a MariaDB Database**

As a Linux administrator, you'll have to deal with database management as well. That is, you do not have to become a skilled DBA, but at least you need to know how to manage database backups, set up a simple database and perform database queries. This chapter teaches how to do all this.

- **Chapter 36: Configuring NFS**

The Network File System (NFS) protocol is used to share files between Linux servers or between Linux servers and clients. This chapter teaches you how to set up Domain Name System (DNS), including advanced setups such as Kerberized NFS servers.

- **Chapter 37: Configuring Samba File Services**

The Samba file server offers a solution to share directories on Linux to make them accessible for Windows clients. This chapter shows you how to set up a Samba server, and also discusses some of the advanced methods that Samba shares can be integrated in the client file system.

- **Chapter 38: Setting Up an SMTP Server**

A Linux server occasionally needs to send email messages to other servers. This chapter shows how to set up a simple configuration for sending email using other mail servers as a relay host.

- **Chapter 39: Configuring SSH**

The Secure Shell (SSH) service is used for remote access, but it can do so much more. In this chapter, you learn how to optimize the SSH service through its many parameters in the configuration files. You also learn how to set up SSH port forwarding.

- Chapter 40: Managing Time Synchronization

As discussed earlier, time is a critical factor for many services to work successfully. This chapter explains how to manage time synchronization by using the Network Time Protocol (NTP).

### Part 3: Final Preparation

- Chapter 41: Final Preparation

In this chapter, you get some final exam preparation tasks. It contains some test exams and many tips that help you maximize your chances of passing the exam.

- Chapter 42: Theoretical Pre-Assessment Exams

In this chapter, you'll get an RHCSA Theoretical Pre-Assessment Exam and an RHCE Theoretical Pre-Assessment Exam, so you can pre-assess your skills and determine the best route forward for studying for the exams.

- Practice Exams: This section supplies two RHCSA Practice Exams and two RHCE Practice Exams, so you can test your knowledge and skills before taking the exams. These exams are also available on the book's companion website and DVD as PDF files.

## Chapter Features

To help you customize your study time using these books, the core chapters have several features that help you make the best use of your time:

- **“Do I Know This Already?” Quizzes:** Each chapter begins with a quiz that helps you determine the amount of time you need to spend studying that chapter.
- **Foundation Topics:** These are the core sections of each chapter. They explain the protocols, concepts, and configuration for the topics in that chapter.
- **Exam Preparation Tasks:** At the end of the “Foundation Topics” section of each chapter, the “Exam Preparation Tasks” section lists a series of study activities that should be done at the end of the chapter. Each chapter includes the activities that make the most sense for studying the topics in that chapter. The activities include the following:

- **Review Key Topics:** The Key Topic icon is shown next to the most important items in the “Foundation Topics” section of the chapter. The Key Topics Review activity lists the key topics from the chapter and their corresponding page numbers. Although the contents of the entire chapter could be on the exam, you should definitely know the information listed in each key topic.
- **Complete Tables and Lists from Memory:** To help you exercise your memory and memorize some lists of facts, many of the more important lists and tables from the chapter are included in a document on the DVD and companion website. This document lists only partial information, allowing you to complete the table or list.
- **Define Key Terms:** This section lists the most important terms from the chapter, asking you to write a short definition and compare your answer to the glossary at the end of this book.
- **Review Questions:** Questions at the end of each chapter that measure insight in the topics that were discussed in the chapter.
- **End-of-Chapter Labs:** Real labs that give you the right impression on what an exam assignment looks like. The end of chapter labs are your first step in finding out what the exam tasks really look like.

## Other Features

In addition to the features in each of the core chapters, this book, as a whole, has additional study resources on the DVD and companion website, including the following:

- **Four practice exams:** The companion website and DVD contains the four practice exams, two RHCSA and two RHCE, provided in the book as PDFs so that you can readily test your skills before taking the exams in the testing facility.
- **Interactive exercises and quizzes:** The companion website and DVD contains more than 40 interactive hands-on exercises and 40 interactive quizzes so that you can test your knowledge on the spot.
- **Four advanced CLI simulations:** The companion website and DVD contains four advanced CLI simulations—two RHCSA and two RHCE—that allow you to walk through multistep CLI scenarios in a simulated environment.
- **Glossary quizzes:** The companion website and DVD contains interactive quizzes that allow you to test yourself on every glossary term in the book.

- **More than 2.5 hours of video training:** The companion website and DVD contains 30 minutes of unique test-prep videos plus more than 2 hours of instruction from the best-selling RHCSA and RHCE Complete Video Course series.
- **Virtual Machines:** The companion website and DVD contains three virtual machines so that you can easily get access to an environment where you can work on the labs and exercises in this book.

## Book Organization, Chapters, and Appendixes

I have also included two tables that detail where every objective in the the RHCSA and RHCE exams is covered in this book so that you can more easily create a successful plan for passing the tests.

**Table 1** RHCSA Objectives

Objective	Chapter Title	Chapter	Page
Understand and use essential tools			
Access a shell prompt and issue commands with correct syntax	Using Essential Tools	2	33
Use input-output redirection (>, >>,  , 2>, etc.)	Using Essential Tools	2	33
Use grep and regular expressions to analyze text	Working with Text Files	4	85
Access remote systems using ssh	Connecting to an RHEL Server	5	103
Log in and switch users in multiuser targets	Connecting to an RHEL Server	5	103
Archive, compress, unpack, and uncompress files using tar, star, gzip, and bzip2	Essential File Management Tools	3	57
Create and edit text files	Working with Text Files	4	85
Create, delete, copy, and move files and directories	Essential File Management Tools	3	57
Create hard and soft links	Essential File Management Tools	3	57
List, set, and change standard ugo/rwx permissions	Permissions Management	7	151

<b>Objective</b>	<b>Chapter Title</b>	<b>Chapter</b>	<b>Page</b>
Locate, read, and use system documentation including man, info, and files in /usr/share/doc	Using Essential Tools	2	33
Note: Red Hat may use applications during the exam that are not included in Red Hat Enterprise Linux for the purpose of evaluating candidate's abilities to meet this objective.			
Operate running systems			
Boot, reboot, and shut down a system normally	Connecting to an RHEL Server	5	103
Boot systems into different targets manually	Essential Book Procedure Troubleshooting	19	429
Interrupt the boot process in order to gain access to a system	Essential Book Procedure Troubleshooting	19	429
Identify CPU/memory intensive processes, adjust process priority with renice, and kill processes	Process Management	9	205
Locate and interpret system log files and journals	Configuring Logging	13	295
Access a virtual machine's console	Working with Virtual Machines	10	225
Start and stop virtual machines	Working with Virtual Machines	10	225
Start, stop, and check the status of network services	Configuring Networking	8	177
Securely transfer files between systems	Connecting to an RHEL Server	5	103
Configure local storage			
List, create, and delete partitions on MBR and GPT disks	Managing Partitions	14	319
Create and remove physical volumes, assign physical volumes to volume groups, and create and delete logical volumes	Managing LVM Logical Volumes	15	349
Configure systems to mount file systems at boot by Universally Unique ID (UUID) or label	Managing Partitions	14	319

<b>Objective</b>	<b>Chapter Title</b>	<b>Chapter</b>	<b>Page</b>
Add new partitions and logical volumes, and swap to a system non-destructively	Managing Partitions	14	319
Create and configure file systems			
Create, mount, unmount, and use vfat, ext4, and xfs file systems	Managing Partitions	14	319
Mount and unmount CIFS and NFS network file systems	Configuring Remote Mounts and FTP	23	515
Extend existing logical volumes	Managing LVM Logical Volumes	15	349
Create and configure set-GID directories for collaboration	Permissions Management	7	151
Create and manage access control lists (ACLs)	Permissions Management	7	151
Diagnose and correct file permission problems	Permissions Management	7	151
Deploy, configure, and maintain systems			
Configure networking and hostname resolution statically or dynamically	Configuring Networking	8	177
Schedule tasks using at and cron	Scheduling Tasks	12	281
Start and stop services and configure services to start automatically at boot	Managing and Understanding the Boot Procedure	18	405
Configure systems to boot into a specific target automatically	Managing and Understanding the Boot Procedure	18	405
Install Red Hat Enterprise Linux automatically using Kickstart	Using Kickstart	20	451
Configure a physical machine to host virtual guests	Working with Virtual Machines	10	225
Install Red Hat Enterprise Linux systems as virtual guests	Working with Virtual Machines	10	225
Configure systems to launch virtual machines at boot	Working with Virtual Machines	10	225
Configure network services to start automatically at boot	Configuring Networking	8	177
Configure a system to use time services	Configuring Time Services	24	539

<b>Objective</b>	<b>Chapter Title</b>	<b>Chapter</b>	<b>Page</b>
Install and update software packages from Red Hat Network, a remote repository, or from the local file system	Installing Software Packages	11	249
Update the kernel package appropriately to ensure a bootable system	Basic Kernel Management	16	369
Modify the system bootloader	Managing and Understanding the Boot Procedure	18	405
Manage users and groups			
Create, delete, and modify local user accounts	User and Group Management	6	123
Change passwords and adjust password aging for local user accounts	User and Group Management	6	123
Create, delete, and modify local groups and group memberships	User and Group Management	6	123
Configure a system to use an existing authentication service for user and group information	User and Group Management	6	123
Manage security			
Configure firewall settings using firewall-config, firewall-cmd, or iptables	Configuring a Firewall	22	499
Configure key-based authentication for SSH	Connecting to an RHEL Server	5	103
Set enforcing and permissive modes for SELinux	Managing SELinux	21	473
List and identify SELinux file and process context	Managing SELinux	21	473
Restore default file contexts	Managing SELinux	21	473
Use boolean settings to modify system SELinux settings	Managing SELinux	21	473
Diagnose and address routine SELinux policy violations	Managing SELinux	21	473

**Table 2** RHCE Objectives

<b>Objective</b>	<b>Chapter Title</b>	<b>Chapter</b>	<b>Page</b>
System configuration and management			
Use network teaming or bonding to configure aggregated network links between two Red Hat Enterprise Linux systems	Configuring Routing and Advanced Networking	30	655
Configure IPv6 addresses and perform basic IPv6 troubleshooting	Configuring Routing and Advanced Networking	30	655
Route IP traffic and create static routes	Configuring Routing and Advanced Networking	30	655
Use firewalld and associated mechanisms such as rich rules, zones and custom rules, to implement packet filtering and configure Network Address Translation (NAT)	Managing Linux-Based Firewalls	32	701
Use <code>/proc/sys</code> and <code>sysctl</code> to modify and set kernel runtime parameters	System Optimization Basics	28	627
Configure a system to authenticate using Kerberos	Configuring External Authentication and Authorization	25	557
Configure a system as either an iSCSI target or initiator that persistently mounts an iSCSI target	Configuring an iSCSI SAN	26	577
Produce and deliver reports on system utilization (processor, memory, disk, and network)	System Performance Reporting	27	607
Use shell scripting to automate system maintenance tasks	An Introduction to Bash Shell Scripting	31	683
Network services			
Install the packages needed to provide the service	Installing Software Packages	11, 25, 26, 31, 33, 34, 35, 36, 37, 38	249, 557, 577, 683, 719, 781, 801, 825
Configure SELinux to support the service	Managing SELinux	21, 33, 35, 36, 37, 39	473, 719, 759, 781, 801, 845
Use SELinux port labeling to allow services to use non-standard ports	Managing SELinux	2, 33, 391	33, 719, 845

<b>Objective</b>	<b>Chapter Title</b>	<b>Chapter</b>	<b>Page</b>
Configure the service to start when the system is booted	Managing and Understanding the Boot Procedure	18, 25, 26, 33, 34, 35, 36, 37, 38	405, 557, 577, 719, 741, 759, 781, 801, 825
Configure the service for basic operation	Sander please insert chapter names and numbers	25, 26, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40	557, 577, 641, 655, 683, 701, 719, 741, 759, 781, 801, 825, 845, 859
Configure host-based and user-based security for the service	Sander please insert chapter names and numbers	25, 26, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40	557, 577, 641, 655, 683, 701, 719, 741, 759, 781, 801, 825, 845, 859
<b>HTTP/HTTPS</b>			
Configure a virtual host	Managing Advanced Apache Services	33	719
Configure private directories	Managing Advanced Apache Services	33	719
Deploy a basic CGI application	Managing Advanced Apache Services	33	719
Configure group-managed content	Managing Advanced Apache Services	33	719
Configure TLS security	Managing Advanced Apache Services	33	719
<b>DNS</b>			
Configure a caching-only name server	Configuring DNS	34	741
Troubleshoot DNS client issues	Configuring DNS	34	741
<b>NFS</b>			
Provide network shares to specific clients	Configuring NFS	36	781
Provide network shares suitable for group collaboration	Configuring NFS	36	781
Use Kerberos to control access to NFS network shares	Configuring NFS	36	781
<b>SMB</b>			
Provide network shares to specific clients	Configuring Samba File Services	37	801

<b>Objective</b>	<b>Chapter Title</b>	<b>Chapter</b>	<b>Page</b>
Provide network shares suitable for group collaboration	Configuring Samba File Services	37	801
<b>SMTP</b>			
Configure a system to forward all email to a central mail server	Setting up an SMTP Server	38	825
<b>SSH</b>			
Configure key-based authentication	Configuring SSH	39	845
Configure additional options described in documentation	Configuring SSH	39	845
<b>NTP</b>			
Synchronize time using other NTP peers	Managing Time Synchronization	40	859
<b>Database services</b>			
Install and configure MariaDB	Configuring a MariaDB Database	35	759
Backup and restore a database	Configuring a MariaDB Database	35	759
Create a simple database schema	Configuring a MariaDB Database	35	759
Perform simple SQL queries against a database	Configuring a MariaDB Database	35	759

## About the Virtual Machines

On the companion website and DVD that comes with this book, you can find a set of virtual machines that you can use to work through the labs in this book. Alternatively, you can set up an IPA server as instructed in Appendix D of this book and install your own environment according to the instructions in Chapter 1.

To use the virtual machines, you need VMware Workstation/Player or Fusion. Using the VMs if one of these virtualization platforms is installed on your computer is easy—just doubleclick the files that you’ll find in the archive after uncompressing it. Notice that you’ll need the following to use these virtual machines:

- A total of 30 GB of disk space
- A total of 3 GB of available RAM

## Where are the Companion Content Files?

Register this print version of Red Hat RHCSA/RHCE 7 Cert Guide to access the Bonus content online.

This print version of this title comes with a disc of companion content. You have online access to these files by following the steps below:

1. Go to [www.pearsonITcertification.com/register](http://www.pearsonITcertification.com/register) and log in or create a new account.
2. Enter the ISBN: 9780789754059
3. Answer the challenge question as proof of purchase.
4. Click on the “Access Bonus Content” link in the Registered Products section of your account page, to be taken to the page where your downloadable content is available.

Please note that many of our companion content files can be very large, especially image and video files.

If you are unable to locate the files for this title by following the steps at left, please visit [www.pearsonITcertification.com/](http://www.pearsonITcertification.com/) contact and select the “Site Problems/ Comments” option. Our customer service representatives will assist you.

This book also includes an exclusive offer for 70% off the Premium Edition eBook and Practice Tests edition of this title. Please see the coupon code included with the DVD for information on how to purchase the Premium Edition.

*This page intentionally left blank*



**The following topics are covered in this chapter:**

- Working with Systemd
- Working with GRUB 2

**The following RHCSA exam objectives are covered in this chapter:**

- Start and stop services and configure services to start automatically at boot
- Configure systems to boot into a specific target automatically
- Modify the system bootloader

# Managing and Understanding the Boot Procedure

In this chapter, you learn how the boot procedure on Red Hat Enterprise Linux is organized. We first go through a section about `systemd`, the overall service that takes care of starting everything on your server. In this section, you also learn how `systemd` targets are used to group `systemd` units and come to a final operational environment.

The second part of this chapter discusses GRUB2 and how to apply changes to the GRUB 2 boot loader. Troubleshooting is not a topic in this chapter; it is covered in Chapter 19, “Troubleshooting the Boot Procedure.”

## “Do I Know This Already?” Quiz

The “Do I Know This Already?” quiz allows you to assess whether you should read this entire chapter thoroughly or jump to the “Exam Preparation Tasks” section. If you are in doubt about your answers to these questions or your own assessment of your knowledge of the topics, read the entire chapter. Table 18.1 lists the major headings in this chapter and their corresponding “Do I Know This Already?” quiz questions. You can find the answers in Appendix A, “Answers to the ‘Do I Know This Already?’ Quizzes and ‘Review Questions.’”

**Table 18.1** “Do I Know This Already?” Section-to-Question Mapping

Foundation Topics Section	Questions
Working with Systemd	1–7, 10
Working with GRUB 2	8, 9

- Which command shows all service unit files on your system that are currently loaded?
  - `systemctl --type=service`
  - `systemctl --type=service --all`
  - `systemctl --list-services`
  - `systemctl --show-units | grep services`

2. Which statement about systemd wants is *not* true?
  - a. You can create wants by using the **systemctl enable** command.
  - b. The target to which a specific want applies is agnostic of the associated wants.
  - c. Wants are always administered in the `/usr/lib/systemd/system` directory.
  - d. Each service knows to which target its wants should be added.
  
3. What is the best solution to avoid conflicts between incompatible units?
  - a. Nothing, the unit files have defined for themselves which units they are not compatible with.
  - b. Disable the service using **systemctl disable**.
  - c. Unmask the service using **systemctl unmask**.
  - d. Mask the service using **systemctl mask**.
  
4. Which of the following is not a valid status for systemd services?
  - a. Running(active)
  - b. Running(exited)
  - c. Running(waiting)
  - d. Running(dead)
  
5. To allow targets to be isolated, you need a specific statement in the target unit file. Which of the following describes that statement?
  - a. **AllowIsolate**
  - b. **Isolate**
  - c. **SetIsolate**
  - d. **Isolated**
  
6. Which of the following is not a valid systemd unit type?
  - a. service
  - b. udev
  - c. mount
  - d. socket

7. You want to find out which other systemd units have dependencies to this specific unit. Which command would you use?
  - a. `systemd list-dependencies --reverse`
  - b. `systemctl list-dependencies --reverse`
  - c. `systemctl status my.unit --show-deps`
  - d. `systemd status my.unit --show-deps -r`
  
8. What is the name of the file where you should apply changes to the GRUB 2 configuration?
  - a. `/boot/grub/menu.lst`
  - b. `/boot/grub2/grub.cfg`
  - c. `/etc/sysconfig/grub`
  - d. `/etc/default/grub`
  
9. After applying changes to the GRUB 2 configuration, you need to write those changes. Which of the following commands will do that for you?
  - a. `grub2 -o /boot/grub/grub.cfg`
  - b. `grub2-mkconfig > /boot/grub2/grub.cfg`
  - c. `grub2 > /boot/grub2/grub.cfg`
  - d. `grub2-install > /boot/grub2/grub.cfg`
  
10. Which of the following is *not* a valid command while working with units in `systemctl`?
  - a. `systemctl unit start`
  - b. `systemctl status -l unit`
  - c. `systemctl mask unit`
  - d. `systemctl disable unit`

## Foundation Topics

### Working with Systemd

Systemd is the new service in Red Hat Enterprise Linux 7 that is responsible for starting all kinds of things. Systemd goes way beyond starting services; other items are started from systemd as well. In this chapter, you learn how systemd is organized and what items are started from systemd.

#### Understanding Systemd

To describe it in a generic way, the systemd System and Service Manager is used to start stuff. The stuff is referred to as *units*. Units can be many things. One of the most important unit types is the service. Typically, services are processes that provide specific functionality and allow connections from external clients coming in. Apart from services, other unit types exist, such as sockets, mounts, and others. To display a list of available units, type **systemctl -t help** (see Listing 18.1).

#### Key Topic

**Listing 18.1** Unit Types in Systemd

```
[root@server1 ~]# systemctl -t help
Available unit types:
service
socket
target
device
mount
automount
snapshot
timer
swap
path
slice
scope
```

**TIP** For RHCSA, you need to know how to work with services. The other unit types do not matter that much.

## Understanding Service Units

The major benefit of working with `systemd`, as compared to previous methods Red Hat used for managing services, is that it provides a uniform interface to start units. This interface is defined in the unit file. The system default unit files are in `/usr/lib/systemd/system`. System-specific modifications (overriding the defaults) are in `/etc/systemd/system`. Also, the runtime configuration that is generated automatically is stored in `/run/systemd/system`. Listing 18.2 gives an example of the `vsftpd.service` unit file.

**Listing 18.2** Example of the `Vsftpd` Unit File

```
[Unit]
Description=Vsftpd ftp daemon
After=network.target

[Service]
Type=forking
ExecStart=/usr/sbin/vsftpd /etc/vsftpd/vsftpd.conf

[Install]
WantedBy=multi-user.target
```

From this unit file example, you can see that it is relatively easy to understand. Any `systemd` service unit file consists of three sections. (You'll find different sections in other types of unit files.)

- **[Unit]**, which describes the unit and defines dependencies. This section also contains the important **After** statement, and optionally the **Before** statement. These statements define dependencies between different units. The **Before** statement relates to another unit that is started after this unit. The **after** unit refers to a unit that needs to be started before this unit can be started.
- **[Service]**, in which there is a description on how to start and stop the service and request status installation. Normally, you can expect an `ExecStart` line, which indicates how to start the unit, or an `ExecStop` line, which indicates how to stop the unit.
- **[Install]**, in which the wants are taken care of. You'll read more about this in the next section, "Understanding Target Units."

**Key  
Topic**

Listing 18.3 shows another example of a unit file. This time it is the `tmp.mount` unit.

**Listing 18.3** Example of a Mount Unit File

```
[Unit]
Description=Temporary Directory
Documentation=man:hier(7)
Documentation=http://www.freedesktop.org/wiki/Software/systemd/
APIFileSystems
DefaultDependencies=no
Conflicts=umount.target
Before=local-fs.target umount.target

[Mount]
What=tmpfs
Where=/tmp
Type=tmpfs
Options=mode=1777,strictatime

# Make 'systemctl enable tmp.mount' work:
[Install]
WantedBy=local-fs.target
```

The `tmp.mount` unit file in Listing 18.3 shows some interesting additional information. In the `Unit` section, you can see the **Conflicts** statement. This is used to list units that cannot be used together with this unit. Use this for mutually exclusive units. Next, there is the `Mount` section, which is specific for this unit type and defines where exactly the mount has to be performed. You'll recognize the arguments that are typically used in any **mount** command. Last, there is the `WantedBy` section, which defines where the unit has to be started.

Another type of unit that is interesting to look at is the `socket`. A socket creates a method for applications to communicate with one another. Some services create their own sockets while starting, whereas other services need a socket unit file to create sockets for them. It is also the other way around: Every socket needs a corresponding service file. The socket file example in Listing 18.4 shows how this happens for `virtlockd`, a `systemd` socket that tracks activity for virtual machines.

**Listing 18.4** Socket Unit File Example

```
[root@server202 system]# cat virtlockd.socket
[Unit]
Description=Virtual machine lock manager socket

[Socket]
ListenStream=/var/run/libvirt/virtlockd-sock

[Install]
WantedBy=multi-user.target
```

When working with systemd unit files, you risk getting overwhelmed with options. Every unit file can be configured with different options. To figure out which options are available for a specific unit, use the **systemctl show** command. For instance, the **systemctl show sshd** command shows all systemd options that can be configured in the `sshd.service` unit, including their current default values. Listing 18.5 shows the output of this command.

**Listing 18.5** Showing Available Options with **systemctl show**

```
Id=sshd.service
Names=sshd.service
Requires=basic.target
Wants=sshd-keygen.service system.slice
WantedBy=multi-user.target
ConsistsOf=sshd-keygen.service
Conflicts=shutdown.target
ConflictedBy=sshd.socket
Before=shutdown.target multi-user.target
After=network.target sshd-keygen.service systemd-journald.socket
basic.target system.slice
Description=OpenSSH server daemon
LoadState=loaded
ActiveState=active
SubState=running
FragmentPath=/usr/lib/systemd/system/sshd.service
UnitFileState=enabled
InactiveExitTimestamp=Sat 2015-05-02 11:06:02 EDT
InactiveExitTimestampMonotonic=2596332166
```

```

ActiveEnterTimestamp=Sat 2015-05-02 11:06:02 EDT
ActiveEnterTimestampMonotonic=2596332166
ActiveExitTimestamp=Sat 2015-05-02 11:05:22 EDT
ActiveExitTimestampMonotonic=2559916100
InactiveEnterTimestamp=Sat 2015-05-02 11:06:02 EDT
InactiveEnterTimestampMonotonic=2596331238
CanStart=yes
CanStop=yes
CanReload=yes
CanIsolate=no
StopWhenUnneeded=no
RefuseManualStart=no
RefuseManualStop=no
AllowIsolate=no
DefaultDependencies=yes
OnFailureIsolate=no
IgnoreOnIsolate=no

```

## Understanding Target Units

### Key Topic

The unit files are used to build the functionality that is needed on your server. To make it possible to load them in the right order and at the right moment, a specific type of unit is used: the target unit. A simple definition of a target unit is “a group of units.” Some targets are used as the equivalents to the old run levels, which on earlier versions of RHEL were used to define the state a server should be started in. A run level was a collection of services that were needed for a server to be started in multi-user mode or in graphical mode. Targets go beyond that. A good starting point to understanding targets is to see them as a group of units.

Targets by themselves can have dependencies to other targets, which are defined in the target unit. Let’s take a look at Listing 18.6, where you can see the definition of the multi-user.target, which defines the normal operational state of an RHEL server.

### Listing 18.6 The Multi-user.target File

```

[root@server202 system]# cat multi-user.target
...

[Unit]
Description=Multi-User System

```

```

Documentation=man:systemd.special(7)
Requires=basic.target
Conflicts=rescue.service rescue.target
After=basic.target rescue.service rescue.target
AllowIsolate=yes

[Install]
Alias=default.target

```

You can see that by itself the target unit does not contain much. It just defines what it requires and which services and targets it cannot coexist with. It also defines load ordering, by using the **After** statement in the Unit section. And you can see that in the Install section it is defined as the `default.target`, so this is what your server starts by default. The target file does not contain any information about the units that should be included; that is in the individual unit files and the wants (explained in the upcoming section “Understanding Wants”).

Even if a `systemd` target looks a bit like the old run levels, it is more than that. A target is a group of units, and there are multiple different targets. Some targets, such as the `multi-user.target` and the `graphical.target`, define a specific state that the system needs to enter. Other targets just bundle a group of units together, such as the `nfs.target` and the `printer.target`. These targets are included from other targets, like the `multi-user` or `graphical` targets.

## Understanding Wants

To understand the concept of a want, let’s start looking at the verb *want* in the English language, as in “I want a cookie.” Wants in `systemd` define which units `systemd` wants when starting a specific target. Wants are created when `systemd` units are enabled, and this happens by creating a symbolic link in the `/etc/systemd/system` directory. In this directory, you’ll find a subdirectory for every target, containing wants as symbolic links to specific services that are to be started.

## Managing Units Through Systemd

As an administrator, you need to manage `systemd` units. It starts by starting and stopping units. You use the **systemctl** command to do that. In Exercise 18.1, you walk start, stop, and manage a unit. After you have configured a unit so that it can be started without problems, you need to make sure that it restarts automatically upon reboot. You do this by enabling or disabling the unit.

**TIP** Memorizing all the different arguments that can be used with the **systemctl** command might seem hard, but you don't have to do that. Instead, just type **systemctl** and press the **Tab** key twice to use command autocompletion. This will show you all available commands.

**Key  
Topic**

### Exercise 18.1 Managing Units with systemctl

1. Type **yum -y install vsftpd** to install the Very Secure FTP service.
2. Type **systemctl start vsftpd**. This activates the FTP server on your machine.
3. Type **systemctl status vsftpd**. You'll get an output as in Listing 18.7 and see that the vsftpd service is currently operational. You can also see in the Loaded line that it is currently disabled, which means that it will not be activated on a system restart.
4. Type **systemctl enable vsftpd**. This creates a symbolic link in the wants directory for the multi-user target to ensure that the service gets back after a restart.
5. Type **systemctl status vsftpd** again. You'll now see that the unit file has changed from being disabled to enabled.

### Listing 18.7 Requesting Current Unit Status with systemctl status

```
[root@server202 system]# systemctl status vsftpd
vsftpd.service - Vsftpd ftp daemon
   Loaded: loaded (/usr/lib/systemd/system/vsftpd.service; disabled)
   Active: active (running) since Sun 2014-09-28 08:42:59 EDT; 2s ago
     Process: 34468 ExecStart=/usr/sbin/vsftpd /etc/vsftpd/vsftpd.conf
 (code=exited, status=0/SUCCESS)
    Main PID: 34469 (vsftpd)
      CGroup: /system.slice/vsftpd.service
             └─34469 /usr/sbin/vsftpd /etc/vsftpd/vsftpd.conf

Sep 28 08:42:59 server202.example.com systemd[1]: Starting Vsftpd ftp
daemon...
Sep 28 08:42:59 server202.example.com systemd[1]: Started Vsftpd ftp
daemon.
Hint: Some lines were ellipsized, use -l to show in full.
```

When requesting the current status of a systemd unit as in Listing 18.6, you can see different kinds of information about it. Table 18.2 shows the different kinds of information that you can get about unit files when using the **systemctl status** command:

**Table 18.2** Systemd Status Overview

Status	Description
Loaded	The unit file has been processed and the unit is active.
Active(running)	Running with one or more active processes.
Active(exited)	Successfully completed a one-time configuration.
Active(waiting)	Running and waiting for an event.
Inactive	Not running.
Enabled	Will be started at boot time.
Disabled	Will not be started at boot time.
Static	This unit can not be enabled but may be started by another unit automatically.

As an administrator, you'll also often need to get a current overview of the current status of systemd unit files. Different commands can help you to get this insight, some of which are shown in Table 18.3.

**Table 18.3** Systemctl Unit Overview Commands

Command	Description
<b>systemctl --type=service</b>	Shows only service units
<b>systemctl list-units --type=service</b>	Shows all active service units (same result as the previous command)
<b>systemctl list-units --type=service --all</b>	Shows inactive service units as well as active service units
<b>systemctl --failed --type=service</b>	Shows all services that have failed
<b>systemctl status -l your.service</b>	Shows detailed status information about services

**Key  
Topic**

## Managing Dependencies

Systemctl units in many cases have dependencies. Some units will be started as a dependency of other units, and an event where one specific unit is requested may

trigger the start of another unit. An example is the `cups.service` service. This service can be started by itself, but it can also be started by activity on the `cups.path` and `cups.socket` units, which may trigger the service to be started again. As an administrator, you can request a list of unit dependencies. Type **`systemctl list-dependencies`** followed by a unit name to find out which dependencies it has, and add the **`--reverse`** option to find out which units are dependent of this unit. Listing 18.8 shows an example of this command.

**Listing 18.8** Showing Unit Dependencies

```
[root@server1 ~]# systemctl list-dependencies vsftpd
vsftpd.service
├system.slice
└basic.target
  ├──alsa-restore.service
  ├──alsa-state.service
  ├──firewalld.service
  ├──microcode.service
  ├──rhel-autorelabel-mark.service
  ├──rhel-autorelabel.service
  ├──rhel-configure.service
  ├──rhel-dmesg.service
  ├──rhel-loadmodules.service
  ├──paths.target
  ├──slices.target
  │   ├──.slice
  │   └system.slice
  ├──sockets.target
  │   ├──avahi-daemon.socket
  │   ├──cups.socket
  │   ├──dbus.socket
  │   ├──dm-event.socket
  │   ├──iscsid.socket
  │   ├──iscsiuio.socket
  │   ├──lvm2-lvmetad.socket
  │   ├──rpcbind.socket
  │   ├──systemd-initctl.socket
  │   ├──systemd-journald.socket
  │   ├──systemd-shutdown.socket
  │   ├──systemd-udev-control.socket
  │   └systemd-udev-kernel.socket
```

```

└─sysinit.target
| └─dev-hugepages.mount
| └─dev-mqueue.mount
| └─dmraid-activation.service
| └─iscsi.service

```

Apart from dependencies, some units have conflicts with other units. Examples of these include the following:

- Mount and umount units that cannot be loaded together
- The network and NetworkManager service
- The iptables and the firewalld service
- The crond and ntpd service

If units have conflicts with other units, this is described in the unit file. As an administrator, you can also make sure that conflicting units will never be loaded at the same time on the same system. To do this, you can use the **systemctl mask** command, which basically makes a unit no longer a candidate for being started. Apply the following procedure to find out how it works:

1. Open a root shell and type **systemctl status firewalld**. Next type **systemctl status iptables**. If one of the services is active, do not load it again in the next step.
2. Type **systemctl start firewalld** and **systemctl start iptables** to load both services. You will see that iptables refuses to start; this is because the firewalld service is already activated.
3. Type **cat /usr/lib/systemd/system/firewalld.service**. Notice the conflicts setting. Type **cat /usr/lib/systemd/system/iptables.service**. Notice that this unit does not have a conflicts line.
4. Unload both services by using **systemctl stop firewalld** followed by **systemctl stop iptables**. Notice that it is not really necessary to stop the iptables service because it has failed to load, but we really need to make sure that it is not loaded at all before continuing.
5. Type **systemctl mask iptables** and look at what is happening: A symbolic link to /dev/null is created for /etc/systemd/system/iptables.service (as you can see in the output of the following command example). Because the unit files in

`/etc/systemd` have precedence over the files in `/usr/lib/systemd`, this makes it impossible to start the `iptables` service by accident:

```
[root@server202 system]# systemctl mask iptables
ln -s '/dev/null' '/etc/systemd/system/iptables.service'
```

6. Type **systemctl start iptables**. You'll see an error message indicating that this service is masked and for that reason cannot be started.
7. Type **systemctl enable iptables**. Notice that no error message is shown and it looks as if it is working all right. Restart your server using **systemctl reboot** (or just **reboot**).
8. After restart, type **systemctl status -l iptables**. You'll see that it is inactive and that the loaded status is indicated as masked:

```
[root@server202 ~]# systemctl status -l iptables
iptables.service
    Loaded: masked (/dev/null)
    Active: inactive (dead)
```

## Managing Systemd Targets

### Key Topic

As an administrator, you need to make sure that the required services are started when your server boots. To do this, use the **systemctl enable** and **systemctl disable** commands. You do not have to think about the specific target a service has to be started in. The services know for themselves in which targets they need to be started and a want is created automatically in that target. The following procedure walks you through the steps of enabling a service:

1. Type **systemctl status vsftpd**. If the service has not yet been enabled, the Loaded line will show that it currently is disabled:
 

```
[root@server202 ~]# systemctl status vsftpd
vsftpd.service - Vsftpd ftp daemon
    Loaded: loaded (/usr/lib/systemd/system/vsftpd.service;
    disabled)
    Active: inactive (dead)
```
2. Type **ls /etc/systemd/system/multi-user.target.wants**. You'll see symbolic links that are taking care of starting the different services on your machine. You can also see that the `vsftpd.service` link does not exist.
3. Type **systemctl enable vsftpd**. The command shows you that it is creating a symbolic link for the file `/usr/lib/systemd/system/vsftpd.service` to the directory `/etc/systemd/system/multi-user.target.wants`. So basically, when you enable a systemd unit file, on the background a symbolic link is created.

**TIP** On both the RHCSA and the RHCE exams, you are likely to configure a couple of services. It is a good idea to read through the exam questions, identify the services that need to be enabled, and enable them all at once to make sure that they are started automatically when you restart. This prevents your being so focused on configuring the service that you completely forget to enable it as well.

## Isolating Targets

As already discussed, on systemd machines there are a couple of targets. You also know that a target is a collection of units. Some of those targets have a special role because they can be isolated. By isolating a target, you start that target with all of its dependencies. Not all targets can be isolated, but only targets that have the `isolate` option enabled. We'll explore the **systemctl isolate** command in a while. Before doing that, let's take a look at the default targets on your computer.

To get a list of all targets currently loaded, type **systemctl --type=target**. You'll see a list of all the targets currently active. If your server is running a graphical environment, this will include all the dependencies required to install the graphical.target also. However, this list does not show all the targets, but only the active targets. Type **systemctl --type=target --all** for an overview of all targets that exist on your computer. You'll now see inactive targets also.

Of the targets on your system, a few have an important role because they can be started (isolated) to determine the state your server starts in. These are also the targets that can be set as the default target. These targets also roughly correspond to run levels as they were used on earlier versions of RHEL. These are the following targets:

- `poweroff.target` - runlevel 0
- `rescue.target` - runlevel 1
- `multi-user.target` - runlevel 3
- `graphical.target` - runlevel 5
- `reboot.target` - runlevel 6

If you look at the contents of each of these targets, you'll also see that they contain the `AllowIsolate=yes` line. That means that you can switch the current state of your computer to either one of these targets using the **systemctl isolate** command. Exercise 18.2 shows you how to do this.

**Key  
Topic****Exercise 18.2 Isolating Targets**

1. From a root shell, go to the directory `/usr/lib/systemd/system`. Type **grep Isolate \*.target**. This shows a list of all targets that allow isolation.
2. Type **systemctl isolate rescue.target**. This switches your computer to rescue.target. You need to type the root password on the console of your server to log in.
3. Type **systemctl isolate reboot.target**. This restarts your computer.

**Setting the Default Target**

Setting the default target is an easy procedure that can be accomplished from the command line. Type **systemctl get-default** to see the current default target and use **systemctl set-default** to set the desired default target.

To set the graphical target as the default target, you need to make sure that the required packages are installed. If this is not the case, you can use the **yum group list** command to show a list of all RPM package groups. The “server with gui” and “GNOME Desktop” package groups both apply. Use **yum group install “server with gui”** to install all GUI packages on a server where they have not been installed yet.

**Working with GRUB 2**

The GRUB 2 boot loader is one of the first things that needs to be working well to boot a Linux server. As an administrator, you will sometimes need to apply modifications to the GRUB 2 boot loader configuration. This section explains how to do so. The RHEL 7 boot procedure is discussed in more detail in Chapter 19, where troubleshooting topics are covered as well.

**Understanding GRUB 2**

The GRUB 2 boot loader makes sure that you can boot Linux. GRUB 2 is installed in the boot sector of your server’s hard drive and is configured to load a Linux kernel and the initramfs:

**Key  
Topic**

- The kernel is the heart of the operating system, allowing users to interact with the hardware that is installed in the server.
- The initramfs contains drivers that are needed to start your server. It contains a mini file system that is mounted during boot. In it are kernel modules that are needed during the rest of the boot process (for example, the LVM modules and SCSI modules for accessing disks that are not supported by default).

Normally, GRUB 2 works just fine and does not need much maintenance. In some cases, though, you might have to change its configuration. To apply changes to the GRUB 2 configuration, the starting point is the `/etc/default/grub` file. In this file, you'll find options that tell GRUB what to do and how to do it. Listing 18.9 shows the contents of this file after an installation with default settings of CentOS 7.

**Listing 18.9** Contents of the `/etc/default/grub` File

```
[root@server202 grub.d]# cat /etc/default/grub
GRUB_TIMEOUT=5
GRUB_DISTRIBUTOR="$(sed 's, release .*$,,g' /etc/system-release)"
GRUB_DEFAULT=saved
GRUB_DISABLE_SUBMENU=true
GRUB_TERMINAL_OUTPUT="console"
GRUB_CMDLINE_LINUX="rd.lvm.lv=centos/swap vconsole.font=latarcyrheb-sun16 rd.lvm.lv=centos/root crashkernel=auto vconsole.keymap=us rhgb quiet"
GRUB_DISABLE_RECOVERY="true"
```

**Key  
Topic**

As you can see, the `/etc/default/grub` file does not contain much information. The most important part that it configures is the `GRUB_CMDLINE_LINUX` option. This line contains boot arguments for the kernel on your server.

**TIP** For the RHCSA exam, make sure that you understand the contents of the `/etc/default/grub` file. That is the most important part of the GRUB 2 configuration anyway.

Apart from the configuration in `/etc/default/grub`, there are a few configuration files in `/etc/grub.d`. In these files, you'll find rather complicated shell code that tells GRUB what to load and how to load it. You typically do not have to modify it. You also will not need to modify anything if you want to make it possible to select from different kernels while booting. GRUB 2 picks up new kernels automatically and adds them to the boot menu automatically, so nothing has to be added manually.

Based on the configuration files mentioned previously, the main configuration file `/boot/grub2/grub.cfg` is created. Even if this looks like a configuration file that can be manually modified, you should never do that, because it will get overwritten at some point. This will happen, for instance, after updating the kernel. The RPM from which the kernel is updated will run a post-installation script that regenerates

the kernel. In the next section, you learn how to make changes to the GRUB 2 configuration.

If you enter the GRUB 2 boot prompt to add kernel startup parameters, the contents of the `/boot/grub2/grub.cfg` file display. From here, you add one-time-only startup options. Listing 18.10 shows the relevant part of the `grub.cfg` file that takes care of loading the Linux kernel. In this listing, you see the part of the configuration file that takes care of loading the default kernel. Notice the line that starts with `linux16`; this line specifies all kernel boot parameters.

**Listing 18.10** Partial Contents of the `/boot/grub2/grub.cfg` Configuration File

```

menuentry 'CentOS Linux (3.10.0-229.1.2.el7.x86_64) 7 (Core)' --class
centos --class gnu-linux --class gnu --class os --unrestricted
$menuentry_id_option 'gnulinux-3.10.0-123.el7.x86_64-advanced-50faa2a1-
01d3-430b-8114-4a98daf5bdb9' {
    load_video
    set gfxpayload=keep
    insmod gzio
    insmod part_msdos
    insmod xfs
    set root='hd0,msdos1'
    if [ x${feature_platform_search_hint} = xy ]; then
        search --no-floppy --fs-uuid --set=root --hint-bios=hd0,msdos1
--hint-efi=hd0,msdos1 --hint-baremetal=ahci0,msdos1 --hint='hd0,msdos1'
057ba3d8-bfe7-4676-bb99-79e9980a1966
    else
        search --no-floppy --fs-uuid --set=root 057ba3d8-bfe7-4676-bb99-
79e9980a1966
    fi
    linux16 /vmlinuz-3.10.0-229.1.2.el7.x86_64 root=/dev/mapper/
centos-root ro rd.lvm.lv=centos/swap vconsole.font=lataarcyheb-sun16
rd.lvm.lv=centos/root crashkernel=auto vconsole.keymap=us rhgb quiet
LANG=en_US.UTF-8
    initrd16 /initramfs-3.10.0-229.1.2.el7.x86_64.img
}

```

One of the most important differences between GRUB 2 and its previous version is the availability of GRUB 2 modules. In GRUB 2, a large number of modules are available. By default, you can find them in `/boot/grub2/i386-pc`. The modules determine what you can and what you cannot do from the GRUB 2 boot loader. If some hardware or file system is not supported in what you want to do, check here to make

sure that a supporting GRUB 2 module is available. In Listing 18.10, you can see examples of the code used to load specific GRUB 2 modules.

### Modifying Default GRUB 2 Boot Options

To apply modifications to the GRUB 2 boot loader, the file `/etc/default/grub` is your entry point; do not change the contents of the `/boot/grub2/grub.cfg` configuration file directly. The most important line in this file is `GRUB_CMDLINE_LINUX`, which defines how the Linux kernel should be started. In this line, you can apply permanent fixes to the GRUB 2 configuration. Some likely candidates for removal are the options `rhgb` and `quiet`. These options tell the kernel to hide all output while booting. That is nice to hide confusing messages for end users, but if you are a server administrator, you probably just want to remove these options.

**TIP** On the exam, you want to know immediately if something does not work out well. To accomplish this, it is a good idea to remove the `rhgb` and `quiet` boot options. Without these you will not have to guess why your server takes a long time after a restart; you'll just be able to see.

Another interesting parameter is `GRUB_TIMEOUT`. This defines the amount of time your server waits for you to access the GRUB 2 boot menu before it continues booting automatically. If your server runs on physical hardware that takes a long time to get through the BIOS checks, it may be interesting to increase this time a bit.

While working with GRUB 2, you need to know a bit about kernel boot arguments. There are many of them, and most of them you'll never use, but it is good to know where you can find them. Type `man 7 bootparam` for a man page that contains an excellent description of all boot parameters that you may use while starting the kernel.

In Exercise 18.3, you learn how to apply modifications to GRUB 2.

**TIP** You should know how to apply changes to the GRUB configuration, but you should also know that the default GRUB 2 configuration works fine as it is for almost all computers. So, you will probably never have to apply any changes at all!

**Key  
Topic****Exercise 18.3 Applying Modifications to GRUB2**

In this exercise you'll apply some changes to the GRUB2 boot configuration and write them to the `/boot/grub2/grub.cfg` configuration file.

1. Open the file `/etc/default/grub` with an editor and remove the **rhgb** and **quiet** options from the `GRUB_CMDLINE_LINUX` line.
2. From the same file, set the `GRUB_TIMEOUT` parameter to 10 seconds. Save changes to the file and close the editor.
3. From the command line, type `grub2-mkconfig > /boot/grub2/grub.cfg` to write the changes to GRUB 2. (Note that instead of using the `redirector >` to write changes to the `grub.cfg` file, you could use the `-o` option. Both methods have the same result.)
4. Reboot and verify that while booting you see boot messages scrolling by.

## Summary

In this chapter you learned how `systemd` and GRUB 2 are used to bring your server into the exact state you desire at the end of the boot procedure. You also learned how `systemd` is organized, and also how units can be configured for automatic start with the use of targets. You also read how to apply changes to the default GRUB 2 boot loader. In the next chapter, you learn how to troubleshoot the boot procedure and fix some common problems.

## Exam Prep Tasks

### Review All Key Topics

Review the most important topics in the chapter, noted with the Key Topic icon in the outer margin of the page. Table 18.4 lists a reference of these key topics and the page numbers on which each is found.

**Table 18.4** Key Topics for Chapter 18

Key Topic Element	Description	Page Number
Listing 18.1	Unit types in <code>systemd</code>	408
List	Three sections of a <code>systemd</code> unit file	409
Paragraph	Understanding Target Units	412
Exercise 18.1	Managing units with <code>systemctl</code>	414

Key Topic Element	Description	Page Number
Table 18.3	Systemctl unit overview commands	415
Section	Managing systemd targets	418
Exercise 18.2	Isolating targets	420
Bullet list	Explanation of the role of kernel and initramfs	420
Listing 18.9	Contents of the <code>/etc/default/grub</code> file	421
Exercise 18.3	Applying modifications to GRUB 2	424

## Complete Tables and Lists from Memory

Print a copy of Appendix B, “Memory Tables” (found on the disc), or at least the section for this chapter, and complete the tables and lists from memory. Appendix C, “Memory Tables Answer Key,” also on the disc, includes completed tables and lists to check your work.

## Define Key Terms

Define the following key terms from this chapter and check your answers in the glossary:

unit, wants, target, systemd, dependencies, initramfs, kernel, boot loader, GRUB

## Review Questions

1. What is a unit?
2. Which command enables you to make sure that a target is no longer eligible for automatic start on system boot?
3. Which configuration file should you modify to apply common changes to GRUB 2?
4. Which command should you use to show all service units that are currently loaded?
5. How do you create a want for a service?
6. How do you switch the current operational target to the rescue target?
7. Why can it happen that you get the message that a target cannot be isolated?

8. You want to shut down a systemd service, but before doing that you want to know which other units have dependencies to this service. Which command would you use?
9. What is the name of the GRUB 2 configuration file where you apply changes to GRUB 2?
10. After applying changes to the GRUB 2 configuration, which command should you run?

## End-of-Chapter Labs

You have now learned how to work with systemd units and the GRUB 2 boot loader. Before continuing, it is a good idea to work on some labs that help you ensure that you can apply the skills that you acquired in this chapter.

### Lab 18.1

Make sure that the firewalld service is started on boot. Also make sure that the iptables service can never be started at the same time.

### Lab 18.2

Change your GRUB 2 boot configuration so that you will see boot messages upon startup.

*This page intentionally left blank*

# Index

## Symbols

---

- ./* (dot-slash), current directory, 37
- (hyphen), in log files, 306
- (minus sign), in command options, 213
- ‘ ‘ (quotation marks), escaping regular expressions, 95
- . (dot)
  - changing group ownership, 156
  - hidden files, 70
  - regular expressions, 95
  - root domain, 744
- .profile* files, changing *umask* setting, 170
- .repo* files, creating, 253-256
- / (forward slash), root directory, 60
- ./autorelabel* file, 444
- /bin* directory, 60
- /boot* directory, 60
  - kernel files, 384
  - mounting, 62
- /boot/grub2/grub.cfg* file, 422-423
- /dev* directory, 60
- /dev/hda* device, 325
- /dev/pts* directory, 110
- /dev/sda* device, 325
- /dev/tty $n$*  files, 109
- /dev/vda* device, 325
- /dev/xvda* device, 325
- /etc* directory, 60
- /etc/anacrontab* file, 288-289
- /etc/auto.guests* file, 819
- /etc/auto.master* file, 819
- /etc/bashrc* file, 46, 136
- /etc/chrony.conf* file, 543, 864-866
- /etc/cron.allow* file, 289
- /etc/cron.d* directory, 287-288
- /etc/cron.daily* directory, 288
- /etc/cron.deny* file, 289
- /etc/cron.hourly* directory, 288
- /etc/cron.monthly* directory, 288
- /etc/crontab* file, 286
- /etc/cron.weekly* directory, 288
- /etc/default/grub* file, 421-423
- /etc/default/useradd* file, 134-135
- /etc/dracut.conf* file, 439-442
- /etc/dracut.conf.d* files, 439
- /etc/exports* file, 786
- /etc/firewalld/services* directory, 505, 706
- /etc/fstab* file, 528, 788
  - ACL support, 166
  - fields, 342
  - iSCSI devices, mounting, 601
  - mount options, 343
  - mounting file systems, 341-343
  - NFS shares, mounting, 528
  - SMB shares, mounting, 529-530
  - troubleshooting, 442-443
  - user extended attributes, 171
- /etc/group* file, 137-138
- /etc/grub.d* files, 421
- /etc/hosts* file, 198
- /etc/httpd* directory, Apache configuration files, 393, 397-398
- /etc/httpd/conf* directory, 397
- /etc/httpd/conf.d* directory, 398
- /etc/httpd/conf.d/php.conf* file, 732
- /etc/httpd/conf.d/ssl.conf* file, 730

- /etc/httpd/conf/httpd.conf* file, 392-395, 723-724
- /etc/httpd/conf.modules.d* directory, 398
- /etc/issue* file, 46-47
- /etc/krb5.conf* file, 567
- /etc/krb5.keytab* file, 563-564, 792-793, 814
- /etc/ldap.conf* file, 567
- /etc/login.defs* file, 135
- /etc/logrotate.conf* file, 309-310
- /etc/modprobe.d* directory, 383
- /etc/modules-load.d* directory, 378
- /etc/motd* file, 46-47
- /etc/my.cnf* file, 765
- /etc/nslcd.conf* file, 143, 567
- /etc/nsswitch.conf* file, 567
- /etc/openldap/cacerts* file, 567
- /etc/pam.d/\** files, 567
- /etc/passwd* file, 560
  - editing, 132-133
  - primary group membership, 137
  - properties of, 129-131
- /etc/postfix/master.cf* configuration file, 831
- /etc/postfix/mail.cf* configuration file, 832
- /etc/profile* file, 46, 136, 170
- /etc/redhat-release* command, 375
- /etc/resolv.conf* file, 745, 755
- /etc/rsyslog.d* directory, 303
- /etc/rsyslogd.conf* file, 303
- /etc/samba/smb.conf* file, 804-806
- /etc/shadow* file, 560
  - editing, 132-133
  - properties of, 131-132
- /etc/skel* directory, 134
- /etc/ssh/ssh\_config* file, 115, 852
- /etc/ssh/sshd\_config* file, 848
- /etc/sss/sss.conf* file, 144, 567, 571-572
- /etc/sysconfig/authconfig* file, 567
- /etc/sysconfig/network-scripts* directory, 661, 666
- /etc/sysconfig/network-scripts/route-interface* file, 678
- /etc/sysconfig/rsyslog* file, 303
- /etc/sysconfig/selinux* file, 478
- /etc/sysctl.conf* file, 635-636
- /etc/sysctl.d* directory, 635-636
- /etc/systemd/journald.conf* file, 315, 646
- /etc/systemd/system* directory, 409
- /etc/target/saveconfig.json* file, 590
- /etc/udev/rules.d* directory, 376
- /etc/xinetd.d/tftp* file, 456
- /home* directory, 60, 62
- /lib* directory, 60
- /lib64* directory, 60
- /media* directory, 60
- /mnt* directory, 60
- /opt* directory, 60
- /proc* directory, 60
- /proc* file system
  - kernel information, 375
  - performance optimization, 631
    - /proc/sys* directory parameters, 633-634
    - configuration files, 631
    - PID (process ID) directories, 632-633
    - sysctl* command, 635-637
- /proc/cpuinfo* file, 231
- /proc/meminfo* file, 613
- /proc/net/bonding* interface, 662
- /proc/sys* directory parameters, 633-634
- /proc/sys/net/ipv4/ip\_forward*, 678
- /root* directory, 60
- /run* directory, 60
- /run/log/journal* file, 314
- /run/systemd/system* directory, 409
- /sbin* directory, 60
- /srv* directory, 60
- /sur/bin/passwd* utility, 162
- /sys* directory, 60
- /sys* file system, hardware initialization, 376-378
- /text* (vim command), 43
- /tmp* directory, 60
- /usr* directory, 60, 62

/usr/lib/dracut/dracut.conf.d/\*.conf files, 439  
 /usr/libexec/mysqld --help --verbose command, 766  
 /usr/lib/firewalld/services directory, 505, 706  
 /usr/lib/sysctl.d directory, 635-636  
 /usr/lib/systemd/system directory, 409  
 /usr/lib/udev/rules.d directory, 376  
 /usr/share/doc documentation files, 53  
 /usr/share/zoneinfo directory, 548  
 /var directory, 60, 62  
 /var/ftp directory, 534  
 /var/lib/iscsi directory, 600  
 /var/lib/libvirt/images directory, 444  
 /var/lib/tftpboot/pxelinux directory, 459  
 /var/log/audit/audit.log file, 300  
 /var/log/boot.log file, 300  
 /var/log/cups file, 300  
 /var/log/dmesg file, 300  
 /var/log/httpd/ directory, 300  
 /var/log/journal file, 314  
 /var/log/maillog file, 300, 838  
 /var/log/messages file, 300-301  
 /var/log/sa directory, 621  
 /var/log/samba file, 300  
 /var/log/secure file, 300, 851  
 /var/log/sssd file, 300  
 /var/spool/cron directory, 287  
 : (colon)  
     changing group ownership, 156  
     mounting shares, 533  
 :%s/old/new/g (vim command), 43  
 :q! (vim command), 43  
 :w (vim command), 43  
 :wq (vim command), 43  
 ; (semicolon)  
     command separator, 690  
     database commands, 768  
 \_netdev mount option, 343, 528-529, 788  
 || (logical OR), 693  
 = (equal sign), log file priorities, 307  
 --add-forward-port option, 713  
 --add-interface option, 507  
 --add-masquerade option, 712  
 --add-port option, 507  
 --add-rich-rule option, 709  
 --add-service option, 507  
 --add-source option, 507  
 --date option, 544  
 --discover option, 597  
 --get-default-zone option, 507  
 --get-services option, 507  
 --get-zones option, 507  
 --help option, 48  
 --list-all option, 507  
 --list-rich-rules option, 709  
 --list-services option, 507  
 --login option, 598  
 --mode discovery option, 597  
 --mode node option, 598  
 --permanent option, 507  
 --portal option, , 598  
 --query-rich-rule option, 709  
 --reload option, 507  
 --remove-interface option, 507  
 --remove-port option, 507  
 --remove-rich-rule option, 709  
 --remove-service option, 507  
 --remove-source option, 507  
 --scripts option, 274  
 --set-default-zone option, 507  
 --targetname option, 598  
 --type sendtargets option, 597  
 -Z option, 481  
 !ls (vim command), 43  
 #!/bin/bash, 686  
 \$ (dollar sign), regular expressions, 95  
 \$ (vim command), 43  
 \$PATH variable, 36-37, 136  
 & (ampersand), background jobs, 209  
 && (logical AND), 693  
 \* (asterisk)  
     cron service time and date fields, 285  
     regular expressions, 95  
     wildcards, 67

**?** (question mark)  
     regular expressions, 95  
     wildcards, 67  
**?text (vim command)**, 43  
**\ls -l command, aliases**, 75  
**[ ] (square brackets)**  
     regular expressions, 95  
     wildcards, 67  
**global] Samba section**, 806  
**homes] share**, 805  
**label] option**, 255  
**printers] share**, 805  
**^ (caret), regular expressions**, 94  
**^ (vim command)**, 43  
**~/.bash\_profile file**, 46  
**~/.bashrc file**, 46, 136  
**~/.profile file**, 136  
**~/.ssh/authorized\_keys file**, 118  
**~/.ssh/config file**, 852  
**~/.ssh/known\_hosts file**, 114  
**< (left arrow)**  
     sorting memory performance  
         parameters, 615  
     STDIN redirection, 38  
**> (right arrow)**  
     sorting memory performance  
         parameters, 615  
     STDOUT redirection, 38  
**>> (double right arrow), STDOUT  
 redirection**, 38  
**2>, STDERR redirection**, 38  
**2>&1, STDERR redirection**, 38  
**802.3ad bonding mode**, 659

---

**A**  
**a (vim command)**, 43  
**a attribute**, 171  
**A resource record type**, 748  
**AAAA resource record type**, 748  
**abi tunable directory**, 633  
**absolute mode, applying permissions**,  
     159-161

**absolute pathnames**, 68-69  
**accepting, license agreement**, 29  
**access control. See also permissions**  
     Apache private directories, 735-736  
     in SSH, 850-851  
     user extended attributes, 170-172  
**access control list (ACL). See ACLs  
 (access control lists)**  
**accessing**  
     GRUB boot prompt, 434-435  
     NFS shares, 519, 521  
         */etc/fstab file*, 787  
         *Kerberos requirements*, 520-521  
         *NFS version support*, 521  
         *persistent mounts*, 788  
         *pseudo root mounts*, 519  
         *security options*, 519-520  
         *systemd process*, 790-791  
         *testing access*, 787-788  
     repositories, 13-14  
     restoring system access from rescue disk,  
         437  
     SMB shares, 522-525  
         *as guest*, 525  
         *user authentication*, 525  
         *via graphical interface*, 526-527  
     VMs  
         *with libvirtd*, 229-231  
         *methods of*, 240-242  
         *recovering access to*, 444-446  
**accounts**  
     group accounts. *See* group accounts  
     user accounts. *See* user accounts  
**acl mount option**, 166, 343  
**ACLs (access control lists)**, 165, 584  
     backing up, 166  
     creating, 588  
     default ACLs, 168  
     to DocumentRoot, 726  
     file system preparation, 166  
     viewing and changing, 166-168  
**Active Directory**, 572  
**active memory**, 613  
**active-backup bonding mode**, 659

- activebackup runner, 663**
- Add Network Device option, 467**
- adding, files, to archives, 77**
- add-ons, list of, 15**
- addresses**
  - IP addresses. *See* IP addresses
  - MAC addresses, 183
  - port addresses, 183
- administration**
  - of databases, 768-773
    - creating databases, 772-773*
    - CRUD operations, 769-770*
    - user management, 771-772*
  - help resources, 47
    - documentation files, 53*
    - help option, 48*
    - info system, 51-52*
    - man pages, 48-51*
  - shell
    - command execution, 36-37*
    - history file, 40*
    - I/O redirection, 37-40*
    - tab completion, 42*
  - shell environment
    - configuration files, 46*
    - managing, 47*
    - user communication in, 46-47*
    - variables, 45-46*
  - vim, editing files, 42-45
- administrator permissions, granting, 128**
- advanced permissions**
  - applying, 164
  - explained, 161-163
- aggregated network interfaces, 658**
  - network bonding, 658-662
  - network teaming
    - configuration, 663-671*
    - runners, 663*
    - troubleshooting, 671-672*
- alert priority, 306**
- aliases, 36, 75, 380**
- AllowOverride parameter, 724**
- AllowUsers option, 850, 853**
- Alt+Fn (virtual terminals), 109**
- anaconda-ks.cfg file, 462, 467-469**
- anacron service, 288-289**
- analyzing, kernel, 374-375**
- anonymous FTP drop boxes, configuration, 533-535**
- Apache web servers**
  - configuration, 392
    - configuration files, 392-395, 397-398*
    - creating content, 395*
    - essential parameters, 723-724*
    - installing required software, 392*
    - private directories, 735-736*
    - SELinux settings, 725*
    - testing, 395-396*
    - write permission to DocumentRoot, 726*
  - dynamic content
    - CGI (Common Gateway Interface), 731-732*
    - database connections, 733*
    - PHP scripts, 732*
    - Python scripts, 733*
  - httpd-manual RPM package, 733-735
  - TLS (Transport Layer Security)
    - configuration, 727-731
  - virtual hosts
    - creating, 398-400*
    - editing configuration, 726-727*
- application servers, 562**
- apropos command, 49-50**
- arch command, 231**
- archives, 76-77**
  - compression, 78-79
  - creating, 77
  - extracting contents, 78
  - listing contents, 77-78
  - tar command usage, 79-80
- arguments, in shell scripts, 688-689**
- at command, 290**
- atd service, 290-291**
- atime mount option, 343**
- atq command, 290**
- atrm command, 290**
- attributes, for file security, 170-172**

audit log file, SELinux troubleshooting, 491-492

auth facility, 305

authconfig command, 142, 565

authconfig-gtk interface, 142, 144, 565

authconfig-tui interface, 142-143, 565, 568

authentication. *See* user authentication

Authentication option, 467

authoritative DNS answers, 746-747

authorization. *See* Kerberos

authpriv facility, 305

AUTHPRIV syslog facility, 851

auto mount option, 343

autofs command, 819-820

autofs service, automount configuration, 530

automated installation with, with Kickstart, 462-463

automatic completion. *See* tab completion

automount mounts, 819-820

- configuration, 530
  - for NFS shares, 531-532
  - for SMB shares, 533
  - wildcards, 532-533

availability, of drivers, 381-383

awk command, 97-98

## B

---

backend storage, 584

background jobs

- running, 208-209
- terminating, 211

backing up, ACLs, 166

backups, MariaDB databases, 773-776

balance-alb bonding mode, 659

balance-rr bonding mode, 659

balance-tlb bonding mode, 659

balance-xor bonding mode, 659

base context, 141

base environment settings, RHEL 7 installation, 22

base parameter, 143

base repository type, 256

baseurl= option, 255-256

bash shell. *See* shell; shell scripts

bash -x command, 697-698

Basic Configuration option, 465

batch command, 291

bg command, 209

binary notation

- decimal conversion, 182
- IP addresses, 182-183

blkid command, 340, 601

Block default zone (firewalld), 503

bonding. *See* network bonding

Boolean settings, SELinux, 489-491

Boot Loader Options, 466

boot menu, CentOS 7, 17

boot procedure

- configuration, overview by boot phase, 433
- GRUB 2 boot loader
  - explained*, 420-423
  - modifying options*, 423
- phases in, 432-433
- PXE boot. *See* PXE boot configuration
- rebooting server, 110-112
- systemd process
  - default targets, setting*, 420
  - dependency management*, 415-418
  - explained*, 408
  - isolating targets*, 419
  - service units*, 409-412
  - target management*, 418-419
  - target units*, 412-413
  - unit management*, 413-415
  - unit types*, 408
  - wants*, 413

troubleshooting

- accessing GRUB boot prompt*, 434-435
- overview by boot phase*, 433
- recovering from file system issues*, 442-443
- recovering virtual machine access*, 444-446

*re-creating initramfs, 439-442*  
*reinstalling GRUB 2 boot loader, 439-442*  
*resetting root password, 443-444*  
*restoring system access from rescue disk, 437*  
*starting from rescue disk, 436*  
*starting troubleshooting targets, 435-436*

**boot.iso image, 456**

**brctl show command, 234**

**bridging configuration, 233-234**

**broadcast addresses, 181**

**broadcast bonding mode, 659**

**broadcast runner, 663**

**browsable directive, 807**

**browsers, launching, 395**

**Btrfs file system, 334**

**buffers, explained, 613**

**buffers parameter (memory usage), 612**

**bunzip2 command, 79**

**bzip2 command, 78-79**

## C

---

**c attribute, 171**

**CA (certificate authority), 728**

**cache**

dropping caches, 614

explained, 613

**cache poisoning, 749**

**cache-only DNS servers, 749**

configuration, 749-751

dumping unbound cache, 753

security issues, 749

**cached Mem parameter (memory usage), 612**

**canceling, shell jobs, 209**

**case loops, 696-697**

**cat command, 88-89**

**cat /proc/cpuinfo command, 231**

**cd command, 68, 768**

**CentOS 7 (Community Enterprise Operating System)**

installing, 17-29

obtaining, 12-13

**certificate authority (CA), 728**

**certificates in TLS, 141, 728**

**CGI (Common Gateway Interface), 731-732**

**chage command, 135-136**

**chage -l command, 135**

**changing**

ACLs, 166-168

effective primary group, 157-158

ownership

*group owners, 156-157*

*user owners, 156*

passwords, permissions needed, 161-162

process priorities, 214-216

/proc/sys directory parameters

*persistently, 635-637*

*temporarily, 634*

**characters, counting, in text files, 93**

**chattr command, 172**

**chcon command, 444, 483**

**chgrp command, 156-157**

**chmod command, 159-161, 164**

**choosing, repositories, 253-256**

**chown command, 156-157**

**chown -R command, 156**

**chrony command, 546**

**chronyc command, 866-871**

**chronyc sources command, 867-868**

**chronyc sourcestats command, 868**

**chronyc tracking command, 868**

**chronyd process, 546, 858-866**

**chroot command, 437**

**chroot environment, Apache web servers, 397**

**chvt command, 109**

**CIDR (classless interdomain routing) notation, 181**

**CIFS (Common Internet File System). See SMB shares**

- cifscreds command, 817-819**
- cifsiostat command, 616**
- cifs-utils package, 816**
- classless interdomain routing (CIDR) notation, 181**
- classroom exam registration, 876**
- cleanup process (Postfix), 831**
- ClientAliveCountMax option, 852-853**
- ClientAliveInterval option, 852-853**
- closed source drivers, open source drivers versus, 373**
- clustered environments, 576**
- cmdline file, 631**
- CNAME resource record type, 748**
- command mode (vim), 43**
- command substitution, 689-691**
- commands**
  - /etc/redhat-release, 375
  - /usr/libexec/mysqld --help --verbose, 766
  - apropos, 49-50
  - arch, 231
  - at, 290
  - atq, 290
  - atrm, 290
  - authconfig, 142, 565
  - autofs, 819-820
  - bash -x, 697-698
  - batch, 291
  - bg, 209
  - blkid, 340, 601
  - brctl show, 234
  - bunzip2, 79
  - bzip2, 78-79
  - cat /proc/cpuinfo, 231
  - cd, 68, 768
  - chage, 135-136
  - chage -l, 135
  - chattr, 172
  - chcon, 444, 483
  - chgrp, 156-157
  - chmod, 159-161, 164
  - chown, 156-157
  - chown -R, 156
  - chrony, 546
  - chronyc, 866-871
  - chronyc sources, 867-868
  - chronyc sourcestats, 868
  - chronyc tracking, 868
  - chroot, 437
  - chvt, 109
  - cifscreds, 817-819
  - cifsiostat, 616
  - cp, 70-71
  - create, 586
  - createrepo, 259
  - crontab -e, 287
  - crontab -l, 289
  - in current directory, 37
  - database administration, 768-773
    - CREATE DATABASE*, 768
    - CREATE TABLE*, 769
    - CREATE USER*, 771
    - DELETE*, 770
    - DESCRIBE*, 769
    - describe user*, 768
    - FLUSH PRIVILEGES*, 772
    - GRANT*, 771-772
    - INSERT*, 770
    - mysqldump*, 774
    - SELECT*, 770
    - show databases*, 767
    - SHOW TABLES*, 768
    - UPDATE*, 770
    - USE*, 768
    - WHERE clause*, 770
  - date, 543-544
  - df -hT, 64, 66
  - dig, 746, 753-754
  - dig +dnssec DNSKEY, 751-752
  - dmesg, 374-375
  - dracut, 439-442
  - dracut --force, 244
  - dump, 343
  - e2label, 341
  - echo, 46, 634
  - echo b > /proc/sysrq-trigger, 112

env, 45  
 executing, in shell, 36-37  
 fdisk, 325-328, 355  
 fg, 209  
 file, 78  
 find, 156  
 findmnt, 64-65  
 firewall-cmd, 506-507, 788, 812  
     *masquerading configuration*, 712  
     *options*, 507  
     *port forwarding configuration*, 713-714  
     *rich rules*, 709-711  
 firewall-cmd --add-port=3260/tcp  
     --permanent, 595  
 firewall-cmd --get-services, 504, 706  
 firewall-cmd --list-all, 595  
 firewall-cmd --reload, 595  
 firewall-config, 508-511, 714  
 free -m, 614  
 fsck, 442  
 gdisk, 325, 330-334  
 getenforce, 478  
 getent hosts, 200  
 getfacl, 166-168  
 getsebool -a, 489  
 gpasswd, 158  
 groupadd, 138  
 groupmems, 139  
 groupmod, 139  
 groups, 157  
 grubby, 241  
 gunzip, 79  
 gzip, 78-79  
 head, 379  
 help resources, 47  
     *documentation files*, 53  
     --help option, 48  
     *info system*, 51-52  
     *man pages*, 48-51  
 history file, 40  
 hostnamectl, 197, 634  
 hostnamectl status, 375  
 hwclock, 543-545  
 id, 126  
 ifconfig, 185  
 insmod, 381  
 iostat, 616-618  
 ip, 185-187  
 ip addr show, 676  
 ip route show, 676, 678  
 iscsiadm, 584, 596-598  
 iscsiadm -m session -P 3, 603  
 iscsiadm --mode node -P, 598  
 jobs, 209  
 journalctl, 298, 310-314  
 journalctl --dmesg, 374  
 journalctl -k, 374  
 journalctl -o verbose, 313  
 kill, 211, 216-217  
 killall, 217  
 klist, 792  
 klist -k, 814  
 kpartx -a, 445  
 less, 39, 379  
 list-timezone, 545  
 ln, 74  
 load\_policy -i, 443  
 logger, 302-303  
 logrotate, 308-310, 648  
 ls, 39, 69-70, 75, 602  
 ls -l, 155, 167  
 lsattr, 172  
 lsblk, 358  
 lsmod, 378-379  
 lspci -k, 381-383  
 lsscsi, 599  
 lvcreate, 360-362  
 lvdisplay, 362  
 lvextend, 364  
 lvresize, 364-365  
 lvs, 362, 445  
 mail, 696  
 man -f, 50  
 man -k, 49-51  
 man -k \_selinux, 486  
 man nmcli-examples, 659

- mkdir, 68
- mkfs, 335
- mod probe -r, 378, 381
- modinfo, 378, 380-381
- modprobe, 378, 381
- more, 89
- mount, 62-63, 340, 525, 787, 816
- mpstat, 616
- mv, 71
- mysql\_secure\_installation, 763-764
- net share -l, 524
- netstat, 187
- netstat -tulpen | grep 123, 863
- newgrp, 157-158
- nfsiostat, 616
- nice, 214-216
- nmcli, 189-193
  - IPv6 address configuration, 675-676*
  - network bonding configuration, 658-660*
  - network teaming configuration, 663-666*
- nm-connection-editor, 194
- nmtui, 193-195, 197, 658, 678
- nohup, 211
- partprobe, 328, 330
- passwd, 134-135
- pdbedit, 809
- pgrep, 214
- pidstat, 616, 620
- pinfo, 51-52
- ping6, 676
- pkill, 217
- postconf, 832-836
- postqueue -f, 839
- postqueue -p, 839
- postsuper -d, 840
- ps, 212-214
- ps aux, 212, 372-373
- ps aux | grep dd, 214
- ps -ef, 213
- ps fax, 213
- pvcreeate, 362
- pvcreeate --help, 354-355
- pvdisplay, 358, 362
- pvs, 356, 362
- pvscaan, 445
- pwd, 67
- read, 689-691
- realm, 572
- renice, 214-216
- repoquery, 275
- restorecon, 487-488
- rm, 71-72
- rmdir, 68
- rmmod, 381
- rpm, 271-272
  - database queries, 273*
  - package file queries, 273-276*
- rsync, 116
- sar, 621-622
- scp, 115-116
- screen, 118-119
- sealert, 492-494
- semanage, 483-485, 535
- semanage boolean -l, 489
- semanage port, 849-850
- sestatus, 478
- setenforce, 478
- setfacl, 166-168
- setfacl -m d, 168
- setfacl -R, 168
- set-local-rtc, 545
- set-ntp, 545
- setsebool, 490
- set-time, 545
- set-timezone, 545
- shell jobs
  - foreground versus background jobs, 208-209*
  - managing, 209-211*
  - parent-child management, 211*
- showmount, 521, 787-788
- smbclient -L, 523-524, 815-816
- smbpasswd, 808
- ss, 187
- ssh, 112-114
- ssh -p, 115
- ssh -v, 114, 115

- ssh -X, 115
- ssh-add, 854
- ssh-agent, 854
- ssh-copy-id, 117
- ssh-keygen, 117
- star, 58, 166
- status, 545
- su, 127
- su -107, 127
- sudo, 127-128
- swapon -s, 615
- sysctl, 635-637
- sysctl -a, 635-636
- system-config-date, 550
- systemctl, 413-415
- systemctl enable target, 594
- systemctl --failed --type=service, 415
- systemctl get-default, 420
- systemctl halt, 111
- systemctl list-dependencies, 416
- systemctl list-units --type=service, 415
- systemctl list-units --type=service --all, 415
- systemctl mask, 417-418
- systemctl mask iptables, 505, 705-706
- systemctl poweroff, 111
- systemctl reboot, 111
- systemctl set-default, 420
- systemctl show, 411-412
- systemctl start nsld, 143
- systemctl start target, 594
- systemctl status, 299, 396, 414-415
- systemctl status chronyd, 869-870
- systemctl status crond -l, 284
- systemctl status iscsi, 602
- systemctl status -l, 415
- systemctl status -l libvirtd, 229
- systemctl status mariadb, 762
- systemctl status NetworkManager, 189
- systemctl status nsld, 143
- systemctl status sssd, 144
- systemctl status target, 602
- systemctl -t help, 408
- systemctl --type=service, 415
- systemctl --type=target, 419
- systemctl --type=target --all, 419
- tab completion, 42, 69, 354
- tail -f, 302-303
- tar, 76-80
  - compression*, 79
  - creating archives*, 77
  - extracting archive contents*, 78
  - lack of ACL support*, 166
  - listing archive contents*, 77-78
  - options*, 79
- targetcli, 585-594, 602
- teamdctl, 666
- teamdctl team0 config dump, 672
- teamnl, 671-672
- test, 690, 692
- testparm, 808
- for text files
  - awk*, 97-98
  - cat*, 89
  - cut*, 91
  - grep*, 96-97
  - head*, 90-91
  - less*, 88-89
  - list of*, 88
  - sed*, 97-98
  - sort*, 91-92
  - tac*, 90
  - tail*, 90-91
  - wc*, 93
- timedatectl, 543-548
- top, 244, 610
  - CPU usage*, 611
  - customizing display*, 615-616
  - load average*, 610-611
  - memory usage*, 612-613
  - process memory usage*, 615
  - process states*, 218-220
  - swap usage*, 613-615
- touch, 68
- tracepath6, 676
- tune2fs, 336-338
- type, 36

- tzselect, 548-549
- udevadm monitor, 376-378
- umount, 340
- uname, 375
- uname -i, 231
- unbound-control dump\_cache, 753
- unbound-control-setup, 751
- useradd, 133-135
- userdel, 132
- userdel -r, 132
- usermod, 134, 139
- vgchange, 445
- vgcreate, 359, 362
- vgdisplay, 360, 362
- vgextend, 363
- vgreduce, 363
- vgs, 360-363
- vigr, 133, 138
- vim, 43
- vimtutor, 44
- vipw, 133
- virsh, 243-244
- virsh console, 241
- virsh dumpxml vmname | grep "source file=", 444
- virsh edit, 240
- virsh list, 241
- virt-viewer, 241
- vmstat, 616-619
- vmstat -s, 619
- which, 36
- xfs\_admin, 338
- xfs\_admin -L, 341
- yum
  - creating repositories, 259-260*
  - finding packages, 261-262*
  - history list, 270-271*
  - information about packages, 262-263*
  - installing packages, 263-265*
  - list of tasks, 260*
  - listing packages, 265-266*
  - managing packages, 271*
  - package groups, 268-270*
  - removing packages, 265*
  - repositories, explained, 252-253*
  - repository security, 256-258*
  - rpm command versus, 271-272*
  - specifying which repository to use, 253-256*
  - updating packages, 267*
- yum group info, 269-270
- yum groups install, 392
- yum groups list, 268-269, 392
- yum history, 270-271
- yum info, 262-263
- yum install, 263-265
- yum install elinks, 395
- yum install httpd, 392
- yum install kernel, 384
- yum install -y screen, 118
- yum list, 265-266
- yum list installed, 266
- yum list kernel, 266
- yum provides, 262
- yum remove, 265
- yum repolist, 260
- yum search, 261-262
- yum search http, 392
- yum update, 267
- yum upgrade kernel, 384
- yum whatprovides, 262, 483
- yumdownloader, 260, 275
- comment directive, 807**
- comment field (/etc/passwd file), 130**
- Common Gateway Interface (CGI), 731-732**
- Common Internet File System (CIFS). See SMB shares**
- communication, with users, in shell environment, 46-47**
- Community Enterprise Operating System (CentOS 7). See CentOS 7**
- completion. See tab completion**
- compression, 78-79**
- conditional loops**
  - case loops, 696-697
  - if.then.else loops, 690-693
  - for loops, 689, 693-694

- types of, 691-692
- until loops, 696
- while loops, 695-696
- configuration**
  - Apache virtual hosts, 398-400, 726-727
  - Apache web servers, 392
    - configuration files*, 392-398
    - creating content*, 395
    - essential parameters*, 723-724
    - installing required software*, 392
    - private directories*, 735-736
    - SELinux settings*, 725
    - testing*, 395-396
    - write permission to DocumentRoot*, 726
  - automount, 530
    - for NFS shares*, 531-532
    - for SMB shares*, 533
    - wildcards*, 532-533
  - boot procedure, overview by boot phase, 433
  - cache-only DNS servers, 749-751
  - chronyd process, 864-866
  - DHCP servers, for PXE boot, 457-458
  - firewalld service, 505
    - firewall-cmd command*, 506-507
    - firewall-config command*, 508-511
  - forwarders, 749
  - FTP servers, 533-535
  - installation servers, 454
    - Kickstart file creation*, 462-469
    - network server configuration*, 454
    - PXE boot configuration*, 455-462
  - ipa clients, 572
  - IPv6 addresses, 675-676
  - iSCSI initiators, 596-598
  - iSCSI targets, 585-595
  - Kerberos, on NFS servers, 791-794
  - LDAP
    - with Kerberos authorization*, 564-568
    - platform configuration*, 142
    - RHEL 7 configuration for*, 142
  - MariaDB, 762-767
  - multiuser Samba mounts, 818-819
  - NAT, 711-712
    - masquerading*, 712
    - port forwarding*, 713-714
  - network addresses, validating, 185-187
  - network bonding, 658-662
  - network teaming, 663-671
  - networking
    - configuration files*, 195-196
    - DNS resolution*, 198-200
    - hostnames*, 196-198
    - for KVM hosts*, 233-234
    - with NetworkManager service*, 189
    - with nmcli*, 189-193
    - with nmtui*, 193-195
    - during RHEL 7 installation*, 26
  - NFSv4 servers, 789-790
    - creating exports*, 786-787
    - firewall configuration*, 788
    - mounting shares*, 787
    - new features*, 785-786
    - persistent mounts*, 788
    - SELinux configuration*, 788-789
    - SELinux transparency*, 794-796
  - null clients, 837-838
  - Postfix parameters, 832-838
  - remote logging, 649-650
  - rich rules, 709-711
  - routing, 677-679
  - rsyslogd process, 303-308
    - facilities, priorities, destinations*, 304-308
    - file locations*, 303
    - modules*, 645-646
    - rsyslog.conf sections*, 304
  - Samba file servers, 809-810
    - /etc/samba/smb.conf file*, 805-806
    - creating shares*, 807-808
    - creating users*, 808-809
    - installing Samba*, 804
    - for keytab files*, 814-815
    - preparing shared directories*, 804-805
    - troubleshooting*, 810

- of sar command, 621-622
- SSH (Secure Shell). *See* SSH (Secure Shell)
  - connection keepalive options*, 852
  - options*, 853
  - session options*, 852
  - tunneling*, 854-855
- TLS (Transport Layer Security), 727-731
- trust anchors, 751-752
- configuration files**
  - Apache web servers, 392-395, 397-398
    - essential parameters*, 723-724
    - PHP scripts*, 732
  - chronyd process, 864-866
  - cron service, 286-288
  - cron service security, 289
  - DHCP servers, 458
  - for dracut, 439-442
  - for group accounts, 138
  - for GRUB 2 boot loader, 421-423
  - for LDAP configuration with Kerberos, 565-567
  - for MariaDB network access, 765-766
  - network bonding, 661-662
  - network teaming, 666-669
  - for networking, 195-196
  - performance optimization, 631
  - picking up changes, 848
  - repositories, specifying which to use, 253-256
  - for routing, 679
  - Samba file servers, 805-806
  - for shell environment, 46
  - for systemctl service, 635
  - for user accounts
    - default properties*, 134-135
    - editing*, 132-133
    - properties of*, 129-132
  - for VMs
    - editing*, 240
    - validation*, 238
- conflicts with units**, 417-418
- connections**
  - to iSCSI targets, 598-602
    - mounting iSCSI devices*, 601-602
    - persistent mounts*, 600-601
  - keepalive options, in SSH, 852
  - to LDAP servers, 144-146
  - in networking, 189
    - changing parameters*, 192-193
    - displaying properties*, 190
    - dual fixed and dynamic IP addresses*, 196
    - managing with nmcli*, 192
    - managing with nmtui*, 193-195
    - showing status*, 190
  - rsyslogd and journald processes, 646-648
- consoles**
  - local consoles, login, 106-107
  - terminals versus, 106
- context switches**, 620
- contexts (SELinux)**, 477, 481
  - finding context types, 486
  - monitoring, 481-482
  - relabeling, 487-488
  - setting context types, 483-486
- copying files**, 70-71, 115-116
- counting lines, words, characters in text files**, 93
- course environment setup**, 16-17
- cp -a command**, 71
- cp command**, 70-71
- cp -R command**, 70
- CPU usage**, 611
- cpuinfo file**, 631
- create command**, 586
- CREATE DATABASE command**, 768
- CREATE TABLE command**, 769
- CREATE USER command**, 771
- CREATE\_HOME property**, 135
- createrepo command**, 259
- credentials files**, 529-530
- crit priority**, 306
- cron facility**, 305

**cron service, 284**

- anacron service, 288-289
- configuration files, 286-288
- exercises, 289-290
- listing cron jobs, 289
- managing, 284-285
- security management, 289
- time and date fields, 285-286

**crond daemon, 284****crontab -e command, 287****crontab -l command, 289****CRUD operations, in databases, 769-770****crypto tunable directory, 633****Ctrl+a (screen command), 118****Ctrl+Alt+Fn (virtual terminals), 109****Ctrl+C, stopping jobs, 209****Ctrl+D, stopping jobs, 209****Ctrl+r (vim command), 43****Ctrl+Z, pausing jobs, 209****cups options Samba parameter, 806****current directory, commands in, 37****customizing, top display, 615-616****cut command, 88, 91**

## D

---

**d attribute, 171****D attribute, 171****daemon facility, 305****daemons, 208****database connections, for dynamic website content, 733****databases**

- administration, 768-773
  - creating databases, 772-773*
  - CRUD operations, 769-770*
  - user management, 771-772*
- defined, 767
- MariaDB. *See* MariaDB
- rpm database, 272
  - querying, 273*
- time synchronization, importance of, 862
- yum database, 272

**date and time settings, RHEL 7 installation, 19-20****date command, 543-544****date fields, cron service, 285-286****daylight savings time (DST). *See* DST (daylight savings time)****dd (vim command), 43****debug priority, 306****debug tunable directory, 633****debugging, shell scripts, 697-698****decimal notation, binary conversion, 182****decompression, 79****dedicated network architecture, 583****default ACLs, 168****default file, in PXE boot configuration, 459****default file contexts, restoring, SELinux, 487-488****default ownership, 157-158****default permissions, setting with umask, 169-170****default properties, for user accounts, 134-135****default targets, setting, 420****default zones, firewalld service, 503****DELETE command, 770****deleting**

- files, 71-72, 163
- user accounts, 132

**dependencies, 252-253, 271-272, 415-418****DESCRIBE command, 769****describe user command, 768****desktop-based virtualization, hypervisor-based virtualization versus, 228****destinations, 304-308****dev tunable directory, 633****device files, 39, 306****device mapper, 361****device names**

- LVM volumes, 361
- mounting file systems, 340-341

**devices in networking, 189, 192****df -hT command, 64-66**

**DHCP servers**

- configuration, for PXE boot, 457-458

- IPv6 address configuration, 675

**dhcpd.conf file, 458****dictionary attacks, 848**

**dig +dnssec DNSKEY command, 751-752**

**dig command, 746, 753-754**

**direct mounts, 531-532**

**direct rules, 708**

**direct write logging, 298**

**directories**

- for file management, 67-68

- in file system hierarchy

- list of, 60*

- mounting on dedicated devices, 61-62*

- home directories, 133-134

- ownership

- changing, 156-157*

- default ownership, 157-158*

- viewing, 155-156*

- permissions

- advanced permissions, 161-164*

- applying, 159-161*

- explained, 158-159*

- setting default, 169-170*

- PID (process ID) directories, 632-633

- private directories, Apache web servers, 735-736

- shared directories, preparing for Samba file servers, 804-805

- sharing, permissions needed, 162-163

- skeleton directory, 134

- user extended attributes, 170-172

**directory field (/etc/passwd file), 130**

**Directory parameter, 724**

**directory shares (Samba). *See* shares (Samba)**

**DirectoryIndex parameter, 724**

**disabled mode (SELinux), 477-481**

**disabling, root login, 848-849**

**discovering**

- iSCSI targets, 596-598

- shares (Samba), 815-816

- SMB shares, 523-525

**discovery process (iSCSI), 584**

**disk device types, 324-325**

**disk labels. *See* labels**

**disk sizes, 324**

**Display Configuration option, 467**

**displaying. *See* viewing**

**dmesg command, 374-375**

**Dmz default zone (firewalld), 503**

**DNS (Domain Name System)**

- cache-only DNS servers, 749

- configuration, 749-751*

- security issues, 749*

- hierarchy, 744

- lookups with, 745-747

- resource records, 747-748

- terminology, 745

- troubleshooting, 752-755

- client issues, 755*

- dig command, 753-754*

- dumping unbound cache, 753*

- trust anchors, 751-752

**DNS resolution, 198-200**

**DNSSEC (Domain Name System Security Extensions), 749**

**documentation files, 53**

**DocumentRoot parameter, 392, 726**

**Domain Name System. *See* DNS (Domain Name System)**

**Domain Name System Security Extensions (DNSSEC), 749**

**domains, 745**

- root domain, 744

- second-level domains, 744

- top-level domains, 744

**downloading, RPM packages, 275**

**dracut command, 439-442**

**dracut --force command, 244**

**drivers, 373**  
   checking availability, 381-383  
   loading, 376-378  
**Drop default zone (firewalld), 503**  
**dropping, caches, 614**  
**DST (daylight savings time), 542**  
**dumb terminals, 109**  
**dump utility, 343**  
**dumping unbound cache, 753**  
**dynamic content on websites**  
   CGI (Common Gateway Interface),  
     731-732  
   database connections, 733  
   PHP scripts, 732  
   Python scripts, 733  
**dynamic IP addresses, with fixed IP  
 addresses, 196**

## E

---

**e2label command, 341**  
**eatables service, 705**  
**echo \$? command, 687**  
**echo b > /proc/sysrq-trigger command,  
 112**  
**echo command, 46, 634**  
**editing**  
   configuration files, for user accounts,  
     132-133  
   files, with vim, 42-45  
   VM configuration files, 240  
**effective primary group, changing,  
 157-158**  
**elinks web browser, 395**  
**email**  
   mail handling  
     *email transmission process, 829-830*  
     *roles, 828*  
   Postfix  
     *configuring parameters, 832-838*  
     *null client setup, 837-838*  
     *processes, 830-832*  
   Sendmail, 830  
   troubleshooting, 838-840  
**emerg priority, 306**  
**emergency reset option, 112**  
**enabled mode (SELinux), 477-481**  
**enabling**  
   routing, 677-678  
   services, 418-419  
**End Of File (EOF) character, 209**  
**enforcing mode (SELinux), 477-481**  
**env command, 45**  
**ENV\_PATH property, 135**  
**environment**  
   course environment setup, 16-17  
   shell environment. *See shell environment*  
   user environments, creating, 136  
**EOF (End Of File) character, 209**  
**EPEL (Extra Packages for Enterprise  
 Linux), 253**  
**epoch time, 544**  
**error messages, STDERR, 37-39**  
**error priority, 306**  
**ErrorLog parameter, 724**  
**Esc (vim command), 43**  
**escaping, regular expressions, 95**  
**exam preparation, 875-878**  
**exam registration, 876**  
**excluding, iptables service, 705-706**  
**exec mount option, 343**  
**execute permission**  
   applying, 159-161  
   explained, 158-159  
**executing**  
   commands in shell, 36-37  
   scripts, 687  
   shell jobs, 208-209  
**exercises**  
   applying modifications to GRUB 2, 423  
   changing connection parameters with  
     nmcli, 192-193  
   changing Postfix parameters with  
     postconf command, 836  
   changing rsyslog.conf rules, 307-308  
   configuring a Samba server, 809-810  
   configuring direct and indirect maps to  
     mount NFS shares, 531-532

- configuring FTP anonymous drop box, 534-535
- configuring Kerberized NFS server, 793-795
- configuring Kerberos authorization, 570-571
- configuring multiuser SMB mounts, 818-819
- configuring network teaming, 669-670
- configuring port forwarding, 714
- configuring Postfix null client setup, 837-838
- configuring Samba server firewalling and SELinux, 812-813
- configuring SSH security options, 851
- configuring TFTP server for PXE boot, 459-461
- connecting to external LDAP server, 144-146
- connecting to remote server with public/private keys, 117
- creating a database, 772-773
- creating custom firewalld service, 707-708
- creating file system, 335
- creating GPT partitions with gdisk, 331-334
- creating logical partitions, 329-330
- creating MBR partitions with fdisk, 325-328
- creating physical MySQL database backup, 775-776
- creating physical volume, 355-357
- creating repositories, 259
- creating swap partition, 339
- creating user accounts, 136-137
- creating volume group and logical volumes, 361
- currently mounted devices, 65
- directory structure, 67-68
- discovering and mounting SMB shares, 525
- displaying system activity information with sar command, 622
- enabling NFS SELinux transparency, 796
- exploring troubleshooting targets, 436
- file management, 72-73
- finalizing iSCSI target configuration, 594-595
- firewall management with firewall-cmd command, 506-507
- firewall-config command usage, 510-511
- grep options, 97
- head and tail command usage, 90-91
- history file, 40
- if.then.else loops, 693
- info system, 52
- installing and configuring unbound caching name server, 749
- installing Apache virtual hosts, 399-400
- installing MariaDB, 766-767
- installing SELinux-specific man pages, 486
- installing VMs, 234-238
- internal and external command usage, 37
- I/O redirection and pipes, 39-40
- isolating targets, 419
- journalctl filtering options, 312-313
- journald journal permanence, 315
- less command usage, 89
- live log monitoring and logger command, 302-303
- loading kernel modules with parameters, 383-384
- local time management, 546-547
- logging into remote server with SSH, 113
- making iSCSI connections, 601-602
- man -k command, 51
- managing advanced permissions using ACLs, 168
- managing basic permissions, 161
- managing jobs, 210
- managing kernel modules from command line, 381
- managing network connections with nmcli, 192
- managing processes from command-line, 217
- managing time synchronization with chrony command, 870-871
- managing units with systemctl, 414
- manipulating SELinux modes, 479-480

- modifying kernel tunables through sysctl command, 636-637
- mounting NFS share, 521
- mounting partitions through /etc/fstab, 343
- mounting Samba shares through automount, 820
- mounting SMB file system, 816
- multiple terminals in graphical environment, 108
- network configuration validation, 187
- network settings validation, 188-189
- NFSv4 server configuration, 789-790
- package management with yum, 271
- performing virtual machine network installation with Kickstart file, 463
- pseudo terminals, 110
- relabeling files with restorecon command, 488
- remote logging setup, 649-650
- Rescue a Red Hat System option usage, 437
- resizing logical volumes, 365
- rich rule usage, 710-711
- RPM queries, 275-276
- running scheduled tasks through cron, 289-290
- scheduling jobs with at, 291
- SELinux Booleans, 490-491
- setting context label on nondefault Apache document root, 485-486
- setting up basic web server, 395
- setting up external authentication, 569-570
- setting up iSCSI target with targetcli utility, 585-588
- setting up network installation server, 454
- setting up server as KVM hypervisor host, 233
- shell environment management, 47
- surviving advanced Apache topics on RHCE test, 733
- switching user accounts, 128-129
- symbolic links and hard links, 76
- tab completion, 42
- tar command usage, 79-80
- temporarily changing /proc settings, 634
- troubleshooting mail servers, 839-840
- vim, 44-45
- working with groups, 139
- working with input, 691
- working with IPv6 addresses, 676-677
- working with positional parameters, 689
- working with special permissions, 164
- writing simple shell script, 687
- exit statement, 687**
- exports (NFS). See NFS shares**
- Ext2 file system, 334**
- Ext3 file system, 334**
- Ext4 file system, 334-338**
- extended partitions, creating, 329-330**
- Extended Support add-on, 15**
- external authentication**
  - Active Directory, 572
  - explained, 560-561
  - ipa client configuration, 572
  - LDAP. *See* LDAP (Lightweight Directory Access Protocol)
- external commands, 36**
- External default zone (firewalld), 503**
- Extra Packages for Enterprise Linux (EPEL), 253**
- extracting, archive contents, 78**
- extras repository type, 256**

## F

---

- facilities, 304-308**
- fdisk command, 325-328, 355**
- Fedora, 13**
- fg command, 209**
- FHS (Filesystem Hierarchy Standard), 60**
- Fibre Channel, iSCSI versus, 581-582**
- fields, in databases, 767**
- file command, 78**

**file management, 72-73**

- absolute and relative pathnames, 68-69
- archives, 76-77
  - creating*, 77
  - extracting contents*, 78
  - listing contents*, 77-78
  - tar command usage*, 79-80
- compression, 78-79
- copying files, 70-71
- creating links, 74-75
- deleting files, 71-72
- directories, 67-68
- hard links, 73-76
- listing files, 69-70
- moving files, 71
- removing links, 75-76
- symbolic links, 74, 76
- tab completion, 69
- wildcards, 67

**file system hierarchy**

- ACL support, 166
- directories
  - list of*, 60
  - mounting on dedicated devices*, 61-62
- mounting, 61-66
  - NFS shares*, 519-521
  - SMB shares*, 522-527
- SELinux. *See* SELinux
- troubleshooting boot problems, 442-443

**file systems**

- creating, 334-335
- managing
  - Ext4 file system properties*, 336-338
  - XFS file system properties*, 338
- mounting
  - automatically with /etc/fstab file*, 341-343
  - with device names, UUIDs, disk labels*, 340-341
  - information needed*, 339-340
  - manually*, 340
- resizing, 364-365
- types of, 334

**filenames, RPM packages, 272-273****files**

- adding to archives, 77
- copying, 70-71
- deleting, 71-72, 163
- editing, with vim, 42-45
- hidden
  - copying*, 71
  - viewing*, 70
- listing, 69-70
- moving, 71
- ownership
  - changing*, 156-157
  - default ownership*, 157-158
  - viewing*, 155-156
- permissions
  - advanced permissions*, 161-164
  - applying*, 159-161
  - drawbacks of*, 472
  - explained*, 158-159
  - setting default*, 169-170
- renaming, 71
- sharing, NFS (Network File System). *See* NFS (Network File System)
- transferring securely, 115-116
- user extended attributes, 170-172

**Filesystem Hierarchy Standard (FHS), 60****filtering text files**

- awk command, 97-98
- cut command, 91
- head command, 90-91
- sed command, 97-98
- tail command, 90-91

**find command, 156****finding**

- context types (SELinux), 486
- man pages, 49-50

**findmnt command, 64-65****Firewall Configuration option, 467**

- firewall-cmd --add-port=3260/tcp --permanent command, 595**

**firewall-cmd** command, 506-507, 788, 812  
 masquerading configuration, 712  
 options, 507  
 port forwarding configuration, 713-714  
 rich rules, 709-711

**firewall-cmd --get-services** command, 504, 706

**firewall-cmd --list-all** command, 595

**firewall-cmd --reload** command, 595

**firewall-config** command, 508-511, 714

**firewalld** service, 502-503  
 configuration, 505  
   *firewall-cmd* command, 506-507  
   *firewall-config* command, 508-511  
 rich rules  
   *configuration*, 709-711  
   *explained*, 708  
   *logging*, 711  
   *ordering*, 709  
   *syntax*, 708-709  
 services  
   *creating*, 706-708  
   *explained*, 504-505  
 zones, 503

**firewalls**  
 configuration, for NFSv4, 788  
 ebtables service, 705  
 firewalld service, 502-503  
   *configuration*, 505-511  
   *rich rules*, 708-711  
   *services*, 504-505, 706-708  
   *zones*, 503  
 iptables service, 502, 705-706  
 NAT configuration, 711-712  
   *masquerading*, 712  
   *port forwarding*, 713-714  
 netfilter, 502  
 in NFSv4, 786, 787-788  
 opening  
   *for iSCSI target*, 594-595  
   *for MariaDB network access*, 766  
 Samba file servers, 811-813

fixed IP addresses, 196  
 fixing, problems. *See* troubleshooting

**FLUSH PRIVILEGES** command, 772

for loops, 689, 693-694

forced reset option, 112

foreground jobs, running, 208-209

formatting, partitions, with file systems, 334-335

forwarders, configuration, 749

FQDN (fully qualified domain name), 196

free -m command, 614

free parameter (memory usage), 612

FreeIPA, 140

fs tunable directory, 633

fsck command, 442

fstab file. *See* /etc/fstab file

FTP servers, configuration, 533-535

fully qualified domain name (FQDN), 196

## G

---

G (vim command), 43

gdisk command, 325, 330-334

getenforce command, 478

getent hosts command, 200

getfacl command, 166-168

getsebool -a command, 489

gg (vim command), 43

gibibyte (GiB), 324

GID field (/etc/passwd file), 130

gigabyte (GB), 324

####GLOBAL DIRECTIVES####  
 section (rsyslog), 304

GNOME Boxes utility, 241

gpasswd command, 158

GPG keys, 256-258

gpgcheck= option, 255

gpgkey= option, 255

GPT (Guid Partition Table) partitions, 323, 330-334

GRANT command, 771-772

**granting permissions**  
 administrator permissions, 128  
 in databases, 771-772

**graphical applications, in SSH (Secure Shell), 114-115**

**graphical environment, switching terminals, 107-108**

**graphical interface, mounting SMB shares, 526-527**

**graphical tools, for time management, 550**

**grep command, 96-97**

**group access, Apache private directories, 735-736**

**group accounts**  
 configuration files, 138  
 creating, 138  
     *groupadd command, 138*  
     *vigr command, 138*  
 property management, 139  
 types of, 137

**group owners**  
 ACLs, viewing and changing, 166-168  
 changing, 156-157  
 default ownership, changing, 157-158  
 viewing, 155-156

**groupadd command, 138**

**grouping, software packages, 268-270**

**groupmems command, 139**

**groupmod command, 139**

**groups. See volume groups**

**groups command, 157**

**GRUB 2 boot loader**  
 accessing boot prompt, 434-435  
 entering troubleshooting options, 435-436  
 explained, 420-423  
 modifying options, 423  
 reinstalling, 439-442

**GRUB\_CMDLINE\_LINUX parameter, 423**

**GRUB\_TIMEOUT parameter, 423**

**grubby command, 241**

**GSSAPIAuthentication option, 852-853**

**guest ok directive, 807**

**guest user, mounting SMB shares as, 525**

**Guid Partition Table (GPT) partitions, 323, 330-334**

**gunzip command, 79**

**gzip command, 78-79**

## H

---

**hard links, 73**  
 creating, 74-75  
 removing, 75-76

**hardware clock, 542**  
 hwclock command, 544-545  
 increasing reliability, 543

**hardware devices, checking driver availability, 381-383**

**hardware initialization, 376-378**

**hardware iSCSI, software iSCSI versus, 582**

**head command, 88-91, 379**

**help resources**  
 for commands, 47  
     *documentation files, 53*  
     *--help option, 48*  
     *info system, 51-52*  
     *man pages, 48-51*  
 httpd-manual RPM package, 728, 733-735

**hexadecimal IP addresses, 459**

**hi parameter (CPU usage), 611**

**hidden files**  
 copying, 71  
 viewing, 70

**High Availability add-on, 15**

**high-availability clusters, 576**

**High-Performance Computing (HPC), server variants, 14**

**history file, 40**

**history list, for yum actions, 270-271**

**Home default zone (firewalld), 503**

**home directories, 133-134**

**host allow Samba parameter, 806**

hostnamectl command, 197, 634  
 hostnamectl status command, 197, 375  
 hostnames, 196-198  
 hosts, 180  
   KVM hosts  
     *networking configuration*, 233-234  
     *system requirements*, 231-232  
 HPC (High-Performance Computing),  
   server variants, 14  
 httpd software package, 392  
 httpd.conf file, 397  
 httpd-manual RPM package, 728,  
   733-735  
 hwclock -c command, 544  
 hwclock command, 543-545  
 hwclock --hctosys command, 544  
 hwclock --systohc command, 544  
 hypervisor-based virtualization,  
   desktop-based virtualization  
   versus, 228

## I

---

i (vim command), 43  
 i attribute, 171  
 I attribute, 171  
 IBM Power, server variants, 14  
 IBM System z, server variants, 14  
 id command, 126  
 id parameter (CPU usage), 611  
 identity management (IdM), 561  
 identity management systems, explained,  
   560-561  
 IdM (identity management), 561  
 ifcfg configuration files, 195-196  
 ifconfig utility, 185  
 if.then.else loops, 690-693  
 imfile (input module file) module, 645  
 inactive memory, 613  
 Include parameter, 724  
 IncludeOptional parameter, 724  
 index.html files, 395  
 indirect mounts, 531-532  
 inet\_interfaces Postfix parameter,  
   833-834  
 inet\_protocols Postfix parameter,  
   833, 835  
 info priority, 306  
 info system, 51-52  
 init=/bin/bash boot option, 435  
 init=/bin/sh boot option, 435  
 initializing, hardware, 376-378  
 initiatorname, setting, 596  
 initiators (iSCSI), 584  
   configuration, 596-598  
   connecting to target, 598-602  
     *mounting iSCSI devices*, 601-602  
     *persistent mounts*, 600-601  
 initramfs, 420, 439-442  
 inodes, 73  
 input mode (vim), 43  
 input modules, 644  
 INSERT command, 770  
 insmod command, 381  
 installation server setup, 454  
   Kickstart files, 462  
     *automated installation with*, 462-463  
     *manual modifications*, 467-469  
     *modifying with system-config-kickstart*  
       *graphical interface*, 464-467  
   network server configuration, 454  
   PXE boot configuration, 455-456  
     *creating TFTP PXE server content*,  
       458-462  
     *DHCP server configuration*, 457-458  
     *TFTP server installation*, 456-457  
 installation source settings, RHEL 7  
   installation, 21  
 installing  
   Apache virtual hosts, 398-400  
   Apache web server software, 392  
   KVM software, 232-233  
   MariaDB, 762-767  
   RHEL 7 Server, 17-29. *See also*  
     installation server setup  
   Samba, 804  
   sealert command, 492

- SELinux-specific man pages, 486
- semanage command, 483
- software packages, 263-265, 271-272
- TFTP servers, 456-457
- VMs, 234-240
- internal clock, 864**
- internal commands, 36**
- Internal default zone (firewalld), 503**
- Internet Protocol (IP) addresses. *See* IP addresses**
- I/O redirection**
  - pipes, 39-40
  - STDIN, STDOUT, STDERR, 37-39
- iostat command, 616-618**
- ip addr show command, 185, 676**
- IP addresses**
  - binary notation, 182-183
  - dual fixed and dynamic IP addresses, 196
  - hexadecimal values, 459
  - IPv6 addresses, 181
  - managing, 183
  - network masks, 181
  - terminology, 180-181
  - versions, 180
- IP-based virtual hosts, 399**
- ip link set command, 186**
- ip link show command, 186**
- IP masquerading, configuration, 712**
- ip route show command, 187, 676, 678**
- ip utility, 185-187**
- ipa clients, configuration, 572**
- IPA servers, client configuration, 572**
- ipa-client-install utility, 572**
- iptables service, 502, 505, 705-706**
- IPv4 addresses, 180**
  - broadcast addresses, 181
  - private network addresses, 180-181
- IPv6 addresses, 180-181**
  - common addresses, 673
  - configuration, 675-676
  - explained, 673-675
  - managing, 676-677
  - troubleshooting, 676

- IQN (iSCSI qualified name), 584, 587**
- iSCSI**
  - architecture, 582-584
  - connecting to target, 598-602
    - mounting iSCSI devices, 601-602*
    - persistent mounts, 600-601*
  - Fibre Channel versus, 581-582
  - hardware versus software solutions, 582
  - initiator configuration, 596-598
  - target configuration, 585-595
  - terminology, 584
  - troubleshooting, 602-603
- iSCSI qualified name (IQN). *See* IQN (iSCSI qualified name)**
- iscsi service, 596**
- iscsiadm command, 584, 596-598**
- iscsiadm -m session -P 3 command, 603**
- iscsiadm --mode node -P command, 598**
- iscsid service, 596**
- isolating, target units, 419**

## J

---

- j attribute, 171**
- jobs, scheduling. *See* scheduling tasks**
- jobs command, 209**
- journalctl command, 298, 310-314**
- journalctl --dmesg command, 374**
- journalctl -k command, 374**
- journalctl -o verbose command, 313**
- journald process, 298, 310**
  - connecting to rsyslog, 646-648
  - journalctl command, 310-314
  - permanent journal storage, 314-316
  - role of, 298-299

## K

---

- kcore file, 631**
- KDC (Key Distribution Center), 562**
- Kdump, 29**

**Kerberos, 560-561**

- explained, 561-562
- LDAP configuration with, 564-568
- on NFS servers, 786
  - configuration, 791-794*
- NFS share mounts, 520-521
- principals, 563-564
- on Samba shares, 813-815
- time synchronization, importance of, 862

**kern facility, 305****kernel, 372, 420**

- analyzing, 374-375
  - boot arguments, passing, 434
  - drivers, 373
    - checking availability, 381-383*
    - loading, 376-378*
  - modules, 375-376
    - checking driver availability, 381-383*
    - hardware initialization, 376-378*
    - managing, 378-381*
    - parameter management, 383-384*
  - performance optimization. *See* performance optimization
  - threads, 211-212, 372-373
  - upgrading, 267, 384
- kernel ring buffer, 374**
- kernel tunable directory, 633**
- Kernel Virtual Machine. *See* KVM (Kernel Virtual Machine)**
- kernel.hostname tunable, 637**
- Key Distribution Center (KDC), 562**
- key-based authentication, in SSH, 116-118, 853-854**
- keyboard settings, RHEL 7 installation, 18-21**
- keytab files, 520, 792, 793**
- creating, 813-814
  - viewing contents, 563-564
- KiB Mem parameter (memory usage), 612**
- kibibyte (KiB), 324**
- Kickstart files, 462**
- automated installation with, 462-463
  - manual modifications, 467-469

- modifying with system-config-kickstart graphical interface, 464-467

**kill command, 211, 216-217****killall command, 217****kilobyte (KB), 324****kiosk exam registration, 876****klist command, 792****klist -k command, 814****kpartx -a command, 445****krb5 security option, 520****krb5i security option, 520, 792****krb5p security option, 520****KVM (Kernel Virtual Machine), 228**

- host requirements, 231-232
- installing software, 232-233
- networking configuration, 233-234
- VM access
  - with libvirt, 229-231*
  - methods of, 240-242*

**L****labels**

- for file systems, 337
- mounting file systems, 340-341
- SELinux, 477, 481
  - finding context types, 486*
  - monitoring, 481-482*
  - relabeling, 487-488*
  - setting context types, 483-486*

**lacp runner, 663****LANG variable, 45****language settings, RHEL 7 installation, 18, 21****launching, browsers, 395****LDAP (Lightweight Directory Access Protocol), 560-561**

- configuration, with Kerberos authorization, 564-568-
- connecting to server, 144-146
- explained, 140-142
- nsld service management, 143
- platform configuration, 142

- RHEL 7 configuration for, 142
- sssd service management, 144
- less command**, 39, 88-89, 379
- libvirtd**, 229-231
- license agreement, accepting**, 29
- Lightweight Directory Access Protocol (LDAP)**. *See* LDAP (Lightweight Directory Access Protocol)
- limiting user access**. *See* access control
- line anchors**, 94-95
- lines, counting, in text files**, 93
- link-local addresses**, 674
- links**
  - creating, 74-75
  - hard links, 73-76
  - removing, 75-76
  - symbolic links, 74-76
- Linux, 11**. *See also* RHEL 7 Server (Red Hat Enterprise Linux 7 Server)
- Linux I/O (LIO) target**, 585
- LIO (Linux I/O) target**, 585
- Listen parameter**, 724
- listening ports**, 188
  - SELinux settings, 849-850
  - SSH configuration, 849
- listing**
  - archive contents, 77-78
  - cron jobs, 289
  - files, 69-70
  - kernel modules, 379
  - package groups, 268-269
  - shares (Samba), 815-816
  - software packages, 265-266
- list-timezone command**, 545
- live log file monitoring**, 302-303
- ln command**, 74
- ln -s command**, 74
- load average**, 610-611
- load printers Samba parameter**, 806
- load\_policy -i command**, 443
- loadbalance runner**, 663
- loading**
  - drivers, 376-378
  - kernel modules, 378, 381-384
- local authoritative data**, 746
- local cached nonauthoritative data**, 746
- local consoles, login**, 106-107
- local time**, 542
  - managing, 546-547
  - time zone settings, 548-549
- local\_transport Postfix parameter**, 833, 835
- local0-7 facilities**, 305
- log file Samba parameter**, 806
- log files**
  - journald process, 310
    - connecting to rsyslog*, 646-648
    - journalctl command*, 310-314
    - permanent journal storage*, 314-316
    - role of*, 298-299
  - reading
    - list of files*, 300
    - live monitoring*, 302-303
    - sample contents*, 300-302
  - remote logging, 648
    - configuration*, 649-650
    - reasons for using*, 648-649
  - rich rules, 711
  - rotating, 308-310
  - rsyslogd modules
    - configuration*, 645-646
    - reasons for using*, 644-645
    - types of*, 644
  - rsyslogd process
    - configuration*, 303-308
    - connecting to journald*, 646-648
    - role of*, 298-299
  - SELinux, analyzing, 491-494
  - types of logging, 298
- log reception, enabling**, 650
- logger command**, 302-303
- logical backups**, 774
- logical extents**, 365
- logical partitions, creating**, 329-330
- logical unit number (LUN)**. *See* LUN (logical unit number)

**Logical Volume Manager (LVM).** *See*  
**LVM (Logical Volume Manager)**

**logical volumes**

- creating, 354-355
  - device names, 361*
  - physical volume creation, 355-358*
  - volume group creation, 359-361*
  - volume size, 360-361*
- LVM architecture, 352-353
- resizing, 353, 363-365
  - file system resizing, 364-365*
  - volume group resizing, 363-364*

**login**

- iSCSI, 584
- key-based login, with SSH, 116-118,  
853-854
- local consoles, 106-107
- remote access, with SSH, 112-114
- root login, disabling, 848-849

**login shells, 46, 127**

**LogLevel parameter, 724**

**logrotate command, 308-310, 648**

**logrotate service, 284**

**lookups, with DNS (Domain Name  
 System), 745-747**

**loops**

- case loops, 696-697
- for loops, 689, 693-694
- if.then.else loops, 690-693
- types of, 691-692
- until loops, 696
- while loops, 695-696

**lpr facility, 305**

**ls -a command, 69**

**ls command, 39, 69-70, 602**

**ls -d command, 69**

**ls -l command, 69, 75, 155, 167**

**ls -lrt command, 69**

**lsattr command, 172**

**lsblk command, 358**

**lsmod command, 378-379**

**lspci -k command, 381-383**

**ls-R command, 69**

**lsscsi command, 599**

**LUN (logical unit number), 584, 588**

**lvcreate command, 360-362**

**lvdisplay command, 362**

**lvextend command, 364**

**LVM (Logical Volume Manager), 352**

architecture, 352-353

features, 353-354

logical volumes

*creating, 354-362*

*resizing, 363-365*

**LVM volumes, snapshots of, 774-775**

**lvresize command, 364-365**

**lvs command, 362, 445**

## M

---

**MAC addresses, 183**

**magic file, 397**

**mail command, 696**

**mail facility, 305**

**mail handling**

email transmission process, 829-830

roles, 828

**mail servers**

email transmission process, 829-830

Postfix

*configuring parameters, 832-838*

*null client setup, 837-838*

*processes, 830-832*

Sendmail, 830

troubleshooting, 838-840

**mail user agent (MUA), 828**

**man -f command, 50**

**man -k \_selinux command, 486**

**man -k command, 49-51**

**man nmcli-examples command, 659**

**man pages, 48-49**

finding, 49-50

mandb updates, 50-51

for NFS versions, 794

SELinux-specific pages, installing, 486

**managing**

- cron service security, 289
- dependencies, 415-418
- file systems
  - Ext4 file system properties*, 336-338
  - XFS file system properties*, 338
- files, 72-73
  - absolute and relative pathnames*, 68-69
  - archives*, 76-80
  - compression*, 78-79
  - copying files*, 70-71
  - creating links*, 74-75
  - deleting files*, 71-72
  - directories*, 67-68
  - hard links*, 73-76
  - listing files*, 69-70
  - moving files*, 71
  - removing links*, 75-76
  - symbolic links*, 74, 76
  - tab completion*, 69
  - wildcards*, 67
- IP addresses, 183
- IPv6 addresses, 676-677
- kernel modules, 378-384
- network connections
  - with nmcli*, 192
  - with nmtui*, 193-195
- parent-child processes, 211
- permissions
  - advanced permissions*, 161-164
  - read/write/execute*, 158-161
- processes. *See* process management
- shell environment, 47
- shell jobs, 209-211
- software packages
  - creating repositories*, 259-260
  - downloading RPM packages*, 275
  - finding packages*, 261-262
  - history list*, 270-271
  - information about packages*, 262-263
  - installing packages*, 263-265
  - listing packages*, 265-266
  - package groups*, 268-270

- removing packages*, 265
- repoquery command*, 275
- repositories, explained*, 252-253
- repository security*, 256-258
- rpm command*, 271-272
- rpm database queries*, 273
- RPM filenames*, 272-273
- rpm package file queries*, 273-276
- specifying which repository to use*, 253-256
- updating packages*, 267
- with yum command*, 271
- yum command tasks*, 260
- target units, 418-419
- time
  - commands, list of*, 543
  - date command*, 544
  - hwclock command*, 544-545
  - timedatectl command*, 545-548
- units (systemd), 413-415
- VMs (virtual machines)
  - from command-line*, 243-244
  - in Virtual Machine Manager*, 242-243

**mandb updates, 50-51****MariaDB**

- backup and restore procedure, 773-776
- configuration, 762-767
- dynamic content, 733
- installing, 762-767
- network access, 765-766
- security, 763-764
- terminology, 767

**mark facility, 305****masquerading, configuration, 712****master process (Postfix), 831****MaxAuthTries option, 850-853****MaxSessions option, 852-853****MBR (Master Boot Record) partitions, 322-323**

- creating, 325-328
- extended and logical partitions, 329-330

**MDA (message delivery agent), 828****measurement units, 324****mebibyte (MiB), 324**

- megabyte (MB), 324
- meminfo file, 631
- memory usage, 612-613. *See also* process memory usage; swap usage
- message delivery agent (MDA), 828
- message transfer agent (MTA), 828
- mirrorlist= option, 255
- mkdir command, 68
- mkfs command, 335
- mod probe -r command, 378, 381
- mod\_php Apache module, 732
- mod\_wsgi Apache module, 733
- modes, SELinux, 477-481
- modinfo command, 378-381
- modprobe command, 378, 381
- modules
  - Apache web server modules, 398
  - kernel modules, 375-376
    - checking driver availability, 381-383
    - hardware initialization, 376-378
    - managing, 378-381
    - parameter management, 383-384
  - rsyslogd
    - configuration, 645-646
    - reasons for using, 644-645
    - types of, 644
- modules file, 631
- ####MODULES#### section (rsyslog), 304
- monitoring, SELinux context labels, 481-482
- monitoring performance. *See* performance monitoring
- more command, 89
- MOTD\_FILE property, 135
- mount command, 62-63, 340, 525, 787, 816
- mount units, 410, 442-443
- mounting, 61-66
  - file systems
    - automatically with /etc/fstab file, 341-343
    - with device names, UUIDs, disk labels, 340-341
    - information needed, 339-340
    - manually, 340
- iSCSI devices, 601-602
- NFS shares, 519, 521
  - /etc/fstab file, 787
  - with automount, 531-532
  - Kerberos requirements, 520-521
  - NFS version support, 521
  - persistent mounts, 788
  - pseudo root mounts, 519
  - security options, 519-520
  - systemd process, 790-791
  - testing access, 787-788
  - via /etc/fstab file, 528
- shares (Samba), 816
  - automount mounts, 819-820
  - multiuser mounts, 817-819
- SMB shares, 522-525
  - with automount, 533
  - as guest, 525
  - user authentication, 525
  - via /etc/fstab file, 529-530
  - via graphical interface, 526-527
- moving files, 71
- mpstat command, 616
- MTA (message transfer agent), 828
- MUA (mail user agent), 828
- multicast addresses, 675
- multiple terminals
  - in graphical environment, 107-108
  - in nongraphical environment, 108-109
  - switching, with screen command, 118-119
- multipliers, in regular expressions, 95-96
- multitasking, context switches, 620
- multiuser Samba mounts, 817-819
- multi-user.target file, 412
- mv command, 71
- MX resource record type, 748
- mydestination Postfix parameter, 833, 835
- mynetworks Postfix parameter, 833, 835
- myorigin Postfix parameter, 833-834
- MySQL. *See* databases

**mysql\_secure\_installation** command, 763-764  
**mysqldump** command, 774

## N

---

**name servers**  
 defined, 745  
 resolving DNS queries, 745-747

**name=** option, 255

**name-based virtual hosts**, 398

**naming conventions**  
 device names. *See* device names  
 initiatorname, 596  
 network cards, 184

**NAS (network-attached storage), SANs (storage-area networks) versus**, 578

**NAT (Network Address Translation), 181**  
 configuration, 711-712  
*masquerading*, 712  
*port forwarding*, 713-714

**net share -l** command, 524

**net tunable directory**, 633

**netfilter**, firewalls, 502

**net.ipv4.icmp\_echo\_ignore\_all** tunable, 637

**net.ipv4.icmp\_echo\_ignore\_broadcasts** tunable, 637

**net.ipv4.ip\_forward** tunable, 637

**netstat** command, 187

**netstat -tulpen | grep 123** command, 863

**Network Address Translation (NAT).** *See* NAT (Network Address Translation)

**network addresses**, 181  
 managing, 183  
 validating configuration, 185-187

**network bonding**  
 configuration, 658-662  
 network teaming versus, 658

**network cards, naming conventions**, 184

**Network Configuration option**, 467

**Network File System (NFS)**, 785

**network masks**, 181  
 binary notation, 182-183

**network servers, configuring as installation servers**, 454

**network teaming**  
 configuration, 663-671  
 network bonding versus, 658  
 runners, 663  
 troubleshooting, 671-672

**Network Time Protocol (NTP).** *See* NTP (Network Time Protocol)

**network-attached storage (NAS), SANs (storage-area networks) versus**, 578

**networking**  
 aggregated network interfaces, 658  
*network bonding*, 658-662  
*network teaming*, 663-672

configuration  
*configuration files*, 195-196  
*DNS resolution*, 198-200  
*hostnames*, 196-198  
*for KVM hosts*, 233-234  
*with NetworkManager service*, 189  
*with nmcli*, 189-193  
*with nmtui*, 193-195  
*during RHEL 7 installation*, 26

DNS. *See* DNS (Domain Name System)

IP addresses  
*binary notation*, 182-183  
*IPv6 addresses*, 181  
*managing*, 183  
*network masks*, 181  
*terminology*, 180-181  
*versions*, 180

IPv6 addresses  
*common addresses*, 673  
*configuration*, 675-676  
*explained*, 673-675  
*managing*, 676-677  
*troubleshooting*, 676

MAC addresses, 183

MariaDB access configuration, 765-766

network cards, naming conventions, 184

- port addresses, 183
- protocols, 183
- routing, configuration, 677-679
- validation
  - network address configuration, 185-187*
  - network settings, 187-189*
  - routing, 187*
- NetworkManager service, 189**
- NetworkManager utility, custom route configuration, 678**
- newgrp command, 157-158**
- news facility, 305**
- NFS (Network File System), 785**
- NFS servers**
  - Kerberos on, 786
    - configuration, 791-794*
- NFS shares**
  - creating, 786-787
  - mounting, 519-521
    - /etc/fstab file, 787*
    - with automount, 531-532*
    - Kerberos requirements, 520-521*
    - NFS version support, 521*
    - pseudo root mounts, 519*
    - security options, 519-520*
    - systemd process, 790-791*
    - via /etc/fstab file, 528*
  - persistent mounts, 788
  - testing access, 787-788
- nfsiostat command, 616**
- nfs-secure service, 792**
- nfs-secure-server service, 792**
- nfs-server service, 792**
- NFSv4 servers**
  - configuration, 789-790
    - creating exports, 786-787*
    - firewall configuration, 788*
    - new features, 785-786*
    - SELinux configuration, 788-789*
    - SELinux transparency, 795-796*
  - shares
    - mounting, 787, 790-791*
    - persistent mounts, 788*
    - testing access, 787-788*
- ni parameter (CPU usage), 611**
- nice command, 214-216**
- NIS, 560**
- NIS+, 560**
- nmap package, 262-263**
- nmcli command, 189-193**
  - IPv6 address configuration, 675-676
  - network bonding configuration, 658-660
  - network teaming configuration, 663-666
- nmcli con add command, 192**
- nmcli con mod command, 192-193**
- nmcli con reload command, 196**
- nmcli con show command, 190**
- nmcli dev show command, 192**
- nmcli dev status command, 192**
- nm-connection-editor command, 194**
- nmtui command, 193-197, 658, 678**
- noatime mount option, 343**
- noauto mount option, 343**
- nodes, 180**
- NOERROR status indicator, 754**
- noexec mount option, 343**
- nohup command, 211**
- nondisclosure agreement, 878**
- none security option, 520, 791**
- nonvoluntary context switches, 620**
- notice priority, 306**
- NS resource record type, 748**
- nsLCD service, 568**
  - as authentication backend service, 142, 568
  - managing, 143
- NTFS file system, 334**
- NTP (Network Time Protocol), 543**
  - explained, 863-864
  - managing, 546
- ntpd process, 546, 862-863**
- null clients, 828**
  - configuration, 837-838
  - troubleshooting, 838-840
- numbers, in regular expressions, 95**
- NXDOMAIN status indicator, 754**

## O

---

o (vim command), 43  
 ommysql module, 646  
 open source drivers, closed source  
   drivers versus, 373  
 opening firewalls  
   for iSCSI target, 594-595  
   for MariaDB network access, 766  
 OpenLDAP, 140  
 OpenStack, 229  
 operators, WHERE clause, 770  
 optimization. *See* performance  
   optimization  
 optional repository type, 256  
 Options parameter, 724  
 ordering, rich rules, 709  
 output modules, 644-645  
 ownership  
   changing  
     *group owners*, 156-157  
     *user owners*, 156  
   default ownership, 157-158  
   viewing, 155-156

## P

---

p (vim command), 43  
 Package Selection option, 467  
 packages. *See* software packages  
 page cache, explained, 613  
 panic priority, 306  
 parameters, kernel modules, 380,  
   383-384  
 parameters (Postfix), configuration,  
   832-838  
 parent-child processes  
   managing, 211  
   terminating, 216  
 Partition Information option, 466

partitioning settings, RHEL 7  
   installation, 23-26  
 partitions, 322  
   disk device types, 324-325  
   formatting, with file systems, 334-335  
   GPT (Guid Partition Table) partitions,  
     323, 330-334  
   LVM (Logical Volume Manager). *See*  
     LVM (Logical Volume Manager)  
   MBR (Master Boot Record) partitions,  
     322-323  
     *creating*, 325-328  
     *extended and logical partitions*, 329-330  
   mounting  
     *automatically with /etc/fstab file*,  
       341-343  
     *information needed*, 339-340  
   swap partitions, creating, 338-339  
 partitions file, 631  
 partprobe command, 328-330  
 PASS\_MAX\_DAYS property, 135  
 PASS\_MIN\_DAYS property, 135  
 PASS\_WARN\_AGE property, 135  
 passing, kernel boot arguments, 434  
 passphrases, 117, 853-854  
 passwd command, 134-135  
 password field (/etc/passwd file), 130  
 PasswordAuthentication option, 853  
 passwords  
   changing, permissions needed, 161-162  
   property management, 135-136  
   RHEL 7 installation, 28  
   root password, resetting, 443-444  
 path directive, 807  
 pathnames  
   absolute pathnames, 68-69  
   relative pathnames, 68-69  
 pausing, shell jobs, 209  
 PCI devices, checking driver availability,  
   381-383  
 pdbedit command, 809

- performance monitoring. *See also* process management**
- sar command, 621-622
- top command, 610
  - CPU usage*, 611
  - customizing display*, 615-616
  - load average*, 610-611
  - memory usage*, 612-613
  - process memory usage*, 615
  - swap usage*, 613-615
- utilities
  - iostat*, 617-618
  - list of*, 616
  - pidstat*, 620
  - vmstat*, 618-619
- performance optimization, 630. *See also* process management**
- /proc file system, 631
  - /proc/sys directory parameters*, 633-634
  - configuration files*, 631
  - PID (process ID) directories*, 632-633
  - sysctl command*, 635-637
- permanent journal storage, 314-316**
- permissions**
  - ACLs, 165
    - backing up*, 166
    - default ACLs*, 168
    - to DocumentRoot*, 726
    - file system preparation*, 166
    - viewing and changing*, 166-168
  - advanced permissions
    - applying*, 164
    - explained*, 161-163
  - copying files, 71
  - default permissions, setting with umask, 169-170
  - file permissions, drawbacks of, 472
  - granting
    - administrator permissions*, 128
    - in databases*, 771-772
  - ownership settings, viewing, 155-156
  - read/write/execute
    - applying*, 159-161
    - explained*, 158-159
    - on Samba shares, 807-808
    - on shared directories, preparing for Samba file servers, 804-805
- permissive mode (SELinux), 477-481**
- PermitRootLogin option, 853**
- persistent mounts (iSCSI), 600-602**
- persistent mounts (NFS), 788**
- pgrep command, 214**
- PHP scripts, 732**
- physical backups, 774-776**
- physical extent size, 359**
- physical volumes, creating, 355-358**
- pickup process (Postfix), 831**
- PID (process ID), 214**
- PID (process ID) directories, 632-633**
- pidstat command, 616, 620**
- pinfo command, 51-52**
- ping6 command, 676**
- pipes, 39-40, 88**
- pkill command, 217**
- policies, SELinux, 477**
- PolicyKit, 127-128**
- port addresses, 183, 187-189**
- port forwarding**
  - configuration, 713-714
  - SSH tunneling configuration, 854-855
- Port option, 853**
- portals, 584, 589**
- ports. *See* listening ports**
- positional parameters, in shell scripts, 688-689**
- postconf command, 832-836**
- Postfix**
  - configuring parameters, 832-838
  - null client setup, 837-838
  - processes, 830-832
  - troubleshooting, 838-840
- Post-Installation Script option, 467**
- postqueue -f command, 839**
- postqueue -p command, 839**
- postsuper -d command, 840**
- Pre-Installation Script option, 467**
- preparation for exam, 875-878**
- primary groups, 137**

**principals (Kerberos), 563-564**

**priorities, 304-308**  
 list of, 306  
 of processes, changing, 214-216

**private directories, Apache web servers, 735-736**

**private network addresses, 180-181**

**privileged user accounts**  
 unprivileged versus, 126  
 working as, 126-127  
*PolicyKit, 128*  
*su command, 127*  
*sudo command, 128*  
*switching user accounts, 128-129*

**privileges. See permissions**

**problem-solving. See troubleshooting**

**process ID (PID), 214**

**process ID (PID) directories, 632-633**

**process management. See also performance monitoring; performance optimization**  
 changing priorities, 214-216  
 exercises, 217  
 kernel threads, 211-212  
 ps command, 212-214  
 shell jobs  
*foreground versus background jobs, 208-209*  
*managing, 209-211*  
*parent-child management, 211*  
 terminating processes, 216-217  
 terminology, 208  
 top command, 218-220

**process memory usage, 615**

**processes, Postfix, 830-832**

**property management**  
 for group accounts, 139  
 for user accounts, 134  
*default properties, 134-135*  
*passwords, 135-136*

**protected software packages, 265**

**protocols, networking, 183**

**ps aux | grep dd command, 214**

**ps aux command, 212, 372-373**

**ps command, 212-214**

**ps -ef command, 213**

**ps fax command, 213**

**pseudo root mounts, 519, 785**

**pseudo terminals, 109-110**

**PTR resource record type, 748**

**Public default zone (firewalld), 503**

**PuTTY, 112**

**pvcreate command, 362**

**pvcreate --help command, 354-355**

**pvdisplay command, 358, 362**

**pvs command, 356, 362**

**pvscan command, 445**

**pwd command, 67**

**PXE boot configuration, 455-456**  
 creating TFTP PXE server content, 458-462  
 DHCP server configuration, 457-458  
 TFTP server installation, 456-457

**Python scripts, 733**

---

## Q

**QEMU (Quick Emulator), 228**

**qmgr process (Postfix), 831**

**querying**  
 rpm database, 273  
 rpm package files, 273-276

**quotation marks ( ' '), escaping regular expressions, 95**

---

## R

**r command (top utility), 215**

**rd.break boot option, 435**

**read command, 689-691**

**read only directive, 807**

**read permission**  
 applying, 159-161  
 explained, 158-159

- reading. *See also* viewing
  - exam questions, 877
  - log files
    - list of files*, 300
    - live monitoring*, 302-303
    - sample contents*, 300-302
- realm command, 572
- realms (Kerberos), 562
- real-time clock, 542
- rebooting
  - during exam, 111, 878
  - RHEL 7 Server, 110-112
- records, in databases, 767
- recovering. *See* restoring
- recurring tasks, scheduling. *See* cron service
- recursive option on commands, 71, 156, 168
- Red Hat Enterprise Linux 7 Server. *See* RHEL 7 Server (Red Hat Enterprise Linux 7 Server)
- Red Hat Enterprise Virtualization (RHEV), 229
- Red Hat Network (RHN), registering with, 253
- Red Hat Package Manager (RPM)
  - format, 252
  - database queries, 273
  - downloading packages, 275
  - filenames, 272-273
  - package file queries, 273-276
- redirection. *See* I/O redirection
- redundant network architecture, 583
- reference clock, 863
- registering, with RHN (Red Hat Network), 253
- registration for exam, 876
- regular expressions, 93-96
  - escaping, 95
  - grep command, 96-97
  - line anchors, 94-95
  - wildcards and multipliers, 95-96
- reinstalling, GRUB 2 boot loader, 439-442
- relabeling, file system (SELinux), 487-488
- relative mode, applying permissions, 159-161
- relative pathnames, 68-69
- relayhost Postfix parameter, 833-834
- remote access, SSH (Secure Shell), 112-114
- remote authentication
  - Active Directory, 572
  - explained, 560-561
  - ipa client configuration, 572
  - LDAP, with Kerberos authorization, 564-568
- remote logging, 648
  - configuration, 649-650
  - reasons for using, 648-649
- remote non-authoritative data via recursion, 746
- remote-fs.target systemd unit, 788
- removing
  - links, 75-76
  - software packages, 265
- renaming files, 71
- renice command, 214-216
- repoquery command, 275
- repositories. *See also* software packages
  - accessing, 13-14
  - creating, 259-260
  - explained, 252-253
  - security, 256-258
  - specifying which to use, 253-256
- Require All parameter, 724
- requirements. *See* system requirements
- rescue disks
  - re-creating initramfs, 439-442
  - reinstalling GRUB 2 boot loader, 439-442
  - restoring system access from rescue disk, 437
  - starting from, 436
- rescue.target mode, 435-436
- resetting root password, 443-444
- resident memory, 615

**Resilient Storage add-on, 15****resizing logical volumes, 353, 363-365**

file system resizing, 364-365

volume group resizing, 363-364

**resolving DNS queries, 745-747****resource records, 745-748****restorecon command, 487-488****restoring**

default file contexts, SELinux, 487-488

MariaDB databases, 773-776

system access

*/etc/fstab file, 442-443**from rescue disk, 437*

VM access, 444-446

**retrieving, user account information, 126****rewrite process (Postfix), 831****RHEL 7 Server (Red Hat Enterprise****Linux 7 Server)**

benefits, 11

configuring for LDAP, 142

course environment setup, 16-17

installing, 17-29. *See also* installation  
source settings

obtaining

*CentOS 7, 12-13**Fedora, 13**paid version, 12**Scientific Linux, 13*

rebooting, 110-112

repository access, 13-14

system requirements, 15

variants and add-ons, 14-15

version information, 375

**RHEV (Red Hat Enterprise****Virtualization), 229****RHN (Red Hat Network), registering  
with, 253****rich rules**

configuration, 709-711

explained, 708

logging, 711

ordering, 709

syntax, 708-709

**rm command, 71-72****rm -f command, 72****rm -r command, 71****rmdir command, 68****rmmod command, 381****ro mount option, 343****roles, in mail handling, 828****root directory, 60****root domain (.), 744****root password, resetting, 443-444****root user account, 126**

disabling root login, 848-849

working as, 126-127

*PolicyKit, 128**su command, 127**sudo command, 128**switching user accounts, 128-129***rotating log files, 308-310****roundrobin runner, 663****routers, 180****routing**

configuration, 677-679

validation, 187

**RPM (Red Hat Package Manager)****format, 252**

database queries, 273

downloading packages, 275

filenames, 272-273

package file queries, 273-276

**rpm command, 271-272**

database queries, 273

package file queries, 273-276

**rpm -q --scripts command, 274****rpm -qa command, 274****rpm -qc command, 274****rpm -qd command, 274****rpm -qf command, 274****rpm -qi command, 274****rpm -ql command, 274****rpm -qp command, 274****rpm -qR command, 274****rpm -V command, 274****rpm -Va command, 274****rsync command, 116****rsyslog.conf file, sections, 304**

**rsyslogd process, 298**  
 configuration, 303-308  
   *facilities, priorities, destinations,*  
   304-308  
   *file locations, 303*  
   *rsyslog.conf sections, 304*  
 connecting to journald, 646-648  
 modules  
   *configuration, 645-646*  
   *reasons for using, 644-645*  
   *types of, 644*  
 role of, 298-299  
**rules, SELinux, 477**  
**#####RULES##### section (rsyslog), 304**  
**run levels, 412**  
**runners, in network teaming, 663**  
**running. See executing**  
**Running process state, 218**

## S

---

**s attribute, 171**  
**sa processes, starting, 621**  
**Samba file servers**  
 configuration, 809-810  
   */etc/samba/smb.conf file, 805-806*  
   *creating shares, 807-808*  
   *creating users, 808-809*  
   *installing Samba, 804*  
   *for keytab files, 814-815*  
   *preparing shared directories, 804-805*  
   *troubleshooting, 810*  
 security  
   *firewalls, 811-813*  
   *Kerberized shares, 813-815*  
   *SELinux settings, 810-811*  
 shares  
   *automount mounts, 819-820*  
   *discovering, 815-816*  
   *mounting, 816*  
   *multiuser mounts, 817-819*

**SANs (storage-area networks), 576**  
 iSCSI  
   *architecture, 582-584*  
   *connecting to target, 598-602*  
   *Fibre Channel versus, 581-582*  
   *hardware versus software solutions, 582*  
   *initiator configuration, 596-598*  
   *target configuration, 585-595*  
   *terminology, 584*  
   *troubleshooting, 602-603*  
 NAS (network-attached storage) versus,  
 578  
**SAP business applications, server  
 variants, 14**  
**SAP HANA, server variants, 14**  
**sar command, 621-622**  
**scheduling tasks**  
 atd service, 290-291  
 cron service, 284-285  
   *anacron service, 288-289*  
   *configuration files, 286-288*  
   *exercises, 289-290*  
   *listing cron jobs, 289*  
   *managing, 284-285*  
   *security management, 289*  
   *time and date fields, 285-286*  
**Scientific Linux, 13**  
**scp command, 115-116**  
**screen command, 118-119**  
**ScriptAlias parameter, 724**  
**scripts. See shell scripts**  
**sealert command, 492-494**  
**searching text files**  
 awk command, 97-98  
 grep command, 96-97  
 regular expressions, 93-96  
 sed command, 97-98  
**sec=method option, 792**  
**second-level domains, 744**  
**secondary groups, 137**  
**Secure Shell. See SSH (Secure Shell)**

**security**

- authentication. *See* user authentication
- cache-only DNS servers, 749
- file permissions, drawbacks of, 472
- MariaDB, 763-764
- NFS shares, 519-520
- permissions. *See* permissions
- private directories, 735-736
- repositories, 256-258
- Samba file servers
  - firewalls*, 811-813
  - Kerberized shares*, 813-815
  - SELinux settings*, 810-811
- SELinux. *See* SELinux
- SSH (Secure Shell), 848
  - configuration*, 851
  - configuring alternative ports*, 849
  - disabling root login*, 848-849
  - limiting user access*, 850-851
  - SELinux settings*, 849-850
- TLS (Transport Layer Security)
  - configuration*, 727-731
- trust anchors, 751-752
- security facility, 305**
- security management, for cron service, 289**
- security message, in remote access, 114**
- security Samba parameter, 806**
- sed command, 97-98**
- SELECT command, 770**
- selecting, repositories, 253-256**
- SELinux**
  - Apache web server settings, 725
  - Boolean settings, 489-491
  - configuration, for NFSv4, 788-789
  - contexts, 481
    - finding context types*, 486
    - monitoring*, 481-482
    - relabeling*, 487-488
    - setting context types*, 483-486
  - modes, 477-481
  - Samba settings, 810-811
  - SSH port changes, 849-850
  - terminology, 477
    - transparency, in NFSv4, 795-796
    - troubleshooting, 491-494
- semanage boolean -l command, 489**
- semanage command, 483-485, 535**
- semanage port command, 849-850**
- sending, signals, to processes, 216-217**
- Sendmail, 830**
- sendmail process (Postfix), 831**
- Server Message Block (SMB). *See* Samba file servers; SMB shares**
- Server with GUI option, RHEL 7 installation, 22**
- ServerAdmin parameter, 724**
- ServerAliveCountMax option, 852-853**
- ServerAliveInterval option, 852-853**
- ServerRoot parameter, 393, 724**
- servers, web servers. *See* Apache web servers**
- SERVFAIL status indicator, 754**
- service files, 505**
- service units, 409-412**
  - dependency management, 415-418
  - managing, 413-415
  - target management, 418-419
- services**
  - enabling, 418-419
  - in firewalld service
    - creating*, 706-708
    - explained*, 504-505
- session options, in SSH, 852**
- sestatus command, 478**
- set group ID (SGID) permission**
  - applying, 164
  - explained, 162-163
- set user ID (SUID) permission**
  - applying, 164
  - explained, 161-162
- setenforce command, 478**
- setfacl command, 166-168**
- setfacl -m d command, 168**
- setfacl -R command, 168**
- set-local-rtc command, 545**
- set-ntp command, 545**

- setsebool command, 490**
- set-time command, 545**
- set-timezone command, 545**
- setup.** *See configuration*
- SGID (set group ID) permission**
  - applying, 164
  - explained, 162-163
- shares (NFS).** *See NFS shares*
- shares (Samba).** *See also SMB shares*
  - creating, 807-808
  - discovering, 815-816
  - Kerberos on, 813-815
  - mounting, 816
    - automount mounts, 819-820*
    - multiuser mounts, 817-819*
- sharing**
  - directories
    - permissions needed, 162-163*
    - preparing for Samba file servers, 804-805*
  - files. *See NFS (Network File System)*
- shebang (in scripts), 686**
- shell, 36**
  - command execution, 36-37
  - history file, 40
  - I/O redirection
    - pipes, 39-40*
    - STDIN, STDOUT, STDERR, 37-39*
  - tab completion, 42
- shell environment, 45**
  - configuration files, 46
  - managing, 47
  - starting with su - command, 127
  - umask setting, 169-170
  - user communication in, 46-47
  - variables, 45-46
- shell field (/etc/passwd file), 131**
- shell jobs, 208**
  - foreground versus background jobs, 208-209
  - managing, 209-211
  - parent-child management, 211
- shell scripts**
  - conditional loops
    - case loops, 696-697*
    - if.then.else loops, 692-693*
    - for loops, 693-694*
    - types of, 691-692*
    - until loops, 696*
    - while loops, 695-696*
  - debugging, 697-698
  - explained, 686-687
  - positional parameters, 688-689
  - variables, 689-691
- show databases command, 767**
- SHOW TABLES command, 768**
- showing.** *See viewing*
- showmount command, 521, 787-788**
- si parameter (CPU usage), 611**
- SIGHUP signal, 216**
- SIGKILL signal, 216**
- signals, sending to processes, 216-217**
- SIGTERM signal, 216**
- sizing, logical volumes, 360-361**
- skeleton directory, 134**
- SLAAC (stateless address autoconfiguration), 675**
- Sleeping process state, 218**
- Smart Management add-on, 15**
- SMB (Server Message Block).** *See Samba file servers*
- SMB shares.** *See also shares (Samba)*
  - discovering, 523-525
  - mounting, 522-525
    - with automount, 533*
    - as guest, 525*
    - user authentication, 525*
    - via /etc/fstab file, 529-530*
    - via graphical interface, 526-527*
- smbclient -L command, 523-524, 815-816**
- smbpasswd command, 808**
- smtp process (Postfix), 831**
- snapshots, 353-354, 774-775**

- SOA resource record type, 748**
- socket units, 410-411**
- soft links. *See* symbolic links**
- software clock, 542**
- software iSCSI, hardware iSCSI versus, 582**
- software packages**
  - downloading RPM packages, 275
  - repoquery command, 275
  - repositories
    - creating, 259-260*
    - explained, 252-253*
    - security, 256-258*
    - specifying which to use, 253-256*
  - rpm command, 271-272
    - database queries, 273*
    - package file queries, 273-276*
    - RPM filenames, 272-273*
  - yum command
    - finding packages, 261-262*
    - history list, 270-271*
    - information about packages, 262-263*
    - installing packages, 263-265*
    - list of tasks, 260*
    - listing packages, 265-266*
    - managing packages, 271*
    - package groups, 268-270*
    - removing packages, 265*
    - updating packages, 267*
- sort command, 88, 91-92**
- sorting**
  - performance parameters, 615
  - text files, sort command, 91-92
- source domains, SELinux, 477**
- SRV resource record type, 748**
- ss command, 187**
- ss -lt command, 187**
- SSH (Secure Shell), 112**
  - configuration
    - connection keepalive options, 852*
    - options, 853*
    - session options, 852*
    - tunneling, 854-855*
  - graphical applications in, 114-115
  - key-based authentication in, 116-118, 853-854
  - remote access, 112-114
  - screen command, 118-119
  - security, 848
    - configuration, 851*
    - configuring alternative ports, 849*
    - disabling root login, 848-849*
    - limiting user access, 850-851*
    - SELinux settings, 849-850*
  - transferring files, 115-116
  - VM access, 241
- ssh command, 112-114**
- ssh -p command, 115**
- ssh -v command, 114-115**
- ssh -X command, 115**
- ssh-add command, 854**
- ssh-agent command, 854**
- ssh-copy-id command, 117**
- ssh-keygen command, 117**
- ssl parameter, 143**
- sssd service, 567**
  - as authentication backend service, 142, 568
  - managing, 144
  - sample configuration file contents, 571-572
- st parameter (CPU usage), 611**
- standard error, 37-39**
- standard input, 37-39**
- standard output, 37-39**
- star command, 78, 166**
- starting sa processes, 621. *See also* boot procedure**
- stateless address autoconfiguration (SLAAC), 675**
- status command, 545**
- STDERR, 37-39**
- STDIN, 37-39**
- STDOUT, 37-39**
- Stevens, Brian, 12**

**sticky bit**

- applying, 164
- explained, 163

**Stopped process state, 218****stopping**

- processes, 216-217
- shell jobs, 209

**storage**

- LVM (Logical Volume Manager). *See* LVM (Logical Volume Manager)
- measurement units, 324
- partitions. *See* partitions
- swap files, creating, 339

**storage-area networks. *See* SANs (storage-area networks)****stratums, 863-864****su - command, 107, 127****su command, 127****subdomains, 745****subnet masks, 181**

- binary notation, 182-183
- IPv6 addresses, 673

**subshells, 46****sudo command, 127-128****SUID (set user ID) permission**

- applying, 164
- explained, 161-162

**sunrpc tunable directory, 633****superuser account. *See* root user account****supplementary repository type, 256****swap files, creating, 339****swap partitions, creating, 338-339****swap usage, 613-615****swapon -s command, 615****switching**

- terminals
  - in graphical environment, 107-108*
  - in nongraphical environment, 108-109*
  - with screen command, 118-119*
- user accounts
  - exercises, 128-129*
  - with su command, 127*
- between VMs, 469

**sy parameter (CPU usage), 611****symbolic links**

- creating, 74-75
- removing, 75-76

**synchronization of time**

- chronyc command, 866-871
- chronyd process, 862-863
- chronyd process configuration, 864-866
- importance of, 862
- monitoring status, 547
- NTP (Network Time Protocol), 863-864

**sys security option, 520****sysctl -a command, 635-636****sysctl command, 635-637****syslog facility, 305****syslogd process, 298****SYSLOGD\_OPTIONS variable, 303****sysrq-trigger file, 631****system accounts, 129****system logging**

- journald process, 310
  - connecting to rsyslog, 646-648*
  - journalctl command, 310-314*
  - permanent journal storage, 314-316*
  - role of, 298-299*
- reading log files
  - list of files, 300*
  - live monitoring, 302-303*
  - sample contents, 300-302*
- remote logging, 648
  - configuration, 649-650*
  - reasons for using, 648-649*
- rich rules, 711
- rotating log files, 308-310
- rsyslogd modules
  - configuration, 645-646*
  - reasons for using, 644-645*
  - types of, 644*
- rsyslogd process
  - configuration, 303-308*
  - connecting to journald, 646-648*
  - role of, 298-299*
  - types of, 298*

system optimization. *See* performance optimization

system requirements  
 KVM hosts, 231-232  
 RHEL 7 Server (Red Hat Enterprise Linux 7 Server), 15

system time, 542  
 date command, 544  
 hardware clock versus, 544-545  
 increasing reliability, 543

system-config-date command, 550

system-config-kickstart graphical interface, modifying Kickstart files, 464-467

systemctl command, 413-415

systemctl enable target command, 594

systemctl --failed --type=service command, 415

systemctl get-default command, 420

systemctl halt command, 111

systemctl list-dependencies command, 416

systemctl list-units --type=service --all command, 415

systemctl list-units --type=service command, 415

systemctl mask command, 417-418

systemctl mask iptables command, 505, 705-706

systemctl poweroff command, 111

systemctl reboot command, 111

systemctl set-default command, 420

systemctl show command, 411-412

systemctl start nsld command, 143

systemctl start target command, 594

systemctl status chronyd command, 869-870

systemctl status command, 299, 396, 414-415

systemctl status crond -l command, 284

systemctl status iscsi command, 602

systemctl status -l command, 415

systemctl status -l libvirtd command, 229

systemctl status mariadb command, 762

systemctl status NetworkManager command, 189

systemctl status nsld command, 143

systemctl status sssd command, 144

systemctl status target command, 602

systemctl -t help command, 408

systemctl --type=service command, 415

systemctl --type=target --all command, 419

systemctl --type=target command, 419

systemd process, 298, 790-791  
 explained, 408  
 rebooting, 111  
 unit types, 408  
*default targets, setting, 420*  
*dependency management, 415-418*  
*isolating targets, 419*  
*service units, 409-412*  
*target management, 418-419*  
*target units, 412-413*  
*unit management, 413-415*  
 wants, 413

systemd-journald service. *See* journald process

systemd-sysctl service, 635

systemd-udev process, 376-378

systemd.unit=emergency.target boot option, 435

systemd.unit=rescue.target boot option, 435

## T

---

tab completion, 42, 69, 354

tables, in databases, 767

tac command, 90

tail command, 88, 90-91

tail -f command, 302-303

tainted kernel, 373

tar -c command, 79

tar -C command, 79

tar -cf command, 77

- tar command, 76-80**
  - compression, 79
  - creating archives, 77
  - extracting archive contents, 78
  - lack of ACL support, 166
  - listing archive contents, 77-78
  - options, 79
- tar -f command, 79**
- tar -j command, 79**
- tar -r command, 77, 79**
- tar -t command, 77, 79**
- tar -u command, 77, 79**
- tar -v command, 77, 79**
- tar -x command, 79**
- tar -xvf command, 78**
- tar -z command, 79**
- target domains, SELinux, 477**
- target portal group (TPG), 584**
- target units, 412-413**
  - default targets, setting, 420
  - isolating, 419
  - managing, 418-419
  - starting troubleshooting targets, 435-436
- targetcli command, 585-594, 602**
- targets (iSCSI), 584**
  - configuration, 585-595
  - connecting to, 598-602
    - mounting iSCSI devices, 601-602*
    - persistent mounts, 600-601*
- tasks, scheduling. *See scheduling tasks***
- TCP (Transfer Control Protocol), 183, 650**
- TCPKeepAlive option, 852-853**
- teamd driver, 663**
- teamdctl command, 666**
- teamdctl team0 config dump command, 672**
- teaming. *See network teaming***
- teamnl command, 671-672**
- terminals**
  - consoles versus, 106
  - pseudo terminals, 109-110
  - switching
    - in graphical environment, 107-108*
    - in nongraphical environment, 108-109*
    - with screen command, 118-119*
- terminating**
  - background jobs, 211
  - processes, 216-217
- test command, 690, 692**
- testing**
  - Apache web servers, 395-396
  - NFS server access, 787-788
- testparm command, 808**
- text consoles, login, 106-107**
- text files**
  - commands
    - awk, 97-98*
    - cat, 89*
    - cut, 91*
    - grep, 96-97*
    - head, 90-91*
    - less, 88-89*
    - list of, 88*
    - sed, 97-98*
    - sort, 91-92*
    - tac, 90*
    - tail, 90-91*
    - wc, 93*
  - counting lines, words, characters, 93
  - filtering
    - awk command, 97-98*
    - cut command, 91*
    - head command, 90-91*
    - sed command, 97-98*
    - tail command, 90-91*
  - searching
    - awk command, 97-98*
    - grep command, 96-97*
    - regular expressions, 93-96*
    - sed command, 97-98*
  - sorting, 91-92
  - viewing
    - cat command, 89*
    - less command, 88-89*
    - tac command, 90*

**text-only consoles, VM access, 241-242****TFTP (Trivial File Transfer Protocol) servers**

- creating content, 458-462
- installing, 456-457

**threads, 208, 211-212, 372-373****tickets (Kerberos), 562****time**

- epoch time, 544
- hardware time, hwclock command, 544-545
- synchronization
  - chronyc command*, 866-871
  - chronyd process*, 862-863
  - chronyd process configuration*, 864-866
  - importance of*, 862
  - monitoring status*, 547
  - NTP (Network Time Protocol)*, 863-864

## system time

- date command*, 544
- increasing reliability*, 543

## terminology, 542

**time fields, cron service, 285-286****time indicator, for kernel messages, 375****time management**

## commands

- date*, 544
- hwclock*, 544-545
- list of*, 543
- timedatectl*, 545-548

## graphical tools for, 550

## time zone settings, 548-549

**Time To Live (TTL), 746-748****time zone settings, 548-549****timedatectl command, 543-548****TLS (Transport Layer Security)**

- certificates, 141
- configuration, 727-731

**tls\_reqcert parameter, 143****top command, 244, 610**

- CPU usage, 611
- customizing display, 615-616
- load average, 610-611

## memory usage, 612-613

## process memory usage, 615

## process states, 218-220

## swap usage, 613-615

**top-level domains, 744-745****touch command, 68****TPG (target portal group), 584****tracepath6 command, 676****Transfer Control Protocol (TCP). See TCP (Transfer Control Protocol)****transferring, files, 115-116****transparency, SELinux, in NFSv4, 794-796****Transport Layer Security (TLS), 727-731**

- certificates, 141
- configuration, 727-731

**Trivial File Transfer Protocol (TFTP) servers**

- creating content, 458-462
- installing, 456-457

**troubleshooting**

## boot procedure

- accessing GRUB boot prompt*, 434-435
- overview by boot phase*, 433
- recovering from file system issues*, 442-443
- recovering virtual machine access*, 444-446
- re-creating initramfs*, 439-442
- reinstalling GRUB 2 boot loader*, 439-442
- resetting root password*, 443-444
- restoring system access from rescue disk*, 437
- starting from rescue disk*, 436
- starting troubleshooting targets*, 435-436

**DNS (Domain Name System), 752-755**

- client issues*, 755
- dig command*, 753-754
- dumping unbound cache*, 753

## firewall-config command, 508

## IPv6 addresses, 676

## iSCSI, 602-603

## Kickstart installation, 469

- mail servers, 838-840
- network teaming, 671-672
- Samba configuration, 810
- SELinux, 480, 491-494
- shell scripts, 697-698
- unbound caching servers, 751
- trust anchors, configuration, 751-752**
- trusted default zone (firewalld), 503**
- TTL (Time To Live), 746-748**
- tune2fs command, 336-338**
- tuning. See performance optimization**
- tunneling (SSH), configuration, 854-855**
- TXT resource record type, 748**
- type command, 36**
- tzselect command, 548-549**

## U

---

- u (vim command), 43**
- u attribute, 171**
- udevadm monitor command, 376-378**
- UDP (User Datagram Protocol), 183, 650**
- UID field (/etc/passwd file), 130**
- UID\_MIN property, 135**
- umask setting, 169-170**
- umount command, 340**
- uname command, 375**
- uname -i command, 231**
- unbound**
  - as cache-only DNS server, 749-751
  - dumping unbound cache, 753
- unbound-control dump\_cache command, 753**
- unbound-control-setup command, 751**
- Uninterruptable sleep process state, 218**
- unique local addresses, 674**
- units (systemd)**
  - dependency management, 415-418
  - managing, 413-415
  - mount units, troubleshooting, 442-443
  - service units, 409-412
  - target units, 412-413
    - default targets, setting, 420*
    - isolating, 419*
    - managing, 418-419*
    - starting troubleshooting targets, 435-436*
  - types of, 408
  - wants, 413
- universal time coordinated (UTC). See UTC (universal time coordinated)**
- unloading, kernel modules, 381**
- unprivileged user accounts, privileged versus, 126**
- until loops, 696**
- UPDATE command, 770**
- updates repository type, 256**
- updating**
  - archives, 77
  - mandb, 50-51
  - software packages, 267
- upgrading, kernel, 267, 384**
- us parameter (CPU usage), 611**
- USE command, 768**
- used parameter (memory usage), 612**
- UseDNS option, 852-853**
- user accounts**
  - configuration files
    - default properties, 134-135*
    - editing, 132-133*
    - properties of, 129-132*
  - creating, 132, 136-137
    - directly in configuration files, 132-133*
    - user environments, 136*
    - useradd command, 133*
  - deleting, 132
  - groups. *See group accounts*
  - home directories, 133-134
  - login, which to use, 106-107
  - privileged versus unprivileged, 126
  - property management, 134
    - default properties, 134-135*
    - passwords, 135-136*
  - retrieving information about, 126

root user account, working as, 126-127

switching

- exercises, 128-129*
- with su command, 127*

system accounts, 129

**user authentication**

- Active Directory, 572
- for databases, 771-772
- ipa client configuration, 572
- IPA server preparation,
- Kerberos. *See* Kerberos
  - explained, 561-562*
  - principals, 563-564*
- LDAP
  - configuration with Kerberos authorization, 565-568*
  - connecting to server, 144-146*
  - explained, 140-142*
  - nsld service management, 143*
  - platform configuration, 142*
  - RHEL 7 configuration for, 142*
  - sssd service management, 144*
- NFS shares, 519-520
- nsld service, as backend service, 568-
- remote authentication, explained, 560-561
- SMB shares, 525
- in SSH, 116-118, 853-854
- sssd service, as backend service, 568

**user communication, in shell environment, 46-47**

**User Datagram Protocol (UDP). *See* UDP (User Datagram Protocol)**

**user environments, creating, 136**

**user extended attributes, 170-172**

**user facility, 305**

**user owners**

- ACLs, changing, 168
- changing, 156
- default ownership, changing, 157-158
- viewing, 155-156

**user settings, RHEL 7 installation, 27-28**

**user\_xattr option, 171, 343**

**useradd command, 133-135**

**userdel command, 132**

**userdel -r command, 132**

**USERGROUPS\_ENAB property, 135**

**usermod command, 134, 139**

**username field (/etc/passwd file), 130**

**users (Samba), creating, 808-809**

**UTC (universal time coordinated), 542**

**utilities. *See* commands**

**uucp facility, 305**

**UUIDs, mounting file systems, 340-341**

## V

---

**v (vim command), 43**

**valid users directive, 807**

**validation**

- network address configuration, 185-187
- network settings, 187-189
- routing, 187
- VM configuration file XML code, 238

**values, in databases, 767**

**variables**

- in shell environment, 45-46
- in shell scripts, 689-691

**variants, list of, 14**

**verifying. *See* validation**

**VFAT file system, 334**

**vgchange command, 445**

**vgcreate command, 359, 362**

**vgdisplay command, 360, 362**

**vgextend command, 363**

**vgreduce command, 363**

**vgs command, 360-363**

**vi, 42**

**viewing**

- ACLs, 166-168
- bridging configuration, 234
- connection properties, 190
- connection status, 190
- device status, 192
- effective primary group, 157
- hidden files, 70
- hostname configuration, 197
- keytab file contents, 563-564

- ownership, 155-156
  - text files
    - cat* command, 89
    - less* command, 88-89
    - tac* command, 90
  - virg** command, 133, 138
  - vim**, 42-45
  - vimtutor** command, 44
  - vipw** command, 133
  - virsh** command, 243-244
  - virsh console** command, 241, 243
  - virsh destroy** command, 243
  - virsh dumpxml** *vmname* | **grep** “source file=” command, 444
  - virsh edit** command, 240, 243
  - virsh help** command, 243
  - virsh list --all** command, 243
  - virsh list** command, 241, 243
  - virsh reboot** command, 243
  - virsh shutdown** command, 243
  - virsh start** command, 243
  - virtual hosts**
    - creating, 398-400
    - editing configuration, 726-727
  - Virtual Machine Manager**, 240-243
  - virtual machines (VMs)**. *See* VMs (virtual machines)
  - virtual memory**
    - explained, 615
    - usage information, 618-619
  - virtual terminals**, 108-109
  - virtualization**
    - KVM, 228
      - host requirements*, 231-232
      - installing software*, 232-233
      - networking configuration*, 233-234
    - libvirtd, 229-231
    - OpenStack, 229
    - QEMU, 228
    - RHEV, 229
    - VMs
      - accessing*, 240-242
      - installing*, 234-240
      - managing*, 242-244
      - monitoring*, 244
      - recovering access to*, 444-446
  - virt-viewer** command, 241
  - vm tunable directory**, 633
  - VMs (virtual machines)**
    - accessing
      - with libvirtd*, 229-231
      - methods of*, 240-242
      - recovering access to*, 444-446
    - installing, 234-240
    - managing
      - from command-line*, 243-244
      - in Virtual Machine Manager*, 242-243
    - monitoring, 244
    - switching between, 469
  - vmstat** command, 616-619
  - vmstat -s** command, 619
  - vm.swappiness** tunable, 637
  - volume groups**
    - creating, 359-361
    - resizing, 363-364
  - volumes**
    - logical volumes. *See* logical volumes
    - physical volumes, creating, 355-358
  - voluntary context switches**, 620
- ## W
- 
- wa** parameter (CPU usage), 611
  - wants** (systemd), 413
  - warning priority**, 306
  - wc** command, 88, 93
  - Web Server Gateway Interface (WSGI)**, 733
  - web servers**. *See* Apache web servers
  - WHERE** clause, 770
  - which** command, 36
  - while** loops, 695-696
  - wildcards**
    - in automount, 532-533
    - file management, 67
    - in regular expressions, 95-96

**windows.** *See* **terminals**

**words, counting, in text files,** 93

**work default zone (firewalld),** 503

**workgroup Samba parameter,** 806

**writable directive,** 807

**write list directive,** 807

**write permission**

- applying, 159-161
- configuring to DocumentRoot, 726
- explained, 158-159
- on Samba shares, 807-808

**WSGI (Web Server Gateway Interface),** 733

## X

---

**X forwarding,** 115

**XFS file system,** 25, 334

- managing properties, 338
- resizing, 365

**xfs\_admin command,** 338

**xfs\_admin -L command,** 341

**xinetd service, TFTP server installation,** 456-457

**x-systemd.automount mount option,** 528, 529

## Y

---

**yum command**

- finding packages, 261-262
- history list, 270-271
- information about packages, 262-263
- installing packages, 263-265
- list of tasks, 260
- listing packages, 265-266
- managing packages, 271
- package groups, 268-270
- removing packages, 265

- repositories
  - creating,* 259-260
  - explained,* 252-253
  - security,* 256-258
  - specifying which to use,* 253-256
- rpm command versus, 271-272
- updating packages, 267

**yum groups info command,** 269-270

**yum groups install command,** 392

**yum groups list command,** 268-269, 392

**yum history command,** 270-271

**yum info command,** 262-263

**yum install command,** 263-265

**yum install elinks command,** 395

**yum install httpd command,** 392

**yum install kernel command,** 384

**yum install -y screen command,** 118

**yum list command,** 265-266

**yum list installed command,** 266

**yum list kernel command,** 266

**yum provides command,** 262

**yum remove command,** 265

**yum repolist command,** 260

**yum search command,** 261-262

**yum search http command,** 392

**yum update command,** 267

**yum upgrade kernel command,** 384

**yum whatprovides command,** 262, 483

**yumdownloader command,** 260, 275

**yy (vim command),** 43

## Z

---

**Zombie process state,** 218

**zones,** 503, 745

*This page intentionally left blank*