


```
!  
!  
voice-card 0  
!  
!  
!  
!  
!  
archive  
  log config  
  hidekeys  
!  
!  
!  
!  
!  
!  
!  
!  
!  
interface Tunnel34  
  no ip address  
  ipv6 address 2026::34:1/122  
  ipv6 enable  
  ipv6 ospf 6 area 34  
  tunnel source 10.1.1.9  
  tunnel destination 10.1.1.10  
  tunnel mode ipv6ip  
!  
interface FastEthernet0/0  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface FastEthernet0/1  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface Serial0/0/0  
  no ip address  
!  
interface Serial0/0/1  
  no ip address  
  clock rate 2000000  
!  
interface Serial0/1/0  
  no ip address  
  shutdown  
!  
interface Serial0/2/0  
  no ip address
```

```
encapsulation frame-relay
!
interface Serial0/2/0.23 point-to-point
 ip address 10.1.1.6 255.255.255.252
 ip pim sparse-dense-mode
 snmp trap link-status
 ipv6 address 2026::1:2/122
 ipv6 enable
 ipv6 ospf 6 area 0
 frame-relay interface-dlci 302
!
interface Serial0/2/0.34 point-to-point
 ip address 10.1.1.9 255.255.255.252
 ip pim sparse-dense-mode
 snmp trap link-status
 frame-relay interface-dlci 304
!
interface Serial0/3/0
 no ip address
!
router ospf 1
 router-id 3.3.3.3
 log-adjacency-changes
 area 34 nssa no-summary
 network 10.1.1.2 0.0.0.0 area 0
 network 10.1.1.9 0.0.0.0 area 34
 network 10.3.3.1 0.0.0.0 area 0
 network 10.3.3.3 0.0.0.0 area 0
 network 0.0.0.0 255.255.255.255 area 0
!
ip forward-protocol nd
no ip http server
no ip http secure-server
!
!
!
ip access-list standard DENY_10
 deny 10.0.0.0 0.255.255.255
 permit any
ip access-list standard DENY_ALL
 deny any
ip access-list standard PERMIT_10
 permit 10.0.0.0 0.255.255.255
ip access-list standard PERMIT_ALL
 permit any
!
ipv6 router ospf 6
 log-adjacency-changes
!
!
!
!
!
```

```
!  
!  
control-plane  
!  
!  
!  
ccm-manager fax protocol cisco  
!  
mgcp fax t38 ecm  
mgcp behavior g729-variants static-pt  
!  
!  
!  
!  
!  
line con 0  
  exec-timeout 0 0  
  logging synchronous  
line aux 0  
line vty 0 4  
  exec-timeout 0 0  
  password cisco  
  login  
!  
scheduler allocate 20000 1000  
end
```

R3#

```
R3#ping 209.65.200.241
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.241, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```

```
R3#ping 209.65.200.226
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.226, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```

```
R3#ping 209.65.200.225
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.225, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```

```
R3#ping 10.1.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.1, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```



```
R3#ping 10.1.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/64/68 ms
```

```
R3#
```

```
R3#ping 10.1.1.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.5, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/92/188 ms
```

```
R3#
```

```
R3#ping 10.1.1.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.6, timeout is 2 seconds:
```

!!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132

ms

R3#

```
R3#ping 10.1.1.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.9, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/132/140
```

```
ms
```

```
R3#
```

```
R3#ping 10.1.1.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.10, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/65/68 ms
```

```
R3#
```

```
R3#ping 10.1.4.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.10, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/67/68 ms
```

```
R3#
```

```
R3#ping 10.1.4.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.9, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms
```

```
R3#
```



```
R3#ping 10.1.4.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.6, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms
```

```
R3#
```

```
R3#ping 10.1.4.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.5, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms
```

```
R3#ping 10.2.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms
```

```
R3#
```

```
R3#ping 10.2.2.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/65/68 ms
```

```
R3#
```

```
R3#ping 10.2.1.254
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.254, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms
```

```
R3#
```

```
R3#ping 10.2.4.14
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.14, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms
```

```
R3#
```

```
R3#ping 10.2.4.13
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.13, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/65/68 ms
```

```
R3#
```

```
R3#ping 10.2.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/64/68 ms
```

```
R3#
```



```
R3#ping 10.2.2.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.1, timeout is 2 seconds:
```

!!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms
R3#

```
R3#ping 10.2.1.4
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.4, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/65/68 ms
```

```
R3#
```

R3#show ip interface brief

Interface Protocol	IP-Address	OK?	Method	Status
FastEthernet0/0 down down	unassigned	YES	NVRAM	administratively
FastEthernet0/1 down down	unassigned	YES	NVRAM	administratively
Serial0/0/0 down	unassigned	YES	NVRAM	down
Serial0/0/1 down	unassigned	YES	NVRAM	down
Serial0/1/0 down down	unassigned	YES	NVRAM	administratively
Serial0/2/0 up	unassigned	YES	NVRAM	up
Serial0/2/0.23 up	10.1.1.6	YES	NVRAM	up
Serial0/2/0.34 up	10.1.1.9	YES	NVRAM	up
Serial0/3/0 down	unassigned	YES	NVRAM	down
Tunnel34 up	unassigned	YES	NVRAM	up

R3#

R3#show ip route

Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS
level-2
ia - IS-IS inter area, * - candidate default, U - per-user static
route
o - ODR, P - periodic downloaded static route

Gateway of last resort is not set

10.0.0.0/8 is variably subnetted, 8 subnets, 2 masks
O N2 10.2.4.12/30 [110/20] via 10.1.1.10, 00:28:53, Serial0/2/0.34
C 10.1.1.8/30 is directly connected, Serial0/2/0.34
O N2 10.1.4.8/30 [110/20] via 10.1.1.10, 00:28:53, Serial0/2/0.34
O N2 10.2.1.0/24 [110/20] via 10.1.1.10, 00:28:53, Serial0/2/0.34
O N2 10.2.2.0/24 [110/20] via 10.1.1.10, 00:28:53, Serial0/2/0.34
O IA 10.1.1.0/30 [110/128] via 10.1.1.5, 00:29:03, Serial0/2/0.23
O N2 10.1.4.4/30 [110/20] via 10.1.1.10, 00:28:54, Serial0/2/0.34
C 10.1.1.4/30 is directly connected, Serial0/2/0.23
R3#

R3#

R3#show processes cpu

CPU utilization for five seconds: 2%/0%; one minute: 1%; five minutes: 1%

PID	Runtime (ms)	Invoked	uSecs	5Sec	1Min	5Min	TTY	Process
1	12	69	173	0.00%	0.00%	0.00%	0	Chunk
Manager								
2	0	425	0	0.00%	0.04%	0.02%	0	Load Meter
3	0	4	0	0.00%	0.00%	0.00%	0	Collection

proce

4	4	1	4000	0.00%	0.00%	0.00%	0	EDDRI_MAIN
5	2548	249	10232	0.00%	0.10%	0.11%	0	Check
heaps								
6	0	1	0	0.00%	0.00%	0.00%	0	Pool
Manager								
7	0	2	0	0.00%	0.00%	0.00%	0	Timers
8	0	1	0	0.00%	0.00%	0.00%	0	License
Client N								
9	72	829	86	0.00%	0.01%	0.00%	0	OSPF-1
Hello								
10	0	36	0	0.00%	0.00%	0.00%	0	IPC
Dynamic Cach								
11	0	1	0	0.00%	0.00%	0.00%	0	IPC Zone
Manager								
12	0	2125	0	0.00%	0.00%	0.00%	0	IPC
Periodic Tim								
13	0	2125	0	0.00%	0.00%	0.00%	0	IPC
Deferred Por								
14	0	1	0	0.00%	0.00%	0.00%	0	IPC Seat
Manager								
15	0	1	0	0.00%	0.00%	0.00%	0	IPC
BackPressure								
16	0	1	0	0.00%	0.00%	0.00%	0	OIR
Handler								
17	0	1	0	0.00%	0.00%	0.00%	0	Crash
writer								
18	0	72	0	0.00%	0.00%	0.00%	0	
Environmental mo								
19	0	1	0	0.00%	0.00%	0.00%	0	ARP Input
20	0	2222	0	0.00%	0.00%	0.00%	0	ARP
Background								
21	0	2	0	0.00%	0.00%	0.00%	0	ATM Idle
Timer								
22	4	2	2000	0.00%	0.00%	0.00%	0	AAA high-
capacit								
23	0	1	0	0.00%	0.00%	0.00%	0	
AAA_SERVER_DEADT								
24	0	1	0	0.00%	0.00%	0.00%	0	Policy
Manager								
25	0	9	0	0.00%	0.00%	0.00%	0	DDR Timers
26	4	2	2000	0.00%	0.00%	0.00%	0	Entity MIB
API								
27	8	45	177	0.00%	0.00%	0.00%	0	EEM ED
Syslog								
28	0	639	0	0.00%	0.00%	0.00%	0	HC Counter
Timer								
29	0	78	0	0.00%	0.00%	0.00%	0	Serial
Backgroun								
30	0	1	0	0.00%	0.00%	0.00%	0	RO Notify
Timers								
31	0	1	0	0.00%	0.00%	0.00%	0	RMI RM
Notify Wa								
32	0	2	0	0.00%	0.00%	0.00%	0	SMART
33	4	2123	1	0.07%	0.00%	0.00%	0	GraphIt

34	0	2	0	0.00%	0.00%	0.00%	0 Dialer
event							
35	0	1	0	0.00%	0.00%	0.00%	0 SERIAL
A'detect							
36	0	2	0	0.00%	0.00%	0.00%	0 XML Proxy
Client							
37	0	1	0	0.00%	0.00%	0.00%	0 Critical
Bkgnd							
38	48	1056	45	0.00%	0.00%	0.00%	0 Net
Background							
39	4	2	2000	0.00%	0.00%	0.00%	0 IDB Work
40	0	52	0	0.00%	0.00%	0.00%	0 Logger
41	0	2120	0	0.00%	0.00%	0.00%	0 TTY
Background							
42	0	2129	0	0.00%	0.02%	0.00%	0 Per-Second
Jobs							
43	0	143	0	0.00%	0.00%	0.00%	0 c2800
Periodic							
44	0	1	0	0.00%	0.00%	0.00%	0 Inode
Table Dest							
45	0	1	0	0.00%	0.00%	0.00%	0 IKE HA Mgr
46	0	1	0	0.00%	0.00%	0.00%	0 IPSEC HA
Mgr							
47	4	4	1000	0.00%	0.00%	0.00%	0 rf task
48	0	3	0	0.00%	0.00%	0.00%	0 Net Input
49	0	427	0	0.00%	0.00%	0.00%	0 Compute
load avg							
50	840	36	23333	0.00%	0.02%	0.00%	0 Per-minute
Jobs							
51	0	1	0	0.00%	0.00%	0.00%	0 AggMgr
Process							
52	0	1	0	0.00%	0.00%	0.00%	0 Token
Daemon							
53	0	1	0	0.00%	0.00%	0.00%	0 Transport
Port A							
54	0	1	0	0.00%	0.00%	0.00%	0
dev_device_inser							
55	0	1	0	0.00%	0.00%	0.00%	0
dev_device_remov							
56	0	1	0	0.00%	0.00%	0.00%	0
sal_dpc_process							
57	0	1	0	0.00%	0.00%	0.00%	0 ARL Table
Manage							
58	0	2	0	0.00%	0.00%	0.00%	0 ESWPPM
59	0	2	0	0.00%	0.00%	0.00%	0 Eswilp
Storm Con							
60	0	2	0	0.00%	0.00%	0.00%	0 ESWILPPM
61	0	2	0	0.00%	0.00%	0.00%	0 Eswilp
Storm Con							
62	4	8504	0	0.07%	0.01%	0.00%	0 Netclock
Backgro							
63	0	2	0	0.00%	0.00%	0.00%	0 SM Monitor
64	0	2	0	0.00%	0.00%	0.00%	0 Bryce I2C
CMD Qu							

65	272	4	68000	0.00%	0.00%	0.00%	0	USB
Startup								
66	0	355	0	0.00%	0.00%	0.00%	0	mxt5100
67	0	2	0	0.00%	0.00%	0.00%	0	VNM DSPRM
MAIN								
68	0	1	0	0.00%	0.00%	0.00%	0	DSPFARM
DSP READ								
69	0	2	0	0.00%	0.00%	0.00%	0	FLEX DNLD
MAIN								
70	0	1	0	0.00%	0.00%	0.00%	0	HDV
background								
71	4	2	2000	0.00%	0.00%	0.00%	0	VMI
Background								
72	0	1	0	0.00%	0.00%	0.00%	0	
RF_INTERDEV_DELA								
73	0	1	0	0.00%	0.00%	0.00%	0	
RF_INTERDEV_SCTP								
74	0	1	0	0.00%	0.00%	0.00%	0	chkpt
message ha								
75	0	2129	0	0.00%	0.00%	0.00%	0	Ether-
Switch RBC								
76	0	1	0	0.00%	0.00%	0.00%	0	IGMP
Snooping Pr								
77	0	1	0	0.00%	0.00%	0.00%	0	IGMP
Snooping Re								
78	0	72	0	0.00%	0.00%	0.00%	0	Call
Management								
79	0	1	0	0.00%	0.00%	0.00%	0	AAL2CPS
TIMER_CU								
80	0	1	0	0.00%	0.00%	0.00%	0	CES Line
Conditi								
81	0	1	0	0.00%	0.00%	0.00%	0	
CF_INTERDEV_SCTP								
82	0	1	0	0.00%	0.00%	0.00%	0	Async
write proc								
83	0	1	0	0.00%	0.00%	0.00%	0	Async
write proc								
84	0	1	0	0.00%	0.00%	0.00%	0	Async
write proc								
85	0	1	0	0.00%	0.00%	0.00%	0	Async
write proc								
86	0	36	0	0.00%	0.00%	0.00%	0	DFS flush
period								
87	0	2	0	0.00%	0.00%	0.00%	0	Dot1x Mgr
Proces								
88	0	1	0	0.00%	0.00%	0.00%	0	MAB
Framework								
89	0	1	0	0.00%	0.00%	0.00%	0	EAP
Framework								
90	0	2	0	0.00%	0.00%	0.00%	0	DTP
Protocol								
91	0	2129	0	0.00%	0.00%	0.00%	0	PI MATM
Aging Pr								
92	0	214	0	0.00%	0.00%	0.00%	0	EtherChnl

123	0	1	0	0.00%	0.00%	0.00%	0	SSS
Feature Time								
124	0	2	0	0.00%	0.00%	0.00%	0	Spanning
Tree								
125	0	1	0	0.00%	0.00%	0.00%	0	X.25
Encaps Mana								
126	0	20	0	0.00%	0.00%	0.00%	0	SSM
connection m								
127	0	1	0	0.00%	0.00%	0.00%	0	AC Switch
128	0	8	0	0.00%	0.00%	0.00%	0	
Authentication P								
129	0	1	0	0.00%	0.00%	0.00%	0	Auth-proxy
AAA B								
130	100	2	50000	0.00%	0.00%	0.00%	0	EAPoUDP
Process								
131	0	2	0	0.00%	0.00%	0.00%	0	IP Host
Track Pr								
132	0	2	0	0.00%	0.00%	0.00%	0	KRB5 AAA
133	0	2	0	0.00%	0.00%	0.00%	0	Ethernet
LMI								
134	0	2	0	0.00%	0.00%	0.00%	0	PPP IP
Route								
135	0	2	0	0.00%	0.00%	0.00%	0	PPP IPCP
136	36	161	223	0.00%	0.00%	0.00%	0	IP
Background								
137	60	17	3529	0.00%	0.00%	0.00%	0	IP RIB
Update								
138	0	2	0	0.00%	0.00%	0.00%	0	Dot1x
Supplicant								
139	0	2	0	0.00%	0.00%	0.00%	0	Dot1x
Supplicant								
140	0	2	0	0.00%	0.00%	0.00%	0	Dot1x
Supplicant								
141	0	1	0	0.00%	0.00%	0.00%	0	Asy FS
Helper								
142	0	36	0	0.00%	0.00%	0.00%	0	Licensing
Auto U								
143	0	1	0	0.00%	0.00%	0.00%	0	Socket
Timers								
144	0	67	0	0.00%	0.00%	0.00%	0	CEF
background p								
145	16	3342	4	0.00%	0.01%	0.00%	0	CEF: IPv4
proces								
146	0	19	0	0.00%	0.00%	0.00%	0	ADJ
background								
147	0	2	0	0.00%	0.00%	0.00%	0	L2MM
148	0	1	0	0.00%	0.00%	0.00%	0	MRD
149	0	1	0	0.00%	0.00%	0.00%	0	IGMP SN
150	0	1	0	0.00%	0.00%	0.00%	0	L2X Data
Daemon								
151	0	1	0	0.00%	0.00%	0.00%	0	TCP Timer
152	0	1	0	0.00%	0.00%	0.00%	0	TCP
Protocols								
153	0	8	0	0.00%	0.00%	0.00%	0	HTTP CORE

274	0	1	0	0.00%	0.00%	0.00%	0	IP SLAs
Ethernet								
275	12	84	142	0.00%	0.00%	0.00%	0	EEM Server
276	0	2	0	0.00%	0.00%	0.00%	0	EEM Policy
Direc								
277	0	3	0	0.00%	0.00%	0.00%	0	EEM ED CLI
278	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
Counter								
279	0	3	0	0.00%	0.00%	0.00%	0	EM ED GOLD
280	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
Interface								
281	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
IOSWD								
282	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
Ipsla								
283	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
None								
284	4	2	2000	0.00%	0.00%	0.00%	0	EEM ED Nf
285	0	3	0	0.00%	0.00%	0.00%	0	EEM ED OIR
286	0	3	0	0.00%	0.00%	0.00%	0	EEM ED RF
287	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
SNMP								
288	0	2	0	0.00%	0.00%	0.00%	0	EEM ED
SNMP Noti								
289	0	55	0	0.00%	0.00%	0.00%	0	EEM ED
Timer								
290	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
Test								
291	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
Config								
292	0	3	0	0.00%	0.00%	0.00%	0	EEM ED Env
293	4	28	142	0.00%	0.00%	0.00%	0	Syslog
294	0	1	0	0.00%	0.00%	0.00%	0	VPDN Test
295	0	3	0	0.00%	0.00%	0.00%	0	EEM ED RPC
296	0	2	0	0.00%	0.00%	0.00%	0	Key Proc
297	0	1	0	0.00%	0.00%	0.00%	0	tHUB
299	8	32	250	0.00%	0.00%	0.00%	0	IPv6 RIB
Event H								
300	4	1075	3	0.00%	0.00%	0.00%	0	CEF: IPv6
proces								
301	4	193	20	0.00%	0.00%	0.00%	0	IPv6 IDB
302	64	460	139	0.00%	0.00%	0.00%	0	IPv6 Input
303	20	14	1428	0.00%	0.00%	0.00%	0	IPv6 ND
304	0	1	0	0.00%	0.00%	0.00%	0	IPv6
Address								
305	0	8614	0	0.07%	0.02%	0.02%	0	MLD
306	52	2194	23	0.00%	0.00%	0.00%	0	OSPFv3-6
Router								
307	252	386	652	0.00%	0.00%	0.00%	0	FR LMI
308	16	42	380	0.00%	0.00%	0.00%	0	FR PVC
event man								
309	16	21473	0	0.00%	0.03%	0.02%	0	FR
Broadcast Out								
310	0	38	0	0.00%	0.00%	0.00%	0	FR ARP

311	0	36	0	0.00%	0.00%	0.00%	0 FR
FRAGMENTATION							
312	0	108	0	0.00%	0.00%	0.00%	0 FR TUNNEL
313	0	1	0	0.00%	0.00%	0.00%	0 FRF9
manager							
314	0	1	0	0.00%	0.00%	0.00%	0 FRF9 timed
event							
315	4	216	18	0.00%	0.00%	0.00%	0 compute
load per							
316	0	2158	0	0.00%	0.01%	0.00%	0 IGMP Input
317	8	21468	0	0.07%	0.03%	0.02%	0 Mwheel
Process							
318	56	43052	1	0.15%	0.15%	0.15%	0 PIM
Process							
321	60	2249	26	0.00%	0.00%	0.00%	0 OSPF-1
Router							
R3#							

R3#show interfaces

FastEthernet0/0 is administratively down, line protocol is down

Hardware is MV96340 Ethernet, address is 0016.479a.f6e8 (bia 0016.479a.f6e8)

MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
reliability 255/255, txload 1/255, rxload 1/255

Encapsulation ARPA, loopback not set

Keepalive set (10 sec)

Auto-duplex, Auto Speed, 100BaseTX/FX

ARP type: ARPA, ARP Timeout 04:00:00

Last input never, output never, output hang never

Last clearing of "show interface" counters never

Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0

Queueing strategy: fifo

Output queue: 0/40 (size/max)

5 minute input rate 0 bits/sec, 0 packets/sec

5 minute output rate 0 bits/sec, 0 packets/sec

0 packets input, 0 bytes

Received 0 broadcasts, 0 runts, 0 giants, 0 throttles

0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored

0 watchdog

0 input packets with dribble condition detected

0 packets output, 0 bytes, 0 underruns

0 output errors, 0 collisions, 0 interface resets

0 unknown protocol drops

0 babbles, 0 late collision, 0 deferred

0 lost carrier, 0 no carrier

0 output buffer failures, 0 output buffers swapped out

FastEthernet0/1 is administratively down, line protocol is down

Hardware is MV96340 Ethernet, address is 0016.479a.f6e9 (bia 0016.479a.f6e9)

MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
reliability 255/255, txload 1/255, rxload 1/255

Encapsulation ARPA, loopback not set

Keepalive set (10 sec)

Auto-duplex, Auto Speed, 100BaseTX/FX

ARP type: ARPA, ARP Timeout 04:00:00

Last input never, output never, output hang never

Last clearing of "show interface" counters never

Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0

```
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 0 interface resets
  0 unknown protocol drops
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier
  0 output buffer failures, 0 output buffers swapped out
Serial0/0/0 is down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
  Conversations 0/0/256 (active/max active/max total)
  Reserved Conversations 0/0 (allocated/max allocated)
  Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 4 interface resets
  0 unknown protocol drops
  0 output buffer failures, 0 output buffers swapped out
  0 carrier transitions
  DCD=down DSR=down DTR=up RTS=up CTS=down

Serial0/0/1 is down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
```

Conversations 0/0/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 5 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=up DSR=up DTR=down RTS=down CTS=up

Serial0/1/0 is administratively down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input 00:36:03, output 00:36:03, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/1/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
1 packets input, 24 bytes, 0 no buffer
Received 1 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
1 packets output, 24 bytes, 0 underruns
0 output errors, 0 collisions, 3 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=down DSR=down DTR=down RTS=down CTS=down

Serial0/2/0 is up, line protocol is up
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY, loopback not set
Keepalive set (10 sec)
CRC checking enabled
LMI enq sent 194, LMI stat recvd 189, LMI upd recvd 0, DTE LMI up
LMI enq recvd 0, LMI stat sent 0, LMI upd sent 0
LMI DLCI 1023 LMI type is CISCO frame relay DTE
FR SVC disabled, LAPF state down

Broadcast queue 0/64, broadcasts sent/dropped 908/8, interface
broadcasts 859
Last input 00:00:02, output 00:00:00, output hang never
Last clearing of "show interface" counters 00:36:02
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/4/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 1000 bits/sec, 1 packets/sec
5 minute output rate 1000 bits/sec, 1 packets/sec
1565 packets input, 142176 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
1692 packets output, 152965 bytes, 0 underruns
0 output errors, 0 collisions, 11 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
76 carrier transitions
DCD=up DSR=up DTR=up RTS=up CTS=up

Serial0/2/0.23 is up, line protocol is up
Hardware is GT96K Serial
Internet address is 10.1.1.6/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY
CRC checking enabled
Last clearing of "show interface" counters never

Serial0/2/0.34 is up, line protocol is up
Hardware is GT96K Serial
Internet address is 10.1.1.9/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY
CRC checking enabled
Last clearing of "show interface" counters never

Serial0/3/0 is down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input 00:35:31, output 00:35:37, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/1/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec

5 minute output rate 0 bits/sec, 0 packets/sec
1 packets input, 24 bytes, 0 no buffer
Received 1 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
5 packets output, 1026 bytes, 0 underruns
0 output errors, 0 collisions, 74 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
8 carrier transitions
DCD=down DSR=down DTR=up RTS=up CTS=down

Tunnel34 is up, line protocol is up
Hardware is Tunnel
MTU 17920 bytes, BW 100 Kbit/sec, DLY 50000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation TUNNEL, loopback not set
Keepalive not set
Tunnel source 10.1.1.9, destination 10.1.1.10
Tunnel protocol/transport IPv6/IP
Tunnel TTL 255
Tunnel transport MTU 1480 bytes
Tunnel transmit bandwidth 8000 (kbps)
Tunnel receive bandwidth 8000 (kbps)
Last input 00:00:01, output 00:00:02, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 9
Queueing strategy: fifo
Output queue: 0/0 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
210 packets input, 30596 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
244 packets output, 24472 bytes, 0 underruns
0 output errors, 0 collisions, 0 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out

R3#

```
R3#show interfaces counters errors
```

```
R3#
```

```
R3#show cdp neighbors
```

```
Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge  
S - Switch, H - Host, I - IGMP, r - Repeater
```

Device ID	Local Intrfce	Holdtme	Capability	Platform	Port
ID					
R2	Ser 0/2/0.23	156	R S I	2811	Ser
0/2/0.23					
R4	Ser 0/2/0.34	156	R S I	1841	Ser
0/1/0.34					
R3#					


```
R3#show cdp neighbors detail
```

```
-----
```

```
Device ID: R2
```

```
Entry address(es):
```

```
  IP address: 10.1.1.5
```

```
  IPv6 address: 2026::1:1 (global unicast)
```

```
  IPv6 address: FE80::216:9DFF:FEFA:CAB0 (link-local)
```

```
Platform: Cisco 2811, Capabilities: Router Switch IGMP
```

```
Interface: Serial0/2/0.23, Port ID (outgoing port): Serial0/2/0.23
```

```
Holdtime : 148 sec
```

Version :
Cisco IOS Software, 2800 Software (C2800NM-ADVIPSERVICESK9-M), Version
12.4(22)T2, RELEASE SOFTWARE (fc4)
Technical Support: <http://www.cisco.com/techsupport>
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Fri 19-Jun-09 15:34 by prod_rel_team

advertisement version: 2
VTP Management Domain: ''

Device ID: R4
Entry address(es):
 IP address: 10.1.1.10
Platform: Cisco 1841, Capabilities: Router Switch IGMP
Interface: Serial0/2/0.34, Port ID (outgoing port): Serial0/1/0.34
Holdtime : 148 sec

Version :
Cisco IOS Software, 1841 Software (C1841-ADVIPSERVICESK9-M), Version
12.4(25b), RELEASE SOFTWARE (fc1)
Technical Support: <http://www.cisco.com/techsupport>
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Wed 12-Aug-09 10:49 by prod_rel_team

advertisement version: 2
VTP Management Domain: ''

R3#

```
R3#show frame-relay map
Serial0/2/0.23 (up): point-to-point dlci, dlci 302(0x12E,0x48E0),
broadcast
        status defined, active
Serial0/2/0.34 (up): point-to-point dlci, dlci 304(0x130,0x4C00),
broadcast
        status defined, active
R3#
```

```
R3#show arp
```

```
R3#
```

```
R3#show ip arp
```

```
R3#
```

```
R3#show ip interface
FastEthernet0/0 is administratively down, line protocol is down
  Internet protocol processing disabled
FastEthernet0/1 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/0/0 is down, line protocol is down
  Internet protocol processing disabled
Serial0/0/1 is down, line protocol is down
  Internet protocol processing disabled
Serial0/1/0 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/2/0 is up, line protocol is up
  Internet protocol processing disabled
Serial0/2/0.23 is up, line protocol is up
  Internet address is 10.1.1.6/30
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is not set
  Directed broadcast forwarding is disabled
  Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
  224.0.0.5
```

```
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP fast switching on the same interface is enabled
IP Flow switching is disabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
Input features: MCI Check
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
Serial0/2/0.34 is up, line protocol is up
  Internet address is 10.1.1.9/30
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is not set
  Directed broadcast forwarding is disabled
  Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
  224.0.0.13
    224.0.0.5
  Outgoing access list is not set
  Inbound access list is not set
  Proxy ARP is enabled
  Local Proxy ARP is disabled
  Security level is default
  Split horizon is enabled
  ICMP redirects are always sent
  ICMP unreachable are always sent
  ICMP mask replies are never sent
  IP fast switching is enabled
  IP fast switching on the same interface is enabled
  IP Flow switching is disabled
  IP CEF switching is enabled
  IP CEF switching turbo vector
  IP multicast fast switching is enabled
```

```
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
Input features: MCI Check
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
Serial0/3/0 is down, line protocol is down
  Internet protocol processing disabled
Tunnel34 is up, line protocol is up
  Internet protocol processing disabled
R3#
```



```
R3#show ip cef
```

Prefix	Next Hop	Interface
0.0.0.0/0	no route	
0.0.0.0/8	drop	
0.0.0.0/32	receive	
10.1.1.0/30	10.1.1.5	Serial0/2/0.23
10.1.1.4/30	attached	Serial0/2/0.23
10.1.1.4/32	receive	Serial0/2/0.23
10.1.1.6/32	receive	Serial0/2/0.23
10.1.1.7/32	receive	Serial0/2/0.23
10.1.1.8/30	attached	Serial0/2/0.34
10.1.1.8/32	receive	Serial0/2/0.34
10.1.1.9/32	receive	Serial0/2/0.34
10.1.1.11/32	receive	Serial0/2/0.34
10.1.4.4/30	10.1.1.10	Serial0/2/0.34
10.1.4.8/30	10.1.1.10	Serial0/2/0.34
10.2.1.0/24	10.1.1.10	Serial0/2/0.34
10.2.2.0/24	10.1.1.10	Serial0/2/0.34
10.2.4.12/30	10.1.1.10	Serial0/2/0.34
127.0.0.0/8	drop	
224.0.0.0/4	multicast	
224.0.0.0/24	receive	
240.0.0.0/4	drop	
255.255.255.255/32	receive	

```
R3#
```

```
R3#show tcp statistics
Rcvd: 0 Total, 0 no port
      0 checksum error, 0 bad offset, 0 too short
      0 packets (0 bytes) in sequence
      0 dup packets (0 bytes)
      0 partially dup packets (0 bytes)
      0 out-of-order packets (0 bytes)
      0 packets (0 bytes) with data after window
      0 packets after close
      0 window probe packets, 0 window update packets
      0 dup ack packets, 0 ack packets with unsend data
      0 ack packets (0 bytes)
Sent: 0 Total, 0 urgent packets
      0 control packets (including 0 retransmitted)
      0 data packets (0 bytes)
      0 data packets (0 bytes) retransmitted
```

0 data packets (0 bytes) fastretransmitted
0 ack only packets (0 delayed)
0 window probe packets, 0 window update packets
0 Connections initiated, 0 connections accepted, 0 connections
established
0 Connections closed (including 0 dropped, 0 embryonic dropped)
0 Total rxmt timeout, 0 connections dropped in rxmt timeout
0 Keepalive timeout, 0 keepalive probe, 0 Connections dropped in
keepalive
R3#

```
R3#show ip protocols
Routing Protocol is "ospf 1"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  Router ID 3.3.3.3
  It is an area border and autonomous system boundary router
  Redistributing External Routes from,
  Number of areas in this router is 2. 1 normal 0 stub 1 nssa
  Maximum path: 4
  Routing for Networks:
    10.1.1.2 0.0.0.0 area 0
    10.1.1.9 0.0.0.0 area 34
    10.3.3.1 0.0.0.0 area 0
    10.3.3.3 0.0.0.0 area 0
    0.0.0.0 255.255.255.255 area 0
  Reference bandwidth unit is 100 mbps
  Routing Information Sources:
    Gateway          Distance      Last Update
    4.4.4.4           110          00:31:06
    2.2.2.2           110          00:31:16
    10.1.1.1          110          00:31:06
  Distance: (default is 110)
```

```
R3#
```

```
R3#show access-lists
Standard IP access list DENY_10
 10 deny 10.0.0.0, wildcard bits 0.255.255.255
 20 permit any
Standard IP access list DENY_ALL
 10 deny any
Standard IP access list PERMIT_10
 10 permit 10.0.0.0, wildcard bits 0.255.255.255
Standard IP access list PERMIT_ALL
 10 permit any
R3#
```

```
R3#show ip ospf neighbor
```

Neighbor ID	Pri	State	Dead Time	Address
Interface				
2.2.2.2	0	FULL/ -	00:00:39	10.1.1.5
Serial0/2/0.23				
4.4.4.4	0	FULL/ -	00:00:39	10.1.1.10
Serial0/2/0.34				

```
R3#
```

```
R3#show ip ospf interface
Serial0/2/0.23 is up, line protocol is up
  Internet Address 10.1.1.6/30, Area 0
  Process ID 1, Router ID 3.3.3.3, Network Type POINT_TO_POINT, Cost: 64
  Transmit Delay is 1 sec, State POINT_TO_POINT
  Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
    oob-resync timeout 40
    Hello due in 00:00:02
  Supports Link-local Signaling (LLS)
  Cisco NSF helper support enabled
  IETF NSF helper support enabled
  Index 1/2, flood queue length 0
```

```
Next 0x0(0)/0x0(0)
Last flood scan length is 6, maximum is 6
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 1, Adjacent neighbor count is 1
  Adjacent with neighbor 2.2.2.2
  Suppress hello for 0 neighbor(s)
Serial0/2/0.34 is up, line protocol is up
  Internet Address 10.1.1.9/30, Area 34
  Process ID 1, Router ID 3.3.3.3, Network Type POINT_TO_POINT, Cost: 64
  Transmit Delay is 1 sec, State POINT_TO_POINT
  Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
    oob-resync timeout 40
    Hello due in 00:00:02
  Supports Link-local Signaling (LLS)
  Cisco NSF helper support enabled
  IETF NSF helper support enabled
  Index 1/1, flood queue length 0
  Next 0x0(0)/0x0(0)
  Last flood scan length is 1, maximum is 1
  Last flood scan time is 0 msec, maximum is 0 msec
  Neighbor Count is 1, Adjacent neighbor count is 1
    Adjacent with neighbor 4.4.4.4
    Suppress hello for 0 neighbor(s)
R3#
```


R3#show ip ospf database

OSPF Router with ID (3.3.3.3) (Process ID 1)

Router Link States (Area 0)

Link ID count	ADV Router	Age	Seq#	Checksum	Link
2.2.2.2	2.2.2.2	1922	0x80000006	0x00CC97	2
3.3.3.3	3.3.3.3	25	0x80000007	0x0070EB	2

Summary Net Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum
10.1.1.0	2.2.2.2	1922	0x80000001	0x0024C7
10.1.1.8	3.3.3.3	25	0x80000002	0x00B32B

Router Link States (Area 34)

Link ID count	ADV Router	Age	Seq#	Checksum	Link
3.3.3.3	3.3.3.3	25	0x80000008	0x00DA6B	2
4.4.4.4	4.4.4.4	65	0x80000010	0x0067D2	2

Summary Net Link States (Area 34)

Link ID	ADV Router	Age	Seq#	Checksum
0.0.0.0	3.3.3.3	25	0x80000002	0x00DC4C

Type-7 AS External Link States (Area 34)

Link ID	ADV Router	Age	Seq#	Checksum	Tag
10.1.4.4	4.4.4.4	65	0x80000005	0x00F16A	0

10.1.4.8	4.4.4.4	66	0x80000005	0x00C98E	0
10.2.1.0	4.4.4.4	66	0x80000003	0x00451C	0
10.2.2.0	4.4.4.4	66	0x80000003	0x003A26	0
10.2.4.12	4.4.4.4	66	0x80000003	0x0099BB	0

Type-5 AS External Link States

Link ID	ADV Router	Age	Seq#	Checksum	Tag
0.0.0.0	10.1.1.1	2234	0x80000001	0x00CBD9	1
10.1.4.4	3.3.3.3	26	0x80000002	0x00AAC2	0
10.1.4.8	3.3.3.3	26	0x80000002	0x0082E6	0
10.2.1.0	3.3.3.3	26	0x80000002	0x00F976	0
10.2.2.0	3.3.3.3	26	0x80000002	0x00EE80	0
10.2.4.12	3.3.3.3	26	0x80000002	0x004E16	0

R3#

```
R3#show ip route ospf
  10.0.0.0/8 is variably subnetted, 8 subnets, 2 masks
O N2   10.2.4.12/30 [110/20] via 10.1.1.10, 00:31:51, Serial0/2/0.34
O N2   10.1.4.8/30 [110/20] via 10.1.1.10, 00:31:51, Serial0/2/0.34
O N2   10.2.1.0/24 [110/20] via 10.1.1.10, 00:31:51, Serial0/2/0.34
O N2   10.2.2.0/24 [110/20] via 10.1.1.10, 00:31:51, Serial0/2/0.34
O IA   10.1.1.0/30 [110/128] via 10.1.1.5, 00:32:01, Serial0/2/0.23
O N2   10.1.4.4/30 [110/20] via 10.1.1.10, 00:31:51, Serial0/2/0.34
R3#
```

R3#