


```
!  
!  
voice-card 0  
!  
!  
!  
!  
!  
archive  
  log config  
  hidekeys  
!  
!  
!  
!  
!  
!  
!  
!  
interface FastEthernet0/0  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface FastEthernet0/1  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface Serial0/0/0  
  no ip address  
  shutdown  
  no fair-queue  
  clock rate 2000000  
!  
interface Serial0/0/1  
  no ip address  
  shutdown  
!  
interface Serial0/1/0  
  no ip address  
  shutdown  
  clock rate 2000000  
!  
interface Serial0/2/0  
  no ip address  
  encapsulation frame-relay  
!  
interface Serial0/2/0.12 point-to-point  
  ip address 10.1.1.1 255.255.255.252  
  ip pim sparse-dense-mode
```

```
ip nat inside
ip virtual-reassembly
snmp trap link-status
ipv6 address 2026::12:1/122
ipv6 enable
ipv6 ospf 6 area 12
frame-relay interface-dlci 102
!
interface Serial0/3/0
ip address 209.65.200.225 255.255.255.252
ip nat outside
ip virtual-reassembly
clock rate 56000
!
router ospf 1
router-id 10.1.1.1
log-adjacency-changes
redistribute static subnets
network 10.1.1.1 0.0.0.0 area 12
default-information originate always
!
router bgp 65001
no synchronization
bgp router-id 1.1.1.1
bgp log-neighbor-changes
neighbor 209.65.200.226 remote-as 65002
no auto-summary
!
ip forward-protocol nd
ip route 0.0.0.0 0.0.0.0 209.65.200.226
ip http server
no ip http secure-server
!
!
ip nat inside source list 10 interface Serial0/3/0 overload
!
ip access-list standard DENY_10
deny 10.0.0.0 0.255.255.255
permit any
ip access-list standard DENY_ALL
deny any
ip access-list standard PERMIT_10
permit 10.0.0.0 0.255.255.255
ip access-list standard PERMIT_ALL
permit any
!
access-list 10 permit 10.0.0.0 0.255.255.255
ipv6 router ospf 6
router-id 1.1.1.1
log-adjacency-changes
!
!
!
!
```

```
!  
!  
!  
!  
control-plane  
!  
!  
!  
ccm-manager fax protocol cisco  
!  
mgcp fax t38 ecm  
mgcp behavior g729-variants static-pt  
!  
!  
!  
!  
!  
!  
line con 0  
  exec-timeout 0 0  
  logging synchronous  
line aux 0  
line vty 0 4  
  password cisco  
  login  
!  
scheduler allocate 20000 1000  
end  
  
R1#
```

R1#

R1#ping 209.65.200.241

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 209.65.200.241, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 32/34/40 ms

R1#

R1#

R1#ping 209.65.200.226

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 209.65.200.226, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 32/36/56 ms

R1#

R1#

R1#ping 209.65.200.225

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 209.65.200.225, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 64/64/68 ms

R1#

```
R1#ping 10.1.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.1, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132  
ms
```

```
R1#
```

```
R1#ping 10.1.1.2
```

```
Type escape sequence to abort.
```



```
Sending 5, 100-byte ICMP Echos to 10.1.1.2, timeout is 2 seconds:  
!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms  
R1#
```

```
R1#ping 10.1.1.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.5, timeout is 2 seconds:  
!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms  
R1#
```

```
R1#ping 10.1.1.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.6, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/129/132
```

```
ms
```

```
R1#
```

```
R1#ping 10.1.1.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.9, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132
```

```
ms
```

```
R1#
```

```
R1#ping 10.1.1.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.10, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/193/196  
ms
```

```
R1#
```

```
R1#ping 10.1.4.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.10, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/200  
ms
```

```
R1#
```

```
R1#ping 10.1.4.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.9, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/194/196
```

```
ms
```

```
R1#
```

```
R1#ping 10.1.4.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.6, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/200
```

```
ms
```

```
R1#
```

```
R1#ping 10.1.4.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.5, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/193/196
```

```
ms
```

```
R1#
```



```
R1#ping 10.2.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.1, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196  
ms
```

```
R1#
```

```
R1#ping 10.2.2.2
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 10.2.2.2, timeout is 2 seconds:  
!!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/194/196  
ms  
R1#
```

```
R1#ping 10.2.1.254
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 10.2.1.254, timeout is 2 seconds:  
!!!!!
```

Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196
ms
R1#

R1#ping 10.2.4.14

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 10.2.4.14, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196
ms

R1#

```
R1#ping 10.2.4.13
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.13, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196
```

```
ms
```

```
R1#
```

```
R1#ping 10.2.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/196/200  
ms
```

```
R1#
```

```
R1#ping 10.2.2.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/200  
ms
```

```
R1#
```

```
R1#ping 10.2.1.4
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.4, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R1#
```

```
R1#show ip interface brief
```

Interface	IP-Address	OK?	Method	Status
FastEthernet0/0	unassigned	YES	NVRAM	administratively
down down				
FastEthernet0/1	unassigned	YES	NVRAM	administratively
down down				
Serial0/0/0	unassigned	YES	NVRAM	administratively
down down				
Serial0/0/1	unassigned	YES	NVRAM	administratively
down down				
Serial0/1/0	unassigned	YES	NVRAM	administratively
down down				
Serial0/2/0	unassigned	YES	NVRAM	up
up				
Serial0/2/0.12	10.1.1.1	YES	NVRAM	up
up				
Serial0/3/0	209.65.200.225	YES	NVRAM	up
up				
NV10	unassigned	YES	unset	administratively
down down				

```
R1#
```


R1#show ip route

Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS
level-2
ia - IS-IS inter area, * - candidate default, U - per-user static
route
o - ODR, P - periodic downloaded static route

Gateway of last resort is 209.65.200.226 to network 0.0.0.0

```
      209.65.200.0/24 is variably subnetted, 2 subnets, 2 masks
B       209.65.200.240/29 [20/0] via 209.65.200.226, 01:01:19
C       209.65.200.224/30 is directly connected, Serial0/3/0
      10.0.0.0/8 is variably subnetted, 8 subnets, 2 masks
O E2    10.2.4.12/30 [110/20] via 10.1.1.2, 01:03:58, Serial0/2/0.12
O IA    10.1.1.8/30 [110/192] via 10.1.1.2, 01:04:13, Serial0/2/0.12
O E2    10.1.4.8/30 [110/20] via 10.1.1.2, 01:03:58, Serial0/2/0.12
O E2    10.2.1.0/24 [110/20] via 10.1.1.2, 01:03:59, Serial0/2/0.12
O E2    10.2.2.0/24 [110/20] via 10.1.1.2, 01:03:59, Serial0/2/0.12
C       10.1.1.0/30 is directly connected, Serial0/2/0.12
O E2    10.1.4.4/30 [110/20] via 10.1.1.2, 01:03:59, Serial0/2/0.12
O IA    10.1.1.4/30 [110/128] via 10.1.1.2, 01:04:15, Serial0/2/0.12
S*     0.0.0.0/0 [1/0] via 209.65.200.226
R1#
```

```
R1#show processes cpu
```

```
CPU utilization for five seconds: 1%/0%; one minute: 1%; five minutes: 1%
```

PID	Runtime (ms)	Invoked	uSecs	5Sec	1Min	5Min	TTY	Process
1	28	81	345	0.00%	0.00%	0.00%	0	Chunk
Manager								
2	4	828	4	0.00%	0.04%	0.05%	0	Load Meter
3	1196	630	1898	0.00%	0.19%	0.19%	0	Exec
4	0	1	0	0.00%	0.00%	0.00%	0	EDDRI_MAIN
5	5784	487	11876	0.00%	0.11%	0.11%	0	Check
heaps								
6	0	1	0	0.00%	0.00%	0.00%	0	Pool
Manager								
7	0	2	0	0.00%	0.00%	0.00%	0	Timers

68	0	1	0	0.00%	0.00%	0.00%	0	DSPFARM
DSP READ								
69	0	2	0	0.00%	0.00%	0.00%	0	FLEX DNLD
MAIN								
70	0	1	0	0.00%	0.00%	0.00%	0	HDV
background								
71	0	2	0	0.00%	0.00%	0.00%	0	VMI
Background								
72	0	1	0	0.00%	0.00%	0.00%	0	
RF_INTERDEV_DELA								
73	0	1	0	0.00%	0.00%	0.00%	0	
RF_INTERDEV_SCTP								
74	128	212	603	0.00%	0.00%	0.00%	0	BGP I/O
75	0	4141	0	0.00%	0.00%	0.00%	0	Ether-
Switch RBC								
76	0	1	0	0.00%	0.00%	0.00%	0	IGMP
Snooping Pr								
77	0	1	0	0.00%	0.00%	0.00%	0	IGMP
Snooping Re								
78	0	139	0	0.00%	0.00%	0.00%	0	Call
Management								
79	0	1	0	0.00%	0.00%	0.00%	0	AAL2CPS
TIMER_CU								
80	0	1	0	0.00%	0.00%	0.00%	0	CES Line
Conditi								
81	0	1	0	0.00%	0.00%	0.00%	0	
CF_INTERDEV_SCTP								
82	0	1	0	0.00%	0.00%	0.00%	0	Async
write proc								
83	0	1	0	0.00%	0.00%	0.00%	0	Async
write proc								
84	0	1	0	0.00%	0.00%	0.00%	0	Async
write proc								
85	0	1	0	0.00%	0.00%	0.00%	0	Async
write proc								
86	0	70	0	0.00%	0.00%	0.00%	0	DFS flush
period								
87	0	2	0	0.00%	0.00%	0.00%	0	Dot1x Mgr
Proces								
88	0	1	0	0.00%	0.00%	0.00%	0	MAB
Framework								
89	0	1	0	0.00%	0.00%	0.00%	0	EAP
Framework								
90	0	2	0	0.00%	0.00%	0.00%	0	DTP
Protocol								
91	0	4141	0	0.00%	0.00%	0.00%	0	PI MATM
Aging Pr								
92	0	415	0	0.07%	0.00%	0.00%	0	EtherChnl
93	0	2	0	0.00%	0.00%	0.00%	0	Ethernet
CFM								
94	0	4044	0	0.00%	0.00%	0.00%	0	Ethernet
Timer C								
95	0	4155	0	0.00%	0.00%	0.00%	0	linktest

249	0	1	0	0.00%	0.00%	0.00%	0 UNICAST
REKEY							
250	0	1	0	0.00%	0.00%	0.00%	0 UNICAST
REKEY AC							
251	0	4171	0	0.00%	0.00%	0.00%	0 Crypto
Device Up							
252	0	2	0	0.00%	0.00%	0.00%	0 Multi-ISA
Event							
253	0	1	0	0.00%	0.00%	0.00%	0 Multi-ISA
Cleanu							
254	0	1	0	0.00%	0.00%	0.00%	0 PM
Callback							
255	0	1	0	0.00%	0.00%	0.00%	0 Licensing
MIB pr							
256	0	20847	0	0.00%	0.01%	0.00%	0 Atheros
LED Ctro							
257	0	2	0	0.00%	0.00%	0.00%	0 Control-
plane ho							
258	0	1	0	0.00%	0.00%	0.00%	0 DATA
Transfer Pr							
259	0	1	0	0.00%	0.00%	0.00%	0 DATA
Collector							
260	4	2	2000	0.00%	0.00%	0.00%	0 AAA SEND
STOP EV							
261	4	2	2000	0.00%	0.00%	0.00%	0 EEM ED
Resource							
262	0	2	0	0.00%	0.00%	0.00%	0 EEM ED
Routing							
263	0	3	0	0.00%	0.00%	0.00%	0 EEM ED
Track							
264	0	417	0	0.00%	0.00%	0.00%	0 RMON
Recycle Pro							
265	0	2	0	0.00%	0.00%	0.00%	0 RMON
Deferred Se							
266	0	1	0	0.00%	0.00%	0.00%	0 Syslog
Traps							
267	0	131	0	0.00%	0.00%	0.00%	0 Crypto
cTCP proc							
268	8	2	4000	0.00%	0.00%	0.00%	0 VLAN
Manager							
269	52	851	61	0.00%	0.00%	0.00%	0 OSPFv3-6
Hello							
270	0	1	0	0.00%	0.00%	0.00%	0 chkpt
message ha							
271	0	4154	0	0.00%	0.00%	0.00%	0 trunk
conditioni							
272	0	1	0	0.00%	0.00%	0.00%	0 trunk
conditioni							
273	0	4173	0	0.00%	0.00%	0.00%	0 CME
Extension Mo							
274	0	1	0	0.00%	0.00%	0.00%	0 IP SLAs
Ethernet							
275	12	220	54	0.00%	0.00%	0.00%	0 EEM Server

276	0	2	0	0.00%	0.00%	0.00%	0	EEM Policy
Direc								
277	0	3	0	0.00%	0.00%	0.00%	0	EEM ED CLI
278	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
Counter								
279	0	3	0	0.00%	0.00%	0.00%	0	EM ED GOLD
280	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
Interface								
281	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
IOSWD								
282	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
Ipsla								
283	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
None								
284	0	2	0	0.00%	0.00%	0.00%	0	EEM ED Nf
285	0	3	0	0.00%	0.00%	0.00%	0	EEM ED OIR
286	0	3	0	0.00%	0.00%	0.00%	0	EEM ED RF
287	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
SNMP								
288	0	2	0	0.00%	0.00%	0.00%	0	EEM ED
SNMP Noti								
289	0	109	0	0.00%	0.00%	0.00%	0	EEM ED
Timer								
290	4	3	1333	0.00%	0.00%	0.00%	0	EEM ED
Test								
291	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
Config								
292	0	3	0	0.00%	0.00%	0.00%	0	EEM ED Env
293	4	12	333	0.00%	0.00%	0.00%	0	Syslog
294	0	1	0	0.00%	0.00%	0.00%	0	VPDN Test
295	0	3	0	0.00%	0.00%	0.00%	0	EEM ED RPC
296	0	2	0	0.00%	0.00%	0.00%	0	Key Proc
297	0	1	0	0.00%	0.00%	0.00%	0	tHUB
299	8	10	800	0.00%	0.00%	0.00%	0	IPv6 RIB
Event H								
300	4	2086	1	0.00%	0.00%	0.00%	0	CEF: IPv6
proces								
301	516	798	646	0.00%	0.00%	0.00%	0	FR LMI
302	8	73	109	0.00%	0.00%	0.00%	0	FR PVC
event man								
303	0	41654	0	0.00%	0.03%	0.02%	0	FR
Broadcast Out								
304	0	70	0	0.00%	0.00%	0.00%	0	FR ARP
305	0	70	0	0.00%	0.00%	0.00%	0	FR
FRAGMENTATION								
306	0	209	0	0.00%	0.00%	0.00%	0	FR TUNNEL
307	0	1	0	0.00%	0.00%	0.00%	0	FRF9
manager								
308	0	1	0	0.00%	0.00%	0.00%	0	FRF9 timed
event								
309	0	418	0	0.00%	0.00%	0.00%	0	compute
load per								
310	0	4163	0	0.00%	0.00%	0.00%	0	IGMP Input


```
R1#show interfaces
FastEthernet0/0 is administratively down, line protocol is down
  Hardware is MV96340 Ethernet, address is 001d.70a0.c690 (bia
001d.70a0.c690)
  MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto Speed, 100BaseTX/FX
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes
    Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 0 interface resets
    0 unknown protocol drops
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/1 is administratively down, line protocol is down
  Hardware is MV96340 Ethernet, address is 001d.70a0.c691 (bia
001d.70a0.c691)
  MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto Speed, 100BaseTX/FX
  ARP type: ARPA, ARP Timeout 04:00:00
```

```
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 0 interface resets
  0 unknown protocol drops
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier
  0 output buffer failures, 0 output buffers swapped out
Serial0/0/0 is administratively down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 3 interface resets
  0 unknown protocol drops
  0 output buffer failures, 0 output buffers swapped out
  0 carrier transitions
  DCD=down DSR=down DTR=down RTS=down CTS=down

Serial0/0/1 is administratively down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
```

Conversations 0/0/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 3 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=down DSR=down DTR=down RTS=down CTS=down

Serial0/1/0 is administratively down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input 01:09:48, output 01:09:48, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/1/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
5 packets input, 1026 bytes, 0 no buffer
Received 5 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
1 packets output, 24 bytes, 0 underruns
0 output errors, 0 collisions, 3 interface resets
3 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=down DSR=down DTR=up RTS=down CTS=down

Serial0/2/0 is up, line protocol is up
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY, loopback not set
Keepalive set (10 sec)
CRC checking enabled
LMI enq sent 400, LMI stat recvd 400, LMI upd recvd 0, DTE LMI up
LMI enq recvd 0, LMI stat sent 0, LMI upd sent 0
LMI DLCI 1023 LMI type is CISCO frame relay DTE
FR SVC disabled, LAPF state down

Broadcast queue 0/64, broadcasts sent/dropped 1074/0, interface
broadcasts 1018
Last input 00:00:01, output 00:00:01, output hang never
Last clearing of "show interface" counters 01:09:47
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/1/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
2006 packets input, 158270 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
1592 packets output, 124042 bytes, 0 underruns
0 output errors, 0 collisions, 1 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
59 carrier transitions
DCD=up DSR=up DTR=up RTS=up CTS=up

Serial0/2/0.12 is up, line protocol is up
Hardware is GT96K Serial
Internet address is 10.1.1.1/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY
CRC checking enabled
Last clearing of "show interface" counters never

Serial0/3/0 is up, line protocol is up
Hardware is GT96K Serial
Internet address is 209.65.200.225/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input 00:00:05, output 00:00:01, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/1/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
671 packets input, 44419 bytes, 0 no buffer
Received 491 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
1092 packets output, 76702 bytes, 0 underruns
0 output errors, 0 collisions, 5 interface resets
3 unknown protocol drops

0 output buffer failures, 0 output buffers swapped out
5 carrier transitions
DCD=up DSR=up DTR=up RTS=up CTS=up

NVIO is administratively down, line protocol is down
Hardware is NVI
MTU 1514 bytes, BW 56 Kbit/sec, DLY 5000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation UNKNOWN, loopback not set
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 0 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out

R1#

```
R1#show interfaces counters errors
```

```
R1#
```

```
R1#show cdp neighbors
```

Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge
S - Switch, H - Host, I - IGMP, r - Repeater

Device ID	Local Intrfce	Holdtme	Capability	Platform	Port
R2	Ser 0/2/0.12	142	R S I	2811	Ser
0/2/0.12					
R5	Ser 0/3/0	121	R S I	2811	Ser
0/3/0					
R1#					

```
R1#show cdp neighbors detail
```

```
-----
```

```
Device ID: R2
```

Entry address(es):
 IP address: 10.1.1.2
 IPv6 address: 2026::12:2 (global unicast)
 IPv6 address: FE80::216:9DFF:FEFA:CAB0 (link-local)
Platform: Cisco 2811, Capabilities: Router Switch IGMP
Interface: Serial0/2/0.12, Port ID (outgoing port): Serial0/2/0.12
Holdtime : 134 sec

Version :
Cisco IOS Software, 2800 Software (C2800NM-ADVIPSERVICESK9-M), Version
12.4(22)T2, RELEASE SOFTWARE (fc4)
Technical Support: <http://www.cisco.com/techsupport>
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Fri 19-Jun-09 15:34 by prod_rel_team

advertisement version: 2
VTP Management Domain: ''

Device ID: R5
Entry address(es):
 IP address: 209.65.200.226
Platform: Cisco 2811, Capabilities: Router Switch IGMP
Interface: Serial0/3/0, Port ID (outgoing port): Serial0/3/0
Holdtime : 174 sec

Version :
Cisco IOS Software, 2800 Software (C2800NM-ADVIPSERVICESK9-M), Version
12.4(22)T2, RELEASE SOFTWARE (fc4)
Technical Support: <http://www.cisco.com/techsupport>
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Fri 19-Jun-09 15:34 by prod_rel_team

advertisement version: 2
VTP Management Domain: ''

R1#

```
R1#show frame-relay map
Serial0/2/0.12 (up): point-to-point dlci, dlci 102(0x66,0x1860),
broadcast
                status defined, active
R1#
```

```
R1#show arp
```

```
R1#
```

```
R1#show ip arp
```

```
R1#
```

```
R1#show ip interface
```

```
FastEthernet0/0 is administratively down, line protocol is down
```

```
Internet protocol processing disabled
```

```
FastEthernet0/1 is administratively down, line protocol is down
```



```
Internet protocol processing disabled
Serial0/0/0 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/0/1 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/1/0 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/2/0 is up, line protocol is up
  Internet protocol processing disabled
Serial0/2/0.12 is up, line protocol is up
  Internet address is 10.1.1.1/30
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is not set
  Directed broadcast forwarding is disabled
  Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
  224.0.0.5
  Outgoing access list is not set
  Inbound access list is not set
  Proxy ARP is enabled
  Local Proxy ARP is disabled
  Security level is default
  Split horizon is enabled
  ICMP redirects are always sent
  ICMP unreachable are always sent
  ICMP mask replies are never sent
  IP fast switching is enabled
  IP fast switching on the same interface is enabled
  IP Flow switching is disabled
  IP CEF switching is enabled
  IP CEF switching turbo vector
  IP multicast fast switching is enabled
  IP multicast distributed fast switching is disabled
  IP route-cache flags are Fast, CEF
  Router Discovery is disabled
  IP output packet accounting is disabled
  IP access violation accounting is disabled
  TCP/IP header compression is disabled
  RTP/IP header compression is disabled
  Policy routing is disabled
  Network address translation is enabled, interface in domain inside
  BGP Policy Mapping is disabled
  Input features: Stateful Inspection, Virtual Fragment Reassembly,
Virtual Fragment Reassembly After IPsec Decryption, MCI Check
  Output features: NAT Inside, Stateful Inspection
  WCCP Redirect outbound is disabled
  WCCP Redirect inbound is disabled
  WCCP Redirect exclude is disabled
Serial0/3/0 is up, line protocol is up
  Internet address is 209.65.200.225/30
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
```

```
MTU is 1500 bytes
Helper address is not set
Directed broadcast forwarding is disabled
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP fast switching on the same interface is enabled
IP Flow switching is disabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is enabled, interface in domain outside
BGP Policy Mapping is disabled
Input features: Stateful Inspection, Virtual Fragment Reassembly,
Virtual Fragment Reassembly After IPsec Decryption, NAT Outside, MCI
Check
Output features: CCE Output Classification, Post-routing NAT Outside,
Stateful Inspection
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
NVIO is administratively down, line protocol is down
Internet protocol processing disabled
R1#
```

R1#show ip cef

Prefix	Next Hop	Interface
0.0.0.0/0	209.65.200.226	Serial0/3/0
0.0.0.0/8	drop	
0.0.0.0/32	receive	
10.1.1.0/30	attached	Serial0/2/0.12
10.1.1.0/32	receive	Serial0/2/0.12
10.1.1.1/32	receive	Serial0/2/0.12
10.1.1.3/32	receive	Serial0/2/0.12
10.1.1.4/30	10.1.1.2	Serial0/2/0.12
10.1.1.8/30	10.1.1.2	Serial0/2/0.12
10.1.4.4/30	10.1.1.2	Serial0/2/0.12
10.1.4.8/30	10.1.1.2	Serial0/2/0.12
10.2.1.0/24	10.1.1.2	Serial0/2/0.12
10.2.2.0/24	10.1.1.2	Serial0/2/0.12
10.2.4.12/30	10.1.1.2	Serial0/2/0.12
127.0.0.0/8	drop	
209.65.200.224/30	attached	Serial0/3/0
209.65.200.224/32	receive	Serial0/3/0
209.65.200.225/32	receive	Serial0/3/0
209.65.200.227/32	receive	Serial0/3/0
209.65.200.240/29	209.65.200.226	Serial0/3/0
224.0.0.0/4	multicast	
224.0.0.0/24	receive	
240.0.0.0/4	drop	
255.255.255.255/32	receive	

R1#

R1#show tcp statistics

Rcvd: 148 Total, 0 no port

0 checksum error, 0 bad offset, 0 too short

75 packets (1562 bytes) in sequence

0 dup packets (0 bytes)

0 partially dup packets (0 bytes)

0 out-of-order packets (0 bytes)

0 packets (0 bytes) with data after window

0 packets after close

0 window probe packets, 0 window update packets

0 dup ack packets, 0 ack packets with unsend data

73 ack packets (1395 bytes)

Sent: 147 Total, 0 urgent packets

1 control packets (including 0 retransmitted)

```
72 data packets (1394 bytes)
0 data packets (0 bytes) retransmitted
0 data packets (0 bytes) fastretransmitted
74 ack only packets (73 delayed)
0 window probe packets, 0 window update packets
0 Connections initiated, 1 connections accepted, 1 connections
established
0 Connections closed (including 0 dropped, 0 embryonic dropped)
0 Total rxmt timeout, 0 connections dropped in rxmt timeout
0 Keepalive timeout, 0 keepalive probe, 0 Connections dropped in
keepalive
R1#
```

```
R1#show ip protocols
```

```
Routing Protocol is "ospf 1"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  Router ID 10.1.1.1
  It is an autonomous system boundary router
  Redistributing External Routes from,
    static, includes subnets in redistribution
  Number of areas in this router is 1. 1 normal 0 stub 0 nssa
  Maximum path: 4
  Routing for Networks:
    10.1.1.1 0.0.0.0 area 12
Reference bandwidth unit is 100 mbps
Routing Information Sources:
  Gateway          Distance      Last Update
  3.3.3.3          110          01:06:21
  2.2.2.2          110          01:06:37
Distance: (default is 110)
```

```
Routing Protocol is "bgp 65001"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  IGP synchronization is disabled
  Automatic route summarization is disabled
  Neighbor(s):
    Address          FiltIn FiltOut DistIn DistOut Weight RouteMap
    209.65.200.226
  Maximum path: 1
  Routing Information Sources:
    Gateway          Distance      Last Update
    209.65.200.226   20           01:03:44
  Distance: external 20 internal 200 local 200
```

R1#

```
R1#show access-lists
Standard IP access list 10
  10 permit 10.0.0.0, wildcard bits 0.255.255.255 (417 matches)
Standard IP access list DENY_10
  10 deny 10.0.0.0, wildcard bits 0.255.255.255
  20 permit any
Standard IP access list DENY_ALL
  10 deny any
Standard IP access list PERMIT_10
  10 permit 10.0.0.0, wildcard bits 0.255.255.255
Standard IP access list PERMIT_ALL
  10 permit any
R1#
```

```
R1#show ip ospf neighbor
```

Neighbor ID	Pri	State	Dead Time	Address
Interface				
2.2.2.2	0	FULL/ -	00:00:39	10.1.1.2
Serial0/2/0.12				

```
R1#
```



```
R1#show ip ospf interface
Serial0/2/0.12 is up, line protocol is up
  Internet Address 10.1.1.1/30, Area 12
  Process ID 1, Router ID 10.1.1.1, Network Type POINT_TO_POINT, Cost: 64
  Transmit Delay is 1 sec, State POINT_TO_POINT
  Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
    oob-resync timeout 40
    Hello due in 00:00:01
  Supports Link-local Signaling (LLS)
  Cisco NSF helper support enabled
  IETF NSF helper support enabled
  Index 1/1, flood queue length 0
  Next 0x0(0)/0x0(0)
  Last flood scan length is 1, maximum is 1
  Last flood scan time is 0 msec, maximum is 0 msec
  Neighbor Count is 1, Adjacent neighbor count is 1
    Adjacent with neighbor 2.2.2.2
  Suppress hello for 0 neighbor(s)
R1#
```

R1#show ip ospf database

OSPF Router with ID (10.1.1.1) (Process ID 1)

Router Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum	Link
count					
2.2.2.2	2.2.2.2	33	0x8000000C	0x00392B	2
10.1.1.1	10.1.1.1	2012	0x80000004	0x00A6C0	2

Summary Net Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
10.1.1.4	2.2.2.2	33	0x80000003	0x00F7ED
10.1.1.8	2.2.2.2	33	0x80000003	0x00524F

Summary ASB Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
3.3.3.3	2.2.2.2	33	0x80000003	0x0033B2

Type-5 AS External Link States

Link ID	ADV Router	Age	Seq#	Checksum	Tag
0.0.0.0	10.1.1.1	240	0x80000003	0x00C7DB	1
10.1.4.4	3.3.3.3	63	0x80000003	0x00A8C3	0
10.1.4.8	3.3.3.3	63	0x80000003	0x0080E7	0
10.2.1.0	3.3.3.3	64	0x80000003	0x00F777	0
10.2.2.0	3.3.3.3	64	0x80000003	0x00EC81	0
10.2.4.12	3.3.3.3	64	0x80000003	0x004C17	0

R1#

```
R1#show ip route ospf
    10.0.0.0/8 is variably subnetted, 8 subnets, 2 masks
O E2   10.2.4.12/30 [110/20] via 10.1.1.2, 01:07:00, Serial0/2/0.12
O IA   10.1.1.8/30 [110/192] via 10.1.1.2, 01:07:16, Serial0/2/0.12
O E2   10.1.4.8/30 [110/20] via 10.1.1.2, 01:07:00, Serial0/2/0.12
O E2   10.2.1.0/24 [110/20] via 10.1.1.2, 01:07:00, Serial0/2/0.12
O E2   10.2.2.0/24 [110/20] via 10.1.1.2, 01:07:00, Serial0/2/0.12
O E2   10.1.4.4/30 [110/20] via 10.1.1.2, 01:07:00, Serial0/2/0.12
O IA   10.1.1.4/30 [110/128] via 10.1.1.2, 01:07:16, Serial0/2/0.12
R1#
```

```
R1#show ip bgp neighbors
BGP neighbor is 209.65.200.226, remote AS 65002, external link
  BGP version 4, remote router ID 5.5.5.5
  BGP state = Established, up for 01:11:41
  Last read 00:00:32, last write 00:00:21, hold time is 180, keepalive
interval is 60 seconds
  Neighbor capabilities:
    Route refresh: advertised and received(new)
    Address family IPv4 Unicast: advertised and received
  Message statistics:
    InQ depth is 0
    OutQ depth is 0

                Sent          Rcvd
Opens:           1            1
Notifications:  0            0
Updates:         0            4
Keepalives:     72           71
```

Route Refresh: 0 0
Total: 73 76
Default minimum time between advertisement runs is 30 seconds

For address family: IPv4 Unicast
BGP table version 4, neighbor version 4/0
Output queue size : 0
Index 1, Offset 0, Mask 0x2
1 update-group member

	Sent	Rcvd
Prefix activity:	----	----
Prefixes Current:	0	1 (Consumes 52 bytes)
Prefixes Total:	0	3
Implicit Withdraw:	0	1
Explicit Withdraw:	0	1
Used as bestpath:	n/a	1
Used as multipath:	n/a	0

	Outbound	Inbound
Local Policy Denied Prefixes:	-----	-----
Bestpath from this peer:	2	n/a
Total:	2	0

Number of NLRI in the update sent: max 0, min 0

Address tracking is enabled, the RIB does have a route to 209.65.200.226

Connections established 1; dropped 0

Last reset never

Transport(tcp) path-mtu-discovery is enabled

Connection state is ESTAB, I/O status: 1, unread input bytes: 0

Connection is ECN Disabled, Minimum incoming TTL 0, Outgoing TTL 1

Local host: 209.65.200.225, Local port: 179

Foreign host: 209.65.200.226, Foreign port: 33879

Connection tableid (VRF): 0

Enqueued packets for retransmit: 0, input: 0 mis-ordered: 0 (0 bytes)

Event Timers (current time is 0x429734):

Timer	Starts	Wakeups	Next
Retrans	74	0	0x0
TimeWait	0	0	0x0
AckHold	76	74	0x0
SendWnd	0	0	0x0
KeepAlive	0	0	0x0
GiveUp	0	0	0x0
PmtuAger	0	0	0x0
DeadWait	0	0	0x0
Linger	0	0	0x0
ProcessQ	0	0	0x0

iss: 2810084649 snduna: 2810086063 sndnxt: 2810086063 sndwnd: 14971

irs: 4186576622 rcvnxt: 4186578204 rcvwnd: 16270 delrcvwnd: 114

SRTT: 300 ms, RTTO: 303 ms, RTV: 3 ms, KRTT: 0 ms
minRTT: 20 ms, maxRTT: 300 ms, ACK hold: 200 ms
Status Flags: passive open, gen tcbs
Option Flags: nagle, path mtu capable
IP Precedence value : 6

Datagrams (max data segment is 1460 bytes):
Rcvd: 150 (out of order: 0), with data: 76, total data bytes: 1581
Sent: 149 (retransmit: 0, fastretransmit: 0, partialack: 0, Second
Congestion: 0), with data: 73, total data bytes: 1413
Packets received in fast path: 0, fast processed: 0, slow path: 0
fast lock acquisition failures: 0, slow path: 0

R1#

```
R1#show ip bgp summary
BGP router identifier 1.1.1.1, local AS number 65001
BGP table version is 4, main routing table version 4
1 network entries using 132 bytes of memory
1 path entries using 52 bytes of memory
2/1 BGP path/bestpath attribute entries using 296 bytes of memory
1 BGP AS-PATH entries using 24 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 504 total bytes of memory
BGP activity 2/1 prefixes, 2/1 paths, scan interval 60 secs

Neighbor          V    AS MsgRcvd MsgSent   TblVer  InQ  OutQ Up/Down
State/PfxRcd
209.65.200.226  4 65002      76      73       4    0    0 01:11:53
1
R1#
```

```
R1#show ip bgp
BGP table version is 4, local router ID is 1.1.1.1
Status codes: s suppressed, d damped, h history, * valid, > best, i -
internal,
                r RIB-failure, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

   Network          Next Hop           Metric LocPrf Weight Path
*> 209.65.200.240/29
                209.65.200.226           0             0 65002 i
R1#
```



```
R1#show ip route bgp
    209.65.200.0/24 is variably subnetted, 2 subnets, 2 masks
B       209.65.200.240/29 [20/0] via 209.65.200.226, 01:04:56
R1#
```

```
R1#show ip nat translations
```

```
R1#
```

```
R1#show ip nat statistics
Total active translations: 0 (0 static, 0 dynamic; 0 extended)
Peak translations: 29, occurred 00:42:25 ago
Outside interfaces:
  Serial0/3/0
Inside interfaces:
  Serial0/2/0.12
Hits: 431 Misses: 0
CEF Translated packets: 13, CEF Punted packets: 418
Expired translations: 94
Dynamic mappings:
-- Inside Source
[Id: 1] access-list 10 interface Serial0/3/0 refcount 0
Appl doors: 0
Normal doors: 0
```

Queued Packets: 0

R1#

R1#