

```
ASW1#
ASW1#show running-config
Building configuration...

Current configuration : 3591 bytes
!
version 12.1
no service pad
service timestamps debug uptime
service timestamps log uptime
no service password-encryption
!
hostname ASW1
!
!
ip subnet-zero
!
!
spanning-tree mode pvst
no spanning-tree optimize bpdu transmission
spanning-tree extend system-id
!
!
!
!
interface Port-channel1
  switchport trunk allowed vlan 10,200
  switchport mode trunk
  flowcontrol send off
!
interface Port-channel2
  switchport trunk allowed vlan 10,200
  switchport mode trunk
  flowcontrol send off
!
interface FastEthernet0/1
  switchport access vlan 10
  switchport mode access
  switchport port-security
  spanning-tree portfast
!
interface FastEthernet0/2
  switchport access vlan 10
  switchport mode access
  switchport port-security
  spanning-tree portfast
!
interface FastEthernet0/3
  switchport access vlan 10
  switchport mode access
  switchport port-security
  spanning-tree portfast
!
interface FastEthernet0/4
```

```
switchport access vlan 10
switchport mode access
switchport port-security
spanning-tree portfast
!
interface FastEthernet0/5
switchport access vlan 10
switchport mode access
switchport port-security
spanning-tree portfast
!
interface FastEthernet0/6
switchport access vlan 10
switchport mode access
switchport port-security
spanning-tree portfast
!
interface FastEthernet0/7
switchport access vlan 10
switchport mode access
switchport port-security
spanning-tree portfast
!
interface FastEthernet0/8
switchport access vlan 10
switchport mode access
switchport port-security
spanning-tree portfast
!
interface FastEthernet0/9
switchport access vlan 10
switchport mode access
switchport port-security
spanning-tree portfast
!
interface FastEthernet0/10
switchport access vlan 10
switchport mode access
switchport port-security
spanning-tree portfast
!
interface FastEthernet0/11
switchport access vlan 10
switchport mode access
switchport port-security
spanning-tree portfast
!
interface FastEthernet0/12
switchport access vlan 10
switchport mode access
switchport port-security
spanning-tree portfast
!
interface FastEthernet0/13
```

```
switchport access vlan 10
switchport mode access
switchport port-security
spanning-tree portfast
!
interface FastEthernet0/14
switchport access vlan 10
switchport mode access
switchport port-security
spanning-tree portfast
!
interface FastEthernet0/15
switchport access vlan 10
switchport mode access
switchport port-security
spanning-tree portfast
!
interface FastEthernet0/16
switchport trunk allowed vlan 10,200
switchport mode trunk
channel-group 2 mode active
!
interface FastEthernet0/17
switchport trunk allowed vlan 10,200
switchport mode trunk
channel-group 2 mode active
!
interface FastEthernet0/18
switchport trunk allowed vlan 10,200
switchport mode trunk
channel-group 2 mode active
!
interface FastEthernet0/19
switchport trunk allowed vlan 10,200
switchport mode trunk
channel-group 1 mode passive
!
interface FastEthernet0/20
switchport trunk allowed vlan 10,200
switchport mode trunk
channel-group 1 mode passive
!
interface FastEthernet0/21
switchport trunk allowed vlan 10,200
switchport mode trunk
channel-group 1 mode passive
!
interface FastEthernet0/22
switchport mode trunk
shutdown
!
interface FastEthernet0/23
switchport mode trunk
shutdown
```

```
!  
interface FastEthernet0/24  
  switchport mode trunk  
  shutdown  
!  
interface Vlan1  
  no ip address  
  no ip route-cache  
  shutdown  
!  
interface Vlan200  
  ip address 192.168.1.131 255.255.255.224  
  no ip route-cache  
!  
ip http server  
!  
line con 0  
  exec-timeout 0 0  
  logging synchronous  
line vty 0 4  
  login  
line vty 5 15  
  login  
!  
!  
end
```

ASW1#

ASW1#show ip interface brief

Interface	IP-Address	OK?	Method	Status
Vlan1	unassigned	YES	NVRAM	administratively
down down				
Vlan200	192.168.1.131	YES	NVRAM	up
up				
FastEthernet0/1	unassigned	YES	unset	up
up				
FastEthernet0/2	unassigned	YES	unset	down
down				
FastEthernet0/3	unassigned	YES	unset	down
down				
FastEthernet0/4	unassigned	YES	unset	down
down				
FastEthernet0/5	unassigned	YES	unset	down
down				
FastEthernet0/6	unassigned	YES	unset	down
down				
FastEthernet0/7	unassigned	YES	unset	down
down				
FastEthernet0/8	unassigned	YES	unset	down
down				
FastEthernet0/9	unassigned	YES	unset	down
down				
FastEthernet0/10	unassigned	YES	unset	down
down				
FastEthernet0/11	unassigned	YES	unset	down
down				
FastEthernet0/12	unassigned	YES	unset	down
down				
FastEthernet0/13	unassigned	YES	unset	down
down				
FastEthernet0/14	unassigned	YES	unset	down
down				
FastEthernet0/15	unassigned	YES	unset	down
down				
FastEthernet0/16	unassigned	YES	unset	up
up				
FastEthernet0/17	unassigned	YES	unset	up
up				
FastEthernet0/18	unassigned	YES	unset	up
up				
FastEthernet0/19	unassigned	YES	unset	up
up				

```

FastEthernet0/20      unassigned      YES unset  up
up
FastEthernet0/21      unassigned      YES unset  up
up
FastEthernet0/22      unassigned      YES unset  administratively
down down
FastEthernet0/23      unassigned      YES unset  administratively
down down
FastEthernet0/24      unassigned      YES unset  administratively
down down
Port-channel1         unassigned      YES unset  up
up
Port-channel2         unassigned      YES unset  up
up
ASW1#

```

```

ASW1#show processes cpu
CPU utilization for five seconds: 2%/1%; one minute: 3%; five minutes: 1%
PID Runtime(ms)   Invoked      uSecs   5Sec   1Min   5Min  TTY Process

```

1	0	1	0	0.00%	0.00%	0.00%	0	Chunk
Manager								
2	12	1416	8	0.00%	0.00%	0.00%	0	Load Meter
3	848	126	6730	0.00%	0.00%	0.00%	0	SpanTree
Helper								
4	1948	721	2701	0.00%	0.03%	0.00%	0	Check
heaps								
5	4	2	2000	0.00%	0.00%	0.00%	0	Pool
Manager								
6	4	2	2000	0.00%	0.00%	0.00%	0	Timers
7	40	3	13333	0.00%	0.00%	0.00%	0	Entity MIB
API								
8	24	1769	13	0.00%	0.00%	0.00%	0	HC Counter
Timer								
9	0	127	0	0.00%	0.00%	0.00%	0	ARP Input
10	0	5	0	0.00%	0.00%	0.00%	0	Net Input
11	0	1	0	0.00%	0.00%	0.00%	0	Critical
Bkgnd								
12	2288	5659	404	0.08%	0.01%	0.00%	0	Net
Background								
13	4	123	32	0.00%	0.00%	0.00%	0	Logger
14	56	7072	7	0.00%	0.00%	0.00%	0	TTY
Background								
15	32	7082	4	0.00%	0.00%	0.00%	0	Per-Second
Jobs								
16	28	1417	19	0.00%	0.00%	0.00%	0	Compute
load avg								
17	1012	119	8504	0.16%	0.01%	0.00%	0	Per-minute
Jobs								
18	8	58	137	0.00%	0.00%	0.00%	0	AggMgr
Process								
19	0	2	0	0.00%	0.00%	0.00%	0	Calhoun
Storm Co								
20	828	176860	4	0.08%	0.01%	0.00%	0	Calhoun
LED Proc								
21	56520	14041	4025	0.81%	0.80%	0.77%	0	Calhoun
Statisti								
22	40	35371	1	0.00%	0.00%	0.00%	0	HMATM
Learn proc								
23	1156	44	26272	0.00%	0.00%	0.00%	0	CalhounPM
24	364	35377	10	0.00%	0.00%	0.00%	0	Link
Status Proc								
25	44	35380	1	0.00%	0.00%	0.00%	0	Calhoun
PHY Loop								
26	0	1	0	0.00%	0.00%	0.00%	0	
CalhounInsIpopti								
27	0	1	0	0.00%	0.00%	0.00%	0	Calhoun
DHCP Sno								
28	1072	1760	609	0.00%	0.00%	0.00%	0	CDP
Protocol								
29	0	59	0	0.00%	0.00%	0.00%	0	DHCP
Snooping								
30	0	118	0	0.00%	0.00%	0.00%	0	IP Input

31	1544	2627	587	0.00%	0.00%	0.00%	0 DTP
Protocol							
32	20	710	28	0.00%	0.00%	0.00%	0 Ethchnl
33	156	88	1772	0.00%	0.00%	0.00%	0 VLAN
Manager							
34	0	2	0	0.00%	0.00%	0.00%	0 PI MATM
Aging Pr							
35	48	55	872	0.00%	0.00%	0.00%	0 VMATM
Callback							
36	12012	13822	869	0.08%	0.07%	0.06%	0 Spanning
Tree							
37	40	7080	5	0.00%	0.00%	0.00%	0 UDLD
38	8	128	62	0.00%	0.00%	0.00%	0 Port-
Security							
39	4	2	2000	0.00%	0.00%	0.00%	0 DHCPD
Receive							
40	0	1	0	0.00%	0.00%	0.00%	0 HTTP Timer
41	0	1	0	0.00%	0.00%	0.00%	0 RARP Input
42	0	1	0	0.00%	0.00%	0.00%	0 TCP Timer
43	0	1	0	0.00%	0.00%	0.00%	0 TCP
Protocols							
44	0	1	0	0.00%	0.00%	0.00%	0 Socket
Timers							
45	36	50	720	0.00%	0.00%	0.00%	0 L2MM
46	272	572	475	0.00%	0.00%	0.00%	0 MRD
47	532	526	1011	0.00%	0.00%	0.00%	0 IGMP SN
48	208	125	1664	0.00%	0.00%	0.00%	0 IGMP
Snooping Pr							
49	252	854	295	0.00%	0.00%	0.00%	0 IGMP
Snooping Re							
50	2016	7741	260	0.00%	0.01%	0.00%	0 IP
Multicast Dat							
51	4	2	2000	0.00%	0.00%	0.00%	0 L2TRACE
SERVER							
52	0	91	0	0.00%	0.00%	0.00%	0 Cluster L2
53	4	709	5	0.00%	0.00%	0.00%	0 Cluster
RARP							
54	552	1598	345	0.00%	0.01%	0.00%	0 Cluster
Base							
55	1312	155	8464	0.49%	1.52%	0.38%	0 Exec
56	0	59	0	0.00%	0.00%	0.00%	0 DHCPD
Timer							
57	0	2	0	0.00%	0.00%	0.00%	0 Router
Autoconf							
58	0	1	0	0.00%	0.00%	0.00%	0 Syslog
Traps							
59	0	2	0	0.00%	0.00%	0.00%	0 VTPMIB
EDIT BUFF							
60	544	19296	28	0.00%	0.00%	0.00%	0 PM
Callback							
61	12	93	129	0.00%	0.00%	0.00%	0 VTP Trap
Process							
62	4	1991	2	0.00%	0.00%	0.00%	0 DHCPD
Database							

63	80	7081	11	0.00%	0.00%	0.00%	0	Calhoun
EnvMon P								
64	0	2	0	0.00%	0.00%	0.00%	0	STP STACK
TOPOLO								
65	4	2	2000	0.00%	0.00%	0.00%	0	STP FAST
TRANSIT								
66	0	2	0	0.00%	0.00%	0.00%	0	STP STACK
TOPOLO								
67	0	2	0	0.00%	0.00%	0.00%	0	CSRT RAPID
TRANS								
69	2368	4641	510	0.00%	0.01%	0.00%	0	LACP
Protocol								
ASW1#								

```

ASW1#show interfaces
Vlan1 is administratively down, line protocol is down
  Hardware is CPU Interface, address is 0015.faac.46c0 (bia
0015.faac.46c0)
  MTU 1500 bytes, BW 1000000 Kbit, DLY 10 usec,

```

```
    reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 IP multicast)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 3 interface resets
    0 output buffer failures, 0 output buffers swapped out
Vlan200 is up, line protocol is up
    Hardware is CPU Interface, address is 0015.faac.46c0 (bia
0015.faac.46c0)
    Internet address is 192.168.1.131/27
    MTU 1500 bytes, BW 1000000 Kbit, DLY 10 usec,
        reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
ARP type: ARPA, ARP Timeout 04:00:00
Last input 01:01:28, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 1000 bits/sec, 2 packets/sec
5 minute output rate 14000 bits/sec, 2 packets/sec
    19363 packets input, 1590367 bytes, 0 no buffer
    Received 4 broadcasts (0 IP multicast)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    21457 packets output, 13072554 bytes, 0 underruns
    0 output errors, 2 interface resets
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/1 is up, line protocol is up (connected)
    Hardware is Fast Ethernet, address is 0015.faac.46c1 (bia
0015.faac.46c1)
    MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
        reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 100BaseTX
input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 01:58:06, output 00:00:00, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
```

```
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1483 packets input, 139375 bytes, 0 no buffer
  Received 1048 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 727 multicast, 0 pause input
  0 input packets with dribble condition detected
  13190 packets output, 959107 bytes, 0 underruns
  0 output errors, 0 collisions, 2 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/2 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 0015.faac.46c2 (bia
0015.faac.46c2)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 100BaseTX
  input flow-control is unsupported output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output 01:58:14, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 64 bytes, 0 no buffer
  Received 0 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  1 packets output, 64 bytes, 0 underruns
  0 output errors, 0 collisions, 2 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/3 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 0015.faac.46c3 (bia
0015.faac.46c3)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 100BaseTX
  input flow-control is unsupported output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output 01:58:16, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
```

```
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 64 bytes, 0 no buffer
  Received 0 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  1 packets output, 64 bytes, 0 underruns
  0 output errors, 0 collisions, 2 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/4 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 0015.faac.46c4 (bia
0015.faac.46c4)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 100BaseTX
  input flow-control is unsupported output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output 01:58:17, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    1 packets input, 64 bytes, 0 no buffer
    Received 0 broadcasts (0 multicast)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
    0 input packets with dribble condition detected
    1 packets output, 64 bytes, 0 underruns
    0 output errors, 0 collisions, 2 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/5 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 0015.faac.46c5 (bia
0015.faac.46c5)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 100BaseTX
  input flow-control is unsupported output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output 01:58:19, output hang never
```

```
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 64 bytes, 0 no buffer
  Received 0 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  1 packets output, 64 bytes, 0 underruns
  0 output errors, 0 collisions, 2 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/6 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 0015.faac.46c6 (bia
0015.faac.46c6)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 100BaseTX
  input flow-control is unsupported output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output 01:58:21, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    1 packets input, 64 bytes, 0 no buffer
    Received 0 broadcasts (0 multicast)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
    0 input packets with dribble condition detected
    1 packets output, 64 bytes, 0 underruns
    0 output errors, 0 collisions, 2 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/7 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 0015.faac.46c7 (bia
0015.faac.46c7)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 100BaseTX
  input flow-control is unsupported output flow-control is unsupported
```

```
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output 01:58:22, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 64 bytes, 0 no buffer
  Received 0 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  1 packets output, 64 bytes, 0 underruns
  0 output errors, 0 collisions, 2 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/8 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 0015.faac.46c8 (bia
0015.faac.46c8)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 100BaseTX
  input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output 01:58:24, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 64 bytes, 0 no buffer
  Received 0 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  1 packets output, 64 bytes, 0 underruns
  0 output errors, 0 collisions, 2 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/9 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 0015.faac.46c9 (bia
0015.faac.46c9)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
```

```
Auto-duplex, Auto-speed, media type is 100BaseTX
input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output 01:58:25, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 64 bytes, 0 no buffer
  Received 0 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  1 packets output, 64 bytes, 0 underruns
  0 output errors, 0 collisions, 2 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/10 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 0015.faac.46ca (bia
0015.faac.46ca)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 100BaseTX
input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output 01:58:27, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 64 bytes, 0 no buffer
  Received 0 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  1 packets output, 64 bytes, 0 underruns
  0 output errors, 0 collisions, 2 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/11 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 0015.faac.46cb (bia
0015.faac.46cb)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
```

```
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 100BaseTX
input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output 01:58:28, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 64 bytes, 0 no buffer
  Received 0 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  1 packets output, 64 bytes, 0 underruns
  0 output errors, 0 collisions, 2 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/12 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 0015.faac.46cc (bia
0015.faac.46cc)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 100BaseTX
input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output 01:58:30, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 64 bytes, 0 no buffer
  Received 0 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  1 packets output, 64 bytes, 0 underruns
  0 output errors, 0 collisions, 2 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/13 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 0015.faac.46cd (bia
0015.faac.46cd)
```



```
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 100BaseTX
input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output 01:58:31, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 64 bytes, 0 no buffer
  Received 0 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  1 packets output, 64 bytes, 0 underruns
  0 output errors, 0 collisions, 2 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/14 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 0015.faac.46ce (bia
0015.faac.46ce)
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 100BaseTX
input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output 01:58:33, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 64 bytes, 0 no buffer
  Received 0 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  1 packets output, 64 bytes, 0 underruns
  0 output errors, 0 collisions, 2 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/15 is down, line protocol is down (notconnect)
```

Hardware is Fast Ethernet, address is 0015.faac.46cf (bia 0015.faac.46cf)
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 100BaseTX
input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output 01:58:34, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
1 packets input, 64 bytes, 0 no buffer
Received 0 broadcasts (0 multicast)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 0 multicast, 0 pause input
0 input packets with dribble condition detected
1 packets output, 64 bytes, 0 underruns
0 output errors, 0 collisions, 2 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/16 is up, line protocol is up (connected)
Hardware is Fast Ethernet, address is 0015.faac.46d0 (bia 0015.faac.46d0)

MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 100BaseTX
input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:10, output 00:00:01, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 1000 bits/sec, 2 packets/sec
5706 packets input, 480663 bytes, 0 no buffer
Received 4831 broadcasts (0 multicast)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 4801 multicast, 0 pause input
0 input packets with dribble condition detected
13014 packets output, 1034403 bytes, 0 underruns
0 output errors, 0 collisions, 2 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output

0 output buffer failures, 0 output buffers swapped out
FastEthernet0/17 is up, line protocol is up (connected)
Hardware is Fast Ethernet, address is 0015.faac.46d1 (bia 0015.faac.46d1)
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 100BaseTX
input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:11, output 00:00:02, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
1431 packets input, 150574 bytes, 0 no buffer
Received 614 broadcasts (0 multicast)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 614 multicast, 0 pause input
0 input packets with dribble condition detected
1698 packets output, 178512 bytes, 0 underruns
0 output errors, 0 collisions, 2 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out

FastEthernet0/18 is up, line protocol is up (connected)
Hardware is Fast Ethernet, address is 0015.faac.46d2 (bia 0015.faac.46d2)
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 100BaseTX
input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:12, output 00:00:04, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
1859 packets input, 180590 bytes, 0 no buffer
Received 1156 broadcasts (0 multicast)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 1156 multicast, 0 pause input
0 input packets with dribble condition detected
1490 packets output, 160230 bytes, 0 underruns
0 output errors, 0 collisions, 2 interface resets

```
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/19 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 0015.faac.46d3 (bia
0015.faac.46d3)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 100BaseTX
  input flow-control is unsupported output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:02, output 00:00:00, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    5857 packets input, 489405 bytes, 0 no buffer
    Received 4843 broadcasts (0 multicast)
    0 runts, 0 giants, 0 throttles
    1 input errors, 0 CRC, 1 frame, 0 overrun, 0 ignored
    0 watchdog, 4806 multicast, 0 pause input
    0 input packets with dribble condition detected
    6538 packets output, 574204 bytes, 0 underruns
    0 output errors, 0 collisions, 2 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/20 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 0015.faac.46d4 (bia
0015.faac.46d4)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 100BaseTX
  input flow-control is unsupported output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:07, output 00:00:07, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    1275 packets input, 138044 bytes, 0 no buffer
    Received 617 broadcasts (0 multicast)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 617 multicast, 0 pause input
    0 input packets with dribble condition detected
```

```
    2200 packets output, 225698 bytes, 0 underruns
    0 output errors, 0 collisions, 2 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/21 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 0015.faac.46d5 (bia
0015.faac.46d5)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 100BaseTX
  input flow-control is unsupported output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:08, output 00:00:08, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    7666 packets input, 597434 bytes, 0 no buffer
  Received 7012 broadcasts (0 multicast)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 7012 multicast, 0 pause input
    0 input packets with dribble condition detected
  1888 packets output, 197880 bytes, 0 underruns
    0 output errors, 0 collisions, 2 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/22 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 0015.faac.46d6 (bia
0015.faac.46d6)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 100BaseTX
  input flow-control is unsupported output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output 01:58:46, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    1 packets input, 64 bytes, 0 no buffer
  Received 0 broadcasts (0 multicast)
    0 runts, 0 giants, 0 throttles
```

```
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 0 multicast, 0 pause input
0 input packets with dribble condition detected
1 packets output, 64 bytes, 0 underruns
0 output errors, 0 collisions, 2 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/23 is administratively down, line protocol is down
(disabled)
Hardware is Fast Ethernet, address is 0015.faac.46d7 (bia
0015.faac.46d7)
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 100BaseTX
input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output 01:58:47, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 64 bytes, 0 no buffer
Received 0 broadcasts (0 multicast)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 0 multicast, 0 pause input
0 input packets with dribble condition detected
1 packets output, 64 bytes, 0 underruns
0 output errors, 0 collisions, 2 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/24 is administratively down, line protocol is down
(disabled)
Hardware is Fast Ethernet, address is 0015.faac.46d8 (bia
0015.faac.46d8)
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 100BaseTX
input flow-control is unsupported output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output 01:58:48, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
```

```
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 64 bytes, 0 no buffer
  Received 0 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  1 packets output, 64 bytes, 0 underruns
  0 output errors, 0 collisions, 2 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
Port-channel1 is up, line protocol is up (connected)
  Hardware is EtherChannel, address is 0015.faac.46d5 (bia
0015.faac.46d5)
  MTU 1500 bytes, BW 300000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Full-duplex, 100Mb/s, media type is unknown media type
  input flow-control is off, output flow-control is off
  Members in this channel: Fa0/19 Fa0/20 Fa0/21
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:00, output 00:00:17, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  14726 packets input, 1217520 bytes, 0 no buffer
  Received 12403 broadcasts (0 multicast)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 12366 multicast, 0 pause input
  0 input packets with dribble condition detected
  8649 packets output, 815273 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
Port-channel2 is up, line protocol is up (connected)
  Hardware is EtherChannel, address is 0015.faac.46d1 (bia
0015.faac.46d1)
  MTU 1500 bytes, BW 300000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Full-duplex, 100Mb/s, media type is unknown media type
  input flow-control is off, output flow-control is off
  Members in this channel: Fa0/16 Fa0/17 Fa0/18
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:58:38, output 00:00:00, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
```

```
Output queue: 0/40 (size/max)
5 minute input rate 1000 bits/sec, 1 packets/sec
5 minute output rate 1000 bits/sec, 2 packets/sec
 8984 packets input, 810391 bytes, 0 no buffer
Received 6587 broadcasts (0 multicast)
 0 runts, 0 giants, 0 throttles
 0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
 0 watchdog, 6561 multicast, 0 pause input
 0 input packets with dribble condition detected
15674 packets output, 1319142 bytes, 0 underruns
 0 output errors, 0 collisions, 1 interface resets
 0 babbles, 0 late collision, 0 deferred
 0 lost carrier, 0 no carrier, 0 PAUSE output
 0 output buffer failures, 0 output buffers swapped out
ASW1#
```

```
ASW1#show interfaces counters errors
```

Port	Align-Err	FCS-Err	Xmit-Err	Rcv-Err	UnderSize
------	-----------	---------	----------	---------	-----------

Fa0/1	0	0	0	0	0
Fa0/2	0	0	0	0	0
Fa0/3	0	0	0	0	0
Fa0/4	0	0	0	0	0
Fa0/5	0	0	0	0	0
Fa0/6	0	0	0	0	0
Fa0/7	0	0	0	0	0
Fa0/8	0	0	0	0	0
Fa0/9	0	0	0	0	0
Fa0/10	0	0	0	0	0
Fa0/11	0	0	0	0	0
Fa0/12	0	0	0	0	0
Fa0/13	0	0	0	0	0
Fa0/14	0	0	0	0	0
Fa0/15	0	0	0	0	0
Fa0/16	0	0	0	0	0
Fa0/17	0	0	0	0	0
Fa0/18	0	0	0	0	0
Fa0/19	1	0	0	2	0
Fa0/20	0	0	0	0	0
Fa0/21	0	0	0	0	0
Fa0/22	0	0	0	0	0
Fa0/23	0	0	0	0	0
Fa0/24	0	0	0	0	0
Po1	0	0	0	0	0
Po2	0	0	0	0	0

Port	Single-Col	Multi-Col	Late-Col	Excess-Col	Carri-Sen	Runts
Giants						
Fa0/1	0	0	0	0	0	0
0						
Fa0/2	0	0	0	0	0	0
0						
Fa0/3	0	0	0	0	0	0
0						
Fa0/4	0	0	0	0	0	0
0						
Fa0/5	0	0	0	0	0	0
0						
Fa0/6	0	0	0	0	0	0
0						
Fa0/7	0	0	0	0	0	0
0						
Fa0/8	0	0	0	0	0	0
0						
Fa0/9	0	0	0	0	0	0
0						
Fa0/10	0	0	0	0	0	0
0						
Fa0/11	0	0	0	0	0	0
0						
Fa0/12	0	0	0	0	0	0
0						

Fa0/13	0	0	0	0	0	0
0						
Fa0/14	0	0	0	0	0	0
0						
Fa0/15	0	0	0	0	0	0
0						
Fa0/16	0	0	0	0	2	0
0						
Fa0/17	0	0	0	0	2	0
0						
Fa0/18	0	0	0	0	2	0
0						
Fa0/19	0	0	0	0	7	0
0						
Fa0/20	0	0	0	0	6	0
0						
Fa0/21	0	0	0	0	6	0
0						
Fa0/22	0	0	0	0	1	0
0						
Fa0/23	0	0	0	0	1	0
0						
Fa0/24	0	0	0	0	1	0
0						
Po1	0	0	0	0	0	0
0						
Po2	0	0	0	0	0	0
0						
ASW1#						

```
ASW1#show cdp neighbors
```

```
Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge  
S - Switch, H - Host, I - IGMP, r - Repeater, P - Phone
```

Device ID	Local Intrfce	Holdtme	Capability	Platform	Port
DSW1 0/21	Fas 0/21	128	R S I	Cisco WS-CFas	
DSW1 0/20	Fas 0/20	128	R S I	Cisco WS-CFas	
DSW1 0/19	Fas 0/19	126	R S I	Cisco WS-CFas	
DSW2 0/21	Fas 0/18	141	R S I	Cisco WS-CFas	
DSW2 0/20	Fas 0/17	140	R S I	Cisco WS-CFas	
DSW2 0/19	Fas 0/16	139	R S I	Cisco WS-CFas	

```
ASW1#
```

```
ASW1#show cdp neighbors detail
```

```
-----
```

```
Device ID: DSW1  
Entry address(es):  
  IP address: 10.2.1.1  
Platform: Cisco WS-C3550-24, Capabilities: Router Switch IGMP  
Interface: FastEthernet0/21, Port ID (outgoing port): FastEthernet0/21  
Holdtime : 120 sec
```

```
Version :  
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version  
12.2(44)SE6, RELEASE SOFTWARE (fc1)  
Copyright (c) 1986-2009 by Cisco Systems, Inc.  
Compiled Mon 09-Mar-09 20:28 by gereddy
```

```
advertisement version: 2  
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,  
value=00000000FFFFFFFFF0102250D0000000000000000DBDE36E00FF0000  
VTP Management Domain: 'netlearning'  
Native VLAN: 1  
Duplex: full  
Management address(es):  
  IP address: 10.2.1.1
```

```
-----
```

```
Device ID: DSW1  
Entry address(es):  
  IP address: 10.2.1.1  
Platform: Cisco WS-C3550-24, Capabilities: Router Switch IGMP  
Interface: FastEthernet0/20, Port ID (outgoing port): FastEthernet0/20  
Holdtime : 179 sec
```

```
Version :  
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version  
12.2(44)SE6, RELEASE SOFTWARE (fc1)  
Copyright (c) 1986-2009 by Cisco Systems, Inc.  
Compiled Mon 09-Mar-09 20:28 by gereddy
```

```
advertisement version: 2  
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,  
value=00000000FFFFFFFFF0102250D0000000000000000DBDE36E00FF0000  
VTP Management Domain: 'netlearning'
```

Native VLAN: 1
Duplex: full
Management address(es):
 IP address: 10.2.1.1

Device ID: DSW1
Entry address(es):
 IP address: 10.2.1.1
Platform: Cisco WS-C3550-24, Capabilities: Router Switch IGMP
Interface: FastEthernet0/19, Port ID (outgoing port): FastEthernet0/19
Holdtime : 176 sec

Version :
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version
12.2(44)SE6, RELEASE SOFTWARE (fc1)
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Mon 09-Mar-09 20:28 by gereddy

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF0102250D0000000000000000DBDE36E00FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
 IP address: 10.2.1.1

Device ID: DSW2
Entry address(es):
 IP address: 10.2.1.2
Platform: Cisco WS-C3550-24-PWR, Capabilities: Router Switch IGMP
Interface: FastEthernet0/18, Port ID (outgoing port): FastEthernet0/21
Holdtime : 130 sec

Version :
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version
12.2(44)SE6, RELEASE SOFTWARE (fc1)
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Mon 09-Mar-09 20:28 by gereddy

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225170000000000000000BFD20BA00FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
 IP address: 10.2.1.2

Device ID: DSW2
Entry address(es):

IP address: 10.2.1.2
Platform: Cisco WS-C3550-24-PWR, Capabilities: Router Switch IGMP
Interface: FastEthernet0/17, Port ID (outgoing port): FastEthernet0/20
Holdtime : 129 sec

Version :
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version
12.2(44)SE6, RELEASE SOFTWARE (fc1)
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Mon 09-Mar-09 20:28 by gereddy

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225170000000000000000BFD20BA00FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
IP address: 10.2.1.2

Device ID: DSW2
Entry address(es):
IP address: 10.2.1.2
Platform: Cisco WS-C3550-24-PWR, Capabilities: Router Switch IGMP
Interface: FastEthernet0/16, Port ID (outgoing port): FastEthernet0/19
Holdtime : 127 sec

Version :
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version
12.2(44)SE6, RELEASE SOFTWARE (fc1)
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Mon 09-Mar-09 20:28 by gereddy

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225170000000000000000BFD20BA00FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
IP address: 10.2.1.2

ASW1#

```
ASW1#show arp
Protocol Address           Age (min)  Hardware Addr  Type   Interface
Internet 192.168.1.131          -          0015.faac.46c0 ARPA   Vlan200
ASW1#
```

```
ASW1#show ip arp
Protocol Address          Age (min)  Hardware Addr  Type   Interface
Internet 192.168.1.131      -         0015.faac.46c0 ARPA   Vlan200
ASW1#
```

```
ASW1#show ip interface
Vlan1 is administratively down, line protocol is down
```



```
Internet protocol processing disabled
Vlan200 is up, line protocol is up
Internet address is 192.168.1.131/27
Broadcast address is 255.255.255.255
Address determined by non-volatile memory
MTU is 1500 bytes
Helper address is not set
Directed broadcast forwarding is disabled
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is disabled
IP fast switching on the same interface is disabled
IP Null turbo vector
IP multicast fast switching is disabled
IP multicast distributed fast switching is disabled
IP route-cache flags are None
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Probe proxy name replies are disabled
Policy routing is disabled
Network address translation is disabled
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
BGP Policy Mapping is disabled
ASW1#
```

```
ASW1#show tcp statistics
Rcvd: 0 Total, 0 no port
      0 checksum error, 0 bad offset, 0 too short
      0 packets (0 bytes) in sequence
      0 dup packets (0 bytes)
      0 partially dup packets (0 bytes)
      0 out-of-order packets (0 bytes)
      0 packets (0 bytes) with data after window
      0 packets after close
      0 window probe packets, 0 window update packets
      0 dup ack packets, 0 ack packets with unsend data
      0 ack packets (0 bytes)
Sent: 0 Total, 0 urgent packets
      0 control packets (including 0 retransmitted)
      0 data packets (0 bytes)
      0 data packets (0 bytes) retransmitted
      0 ack only packets (0 delayed)
      0 window probe packets, 0 window update packets
0 Connections initiated, 0 connections accepted, 0 connections
established
0 Connections closed (including 0 dropped, 0 embryonic dropped)
0 Total rxmt timeout, 0 connections dropped in rxmt timeout
0 Keepalive timeout, 0 keepalive probe, 0 Connections dropped in
keepalive
ASW1#
```

```
ASW1#show access-lists
```

```
ASW1#
```

ASW1#show vlan

VLAN Name	Status	Ports
1 default	active	Fa0/22, Fa0/23, Fa0/24
10 VLAN0010	active	Fa0/1, Fa0/2, Fa0/3, Fa0/4 Fa0/5, Fa0/6, Fa0/7, Fa0/8 Fa0/9, Fa0/10, Fa0/11, Fa0/12 Fa0/13, Fa0/14, Fa0/15
20 VLAN0020	active	
200 VLAN0200	active	
1002 fddi-default	act/unsup	
1003 trcrf-default	act/unsup	
1004 fddinet-default	act/unsup	
1005 trbrf-default	act/unsup	

VLAN Type	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Trans1	Trans2
1 enet	100001	1500	-	-	-	-	-	0	0
10 enet	100010	1500	-	-	-	-	-	0	0
20 enet	100020	1500	-	-	-	-	-	0	0
200 enet	100200	1500	-	-	-	-	-	0	0
1002 fddi	101002	1500	-	-	-	-	-	0	0
1003 trcrf	101003	4472	1005	3276	-	-	srb	0	0
1004 fdnet	101004	1500	-	-	-	ieee	-	0	0
1005 trbrf	101005	4472	-	-	15	ibm	-	0	0

VLAN	AREHops	STEHops	Backup	CRF
1003	7	7	off	

Remote SPAN VLANs

Primary Secondary Type Ports

ASW1#

ASW1#show spanning-tree

VLAN0010

Spanning tree enabled protocol ieee

Root ID	Priority	4106			
	Address	000d.bde3.6e00			
	Cost	9			
	Port	65 (Port-channell)			
	Hello Time	2 sec	Max Age 20 sec	Forward Delay 15 sec	

Bridge ID	Priority	32778	(priority 32768 sys-id-ext 10)		
	Address	0015.faac.46c0			
	Hello Time	2 sec	Max Age 20 sec	Forward Delay 15 sec	
	Aging Time	300			

Interface	Role	Sts	Cost	Prio.Nbr	Type
-----	-----	-----	-----	-----	-----

Fa0/1	Desg	FWD	19	128.1	Edge P2p
Po1	Root	FWD	9	128.65	P2p
Po2	Desg	FWD	9	128.66	P2p

VLAN0200

Spanning tree enabled protocol ieee

Root ID Priority 4296
 Address 000d.bde3.6e00
 Cost 9
 Port 65 (Port-channell)
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec

Bridge ID Priority 32968 (priority 32768 sys-id-ext 200)
 Address 0015.faac.46c0
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
 Aging Time 300

Interface	Role	Sts	Cost	Prio.Nbr	Type
-----	-----	-----	-----	-----	-----

Po1	Root	FWD	9	128.65	P2p
Po2	Desg	FWD	9	128.66	P2p

ASW1#

ASW1#show interfaces status

Port	Name	Status	Vlan	Duplex	Speed	Type
Fa0/1		connected	10	a-full	a-100	
10/100BaseTX						
Fa0/2		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/3		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/4		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/5		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/6		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/7		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/8		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/9		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/10		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/11		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/12		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/13		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/14		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/15		notconnect	10	auto	auto	
10/100BaseTX						
Fa0/16		connected	trunk	a-full	a-100	
10/100BaseTX						
Fa0/17		connected	trunk	a-full	a-100	
10/100BaseTX						
Fa0/18		connected	trunk	a-full	a-100	
10/100BaseTX						
Fa0/19		connected	trunk	a-full	a-100	
10/100BaseTX						
Fa0/20		connected	trunk	a-full	a-100	
10/100BaseTX						

Fa0/21	connected	trunk	a-full	a-100
10/100BaseTX				
Fa0/22	disabled	1	auto	auto
10/100BaseTX				
Fa0/23	disabled	1	auto	auto
10/100BaseTX				
Fa0/24	disabled	1	auto	auto
10/100BaseTX				
Po1	connected	trunk	a-full	a-100
Po2	connected	trunk	a-full	a-100
ASW1#				

```

ASW1#show interfaces switchport
Name: Fa0/1
Switchport: Enabled
Administrative Mode: static access
Operational Mode: static access
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: native

```


Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/2
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/3
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q

Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/4
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/5
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false

Appliance trust: none

Name: Fa0/6
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/7
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/8
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off

Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/9
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/10
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none

Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/11
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/12
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/13
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/14
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/15
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: Off
Access Mode VLAN: 10 (VLAN0010)

Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/16
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po2)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/17
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po2)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q

Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/18
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po2)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/19
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po1)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled

Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/20
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po1)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/21
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po1)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/22
Switchport: Enabled

Administrative Mode: trunk
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/23
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Fa0/24
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: down
Administrative Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none

Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL
Protected: false
Appliance trust: none

Name: Po1
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001
Protected: false
Appliance trust: none

Name: Po2
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk private VLANs: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001

Protected: false
Appliance trust: none
ASW1#

ASW1#show interfaces trunk

Port	Mode	Encapsulation	Status	Native vlan
Po1	on	802.1q	trunking	1
Po2	on	802.1q	trunking	1

Port	Vlans allowed on trunk
Po1	10,200
Po2	10,200

Port	Vlans allowed and active in management domain
Po1	10,200
Po2	10,200

Port	Vlans in spanning tree forwarding state and not pruned
------	--

```
Po1          10,200
Po2          10,200
ASW1#
```

```
ASW1#show vtp status
VTP Version                : 2
Configuration Revision     : 36
Maximum VLANs supported locally : 64
Number of existing VLANs   : 8
VTP Operating Mode         : Server
VTP Domain Name            : netlearning
VTP Pruning Mode           : Disabled
VTP V2 Mode                : Enabled
VTP Traps Generation       : Disabled
MD5 digest                 : 0x3A 0xD8 0x7D 0x4B 0xF5 0x78 0x54 0xCE
Configuration last modified by 10.2.1.1 at 3-1-93 00:50:15
Local updater ID is 192.168.1.131 on interface Vl200 (lowest numbered
VLAN interface found)
ASW1#
```

```
ASW1#show vtp password
VTP Password: cisco
ASW1#
```

ASW1#show etherchannel detail

Channel-group listing:

Group: 1

Group state = L2

Ports: 3 Maxports = 16

Port-channels: 1 Max Port-channels = 16

Protocol: LACP

Ports in the group:

Port: Fa0/19

Port state = Up Mstr In-Bndl

Channel group = 1 Mode = Passive

Gcchange = -

Port-channel = Po1

GC = -

Pseudo port-channel =

Po1

Port index = 0

Load = 0x00

Protocol = LACP

Flags: S - Device is sending Slow LACPDU's F - Device is sending fast LACPDU's.

A - Device is in active mode.

P - Device is in passive mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number	Port
Fa0/19	SP	bndl	32768	0x1	0x1	0x13	0x3C

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/19	SA	32768	000d.bde3.6e00	2s	0xD	0x10	0x3D

Age of the port in the current state: 0d:01h:01m:14s

Port: Fa0/20

Port state = Up Mstr In-Bndl
Channel group = 1 Mode = Passive Gcchange = -
Port-channel = Po1 GC = - Pseudo port-channel =
Po1
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDU's F - Device is sending fast LACPDU's.
A - Device is in active mode. P - Device is in passive mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number	Port State
Fa0/20	SP	bndl	32768	0x1	0x1	0x14	0x3C

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/20	SA	32768	000d.bde3.6e00	15s	0xD	0x11	0x3D

Age of the port in the current state: 0d:01h:01m:15s

Port: Fa0/21

Port state = Up Mstr In-Bndl
Channel group = 1 Mode = Passive Gcchange = -
Port-channel = Po1 GC = - Pseudo port-channel =
Po1
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDU's F - Device is sending fast LACPDU's.
A - Device is in active mode. P - Device is in passive mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number	Port State
Fa0/21	SP	bndl	32768	0x1	0x1	0x15	0x3C

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/21	SA	32768	000d.bde3.6e00	7s	0xD	0x12	0x3D

Age of the port in the current state: 0d:01h:01m:16s

Port-channels in the group:

Port-channel: Po1 (Primary Aggregator)

Age of the Port-channel = 0d:02h:01m:23s
 Logical slot/port = 1/0 Number of ports = 3
 HotStandBy port = null
 Port state = Port-channel Ag-Inuse
 Protocol = LACP

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/19	Passive	0
0	00	Fa0/20	Passive	0
0	00	Fa0/21	Passive	0

Time since last port bundled: 0d:01h:01m:17s Fa0/21
 Time since last port Un-bundled: 0d:01h:03m:30s Fa0/21

Group: 2

Group state = L2
 Ports: 3 Maxports = 16
 Port-channels: 1 Max Port-channels = 16
 Protocol: LACP

Ports in the group:

Port: Fa0/16

Port state = Up Mstr In-Bndl
 Channel group = 2 Mode = Active Gcchange = -
 Port-channel = Po2 GC = - Pseudo port-channel =
 Po2
 Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast LACPDUs.
 A - Device is in active mode. P - Device is in passive mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number	Port
Fa0/16	SA	bndl	32768	0x2	0x2	0x10	0x3D

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/16	SA	32768	000b.fd20.ba00	6s	0x17	0x10	0x3D

Age of the port in the current state: 0d:01h:59m:04s

Port: Fa0/17

Port state = Up Mstr In-Bndl
Channel group = 2 Mode = Active Gcchange = -
Port-channel = Po2 GC = - Pseudo port-channel =
Po2
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast
LACPDUs.
A - Device is in active mode. P - Device is in passive
mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number	Port
Fa0/17	SA	bndl	32768	0x2	0x2	0x11	0x3D

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/17	SA	32768	000b.fd20.ba00	24s	0x17	0x11	0x3D

Age of the port in the current state: 0d:01h:59m:05s

Port: Fa0/18

Port state = Up Mstr In-Bndl
Channel group = 2 Mode = Active Gcchange = -
Port-channel = Po2 GC = - Pseudo port-channel =
Po2
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast
LACPDUs.

A - Device is in active mode. P - Device is in passive mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number	Port
Fa0/18	SA	bndl	32768	0x2	0x2	0x12	0x3D

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/18	SA	32768	000b.fd20.ba00	23s	0x17	0x12	0x3D

Age of the port in the current state: 0d:01h:59m:06s

Port-channels in the group:

Port-channel: Po2 (Primary Aggregator)

Age of the Port-channel = 0d:02h:01m:28s
Logical slot/port = 1/1 Number of ports = 3
HotStandBy port = null
Port state = Port-channel Ag-Inuse
Protocol = LACP

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/16	Active	0
0	00	Fa0/17	Active	0
0	00	Fa0/18	Active	0

Time since last port bundled: 0d:01h:59m:07s Fa0/16

ASW1#

```
ASW1#show spanning-tree inconsistentports
```

Name	Interface	Inconsistency
-----	-----	-----

```
Number of inconsistent ports (segments) in the system : 0
```

```
ASW1#
```

ASW1#show spanning-tree summary

Switch is in pvst mode

Root bridge for: none

EtherChannel misconfig guard is enabled

Extended system ID is enabled

Portfast Default is disabled

PortFast BPDU Guard Default is disabled

Portfast BPDU Filter Default is disabled

Loopguard Default is disabled

UplinkFast is disabled

BackboneFast is disabled

Pathcost method used is short

Name	Blocking	Listening	Learning	Forwarding	STP Active
VLAN0010	0	0	0	3	3
VLAN0200	0	0	0	2	2
2 vlans	0	0	0	5	5

ASW1#

ASW1#show udld

Interface Fa0/1

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/2

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/3

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/4

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/5

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/6

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/7

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/8

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/9

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/10

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/11

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/12

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/13

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/14

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/15

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/16

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/17

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/18

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/19

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/20

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/21

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/22

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/23

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/24

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

ASW1#


```
ASW1#show etherchannel summary
```

```
Flags: D - down          P - in port-channel  
       I - stand-alone  s - suspended  
       H - Hot-standby (LACP only)  
       R - Layer3       S - Layer2  
       u - unsuitable for bundling  
       U - in use      f - failed to allocate aggregator  
       d - default port
```

```
Number of channel-groups in use: 2
```

```
Number of aggregators: 2
```

Group	Port-channel	Protocol	Ports		
1	Po1 (SU)	LACP	Fa0/19 (Pd)	Fa0/20 (P)	Fa0/21 (P)
2	Po2 (SU)	LACP	Fa0/16 (Pd)	Fa0/17 (P)	Fa0/18 (P)

```
ASW1#
```

```
ASW1#show etherchannel protocol
      Channel-group listing:
```

```
-----
Group: 1
-----
Protocol: LACP
```

```
-----
Group: 2
-----
Protocol: LACP
```

```
ASW1#
```

```
ASW1#show etherchannel port
```

```
Channel-group listing:
```

```
-----
```

```
Group: 1
```

```
-----
```

```
Ports in the group:
```

```
-----
```

```
Port: Fa0/19
```

```
-----
```

```
Port state = Up Mstr In-Bndl
```

```
Channel group = 1 Mode = Passive
```

```
Gcchange = -
```

```
Port-channel = Po1 GC = -
```

```
Pseudo port-channel =
```

```
Po1
```

```
Port index = 0 Load = 0x00
```

```
Protocol = LACP
```

```
Flags: S - Device is sending Slow LACPDUs F - Device is sending fast LACPDUs.
```

```
A - Device is in active mode.
```

```
P - Device is in passive mode.
```

```
Local information:
```

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number	Port
Fa0/19	SP	bndl	32768	0x1	0x1	0x13	0x3C

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/19	SA	32768	000d.bde3.6e00	0s	0xD	0x10	0x3D

Age of the port in the current state: 0d:01h:02m:10s

Port: Fa0/20

Port state = Up Mstr In-Bndl
Channel group = 1 Mode = Passive Gcchange = -
Port-channel = Po1 GC = - Pseudo port-channel =
Po1
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast LACPDUs.
A - Device is in active mode. P - Device is in passive mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number	Port
Fa0/20	SP	bndl	32768	0x1	0x1	0x14	0x3C

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/20	SA	32768	000d.bde3.6e00	17s	0xD	0x11	0x3D

Age of the port in the current state: 0d:01h:02m:10s

Port: Fa0/21

Port state = Up Mstr In-Bndl
Channel group = 1 Mode = Passive Gcchange = -
Port-channel = Po1 GC = - Pseudo port-channel =
Po1
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast LACPDUs.
A - Device is in active mode. P - Device is in passive mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number	Port
Fa0/21	SP	bndl	32768	0x1	0x1	0x15	0x3C

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/21	SA	32768	000d.bde3.6e00	7s	0xD	0x12	0x3D

Age of the port in the current state: 0d:01h:02m:11s

Group: 2

Ports in the group:

Port: Fa0/16

Port state = Up Mstr In-Bndl
Channel group = 2 Mode = Active Gcchange = -
Port-channel = Po2 GC = - Pseudo port-channel =
Po2
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast
LACPDUs.
A - Device is in active mode. P - Device is in passive
mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number	Port
Fa0/16	SA	bndl	32768	0x2	0x2	0x10	0x3D

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/16	SA	32768	000b.fd20.ba00	4s	0x17	0x10	0x3D

Age of the port in the current state: 0d:01h:59m:58s

Port: Fa0/17

Port state = Up Mstr In-Bndl
Channel group = 2 Mode = Active Gcchange = -

Port-channel = Po2 GC = - Pseudo port-channel =
Po2
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast LACPDUs.
A - Device is in active mode. P - Device is in passive mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number	Port
Fa0/17	SA	bndl	32768	0x2	0x2	0x11	0x3D

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/17	SA	32768	000b.fd20.ba00	22s	0x17	0x11	0x3D

Age of the port in the current state: 0d:02h:00m:00s

Port: Fa0/18

Port state = Up Mstr In-Bndl
Channel group = 2 Mode = Active Gcchange = -
Port-channel = Po2 GC = - Pseudo port-channel =
Po2
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast LACPDUs.
A - Device is in active mode. P - Device is in passive mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number	Port
Fa0/18	SA	bndl	32768	0x2	0x2	0x12	0x3D

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/18	SA	32768	000b.fd20.ba00	22s	0x17	0x12	0x3D

Age of the port in the current state: 0d:02h:00m:01s

ASW1#

```
ASW1#show etherchannel load-balance
Source MAC address
ASW1#
```

```
ASW1#show etherchannel port-channel
      Channel-group listing:
      -----
```

```
Group: 1
-----
```

```
      Port-channels in the group:
      -----
```

```
Port-channel: Po1      (Primary Aggregator)
-----
```

```
Age of the Port-channel      = 0d:02h:02m:32s
Logical slot/port      = 1/0      Number of ports = 3
HotStandBy port = null
Port state      = Port-channel Ag-Inuse
Protocol      = LACP
```

```
Ports in the Port-channel:
```

Index	Load	Port	EC state	No of bits
0	00	Fa0/19	Passive	0
0	00	Fa0/20	Passive	0
0	00	Fa0/21	Passive	0

```
Time since last port bundled:      0d:01h:02m:26s      Fa0/21
Time since last port Un-bundled: 0d:01h:04m:39s      Fa0/21
```

```
Group: 2
-----
```

```
      Port-channels in the group:
      -----
```


Port-channel: Po2 (Primary Aggregator)

Age of the Port-channel = 0d:02h:02m:33s
Logical slot/port = 1/1 Number of ports = 3
HotStandBy port = null
Port state = Port-channel Ag-Inuse
Protocol = LACP

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/16	Active	0
0	00	Fa0/17	Active	0
0	00	Fa0/18	Active	0

Time since last port bundled: 0d:02h:00m:13s Fa0/16

ASW1#

```
ASW1#show etherchannel port-channel
      Channel-group listing:
      -----
```

```
Group: 1
-----
```

```
      Port-channels in the group:
      -----
```

```
Port-channel: Po1      (Primary Aggregator)
```

```
-----
```

```
Age of the Port-channel   = 0d:02h:02m:41s
Logical slot/port        = 1/0           Number of ports = 3
HotStandBy port = null
Port state                = Port-channel Ag-Inuse
Protocol                  = LACP
```

```
Ports in the Port-channel:
```

Index	Load	Port	EC state	No of bits
0	00	Fa0/19	Passive	0
0	00	Fa0/20	Passive	0
0	00	Fa0/21	Passive	0

```
Time since last port bundled:    0d:01h:02m:35s    Fa0/21
Time since last port Un-bundled: 0d:01h:04m:48s    Fa0/21
```

```
Group: 2
-----
```

```
      Port-channels in the group:
      -----
```

```
Port-channel: Po2      (Primary Aggregator)
```

```
-----
```

```
Age of the Port-channel   = 0d:02h:02m:42s
Logical slot/port        = 1/1           Number of ports = 3
HotStandBy port = null
Port state                = Port-channel Ag-Inuse
Protocol                  = LACP
```

```
Ports in the Port-channel:
```

Index	Load	Port	EC state	No of bits
0	00	Fa0/16	Active	0

0	00	Fa0/17	Active	0
0	00	Fa0/18	Active	0

Time since last port bundled: 0d:02h:00m:21s Fa0/16

ASW1#show pagp neighbor

ASW1#

ASW1#show lacp neighbor

Flags: S - Device is requesting Slow LACPDUs
F - Device is requesting Fast LACPDUs
A - Device is in Active mode P - Device is in Passive mode

Channel group 1 neighbors

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/19	SA	32768	000d.bde3.6e00	11s	0xD	0x10	0x3D
Fa0/20	SA	32768	000d.bde3.6e00	26s	0xD	0x11	0x3D
Fa0/21	SA	32768	000d.bde3.6e00	17s	0xD	0x12	0x3D

Channel group 2 neighbors

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Oper Key	Port Number	Port State
Fa0/16	SA	32768	000b.fd20.ba00	11s	0x17	0x10	0x3D
Fa0/17	SA	32768	000b.fd20.ba00	27s	0x17	0x11	0x3D
Fa0/18	SA	32768	000b.fd20.ba00	2s	0x17	0x12	0x3D

ASW1#

ASW1#show port-security

Secure Port	MaxSecureAddr	CurrentAddr	SecurityViolation	Security
-------------	---------------	-------------	-------------------	----------

Action

(Count)

(Count)

(Count)

--

Fa0/1	1	1	0	
Shutdown				
Fa0/2	1	0	0	
Shutdown				
Fa0/3	1	0	0	
Shutdown				
Fa0/4	1	0	0	
Shutdown				
Fa0/5	1	0	0	
Shutdown				
Fa0/6	1	0	0	
Shutdown				
Fa0/7	1	0	0	
Shutdown				

Fa0/8	1	0	0
Shutdown			
Fa0/9	1	0	0
Shutdown			
Fa0/10	1	0	0
Shutdown			
Fa0/11	1	0	0
Shutdown			
Fa0/12	1	0	0
Shutdown			
Fa0/13	1	0	0
Shutdown			
Fa0/14	1	0	0
Shutdown			
Fa0/15	1	0	0
Shutdown			

--

Total Addresses in System (excluding one mac per port) : 0
Max Addresses limit in System (excluding one mac per port) : 1024

ASW1#

ASW1#show port-security address
Secure Mac Address Table

```
-----  
Vlan      Mac Address      Type              Ports      Remaining Age  
          (mins)  
-----  
10        001c.238e.dbbc   SecureDynamic     Fa0/1      -  
-----
```

Total Addresses in System (excluding one mac per port) : 0
Max Addresses limit in System (excluding one mac per port) : 1024

ASW1#