

```
R2#
R2#show running-config
Building configuration...

Current configuration : 2454 bytes
!
! NVRAM config last updated at 14:12:53 UTC Wed Jun 2 2010
!
version 12.4
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname R2
!
boot-start-marker
boot-end-marker
!
logging message-counter syslog
enable secret 5 $1$NytN$xb8Trn0Re9vS6jGlygMv00
!
no aaa new-model
!
dot11 syslog
ip source-route
!
!
ip cef
!
!
ip multicast-routing
ipv6 unicast-routing
ipv6 cef
!
multilink bundle-name authenticated
!
!
!
!
!
!
!
!
!
!
!
!
!
!
!
!
!
!
!
!
!
!
!
```

```
!  
!  
!  
!  
voice-card 0  
!  
!  
!  
!  
archive  
  log config  
  hidekeys  
!  
!  
!  
!  
!  
!  
!  
!  
!  
interface FastEthernet0/0  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface FastEthernet0/1  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface Serial0/0/0  
  no ip address  
!  
interface Serial0/0/1  
  no ip address  
!  
interface Serial0/1/0  
  no ip address  
  ip nat outside  
  ip virtual-reassembly  
  shutdown  
  clock rate 56000  
!  
interface Serial0/2/0  
  no ip address  
  encapsulation frame-relay  
!  
interface Serial0/2/0.12 point-to-point  
  ip address 10.1.1.2 255.255.255.252  
  ip pim sparse-dense-mode
```

```
snmp trap link-status
ipv6 address 2026::12:2/122
ipv6 enable
ipv6 ospf 6 area 12
frame-relay interface-dlci 201
!
interface Serial0/2/0.23 point-to-point
 ip address 10.1.1.5 255.255.255.252
 ip pim sparse-dense-mode
 snmp trap link-status
 ipv6 address 2026::1:1/122
 ipv6 enable
 ipv6 ospf 6 area 0
 frame-relay interface-dlci 203
!
interface Serial0/3/0
 no ip address
 ip virtual-reassembly
 shutdown
 clock rate 56000
!
router ospf 1
 router-id 2.2.2.2
 log-adjacency-changes
 network 10.1.1.1 0.0.0.0 area 0
 network 10.1.1.5 0.0.0.0 area 0
 network 10.2.2.1 0.0.0.0 area 0
 network 10.0.0.0 0.255.255.255 area 12
!
ip forward-protocol nd
ip http server
no ip http secure-server
!
!
!
ip access-list standard DENY_10
 deny 10.0.0.0 0.255.255.255
 permit any
ip access-list standard DENY_ALL
 deny any
ip access-list standard PERMIT_10
 permit 10.0.0.0 0.255.255.255
ip access-list standard PERMIT_ALL
 permit any
!
ipv6 router ospf 6
 router-id 2.2.2.2
 log-adjacency-changes
!
!
!
!
!
!
```

```
!  
!  
control-plane  
!  
!  
!  
ccm-manager fax protocol cisco  
!  
mgcp fax t38 ecm  
mgcp behavior g729-variants static-pt  
!  
!  
!  
!  
!  
line con 0  
  exec-timeout 0 0  
  logging synchronous  
line aux 0  
line vty 0 4  
  exec-timeout 0 0  
  password cisco  
  login  
line vty 5  
  exec-timeout 0 0  
  login  
!  
scheduler allocate 20000 1000  
ntp server 10.1.1.1  
ntp peer 10.1.1.1  
end
```

R2#

```
R2#ping 209.65.200.241
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.241, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 32/33/36 ms
```

```
R2#
```

```
R2#ping 209.65.200.226
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.226, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 32/32/32 ms
```

```
R2#
```

```
R2#ping 209.65.200.225
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.225, timeout is 2 seconds:  
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/71/96 ms  
R2#
```

```
R2#ping 10.1.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.1, timeout is 2 seconds:  
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/129/132  
ms  
R2#
```

```
R2#ping 10.1.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/67/76 ms
```

```
R2#
```



```
R2#ping 10.1.1.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.5, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/67/72 ms
```

```
R2#
```

```
R2#ping 10.1.1.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.6, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132
```

```
ms
```

```
R2#
```

```
R2#ping 10.1.1.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.9, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132
```

```
ms
```

```
R2#
```

```
R2#ping 10.1.1.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.10, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/196/208
```

```
ms
```

```
R2#
```

```
R2#ping 10.1.4.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.10, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/194/196
ms
R2#
```

```
R2#ping 10.1.4.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.9, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/194/196
ms
```

```
R2#
```

```
R2#ping 10.1.4.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.6, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/194/196  
ms
```

```
R2#
```

```
R2#ping 10.1.4.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.5, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/194/196  
ms
```

```
R2#
```

```
R2#ping 10.2.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196
```

```
ms
```

```
R2#
```



```
R2#ping 10.2.2.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/250/316
```

```
ms
```

```
R2#
```

```
R2#ping 10.2.1.254
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.254, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196
```

```
ms
```

```
R2#
```

```
R2#ping 10.2.4.14
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.14, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/196/204
```

```
ms
```

R2#

R2#ping 10.2.4.13

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 10.2.4.13, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 192/196/204
ms

R2#

```
R2#ping 10.2.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/194/200  
ms
```

```
R2#
```

```
R2#ping 10.2.2.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/200  
ms
```

```
R2#
```

```
R2#ping 10.2.1.4
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.4, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/194/196  
ms
```

```
R2#
```

```

R2#
R2#show ip interface brief
Interface          IP-Address      OK? Method Status
Protocol
FastEthernet0/0    unassigned      YES NVRAM  administratively
down down
FastEthernet0/1    unassigned      YES NVRAM  administratively
down down
Serial0/0/0        unassigned      YES NVRAM  down
down
Serial0/0/1        unassigned      YES NVRAM  down
down
Serial0/1/0        unassigned      YES NVRAM  administratively
down down
Serial0/2/0        unassigned      YES NVRAM  up
up
Serial0/2/0.12     10.1.1.2       YES NVRAM  up
up
Serial0/2/0.23     10.1.1.5       YES NVRAM  up
up
Serial0/3/0        unassigned      YES NVRAM  administratively
down down
NVI0               unassigned      YES unset  administratively
down down
R2#

```

R2#show ip route

Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS
level-2
ia - IS-IS inter area, * - candidate default, U - per-user static
route
o - ODR, P - periodic downloaded static route

Gateway of last resort is 10.1.1.1 to network 0.0.0.0

10.0.0.0/8 is variably subnetted, 8 subnets, 2 masks
O E2 10.2.4.12/30 [110/20] via 10.1.1.6, 00:24:56, Serial0/2/0.23
O IA 10.1.1.8/30 [110/128] via 10.1.1.6, 01:11:49, Serial0/2/0.23
O E2 10.1.4.8/30 [110/20] via 10.1.1.6, 01:11:33, Serial0/2/0.23
O E2 10.2.1.0/24 [110/20] via 10.1.1.6, 01:11:33, Serial0/2/0.23
O E2 10.2.2.0/24 [110/20] via 10.1.1.6, 01:11:33, Serial0/2/0.23
C 10.1.1.0/30 is directly connected, Serial0/2/0.12
O E2 10.1.4.4/30 [110/20] via 10.1.1.6, 00:24:56, Serial0/2/0.23
C 10.1.1.4/30 is directly connected, Serial0/2/0.23
O*E2 0.0.0.0/0 [110/1] via 10.1.1.1, 01:11:50, Serial0/2/0.12
R2#

R2#

R2#show processes cpu

CPU utilization for five seconds: 2%/0%; one minute: 3%; five minutes: 2%

PID	Runtime(ms)	Invoked	uSecs	5Sec	1Min	5Min	TTY	Process
1	20	75	266	0.00%	0.00%	0.00%	0	Chunk
Manager								
2	8	1002	7	0.00%	0.04%	0.02%	0	Load Meter
3	1108	183	6054	0.00%	1.23%	0.33%	0	Exec
4	0	1	0	0.00%	0.00%	0.00%	0	EDDRI_MAIN
5	6772	599	11305	0.79%	0.19%	0.13%	0	Check
heaps								
6	0	1	0	0.00%	0.00%	0.00%	0	Pool
Manager								
7	0	2	0	0.00%	0.00%	0.00%	0	Timers
8	0	1	0	0.00%	0.00%	0.00%	0	License
Client N								
9	156	2006	77	0.07%	0.01%	0.00%	0	OSPF-1
Hello								
10	0	85	0	0.00%	0.00%	0.00%	0	IPC
Dynamic Cach								
11	0	1	0	0.00%	0.00%	0.00%	0	IPC Zone
Manager								
12	0	5019	0	0.00%	0.00%	0.00%	0	IPC
Periodic Tim								
13	0	5019	0	0.00%	0.00%	0.00%	0	IPC
Deferred Por								
14	0	1	0	0.00%	0.00%	0.00%	0	IPC Seat
Manager								

134	0	2	0	0.00%	0.00%	0.00%	0	PPP IP
Route								
135	0	2	0	0.00%	0.00%	0.00%	0	PPP IPCP
136	176	181	972	0.00%	0.00%	0.00%	0	IP
Background								
137	364	117	3111	0.00%	0.00%	0.00%	0	IP RIB
Update								
138	0	2	0	0.00%	0.00%	0.00%	0	Dot1x
Supplicant								
139	0	2	0	0.00%	0.00%	0.00%	0	Dot1x
Supplicant								
140	0	2	0	0.00%	0.00%	0.00%	0	Dot1x
Supplicant								
141	0	1	0	0.00%	0.00%	0.00%	0	Asy FS
Helper								
142	0	84	0	0.00%	0.00%	0.00%	0	Licensing
Auto U								
143	0	1	0	0.00%	0.00%	0.00%	0	Socket
Timers								
144	0	85	0	0.00%	0.00%	0.00%	0	CEF
background p								
145	12	7671	1	0.00%	0.00%	0.00%	0	CEF: IPv4
proces								
146	0	31	0	0.00%	0.00%	0.00%	0	ADJ
background								
147	0	2	0	0.00%	0.00%	0.00%	0	L2MM
148	0	1	0	0.00%	0.00%	0.00%	0	MRD
149	0	1	0	0.00%	0.00%	0.00%	0	IGMPSN
150	0	1	0	0.00%	0.00%	0.00%	0	L2X Data
Daemon								
151	0	1	0	0.00%	0.00%	0.00%	0	TCP Timer
152	0	1	0	0.00%	0.00%	0.00%	0	TCP
Protocols								
153	0	18	0	0.00%	0.00%	0.00%	0	HTTP CORE
154	0	1	0	0.00%	0.00%	0.00%	0	IP
Traceroute								
155	0	2	0	0.00%	0.00%	0.00%	0	RLM groups
Proce								
156	0	2	0	0.00%	0.00%	0.00%	0	PPPoE Flow
Contr								
157	0	1	0	0.00%	0.00%	0.00%	0	SNMP
Timers								
158	4	2	2000	0.00%	0.00%	0.00%	0	SCTP Main
Proces								
159	0	1	0	0.00%	0.00%	0.00%	0	IUA Main
Process								
160	4	5018	0	0.00%	0.00%	0.00%	0	RUDPV1
Main Proc								
161	0	1	0	0.00%	0.00%	0.00%	0	bsm_timers
162	0	5032	0	0.00%	0.00%	0.00%	0	
bsm_xmt_proc								
163	0	1	0	0.00%	0.00%	0.00%	0	CES Client
SVC R								
164	0	1	0	0.00%	0.00%	0.00%	0	COPS

165	0	2	0	0.00%	0.00%	0.00%	0 Dialer
Forwarder							
166	0	3	0	0.00%	0.00%	0.00%	0 Flow
Exporter Ti							
167	0	2	0	0.00%	0.00%	0.00%	0 ATM OAM
Input							
168	0	2	0	0.00%	0.00%	0.00%	0 ATM OAM
TIMER							
169	0	1	0	0.00%	0.00%	0.00%	0 RARP Input
170	0	1	0	0.00%	0.00%	0.00%	0 LAPB
Process							
171	0	1	0	0.00%	0.00%	0.00%	0 IPv6
Inspect Tim							
172	0	2	0	0.00%	0.00%	0.00%	0 LFDp Input
Proc							
173	0	1	0	0.00%	0.00%	0.00%	0 PAD InCall
174	0	2	0	0.00%	0.00%	0.00%	0 X.25
Background							
175	0	2	0	0.00%	0.00%	0.00%	0 PPP Bind
176	0	2	0	0.00%	0.00%	0.00%	0 PPP SSS
177	0	1	0	0.00%	0.00%	0.00%	0 MQC Flow
Event B							
178	4	1252791	0	0.71%	0.74%	0.74%	0 HQF Shaper
Backg							
179	0	50155	0	0.07%	0.03%	0.02%	0 RBSCP
Background							
180	0	1	0	0.00%	0.00%	0.00%	0 VPDN call
manage							
181	0	1	0	0.00%	0.00%	0.00%	0 CHKPT
EXAMPLE							
182	0	1	0	0.00%	0.00%	0.00%	0 CHKPT
DevTest							
183	0	1	0	0.00%	0.00%	0.00%	0 IPS
Process							
184	4	2	2000	0.00%	0.00%	0.00%	0 IPS Auto
Update							
185	4	2	2000	0.00%	0.00%	0.00%	0 SDEE
Management							
186	0	9803	0	0.00%	0.00%	0.00%	0 Inspect
process							
187	0	2	0	0.00%	0.00%	0.00%	0
cpf_process_msg_							
188	0	9803	0	0.00%	0.00%	0.00%	0 FW DP
Inspect pr							
189	0	9803	0	0.00%	0.00%	0.00%	0 CCE DP
URLF cach							
190	0	2	0	0.00%	0.00%	0.00%	0 URL filter
proc							
191	0	1	0	0.00%	0.00%	0.00%	0 Select
Timers							
192	32	2	16000	0.00%	0.00%	0.00%	0 HTTP
Process							
193	0	2	0	0.00%	0.00%	0.00%	0 CIFS API
Process							


```
325          176          5256          33  0.00%  0.00%  0.00%  0 OSPF-1
Router
R2#
```

```
R2#show interfaces
FastEthernet0/0 is administratively down, line protocol is down
  Hardware is MV96340 Ethernet, address is 0016.9dfa.cab0 (bia
0016.9dfa.cab0)
  MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto Speed, 100BaseTX/FX
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
```

```
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 0 interface resets
  0 unknown protocol drops
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/1 is administratively down, line protocol is down
  Hardware is MV96340 Ethernet, address is 0016.9dfa.cab1 (bia
0016.9dfa.cab1)
  MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto Speed, 100BaseTX/FX
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes
    Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 0 interface resets
    0 unknown protocol drops
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier
    0 output buffer failures, 0 output buffers swapped out
Serial0/0/0 is down, line protocol is down
  Hardware is GT96K Serial
  MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation HDLC, loopback not set
  Keepalive set (10 sec)
  CRC checking enabled
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: weighted fair
  Output queue: 0/1000/64/0 (size/max total/threshold/drops)
```

Conversations 0/0/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 4 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=down DSR=down DTR=up RTS=up CTS=down

Serial0/0/1 is down, line protocol is down

Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/0/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 4 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=down DSR=down DTR=up RTS=up CTS=down

Serial0/1/0 is administratively down, line protocol is down

Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)

Conversations 0/0/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 3 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=down DSR=down DTR=down RTS=down CTS=down

Serial0/2/0 is up, line protocol is up

Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY, loopback not set
Keepalive set (10 sec)
CRC checking enabled
LMI enq sent 450, LMI stat recvd 445, LMI upd recvd 0, DTE LMI up
LMI enq recvd 0, LMI stat sent 0, LMI upd sent 0
LMI DLCI 1023 LMI type is CISCO frame relay DTE
FR SVC disabled, LAPF state down
Broadcast queue 0/64, broadcasts sent/dropped 2897/0, interface
broadcasts 2778
Last input 00:00:02, output 00:00:00, output hang never
Last clearing of "show interface" counters 01:24:04
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/4/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 1 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
3220 packets input, 281558 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
3718 packets output, 321253 bytes, 0 underruns
0 output errors, 0 collisions, 14 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
184 carrier transitions
DCD=up DSR=up DTR=up RTS=up CTS=up

Serial0/2/0.12 is up, line protocol is up

Hardware is GT96K Serial
Internet address is 10.1.1.2/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY

```
CRC checking enabled
Last clearing of "show interface" counters never
Serial0/2/0.23 is up, line protocol is up
Hardware is GT96K Serial
Internet address is 10.1.1.5/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY
CRC checking enabled
Last clearing of "show interface" counters never
Serial0/3/0 is administratively down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input 01:24:20, output 01:24:19, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
  Conversations 0/1/256 (active/max active/max total)
  Reserved Conversations 0/0 (allocated/max allocated)
  Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 24 bytes, 0 no buffer
  Received 1 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
  1 packets output, 24 bytes, 0 underruns
  0 output errors, 0 collisions, 3 interface resets
  0 unknown protocol drops
  0 output buffer failures, 0 output buffers swapped out
  3 carrier transitions
  DCD=down DSR=down DTR=down RTS=down CTS=down
```

```
NV10 is administratively down, line protocol is down
Hardware is NVI
MTU 1514 bytes, BW 56 Kbit/sec, DLY 5000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation UNKNOWN, loopback not set
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 0 interface resets
  0 unknown protocol drops
  0 output buffer failures, 0 output buffers swapped out
```


R2#

R2#show interfaces counters errors

R2#

```
R2#show cdp neighbors
```

```
Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge  
S - Switch, H - Host, I - IGMP, r - Repeater
```

Device ID	Local Intrfce	Holdtme	Capability	Platform	Port
R3	Ser 0/2/0.23	173	R S I	2811	Ser
0/2/0.23					
R1	Ser 0/2/0.12	172	R S I	2811	Ser
0/2/0.12					

```
R2#
```

R2#

R2#show cdp neighbors detail

Device ID: R3

Entry address(es):

IP address: 10.1.1.6

IPv6 address: 2026::1:2 (global unicast)

IPv6 address: FE80::216:47FF:FE9A:F6E8 (link-local)

Platform: Cisco 2811, Capabilities: Router Switch IGMP

Interface: Serial0/2/0.23, Port ID (outgoing port): Serial0/2/0.23

Holdtime : 165 sec

Version :

Cisco IOS Software, 2800 Software (C2800NM-ADVIPSERVICESK9-M), Version 12.4(22)T2, RELEASE SOFTWARE (fc4)

Technical Support: <http://www.cisco.com/techsupport>

Copyright (c) 1986-2009 by Cisco Systems, Inc.

Compiled Fri 19-Jun-09 15:34 by prod_rel_team

advertisement version: 2

VTP Management Domain: ''

Device ID: R1

Entry address(es):

IP address: 10.1.1.1

IPv6 address: 2026::12:1 (global unicast)

IPv6 address: FE80::21D:70FF:FEA0:C690 (link-local)

Platform: Cisco 2811, Capabilities: Router Switch IGMP

Interface: Serial0/2/0.12, Port ID (outgoing port): Serial0/2/0.12

Holdtime : 164 sec

Version :

Cisco IOS Software, 2800 Software (C2800NM-ADVIPSERVICESK9-M), Version
12.4(22)T2, RELEASE SOFTWARE (fc4)
Technical Support: <http://www.cisco.com/techsupport>
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Fri 19-Jun-09 15:34 by prod_rel_team

advertisement version: 2
VTP Management Domain: ''

R2#

R2#show frame-relay map
Serial0/2/0.12 (up): point-to-point dlci, dlci 201(0xC9,0x3090),
broadcast
 status defined, active
Serial0/2/0.23 (up): point-to-point dlci, dlci 203(0xCB,0x30B0),
broadcast

```
R2#          status defined, active
```

```
R2#show arp
```

```
R2#
```

```
R2#show ip arp
```

```
R2#
```

```
R2#show ip interface
FastEthernet0/0 is administratively down, line protocol is down
  Internet protocol processing disabled
FastEthernet0/1 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/0/0 is down, line protocol is down
  Internet protocol processing disabled
Serial0/0/1 is down, line protocol is down
  Internet protocol processing disabled
Serial0/1/0 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/2/0 is up, line protocol is up
  Internet protocol processing disabled
Serial0/2/0.12 is up, line protocol is up
  Internet address is 10.1.1.2/30
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is not set
  Directed broadcast forwarding is disabled
  Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
  224.0.0.13
    224.0.0.5
  Outgoing access list is not set
  Inbound access list is not set
  Proxy ARP is enabled
  Local Proxy ARP is disabled
  Security level is default
  Split horizon is enabled
  ICMP redirects are always sent
  ICMP unreachable are always sent
  ICMP mask replies are never sent
  IP fast switching is enabled
  IP fast switching on the same interface is enabled
  IP Flow switching is disabled
  IP CEF switching is enabled
  IP CEF switching turbo vector
  IP multicast fast switching is enabled
  IP multicast distributed fast switching is disabled
  IP route-cache flags are Fast, CEF
```

```
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
Input features: MCI Check
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
Serial0/2/0.23 is up, line protocol is up
  Internet address is 10.1.1.5/30
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is not set
  Directed broadcast forwarding is disabled
  Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
  224.0.0.13
    224.0.0.5
  Outgoing access list is not set
  Inbound access list is not set
  Proxy ARP is enabled
  Local Proxy ARP is disabled
  Security level is default
  Split horizon is enabled
  ICMP redirects are always sent
  ICMP unreachable are always sent
  ICMP mask replies are never sent
  IP fast switching is enabled
  IP fast switching on the same interface is enabled
  IP Flow switching is disabled
  IP CEF switching is enabled
  IP CEF switching turbo vector
  IP multicast fast switching is enabled
  IP multicast distributed fast switching is disabled
  IP route-cache flags are Fast, CEF
  Router Discovery is disabled
  IP output packet accounting is disabled
  IP access violation accounting is disabled
  TCP/IP header compression is disabled
  RTP/IP header compression is disabled
  Policy routing is disabled
  Network address translation is disabled
  BGP Policy Mapping is disabled
  Input features: MCI Check
  WCCP Redirect outbound is disabled
  WCCP Redirect inbound is disabled
  WCCP Redirect exclude is disabled
Serial0/3/0 is administratively down, line protocol is down
  Internet protocol processing disabled
  NVIO is administratively down, line protocol is down
```


Internet protocol processing disabled
R2#

```
R2#show ip cef
Prefix          Next Hop          Interface
0.0.0.0/0       10.1.1.1         Serial0/2/0.12
0.0.0.0/8       drop
0.0.0.0/32      receive
10.1.1.0/30     attached         Serial0/2/0.12
10.1.1.0/32     receive         Serial0/2/0.12
10.1.1.2/32     receive         Serial0/2/0.12
10.1.1.3/32     receive         Serial0/2/0.12
10.1.1.4/30     attached         Serial0/2/0.23
10.1.1.4/32     receive         Serial0/2/0.23
10.1.1.5/32     receive         Serial0/2/0.23
10.1.1.7/32     receive         Serial0/2/0.23
10.1.1.8/30     10.1.1.6         Serial0/2/0.23
```

```
10.1.4.4/30      10.1.1.6      Serial0/2/0.23
10.1.4.8/30      10.1.1.6      Serial0/2/0.23
10.2.1.0/24      10.1.1.6      Serial0/2/0.23
10.2.2.0/24      10.1.1.6      Serial0/2/0.23
10.2.4.12/30     10.1.1.6      Serial0/2/0.23
127.0.0.0/8      drop
224.0.0.0/4      multicast
224.0.0.0/24     receive
240.0.0.0/4      drop
255.255.255.255/32 receive
R2#
```

```
R2#show tcp statistics
Rcvd: 0 Total, 0 no port
      0 checksum error, 0 bad offset, 0 too short
      0 packets (0 bytes) in sequence
      0 dup packets (0 bytes)
```

0 partially dup packets (0 bytes)
0 out-of-order packets (0 bytes)
0 packets (0 bytes) with data after window
0 packets after close
0 window probe packets, 0 window update packets
0 dup ack packets, 0 ack packets with unsend data
0 ack packets (0 bytes)
Sent: 0 Total, 0 urgent packets
0 control packets (including 0 retransmitted)
0 data packets (0 bytes)
0 data packets (0 bytes) retransmitted
0 data packets (0 bytes) fastretransmitted
0 ack only packets (0 delayed)
0 window probe packets, 0 window update packets
0 Connections initiated, 0 connections accepted, 0 connections
established
0 Connections closed (including 0 dropped, 0 embryonic dropped)
0 Total rxmt timeout, 0 connections dropped in rxmt timeout
0 Keepalive timeout, 0 keepalive probe, 0 Connections dropped in
keepalive
R2#

```
R2#show ip protocols
Routing Protocol is "ospf 1"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  Router ID 2.2.2.2
  It is an area border router
  Number of areas in this router is 2. 2 normal 0 stub 0 nssa
  Maximum path: 4
  Routing for Networks:
    10.1.1.1 0.0.0.0 area 0
    10.1.1.5 0.0.0.0 area 0
    10.2.2.1 0.0.0.0 area 0
    10.0.0.0 0.255.255.255 area 12
Reference bandwidth unit is 100 mbps
Routing Information Sources:
  Gateway         Distance      Last Update
  3.3.3.3          110          00:27:04
  10.1.1.1         110          01:13:58
Distance: (default is 110)
```

```
R2#
```

```
R2#show access-lists
Standard IP access list DENY_10
 10 deny 10.0.0.0, wildcard bits 0.255.255.255
 20 permit any
Standard IP access list DENY_ALL
 10 deny any
Standard IP access list PERMIT_10
 10 permit 10.0.0.0, wildcard bits 0.255.255.255
Standard IP access list PERMIT_ALL
 10 permit any
R2#
```

```
R2#show ip ospf neighbor
```

Neighbor ID	Pri	State	Dead Time	Address
Interface				
3.3.3.3	0	FULL/ -	00:00:30	10.1.1.6
Serial0/2/0.23				
10.1.1.1	0	FULL/ -	00:00:38	10.1.1.1
Serial0/2/0.12				

```
R2#
```

```
R2#show ip ospf interface  
Serial0/2/0.23 is up, line protocol is up
```

```
Internet Address 10.1.1.5/30, Area 0
Process ID 1, Router ID 2.2.2.2, Network Type POINT_TO_POINT, Cost: 64
Transmit Delay is 1 sec, State POINT_TO_POINT
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
  oob-resync timeout 40
  Hello due in 00:00:01
Supports Link-local Signaling (LLS)
Cisco NSF helper support enabled
IETF NSF helper support enabled
Index 1/1, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 2, maximum is 2
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 1, Adjacent neighbor count is 1
  Adjacent with neighbor 3.3.3.3
  Suppress hello for 0 neighbor(s)
Serial0/2/0.12 is up, line protocol is up
Internet Address 10.1.1.2/30, Area 12
Process ID 1, Router ID 2.2.2.2, Network Type POINT_TO_POINT, Cost: 64
Transmit Delay is 1 sec, State POINT_TO_POINT
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
  oob-resync timeout 40
  Hello due in 00:00:06
Supports Link-local Signaling (LLS)
Cisco NSF helper support enabled
IETF NSF helper support enabled
Index 1/2, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 3, maximum is 3
Last flood scan time is 0 msec, maximum is 4 msec
Neighbor Count is 1, Adjacent neighbor count is 1
  Adjacent with neighbor 10.1.1.1
  Suppress hello for 0 neighbor(s)
R2#
```

R2#show ip ospf database

OSPF Router with ID (2.2.2.2) (Process ID 1)

Router Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum	Link
count					
2.2.2.2	2.2.2.2	576	0x8000001A	0x00A4AB	2
3.3.3.3	3.3.3.3	671	0x8000001A	0x004AFE	2

Summary Net Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum
10.1.1.0	2.2.2.2	576	0x80000003	0x0020C9
10.1.1.8	3.3.3.3	671	0x80000003	0x00B12C

Summary ASB Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum
10.1.1.1	2.2.2.2	576	0x80000003	0x001ACA

Router Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum	Link
count					
2.2.2.2	2.2.2.2	576	0x8000001A	0x001D39	2
10.1.1.1	10.1.1.1	577	0x80000009	0x009CC5	2

Summary Net Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
10.1.1.4	2.2.2.2	576	0x80000003	0x00F7ED
10.1.1.8	2.2.2.2	577	0x80000003	0x00524F

Summary ASB Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
3.3.3.3	2.2.2.2	577	0x80000003	0x0033B2

Type-5 AS External Link States

Link ID	ADV Router	Age	Seq#	Checksum	Tag
0.0.0.0	10.1.1.1	1069	0x80000003	0x00C7DB	1
10.1.4.4	3.3.3.3	1659	0x80000001	0x00ACC1	0
10.1.4.8	3.3.3.3	672	0x80000003	0x0080E7	0
10.2.1.0	3.3.3.3	672	0x80000003	0x00F777	0
10.2.2.0	3.3.3.3	672	0x80000003	0x00EC81	0
10.2.4.12	3.3.3.3	1659	0x80000001	0x005015	0

R2#

R2#show ip route ospf
10.0.0.0/8 is variably subnetted, 8 subnets, 2 masks

```
O E2    10.2.4.12/30 [110/20] via 10.1.1.6, 00:27:47, Serial0/2/0.23
O IA    10.1.1.8/30 [110/128] via 10.1.1.6, 01:14:40, Serial0/2/0.23
O E2    10.1.4.8/30 [110/20] via 10.1.1.6, 01:14:24, Serial0/2/0.23
O E2    10.2.1.0/24 [110/20] via 10.1.1.6, 01:14:24, Serial0/2/0.23
O E2    10.2.2.0/24 [110/20] via 10.1.1.6, 01:14:24, Serial0/2/0.23
O E2    10.1.4.4/30 [110/20] via 10.1.1.6, 00:27:46, Serial0/2/0.23
O*E2 0.0.0.0/0 [110/1] via 10.1.1.1, 01:14:40, Serial0/2/0.12
R2#
```

```
R2#
R2#show ntp status
Clock is synchronized, stratum 6, reference is 10.1.1.1
nominal freq is 250.0000 Hz, actual freq is 250.0000 Hz, precision is
2**24
reference time is CFB0E53D.89F042A7 (14:12:13.538 UTC Wed Jun 2 2010)
clock offset is -0.0072 msec, root delay is 0.05 msec
root dispersion is 0.02 msec, peer dispersion is 0.00 msec
loopfilter state is 'CTRL' (Normal Controlled Loop), drift is -
0.000000008 s/s
```

system poll interval is 64, last update was 361 sec ago.
R2#

R2#show ntp associations

address	ref clock	st	when	poll	reach	delay	offset
disp							
*~10.1.1.1	127.127.1.1	5	46	64	377	0.000	-7.221
4.759							
+~10.1.1.1	127.127.1.1	5	30	64	376	0.000	-6.508
4.395							

* sys.peer, # selected, + candidate, - outlyer, x falseticker, ~
configured

R2#