


```
!  
!  
!  
!  
!  
voice-card 0  
!  
!  
!  
!  
!  
archive  
  log config  
  hidekeys  
!  
!  
!  
!  
!  
!  
!  
!  
!  
interface Tunnel34  
  no ip address  
  ipv6 address 2026::34:1/122  
  ipv6 enable  
  ipv6 ospf 6 area 34  
  tunnel source 10.1.1.9  
  tunnel destination 10.1.1.10  
  tunnel mode ipv6ip  
!  
interface FastEthernet0/0  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface FastEthernet0/1  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface Serial0/0/0  
  no ip address  
!  
interface Serial0/0/1  
  no ip address  
  clock rate 2000000  
!  
interface Serial0/1/0  
  no ip address  
  shutdown
```

```
!  
interface Serial0/2/0  
  no ip address  
  encapsulation frame-relay  
!  
interface Serial0/2/0.23 point-to-point  
  ip address 10.1.1.6 255.255.255.252  
  ip pim sparse-dense-mode  
  snmp trap link-status  
  ipv6 address 2026::1:2/122  
  ipv6 enable  
  ipv6 ospf 6 area 0  
  frame-relay interface-dlci 302  
!  
interface Serial0/2/0.34 point-to-point  
  ip address 10.1.1.9 255.255.255.252  
  ip pim sparse-dense-mode  
  snmp trap link-status  
  frame-relay interface-dlci 304  
!  
interface Serial0/3/0  
  no ip address  
!  
router ospf 1  
  router-id 3.3.3.3  
  log-adjacency-changes  
  area 34 nssa no-summary  
  passive-interface Serial0/2/0  
  network 10.1.1.2 0.0.0.0 area 0  
  network 10.1.1.9 0.0.0.0 area 0  
  network 10.1.1.8 0.0.0.3 area 34  
  network 10.3.3.1 0.0.0.0 area 0  
  network 10.3.3.3 0.0.0.0 area 0  
  network 0.0.0.0 255.255.255.255 area 0  
!  
ip forward-protocol nd  
no ip http server  
no ip http secure-server  
!  
!  
!  
ip access-list standard DENY_10  
  deny 10.0.0.0 0.255.255.255  
  permit any  
ip access-list standard DENY_ALL  
  deny any  
ip access-list standard PERMIT_10  
  permit 10.0.0.0 0.255.255.255  
ip access-list standard PERMIT_ALL  
  permit any  
!  
ipv6 router ospf 6  
  log-adjacency-changes  
!
```

```
!  
!  
!  
!  
!  
!  
!  
control-plane  
!  
!  
!  
ccm-manager fax protocol cisco  
!  
mgcp fax t38 ecm  
mgcp behavior g729-variants static-pt  
!  
!  
!  
!  
!  
!  
line con 0  
  exec-timeout 0 0  
  logging synchronous  
line aux 0  
line vty 0 4  
  exec-timeout 0 0  
  password cisco  
  login  
!  
scheduler allocate 20000 1000  
ntp server 10.1.1.1  
ntp peer 10.1.1.1  
end  
  
R3#
```

```
R3#ping 209.65.200.241
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.241, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 160/162/164  
ms
```

```
R3#
```

```
R3#ping 209.65.200.226
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.226, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 160/160/164  
ms
```

```
R3#
```

```
R3#ping 209.65.200.225
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 209.65.200.225, timeout is 2 seconds:  
!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132  
ms  
R3#
```

```
R3#ping 10.1.1.1
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 10.1.1.1, timeout is 2 seconds:  
!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/131/136  
ms  
R3#
```

```
R3#ping 10.1.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/65/68 ms
```

```
R3#
```



```
R3#ping 10.1.1.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.5, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms
```

```
R3#
```

```
R3#ping 10.1.1.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.6, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/129/132  
ms
```

```
R3#
```

```
R3#ping 10.1.1.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.9, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/132/140  
ms
```

```
R3#
```

```
R3#ping 10.1.1.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.10, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/65/68 ms  
R3#
```

```
R3#ping 10.1.4.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.10, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```

```
R3#ping 10.1.4.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.9, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```

```
R3#ping 10.1.4.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.6, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```

```
R3#ping 10.1.4.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.5, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```

```
R3#ping 10.2.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.1, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```

```
R3#ping 10.2.2.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.2, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```



```
R3#ping 10.2.1.254
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.254, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```

```
R3#ping 10.2.4.14
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.14, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```

```
R3#ping 10.2.4.13
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 10.2.4.13, timeout is 2 seconds:  
.....  
Success rate is 0 percent (0/5)  
R3#
```

```
R3#ping 10.2.1.2
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 10.2.1.2, timeout is 2 seconds:  
.....  
Success rate is 0 percent (0/5)  
R3#
```

```
R3#ping 10.2.2.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.1, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```

```
R3#ping 10.2.1.4
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.4, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R3#
```

```
R3#show ip interface brief
```

Interface	IP-Address	OK?	Method	Status
FastEthernet0/0	unassigned	YES	NVRAM	administratively
down down				
FastEthernet0/1	unassigned	YES	NVRAM	administratively
down down				
Serial0/0/0	unassigned	YES	NVRAM	down
down				
Serial0/0/1	unassigned	YES	NVRAM	down
down				
Serial0/1/0	unassigned	YES	NVRAM	administratively
down down				
Serial0/2/0	unassigned	YES	NVRAM	up
up				
Serial0/2/0.23	10.1.1.6	YES	NVRAM	up
up				
Serial0/2/0.34	10.1.1.9	YES	NVRAM	up
up				
Serial0/3/0	unassigned	YES	NVRAM	down
down				
Tunnel34	unassigned	YES	NVRAM	up
up				

```
R3#
```

```
R3#show ip route
```

```
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP  
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
        E1 - OSPF external type 1, E2 - OSPF external type 2  
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS  
level-2  
        ia - IS-IS inter area, * - candidate default, U - per-user static  
route  
        o - ODR, P - periodic downloaded static route
```

```
Gateway of last resort is not set
```

```
        209.65.200.0/24 is variably subnetted, 2 subnets, 2 masks  
O E2    209.65.200.240/29 [110/1] via 10.1.1.5, 00:48:45, Serial0/2/0.23  
O E2    209.65.200.224/30 [110/20] via 10.1.1.5, 00:48:45, Serial0/2/0.23  
        10.0.0.0/30 is subnetted, 3 subnets  
C       10.1.1.8 is directly connected, Serial0/2/0.34  
O IA    10.1.1.0 [110/128] via 10.1.1.5, 01:02:45, Serial0/2/0.23  
C       10.1.1.4 is directly connected, Serial0/2/0.23  
R3#
```

R3#show processes cpu

CPU utilization for five seconds: 2%/0%; one minute: 1%; five minutes: 1%

PID	Runtime (ms)	Invoked	uSecs	5Sec	1Min	5Min	TTY	Process
1	12	69	173	0.00%	0.00%	0.00%	0	Chunk
Manager								
2	4	897	4	0.07%	0.04%	0.03%	0	Load Meter
3	0	10	0	0.00%	0.00%	0.00%	0	Collection
proce								
4	0	1	0	0.00%	0.00%	0.00%	0	EDDRI_MAIN
5	5660	530	10679	0.00%	0.15%	0.12%	0	Check
heaps								
6	0	1	0	0.00%	0.00%	0.00%	0	Pool
Manager								
7	0	2	0	0.00%	0.00%	0.00%	0	Timers
8	0	1	0	0.00%	0.00%	0.00%	0	License
Client N								
9	108	1729	62	0.00%	0.00%	0.00%	0	OSPF-1
Hello								
10	0	76	0	0.00%	0.00%	0.00%	0	IPC
Dynamic Cach								
11	0	1	0	0.00%	0.00%	0.00%	0	IPC Zone
Manager								
12	0	4485	0	0.00%	0.00%	0.00%	0	IPC
Periodic Tim								
13	0	4485	0	0.00%	0.00%	0.00%	0	IPC
Deferred Por								
14	0	1	0	0.00%	0.00%	0.00%	0	IPC Seat
Manager								
15	0	1	0	0.00%	0.00%	0.00%	0	IPC
BackPressure								
16	0	1	0	0.00%	0.00%	0.00%	0	OIR
Handler								
17	0	1	0	0.00%	0.00%	0.00%	0	Crash
writer								
18	4	151	26	0.00%	0.00%	0.00%	0	
Environmental mo								

197	116	2	58000	0.00%	0.00%	0.00%	0
CCVPM_HDSPRM							
198	0	4	0	0.00%	0.00%	0.00%	0 HDA DSPRM
MAIN							
199	4	2	2000	0.00%	0.00%	0.00%	0 STUN_APP
200	0	1	0	0.00%	0.00%	0.00%	0 STUN_TEST
201	0	1	0	0.00%	0.00%	0.00%	0
cpf_process_tpQ							
202	0	2	0	0.00%	0.00%	0.00%	0 AAA Cached
Serve							
203	0	2	0	0.00%	0.00%	0.00%	0 ENABLE AAA
204	0	1	0	0.00%	0.00%	0.00%	0 EM
Background Pr							
205	0	1	0	0.00%	0.00%	0.00%	0 Key chain
liveke							
206	0	2	0	0.00%	0.00%	0.00%	0 LINE AAA
207	0	2	0	0.00%	0.00%	0.00%	0 LOCAL AAA
208	0	4	0	0.00%	0.00%	0.00%	0 MPLS Auto
Mesh P							
209	4	2	2000	0.00%	0.00%	0.00%	0 TPLUS
210	0	2	0	0.00%	0.00%	0.00%	0 VSP_MGR
211	0	1	0	0.00%	0.00%	0.00%	0
FW_TEST_TRP							
212	0	1	0	0.00%	0.00%	0.00%	0 EPM MAIN
PROCESS							
213	0	3	0	0.00%	0.00%	0.00%	0 Crypto WUI
214	0	2	0	0.00%	0.00%	0.00%	0 Crypto
Support							
215	0	1	0	0.00%	0.00%	0.00%	0 IPSECv6 PS
Proc							
216	0	1	0	0.00%	0.00%	0.00%	0 CCVPM_HTSP
217	0	2	0	0.00%	0.00%	0.00%	0
VPM_MWI_BACKGROU							
218	0	1	0	0.00%	0.00%	0.00%	0 CCVPM_R2
219	0	1	0	0.00%	0.00%	0.00%	0 EPHONE MWI
Refre							
220	0	6	0	0.00%	0.00%	0.00%	0 FB/KS Log
HouseK							
221	0	2	0	0.00%	0.00%	0.00%	0 EPHONE MWI
BG Pr							
222	4	1	4000	0.00%	0.00%	0.00%	0 Skinny HW
confer							
223	4	1669	2	0.00%	0.00%	0.00%	0 FLEX DSPRM
MAIN							
224	0	1667	0	0.00%	0.00%	0.00%	0 FLEX DSP
KEEPALI							
225	0	152	0	0.00%	0.00%	0.00%	0 VOICE REG
BG Pro							
226	0	1	0	0.00%	0.00%	0.00%	0 Presence
Process							
227	0	1	0	0.00%	0.00%	0.00%	0 CCSWVOICE
229	0	1	0	0.00%	0.00%	0.00%	0 http
client proc							


```
R3#show interfaces
FastEthernet0/0 is administratively down, line protocol is down
  Hardware is MV96340 Ethernet, address is 0016.479a.f6e8 (bia
0016.479a.f6e8)
  MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto Speed, 100BaseTX/FX
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes
    Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 0 interface resets
    0 unknown protocol drops
    0 babbles, 0 late collision, 0 deferred
```

```
0 lost carrier, 0 no carrier
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/1 is administratively down, line protocol is down
Hardware is MV96340 Ethernet, address is 0016.479a.f6e9 (bia
0016.479a.f6e9)
MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto Speed, 100BaseTX/FX
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 0 interface resets
  0 unknown protocol drops
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier
  0 output buffer failures, 0 output buffers swapped out
Serial0/0/0 is down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
  Conversations 0/0/256 (active/max active/max total)
  Reserved Conversations 0/0 (allocated/max allocated)
  Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 4 interface resets
  0 unknown protocol drops
  0 output buffer failures, 0 output buffers swapped out
  0 carrier transitions
```

DCD=down DSR=down DTR=up RTS=up CTS=down

Serial0/0/1 is down, line protocol is down

Hardware is GT96K Serial

MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255

Encapsulation HDLC, loopback not set

Keepalive set (10 sec)

CRC checking enabled

Last input never, output never, output hang never

Last clearing of "show interface" counters never

Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0

Queueing strategy: weighted fair

Output queue: 0/1000/64/0 (size/max total/threshold/drops)

Conversations 0/0/256 (active/max active/max total)

Reserved Conversations 0/0 (allocated/max allocated)

Available Bandwidth 1158 kilobits/sec

5 minute input rate 0 bits/sec, 0 packets/sec

5 minute output rate 0 bits/sec, 0 packets/sec

0 packets input, 0 bytes, 0 no buffer

Received 0 broadcasts, 0 runts, 0 giants, 0 throttles

0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort

0 packets output, 0 bytes, 0 underruns

0 output errors, 0 collisions, 5 interface resets

0 unknown protocol drops

0 output buffer failures, 0 output buffers swapped out

0 carrier transitions

DCD=up DSR=up DTR=down RTS=down CTS=up

Serial0/1/0 is administratively down, line protocol is down

Hardware is GT96K Serial

MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255

Encapsulation HDLC, loopback not set

Keepalive set (10 sec)

CRC checking enabled

Last input 01:15:21, output 01:15:22, output hang never

Last clearing of "show interface" counters never

Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0

Queueing strategy: weighted fair

Output queue: 0/1000/64/0 (size/max total/threshold/drops)

Conversations 0/1/256 (active/max active/max total)

Reserved Conversations 0/0 (allocated/max allocated)

Available Bandwidth 1158 kilobits/sec

5 minute input rate 0 bits/sec, 0 packets/sec

5 minute output rate 0 bits/sec, 0 packets/sec

1 packets input, 24 bytes, 0 no buffer

Received 1 broadcasts, 0 runts, 0 giants, 0 throttles

0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort

1 packets output, 24 bytes, 0 underruns

0 output errors, 0 collisions, 3 interface resets

0 unknown protocol drops

0 output buffer failures, 0 output buffers swapped out

1 carrier transitions

DCD=down DSR=down DTR=down RTS=down CTS=down

Serial0/2/0 is up, line protocol is up

Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY, loopback not set
Keepalive set (10 sec)
CRC checking enabled
LMI enq sent 395, LMI stat recvd 393, LMI upd recvd 0, DTE LMI up
LMI enq recvd 0, LMI stat sent 0, LMI upd sent 0
LMI DLCI 1023 LMI type is CISCO frame relay DTE
FR SVC disabled, LAPF state down
Broadcast queue 0/64, broadcasts sent/dropped 1932/0, interface
broadcasts 1829
Last input 00:00:00, output 00:00:01, output hang never
Last clearing of "show interface" counters 01:15:21
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/4/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
2906 packets input, 255780 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
3289 packets output, 290014 bytes, 0 underruns
0 output errors, 0 collisions, 17 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
168 carrier transitions
DCD=up DSR=up DTR=up RTS=up CTS=up

Serial0/2/0.23 is up, line protocol is up

Hardware is GT96K Serial
Internet address is 10.1.1.6/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY
CRC checking enabled
Last clearing of "show interface" counters never

Serial0/2/0.34 is up, line protocol is up

Hardware is GT96K Serial
Internet address is 10.1.1.9/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY
CRC checking enabled
Last clearing of "show interface" counters never

Serial0/3/0 is down, line protocol is down

Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,

```
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input 01:14:50, output 01:14:55, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
  Conversations 0/1/256 (active/max active/max total)
  Reserved Conversations 0/0 (allocated/max allocated)
  Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1 packets input, 24 bytes, 0 no buffer
  Received 1 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
  5 packets output, 1026 bytes, 0 underruns
  0 output errors, 0 collisions, 153 interface resets
  0 unknown protocol drops
  0 output buffer failures, 0 output buffers swapped out
  8 carrier transitions
  DCD=down DSR=down DTR=up RTS=up CTS=down
```

```
Tunnel34 is up, line protocol is up
Hardware is Tunnel
MTU 17920 bytes, BW 100 Kbit/sec, DLY 50000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation TUNNEL, loopback not set
Keepalive not set
Tunnel source 10.1.1.9, destination 10.1.1.10
Tunnel protocol/transport IPv6/IP
Tunnel TTL 255
Tunnel transport MTU 1480 bytes
Tunnel transmit bandwidth 8000 (kbps)
Tunnel receive bandwidth 8000 (kbps)
Last input 00:00:00, output 00:00:03, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 38
Queueing strategy: fifo
Output queue: 0/0 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  405 packets input, 59372 bytes, 0 no buffer
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
  545 packets output, 54356 bytes, 0 underruns
  0 output errors, 0 collisions, 0 interface resets
  0 unknown protocol drops
  0 output buffer failures, 0 output buffers swapped out
```

R3#

```
R3#show cdp neighbors
```

```
Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge  
                  S - Switch, H - Host, I - IGMP, r - Repeater
```

Device ID	Local Intrfce	Holdtme	Capability	Platform	Port
ID					
R2	Ser 0/2/0.23	123	R S I	2811	Ser
0/2/0.23					
R4	Ser 0/2/0.34	122	R S I	1841	Ser
0/1/0.34					
R3#					


```
R3#show cdp neighbors detail
```

```
-----
```

```
Device ID: R2
```

```
Entry address(es):
```

```
  IP address: 10.1.1.5
```

```
  IPv6 address: 2026::1:1 (global unicast)
```

```
  IPv6 address: FE80::216:9DFF:FEFA:CAB0 (link-local)
```

```
Platform: Cisco 2811, Capabilities: Router Switch IGMP
```

```
Interface: Serial0/2/0.23, Port ID (outgoing port): Serial0/2/0.23
```

```
Holdtime : 175 sec
```

```
Version :
```

```
Cisco IOS Software, 2800 Software (C2800NM-ADVIPSERVICESK9-M), Version  
12.4(22)T2, RELEASE SOFTWARE (fc4)
```

```
Technical Support: http://www.cisco.com/techsupport
```

```
Copyright (c) 1986-2009 by Cisco Systems, Inc.
```

```
Compiled Fri 19-Jun-09 15:34 by prod_rel_team
```

```
advertisement version: 2
```

```
VTP Management Domain: ''
```

```
-----
```

```
Device ID: R4
```

```
Entry address(es):
```

```
  IP address: 10.1.1.10
```

```
Platform: Cisco 1841, Capabilities: Router Switch IGMP
```

```
Interface: Serial0/2/0.34, Port ID (outgoing port): Serial0/1/0.34
```

```
Holdtime : 174 sec
```

Version :
Cisco IOS Software, 1841 Software (C1841-ADVIPSERVICESK9-M), Version
12.4(25b), RELEASE SOFTWARE (fc1)
Technical Support: <http://www.cisco.com/techsupport>
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Wed 12-Aug-09 10:49 by prod_rel_team

advertisement version: 2
VTP Management Domain: ''

R3#

R3#show frame-relay map
Serial0/2/0.23 (up): point-to-point dlci, dlci 302(0x12E,0x48E0),
broadcast
 status defined, active
Serial0/2/0.34 (up): point-to-point dlci, dlci 304(0x130,0x4C00),
broadcast

```
status defined, active
R3#
```

```
R3#show ip interface
FastEthernet0/0 is administratively down, line protocol is down
  Internet protocol processing disabled
FastEthernet0/1 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/0/0 is down, line protocol is down
  Internet protocol processing disabled
Serial0/0/1 is down, line protocol is down
  Internet protocol processing disabled
Serial0/1/0 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/2/0 is up, line protocol is up
  Internet protocol processing disabled
Serial0/2/0.23 is up, line protocol is up
  Internet address is 10.1.1.6/30
  Broadcast address is 255.255.255.255
```

```
Address determined by non-volatile memory
MTU is 1500 bytes
Helper address is not set
Directed broadcast forwarding is disabled
Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
    224.0.0.5
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP fast switching on the same interface is enabled
IP Flow switching is disabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
Input features: MCI Check
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
Serial0/2/0.34 is up, line protocol is up
Internet address is 10.1.1.9/30
Broadcast address is 255.255.255.255
Address determined by non-volatile memory
MTU is 1500 bytes
Helper address is not set
Directed broadcast forwarding is disabled
Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
    224.0.0.5
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
```

```
ICMP mask replies are never sent
IP fast switching is enabled
IP fast switching on the same interface is enabled
IP Flow switching is disabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
Input features: MCI Check
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
Serial0/3/0 is down, line protocol is down
  Internet protocol processing disabled
Tunnel34 is up, line protocol is up
  Internet protocol processing disabled
R3#
```

```
R3#show ip cef
```

Prefix	Next Hop	Interface
0.0.0.0/0	no route	
0.0.0.0/8	drop	
0.0.0.0/32	receive	
10.1.1.0/30	10.1.1.5	Serial0/2/0.23
10.1.1.4/30	attached	Serial0/2/0.23
10.1.1.4/32	receive	Serial0/2/0.23
10.1.1.6/32	receive	Serial0/2/0.23
10.1.1.7/32	receive	Serial0/2/0.23
10.1.1.8/30	attached	Serial0/2/0.34
10.1.1.8/32	receive	Serial0/2/0.34
10.1.1.9/32	receive	Serial0/2/0.34
10.1.1.11/32	receive	Serial0/2/0.34
127.0.0.0/8	drop	
209.65.200.224/30	10.1.1.5	Serial0/2/0.23
209.65.200.240/29	10.1.1.5	Serial0/2/0.23
224.0.0.0/4	multicast	
224.0.0.0/24	receive	
240.0.0.0/4	drop	
255.255.255.255/32	receive	

```
R3#
```

```
R3#show tcp statistics
Rcvd: 0 Total, 0 no port
      0 checksum error, 0 bad offset, 0 too short
      0 packets (0 bytes) in sequence
      0 dup packets (0 bytes)
      0 partially dup packets (0 bytes)
      0 out-of-order packets (0 bytes)
      0 packets (0 bytes) with data after window
      0 packets after close
      0 window probe packets, 0 window update packets
      0 dup ack packets, 0 ack packets with unsend data
      0 ack packets (0 bytes)
Sent: 0 Total, 0 urgent packets
      0 control packets (including 0 retransmitted)
      0 data packets (0 bytes)
      0 data packets (0 bytes) retransmitted
      0 data packets (0 bytes) fastretransmitted
      0 ack only packets (0 delayed)
      0 window probe packets, 0 window update packets
0 Connections initiated, 0 connections accepted, 0 connections
established
0 Connections closed (including 0 dropped, 0 embryonic dropped)
0 Total rxmt timeout, 0 connections dropped in rxmt timeout
0 Keepalive timeout, 0 keepalive probe, 0 Connections dropped in
keepalive
R3#
```

```
R3#show ip protocols
Routing Protocol is "ospf 1"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  Router ID 3.3.3.3
  Number of areas in this router is 2. 1 normal 0 stub 1 nssa
  Maximum path: 4
  Routing for Networks:
    10.1.1.2 0.0.0.0 area 0
    10.1.1.9 0.0.0.0 area 0
    10.1.1.8 0.0.0.3 area 34
    10.3.3.1 0.0.0.0 area 0
    10.3.3.3 0.0.0.0 area 0
    0.0.0.0 255.255.255.255 area 0
  Reference bandwidth unit is 100 mbps
  Passive Interface(s):
    Serial0/2/0
  Routing Information Sources:
    Gateway         Distance      Last Update
    4.4.4.4          110          01:04:39
    2.2.2.2          110          01:04:39
    10.1.1.1         110          00:50:39
  Distance: (default is 110)
```

```
R3#
```



```
R3#show access-lists
Standard IP access list DENY_10
  10 deny 10.0.0.0, wildcard bits 0.255.255.255
  20 permit any
Standard IP access list DENY_ALL
  10 deny any
Standard IP access list PERMIT_10
  10 permit 10.0.0.0, wildcard bits 0.255.255.255
Standard IP access list PERMIT_ALL
  10 permit any
R3#
```

```
R3#show ip ospf neighbor
```

Neighbor ID	Pri	State	Dead Time	Address
Interface				
2.2.2.2	0	FULL/ -	00:00:37	10.1.1.5
Serial0/2/0.23				

```
R3#
```

```
R3#show ip ospf interface
Serial0/2/0.34 is up, line protocol is up
  Internet Address 10.1.1.9/30, Area 0
  Process ID 1, Router ID 3.3.3.3, Network Type POINT_TO_POINT, Cost: 64
  Transmit Delay is 1 sec, State POINT_TO_POINT
  Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
    oob-resync timeout 40
    Hello due in 00:00:03
  Supports Link-local Signaling (LLS)
  Cisco NSF helper support enabled
  IETF NSF helper support enabled
  Index 2/1, flood queue length 0
  Next 0x0(0)/0x0(0)
  Last flood scan length is 0, maximum is 0
  Last flood scan time is 0 msec, maximum is 0 msec
  Neighbor Count is 0, Adjacent neighbor count is 0
  Suppress hello for 0 neighbor(s)
Serial0/2/0.23 is up, line protocol is up
  Internet Address 10.1.1.6/30, Area 0
  Process ID 1, Router ID 3.3.3.3, Network Type POINT_TO_POINT, Cost: 64
  Transmit Delay is 1 sec, State POINT_TO_POINT
  Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
    oob-resync timeout 40
    Hello due in 00:00:02
  Supports Link-local Signaling (LLS)
  Cisco NSF helper support enabled
  IETF NSF helper support enabled
  Index 1/2, flood queue length 0
  Next 0x0(0)/0x0(0)
  Last flood scan length is 1, maximum is 4
  Last flood scan time is 0 msec, maximum is 0 msec
  Neighbor Count is 1, Adjacent neighbor count is 1
    Adjacent with neighbor 2.2.2.2
  Suppress hello for 0 neighbor(s)
R3#
```

R3#show ip ospf database

OSPF Router with ID (3.3.3.3) (Process ID 1)

Router Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum	Link
count					
2.2.2.2	2.2.2.2	51	0x80000016	0x00ACA7	2
3.3.3.3	3.3.3.3	1126	0x80000016	0x00A24C	3

Summary Net Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum
10.1.1.0	2.2.2.2	51	0x80000003	0x0020C9

Summary ASB Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum
10.1.1.1	2.2.2.2	51	0x80000003	0x001ACA

Router Link States (Area 34)

Link ID	ADV Router	Age	Seq#	Checksum	Link
count					
3.3.3.3	3.3.3.3	1126	0x80000017	0x0032DC	0

Type-5 AS External Link States

Link ID	ADV Router	Age	Seq#	Checksum	Tag
209.65.200.224	10.1.1.1	562	0x80000003	0x004295	0
209.65.200.240	10.1.1.1	561	0x80000003	0x002DC8	65002

R3#

```
R3#show ip route ospf
  209.65.200.0/24 is variably subnetted, 2 subnets, 2 masks
O E2   209.65.200.240/29 [110/1] via 10.1.1.5, 00:51:25, Serial0/2/0.23
O E2   209.65.200.224/30 [110/20] via 10.1.1.5, 00:51:25, Serial0/2/0.23
  10.0.0.0/30 is subnetted, 3 subnets
O IA   10.1.1.0 [110/128] via 10.1.1.5, 01:05:25, Serial0/2/0.23
R3#
```