


```
!  
!  
!  
!  
voice-card 0  
!  
!  
!  
!  
archive  
  log config  
  hidekeys  
!  
!  
!  
!  
!  
!  
!  
!  
!  
interface FastEthernet0/0  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface FastEthernet0/1  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface Serial0/0/0  
  no ip address  
!  
interface Serial0/0/1  
  no ip address  
!  
interface Serial0/1/0  
  no ip address  
  ip nat outside  
  ip virtual-reassembly  
  shutdown  
  clock rate 56000  
!  
interface Serial0/2/0  
  no ip address  
  encapsulation frame-relay  
!  
interface Serial0/2/0.12 point-to-point  
  ip address 10.1.1.2 255.255.255.252  
  ip pim sparse-dense-mode
```

```
snmp trap link-status
ipv6 address 2026::12:2/122
ipv6 enable
ipv6 ospf 6 area 12
frame-relay interface-dlci 201
!
interface Serial0/2/0.23 point-to-point
 ip address 10.1.1.5 255.255.255.252
 ip pim sparse-dense-mode
 snmp trap link-status
 ipv6 address 2026::1:1/122
 ipv6 enable
 ipv6 ospf 6 area 0
 frame-relay interface-dlci 203
!
interface Serial0/3/0
 no ip address
 ip virtual-reassembly
 shutdown
 clock rate 56000
!
router ospf 1
 router-id 2.2.2.2
 log-adjacency-changes
 network 10.1.1.1 0.0.0.0 area 0
 network 10.1.1.5 0.0.0.0 area 0
 network 10.2.2.1 0.0.0.0 area 0
 network 10.0.0.0 0.255.255.255 area 12
!
ip forward-protocol nd
ip http server
no ip http secure-server
!
!
!
ip access-list standard DENY_10
 deny 10.0.0.0 0.255.255.255
 permit any
ip access-list standard DENY_ALL
 deny any
ip access-list standard PERMIT_10
 permit 10.0.0.0 0.255.255.255
ip access-list standard PERMIT_ALL
 permit any
!
ipv6 router ospf 6
 router-id 2.2.2.2
 log-adjacency-changes
!
!
!
!
!
```

```
!  
!  
control-plane  
!  
!  
!  
ccm-manager fax protocol cisco  
!  
mgcp fax t38 ecm  
mgcp behavior g729-variants static-pt  
!  
!  
!  
!  
!  
line con 0  
  exec-timeout 0 0  
  logging synchronous  
line aux 0  
line vty 0 4  
  exec-timeout 0 0  
  password cisco  
  login  
line vty 5  
  exec-timeout 0 0  
  login  
!  
scheduler allocate 20000 1000  
ntp server 10.1.1.1  
ntp peer 10.1.1.1  
end
```

R2#

```
R2#ping 209.65.200.241
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.241, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 96/96/100 ms
```

```
R2#
```

```
R2#ping 209.65.200.226
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.226, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 96/97/100 ms
```

```
R2#
```

```
R2#ping 209.65.200.225
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.225, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/65/68 ms
```

```
R2#
```

```
R2#ping 10.1.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms
```

```
R2#
```



```
R2#ping 10.1.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.2, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/131/132
```

```
ms
```

```
R2#
```

```
R2#ping 10.1.1.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.5, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/131/132  
ms
```

```
R2#
```

```
R2#ping 10.1.1.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.6, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/65/68 ms
```

```
R2#
```

```
R2#ping 10.1.1.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.9, timeout is 2 seconds:  
!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/67/72 ms  
R2#
```

```
R2#ping 10.1.1.10
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 10.1.1.10, timeout is 2 seconds:  
!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/129/132  
ms
```

R2#

R2#ping 10.1.4.10

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 10.1.4.10, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132
ms

R2#

```
R2#ping 10.1.4.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.9, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/129/132
```

```
ms  
R2#
```

```
R2#ping 10.1.4.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.6, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132  
ms
```

```
R2#
```

```
R2#ping 10.1.4.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.5, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132
```

```
ms  
R2#
```



```
R2#ping 10.2.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.1, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R2#
```

```
R2#ping 10.2.2.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132  
ms
```

```
R2#
```

```
R2#ping 10.2.1.254
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.254, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132  
ms
```

```
R2#
```

```
R2#ping 10.2.4.14
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.14, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132  
ms
```

```
R2#
```

```
R2#ping 10.2.4.13
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.13, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132  
ms
```

```
R2#
```

```
R2#ping 10.2.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/129/132  
ms
```

```
R2#
```

```
R2#ping 10.2.2.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132
```

```
ms
```

```
R2#
```

```
R2#ping 10.2.1.4
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.4, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R2#
```



```
R2#show ip interface brief
```

Interface	IP-Address	OK?	Method	Status
FastEthernet0/0 down down	unassigned	YES	NVRAM	administratively
FastEthernet0/1 down down	unassigned	YES	NVRAM	administratively
Serial0/0/0 down	unassigned	YES	NVRAM	down
Serial0/0/1 down	unassigned	YES	NVRAM	down
Serial0/1/0 down down	unassigned	YES	NVRAM	administratively
Serial0/2/0 up	unassigned	YES	NVRAM	up
Serial0/2/0.12 up	10.1.1.2	YES	NVRAM	up
Serial0/2/0.23 up	10.1.1.5	YES	NVRAM	up
Serial0/3/0 down down	unassigned	YES	NVRAM	administratively
NVI0 down down	unassigned	YES	unset	administratively

```
R2#
```

```
R2#show ip route
```

```
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2  
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS  
level-2  
ia - IS-IS inter area, * - candidate default, U - per-user static  
route  
o - ODR, P - periodic downloaded static route
```

```
Gateway of last resort is not set
```

```
209.65.200.0/24 is variably subnetted, 2 subnets, 2 masks  
O E2 209.65.200.240/29 [110/1] via 10.1.1.1, 00:23:47, Serial0/2/0.12  
O E2 209.65.200.224/30 [110/20] via 10.1.1.1, 00:23:47, Serial0/2/0.12  
10.0.0.0/8 is variably subnetted, 8 subnets, 2 masks  
O E2 10.2.4.12/30 [110/20] via 10.1.1.6, 00:23:31, Serial0/2/0.23  
O IA 10.1.1.8/30 [110/128] via 10.1.1.6, 00:23:47, Serial0/2/0.23  
O E2 10.1.4.8/30 [110/20] via 10.1.1.6, 00:23:31, Serial0/2/0.23  
O E2 10.2.1.0/24 [110/20] via 10.1.1.6, 00:23:32, Serial0/2/0.23  
O E2 10.2.2.0/24 [110/20] via 10.1.1.6, 00:23:32, Serial0/2/0.23  
C 10.1.1.0/30 is directly connected, Serial0/2/0.12  
O E2 10.1.4.4/30 [110/20] via 10.1.1.6, 00:23:32, Serial0/2/0.23  
C 10.1.1.4/30 is directly connected, Serial0/2/0.23  
R2#
```

R2#show processes cpu

CPU utilization for five seconds: 1%/0%; one minute: 2%; five minutes: 2%

PID	Runtime (ms)	Invoked	uSecs	5Sec	1Min	5Min	TTY	Process
1	12	75	160	0.00%	0.00%	0.00%	0	Chunk
Manager								
2	4	346	11	0.00%	0.04%	0.02%	0	Load Meter
3	1268	621	2041	0.00%	0.19%	0.21%	0	Exec
4	0	1	0	0.00%	0.00%	0.00%	0	EDDRI_MAIN
5	2264	201	11263	0.00%	0.14%	0.12%	0	Check
heaps								
6	0	1	0	0.00%	0.00%	0.00%	0	Pool
Manager								
7	0	2	0	0.00%	0.00%	0.00%	0	Timers
8	0	1	0	0.00%	0.00%	0.00%	0	License
Client N								
9	36	701	51	0.00%	0.01%	0.00%	0	OSPF-1
Hello								
10	0	30	0	0.00%	0.00%	0.00%	0	IPC
Dynamic Cach								

11	0	1	0	0.00%	0.00%	0.00%	0	IPC Zone
Manager								
12	0	1741	0	0.07%	0.00%	0.00%	0	IPC
Periodic Tim								
13	0	1741	0	0.07%	0.00%	0.00%	0	IPC
Deferred Por								
14	0	1	0	0.00%	0.00%	0.00%	0	IPC Seat
Manager								
15	0	1	0	0.00%	0.00%	0.00%	0	IPC
BackPressure								
16	0	1	0	0.00%	0.00%	0.00%	0	OIR
Handler								
17	0	1	0	0.00%	0.00%	0.00%	0	Crash
writer								
18	0	59	0	0.00%	0.00%	0.00%	0	
Environmental mo								
19	0	1	0	0.00%	0.00%	0.00%	0	ARP Input
20	0	1821	0	0.00%	0.00%	0.00%	0	ARP
Background								
21	0	2	0	0.00%	0.00%	0.00%	0	ATM Idle
Timer								
22	0	2	0	0.00%	0.00%	0.00%	0	AAA high-
capacit								
23	0	1	0	0.00%	0.00%	0.00%	0	
AAA_SERVER_DEADT								
24	0	1	0	0.00%	0.00%	0.00%	0	Policy
Manager								
25	0	7	0	0.00%	0.00%	0.00%	0	DDR Timers
26	4	2	2000	0.00%	0.00%	0.00%	0	Entity MIB
API								
27	8	40	200	0.00%	0.00%	0.00%	0	EEM ED
Syslog								
28	0	524	0	0.00%	0.00%	0.00%	0	HC Counter
Timer								
29	4	9	444	0.00%	0.00%	0.00%	0	Serial
Backgroun								
30	0	1	0	0.00%	0.00%	0.00%	0	RO Notify
Timers								
31	0	1	0	0.00%	0.00%	0.00%	0	RMI RM
Notify Wa								
32	0	2	0	0.00%	0.00%	0.00%	0	SMART
33	0	1728	0	0.00%	0.00%	0.00%	0	GraphIt
34	0	2	0	0.00%	0.00%	0.00%	0	Dialer
event								
35	0	1	0	0.00%	0.00%	0.00%	0	SERIAL
A'detect								
36	0	2	0	0.00%	0.00%	0.00%	0	XML Proxy
Client								
37	0	1	0	0.00%	0.00%	0.00%	0	Critical
Bkgnd								
38	32	747	42	0.00%	0.00%	0.00%	0	Net
Background								
39	0	2	0	0.00%	0.00%	0.00%	0	IDB Work
40	0	31	0	0.00%	0.00%	0.00%	0	Logger

71	0	2	0	0.00%	0.00%	0.00%	0	VMI
Background								
72	0	1	0	0.00%	0.00%	0.00%	0	
RF_INTERDEV_DELA								
73	0	1	0	0.00%	0.00%	0.00%	0	
RF_INTERDEV_SCTP								
74	0	1	0	0.00%	0.00%	0.00%	0	chkpt
message ha								
75	0	1733	0	0.00%	0.00%	0.00%	0	Ether-
Switch RBC								
76	0	1	0	0.00%	0.00%	0.00%	0	IGMP
Snooping Pr								
77	0	1	0	0.00%	0.00%	0.00%	0	IGMP
Snooping Re								
78	0	59	0	0.00%	0.00%	0.00%	0	Call
Management								
79	0	1	0	0.00%	0.00%	0.00%	0	AAL2CPS
TIMER_CU								
80	0	1	0	0.00%	0.00%	0.00%	0	CES Line
Conditi								
81	0	1	0	0.00%	0.00%	0.00%	0	
CF_INTERDEV_SCTP								
82	0	1	0	0.00%	0.00%	0.00%	0	Async
write proc								
83	0	1	0	0.00%	0.00%	0.00%	0	Async
write proc								
84	0	1	0	0.00%	0.00%	0.00%	0	Async
write proc								
85	0	1	0	0.00%	0.00%	0.00%	0	Async
write proc								
86	0	30	0	0.00%	0.00%	0.00%	0	DFS flush
period								
87	0	2	0	0.00%	0.00%	0.00%	0	Dot1x Mgr
Proces								
88	0	1	0	0.00%	0.00%	0.00%	0	MAB
Framework								
89	0	1	0	0.00%	0.00%	0.00%	0	EAP
Framework								
90	0	2	0	0.00%	0.00%	0.00%	0	DTP
Protocol								
91	0	1733	0	0.00%	0.00%	0.00%	0	PI MATM
Aging Pr								
92	0	175	0	0.00%	0.00%	0.00%	0	EtherChnl
93	0	2	0	0.00%	0.00%	0.00%	0	Ethernet
CFM								
94	0	1693	0	0.00%	0.00%	0.00%	0	Ethernet
Timer C								
95	0	1748	0	0.00%	0.00%	0.00%	0	linktest
96	0	2	0	0.00%	0.00%	0.00%	0	Dot11 Mgmt
& Ass								
97	0	2	0	0.00%	0.00%	0.00%	0	Dot11 aaa
proces								
98	0	30	0	0.00%	0.00%	0.00%	0	pmkid


```
R2#show interfaces
FastEthernet0/0 is administratively down, line protocol is down
  Hardware is MV96340 Ethernet, address is 0016.9dfa.cab0 (bia
0016.9dfa.cab0)
  MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto Speed, 100BaseTX/FX
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes
    Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 0 interface resets
    0 unknown protocol drops
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/1 is administratively down, line protocol is down
  Hardware is MV96340 Ethernet, address is 0016.9dfa.cab1 (bia
0016.9dfa.cab1)
  MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto Speed, 100BaseTX/FX
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes
    Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog
    0 input packets with dribble condition detected
```

0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 0 interface resets
0 unknown protocol drops
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier
0 output buffer failures, 0 output buffers swapped out
Serial0/0/0 is down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/0/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 4 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=down DSR=down DTR=up RTS=up CTS=down

Serial0/0/1 is down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/0/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns

0 output errors, 0 collisions, 4 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=down DSR=down DTR=up RTS=up CTS=down

Serial0/1/0 is administratively down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/0/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 3 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=down DSR=down DTR=down RTS=down CTS=down

Serial0/2/0 is up, line protocol is up
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY, loopback not set
Keepalive set (10 sec)
CRC checking enabled
LMI enq sent 161, LMI stat recvd 159, LMI upd recvd 0, DTE LMI up
LMI enq recvd 0, LMI stat sent 0, LMI upd sent 0
LMI DLCI 1023 LMI type is CISCO frame relay DTE
FR SVC disabled, LAPF state down
Broadcast queue 0/64, broadcasts sent/dropped 1098/0, interface
broadcasts 1055
Last input 00:00:00, output 00:00:00, output hang never
Last clearing of "show interface" counters 00:29:35
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/4/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec

5 minute input rate 1000 bits/sec, 1 packets/sec
5 minute output rate 1000 bits/sec, 0 packets/sec
1838 packets input, 160497 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
2085 packets output, 183436 bytes, 0 underruns
0 output errors, 0 collisions, 6 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
64 carrier transitions
DCD=up DSR=up DTR=up RTS=up CTS=up

Serial0/2/0.12 is up, line protocol is up

Hardware is GT96K Serial
Internet address is 10.1.1.2/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY
CRC checking enabled
Last clearing of "show interface" counters never

Serial0/2/0.23 is up, line protocol is up

Hardware is GT96K Serial
Internet address is 10.1.1.5/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY
CRC checking enabled
Last clearing of "show interface" counters never

Serial0/3/0 is administratively down, line protocol is down

Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input 00:29:51, output 00:29:51, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/1/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec

5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
1 packets input, 24 bytes, 0 no buffer
Received 1 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
1 packets output, 24 bytes, 0 underruns
0 output errors, 0 collisions, 3 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
3 carrier transitions
DCD=down DSR=down DTR=down RTS=down CTS=down

```
NV10 is administratively down, line protocol is down
Hardware is NVI
MTU 1514 bytes, BW 56 Kbit/sec, DLY 5000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation UNKNOWN, loopback not set
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 0 interface resets
  0 unknown protocol drops
  0 output buffer failures, 0 output buffers swapped out
```

R2#

```
R2#show cdp neighbors
```

```
Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge  
S - Switch, H - Host, I - IGMP, r - Repeater
```

Device ID	Local Intrfce	Holdtme	Capability	Platform	Port
R3	Ser 0/2/0.23	167	R S I	2811	Ser
0/2/0.23					
R1	Ser 0/2/0.12	167	R S I	2811	Ser
0/2/0.12					

R2#show cdp neighbors detail

Device ID: R3

Entry address(es):

IP address: 10.1.1.6

IPv6 address: 2026::1:2 (global unicast)

IPv6 address: FE80::216:47FF:FE9A:F6E8 (link-local)

Platform: Cisco 2811, Capabilities: Router Switch IGMP

Interface: Serial0/2/0.23, Port ID (outgoing port): Serial0/2/0.23

Holdtime : 160 sec

Version :

Cisco IOS Software, 2800 Software (C2800NM-ADVIPSERVICESK9-M), Version 12.4(22)T2, RELEASE SOFTWARE (fc4)

Technical Support: <http://www.cisco.com/techsupport>

Copyright (c) 1986-2009 by Cisco Systems, Inc.

Compiled Fri 19-Jun-09 15:34 by prod_rel_team

advertisement version: 2

VTP Management Domain: ''

Device ID: R1

Entry address(es):

IP address: 10.1.1.1

IPv6 address: 2026::12:1 (global unicast)

IPv6 address: FE80::21D:70FF:FEA0:C690 (link-local)

Platform: Cisco 2811, Capabilities: Router Switch IGMP

Interface: Serial0/2/0.12, Port ID (outgoing port): Serial0/2/0.12

Holdtime : 159 sec

Version :

Cisco IOS Software, 2800 Software (C2800NM-ADVIPSERVICESK9-M), Version 12.4(22)T2, RELEASE SOFTWARE (fc4)

Technical Support: <http://www.cisco.com/techsupport>

Copyright (c) 1986-2009 by Cisco Systems, Inc.

Compiled Fri 19-Jun-09 15:34 by prod_rel_team

advertisement version: 2

VTP Management Domain: ''

R2#

```
R2#show frame-relay map
Serial0/2/0.12 (up): point-to-point dlci, dlci 201(0xC9,0x3090),
broadcast
                    status defined, active
Serial0/2/0.23 (up): point-to-point dlci, dlci 203(0xCB,0x30B0),
broadcast
                    status defined, active
R2#
```

```
R2#show ip interface
FastEthernet0/0 is administratively down, line protocol is down
  Internet protocol processing disabled
FastEthernet0/1 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/0/0 is down, line protocol is down
  Internet protocol processing disabled
Serial0/0/1 is down, line protocol is down
  Internet protocol processing disabled
Serial0/1/0 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/2/0 is up, line protocol is up
  Internet protocol processing disabled
Serial0/2/0.12 is up, line protocol is up
  Internet address is 10.1.1.2/30
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is not set
```

```
Directed broadcast forwarding is disabled
Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
    224.0.0.5
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP fast switching on the same interface is enabled
IP Flow switching is disabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
Input features: MCI Check
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
Serial0/2/0.23 is up, line protocol is up
Internet address is 10.1.1.5/30
Broadcast address is 255.255.255.255
Address determined by non-volatile memory
MTU is 1500 bytes
Helper address is not set
Directed broadcast forwarding is disabled
Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
    224.0.0.5
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP fast switching on the same interface is enabled
```



```
IP Flow switching is disabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
Input features: MCI Check
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
Serial0/3/0 is administratively down, line protocol is down
  Internet protocol processing disabled
NV10 is administratively down, line protocol is down
  Internet protocol processing disabled
R2#
```

```

R2#show ip cef
Prefix                Next Hop                Interface
0.0.0.0/0             no route
0.0.0.0/8             drop
0.0.0.0/32            receive
10.1.1.0/30           attached                Serial0/2/0.12
10.1.1.0/32           receive                 Serial0/2/0.12
10.1.1.2/32           receive                 Serial0/2/0.12
10.1.1.3/32           receive                 Serial0/2/0.12
10.1.1.4/30           attached                Serial0/2/0.23
10.1.1.4/32           receive                 Serial0/2/0.23
10.1.1.5/32           receive                 Serial0/2/0.23
10.1.1.7/32           receive                 Serial0/2/0.23
10.1.1.8/30           10.1.1.6                Serial0/2/0.23
10.1.4.4/30           10.1.1.6                Serial0/2/0.23
10.1.4.8/30           10.1.1.6                Serial0/2/0.23
10.2.1.0/24           10.1.1.6                Serial0/2/0.23
10.2.2.0/24           10.1.1.6                Serial0/2/0.23
10.2.4.12/30          10.1.1.6                Serial0/2/0.23
127.0.0.0/8          drop
209.65.200.224/30    10.1.1.1                Serial0/2/0.12
209.65.200.240/29    10.1.1.1                Serial0/2/0.12
224.0.0.0/4          multicast
224.0.0.0/24         receive
240.0.0.0/4          drop
255.255.255.255/32   receive
R2#

```

```
R2#show tcp statistics
Rcvd: 0 Total, 0 no port
      0 checksum error, 0 bad offset, 0 too short
      0 packets (0 bytes) in sequence
      0 dup packets (0 bytes)
      0 partially dup packets (0 bytes)
      0 out-of-order packets (0 bytes)
      0 packets (0 bytes) with data after window
      0 packets after close
      0 window probe packets, 0 window update packets
      0 dup ack packets, 0 ack packets with unsend data
      0 ack packets (0 bytes)
Sent: 0 Total, 0 urgent packets
      0 control packets (including 0 retransmitted)
      0 data packets (0 bytes)
      0 data packets (0 bytes) retransmitted
      0 data packets (0 bytes) fastretransmitted
      0 ack only packets (0 delayed)
      0 window probe packets, 0 window update packets
0 Connections initiated, 0 connections accepted, 0 connections
established
0 Connections closed (including 0 dropped, 0 embryonic dropped)
0 Total rxmt timeout, 0 connections dropped in rxmt timeout
0 Keepalive timeout, 0 keepalive probe, 0 Connections dropped in
keepalive
R2#
```

```
R2#show ip protocols
Routing Protocol is "ospf 1"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  Router ID 2.2.2.2
  It is an area border router
  Number of areas in this router is 2. 2 normal 0 stub 0 nssa
  Maximum path: 4
  Routing for Networks:
    10.1.1.1 0.0.0.0 area 0
    10.1.1.5 0.0.0.0 area 0
```

```
10.2.2.1 0.0.0.0 area 0
10.0.0.0 0.255.255.255 area 12
Reference bandwidth unit is 100 mbps
Routing Information Sources:
  Gateway          Distance      Last Update
  3.3.3.3           110           00:25:39
  10.1.1.1          110           00:25:55
Distance: (default is 110)
```

R2#

R2#show access-lists

```
Standard IP access list DENY_10
  10 deny 10.0.0.0, wildcard bits 0.255.255.255
  20 permit any
Standard IP access list DENY_ALL
  10 deny any
Standard IP access list PERMIT_10
  10 permit 10.0.0.0, wildcard bits 0.255.255.255
Standard IP access list PERMIT_ALL
  10 permit any
R2#
```

```
R2#show ip ospf neighbor
```

Neighbor ID	Pri	State	Dead Time	Address
Interface				
3.3.3.3	0	FULL/ -	00:00:35	10.1.1.6
Serial0/2/0.23				
10.1.1.1	0	FULL/ -	00:00:30	10.1.1.1
Serial0/2/0.12				

R2#

```
R2#show ip ospf interface
Serial0/2/0.23 is up, line protocol is up
  Internet Address 10.1.1.5/30, Area 0
```

```
Process ID 1, Router ID 2.2.2.2, Network Type POINT_TO_POINT, Cost: 64
Transmit Delay is 1 sec, State POINT_TO_POINT
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
  oob-resync timeout 40
  Hello due in 00:00:04
Supports Link-local Signaling (LLS)
Cisco NSF helper support enabled
IETF NSF helper support enabled
Index 1/1, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 1, maximum is 1
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 1, Adjacent neighbor count is 1
  Adjacent with neighbor 3.3.3.3
  Suppress hello for 0 neighbor(s)
Serial0/2/0.12 is up, line protocol is up
Internet Address 10.1.1.2/30, Area 12
Process ID 1, Router ID 2.2.2.2, Network Type POINT_TO_POINT, Cost: 64
Transmit Delay is 1 sec, State POINT_TO_POINT
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
  oob-resync timeout 40
  Hello due in 00:00:07
Supports Link-local Signaling (LLS)
Cisco NSF helper support enabled
IETF NSF helper support enabled
Index 1/2, flood queue length 0
Next 0x0(0)/0x0(0)
Last flood scan length is 3, maximum is 3
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 1, Adjacent neighbor count is 1
  Adjacent with neighbor 10.1.1.1
  Suppress hello for 0 neighbor(s)
R2#
```


R2#show ip ospf database

OSPF Router with ID (2.2.2.2) (Process ID 1)

Router Link States (Area 0)

Link ID count	ADV Router	Age	Seq#	Checksum	Link
2.2.2.2	2.2.2.2	1597	0x8000000C	0x00C09D	2
3.3.3.3	3.3.3.3	1598	0x8000000C	0x0066F0	2

Summary Net Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum
10.1.1.0	2.2.2.2	1597	0x80000001	0x0024C7
10.1.1.8	3.3.3.3	1598	0x80000001	0x00B52A

Summary ASB Link States (Area 0)

Link ID	ADV Router	Age	Seq#	Checksum
10.1.1.1	2.2.2.2	1587	0x80000001	0x001EC8

Router Link States (Area 12)

Link ID count	ADV Router	Age	Seq#	Checksum	Link
2.2.2.2	2.2.2.2	1597	0x8000000C	0x00392B	2
10.1.1.1	10.1.1.1	1598	0x80000007	0x00A0C3	2

Summary Net Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
---------	------------	-----	------	----------

10.1.1.4	2.2.2.2	1597	0x80000001	0x00FBEB
10.1.1.8	2.2.2.2	1589	0x80000001	0x00564D

Summary ASB Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
3.3.3.3	2.2.2.2	1589	0x80000001	0x0037B0

Type-5 AS External Link States

Link ID	ADV Router	Age	Seq#	Checksum	Tag
10.1.4.4	3.3.3.3	1574	0x80000001	0x00ACC1	0
10.1.4.8	3.3.3.3	1573	0x80000001	0x0084E5	0
10.2.1.0	3.3.3.3	1573	0x80000001	0x00FB75	0
10.2.2.0	3.3.3.3	1573	0x80000001	0x00F07F	0
10.2.4.12	3.3.3.3	1573	0x80000001	0x005015	0
209.65.200.224	10.1.1.1	1833	0x80000001	0x004693	0
209.65.200.240	10.1.1.1	1774	0x80000001	0x0031C6	65002

R2#

```
R2#show ip route ospf
    209.65.200.0/24 is variably subnetted, 2 subnets, 2 masks
O E2    209.65.200.240/29 [110/1] via 10.1.1.1, 00:26:37, Serial0/2/0.12
O E2    209.65.200.224/30 [110/20] via 10.1.1.1, 00:26:37, Serial0/2/0.12
    10.0.0.0/8 is variably subnetted, 8 subnets, 2 masks
O E2    10.2.4.12/30 [110/20] via 10.1.1.6, 00:26:21, Serial0/2/0.23
O IA    10.1.1.8/30 [110/128] via 10.1.1.6, 00:26:37, Serial0/2/0.23
O E2    10.1.4.8/30 [110/20] via 10.1.1.6, 00:26:21, Serial0/2/0.23
O E2    10.2.1.0/24 [110/20] via 10.1.1.6, 00:26:21, Serial0/2/0.23
O E2    10.2.2.0/24 [110/20] via 10.1.1.6, 00:26:21, Serial0/2/0.23
O E2    10.1.4.4/30 [110/20] via 10.1.1.6, 00:26:21, Serial0/2/0.23
R2#
```

