


```
!  
!  
!  
!  
!  
!  
voice-card 0  
!  
!  
!  
!  
!  
archive  
  log config  
  hidekeys  
!  
!  
!  
!  
!  
!  
!  
!  
interface FastEthernet0/0  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface FastEthernet0/1  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface Serial0/0/0  
  no ip address  
  shutdown  
  no fair-queue  
  clock rate 2000000  
!  
interface Serial0/0/1  
  no ip address  
  shutdown  
!  
interface Serial0/1/0  
  no ip address  
  shutdown  
  clock rate 2000000  
!  
interface Serial0/2/0  
  no ip address  
  encapsulation frame-relay
```

```
!  
interface Serial0/2/0.12 point-to-point  
 ip address 10.1.1.1 255.255.255.252  
 ip pim sparse-dense-mode  
 ip nat inside  
 ip virtual-reassembly  
 snmp trap link-status  
 ipv6 address 2026::12:1/122  
 ipv6 enable  
 ipv6 ospf 6 area 12  
 frame-relay interface-dlci 102  
!  
interface Serial0/3/0  
 ip address 209.65.200.225 255.255.255.252  
 ip nat outside  
 ip virtual-reassembly  
 clock rate 56000  
!  
router ospf 1  
 router-id 10.1.1.1  
 log-adjacency-changes  
 redistribute connected subnets  
 redistribute static subnets  
 redistribute bgp 65001 subnets  
 network 10.1.1.1 0.0.0.0 area 12  
!  
router bgp 65001  
 no synchronization  
 bgp router-id 1.1.1.1  
 bgp log-neighbor-changes  
 neighbor 209.65.200.226 remote-as 65002  
 no auto-summary  
!  
ip forward-protocol nd  
ip http server  
no ip http secure-server  
!  
!  
ip nat inside source list 10 interface Serial0/3/0 overload  
!  
ip access-list standard DENY_10  
 deny 10.0.0.0 0.255.255.255  
 permit any  
ip access-list standard DENY_ALL  
 deny any  
ip access-list standard PERMIT_10  
 permit 10.0.0.0 0.255.255.255  
ip access-list standard PERMIT_ALL  
 permit any  
!  
access-list 10 permit 10.0.0.0 0.255.255.255  
ipv6 router ospf 6  
 router-id 1.1.1.1  
 log-adjacency-changes
```

```
!  
!  
!  
!  
!  
!  
!  
!  
control-plane  
!  
!  
!  
ccm-manager fax protocol cisco  
!  
mgcp fax t38 ecm  
mgcp behavior g729-variants static-pt  
!  
!  
!  
!  
!  
!  
line con 0  
  exec-timeout 0 0  
  logging synchronous  
line aux 0  
line vty 0 4  
  password cisco  
  login  
!  
scheduler allocate 20000 1000  
ntp master 5  
ntp peer 10.1.1.2  
ntp peer 10.1.4.6  
ntp peer 10.1.1.6  
ntp peer 10.1.4.10  
ntp peer 10.1.1.10  
ntp peer 10.2.4.13  
ntp peer 10.2.4.14  
end
```

```
R1#
```

```
R1#ping 209.65.200.241
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.241, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 32/32/32 ms
```

```
R1#
```

```
R1#ping 209.65.200.226
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.226, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 32/32/36 ms
```

```
R1#
```

```
R1#ping 209.65.200.225
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.225, timeout is 2 seconds:  
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/64/64 ms  
R1#
```

```
R1#ping 10.1.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/131/140  
ms
```

```
R1#
```



```
R1#ping 10.1.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms
```

```
R1#
```

```
R1#ping 10.1.1.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.5, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/67/72 ms
```

```
R1#
```

```
R1#ping 10.1.1.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.6, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/136  
ms
```

```
R1#
```

```
R1#ping 10.1.1.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.9, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132
```

```
ms
```

```
R1#
```

```
R1#ping 10.1.1.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.10, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/194/196  
ms
```

```
R1#
```

```
R1#ping 10.1.4.10
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 10.1.4.10, timeout is 2 seconds:  
!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196  
ms  
R1#
```

```
R1#ping 10.1.4.9
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 10.1.4.9, timeout is 2 seconds:
```

```
!!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 196/196/196  
ms  
R1#
```

```
R1#ping 10.1.4.6
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 10.1.4.6, timeout is 2 seconds:  
!!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196  
ms
```

R1#

R1#ping 10.1.4.5

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 10.1.4.5, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 192/196/204
ms

R1#


```
R1#ping 10.2.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.1, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R1#
```

```
R1#ping 10.2.2.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/196/200  
ms
```

```
R1#
```

```
R1#ping 10.2.1.254
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.254, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R1#
```

```
R1#ping 10.2.4.14
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.14, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/194/196  
ms
```

```
R1#
```

```
R1#ping 10.2.4.13
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.13, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/194/196  
ms
```

```
R1#
```

```
R1#ping 10.2.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.2, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R1#
```

```
R1#ping 10.2.2.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196  
ms
```

```
R1#
```

```
R1#ping 10.2.1.4
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.4, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R1#
```



```
R1#show ip interface brief
```

Interface	IP-Address	OK?	Method	Status
Protocol				
FastEthernet0/0 down down	unassigned	YES	NVRAM	administratively
FastEthernet0/1 down down	unassigned	YES	NVRAM	administratively
Serial0/0/0 down down	unassigned	YES	NVRAM	administratively
Serial0/0/1 down down	unassigned	YES	NVRAM	administratively
Serial0/1/0 down down	unassigned	YES	NVRAM	administratively
Serial0/2/0 up	unassigned	YES	NVRAM	up
Serial0/2/0.12 up	10.1.1.1	YES	NVRAM	up
Serial0/3/0 up	209.65.200.225	YES	NVRAM	up
NV10 up	10.1.1.1	YES	unset	up

```
R1#
```

```
R1#show ip route
```

```
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP  
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
        E1 - OSPF external type 1, E2 - OSPF external type 2  
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS  
level-2  
        ia - IS-IS inter area, * - candidate default, U - per-user static  
route  
        o - ODR, P - periodic downloaded static route
```

```
Gateway of last resort is not set
```

```
          209.65.200.0/24 is variably subnetted, 2 subnets, 2 masks  
B          209.65.200.240/29 [20/0] via 209.65.200.226, 01:29:14  
C          209.65.200.224/30 is directly connected, Serial0/3/0  
          10.0.0.0/8 is variably subnetted, 8 subnets, 2 masks  
O E2      10.2.4.12/30 [110/20] via 10.1.1.2, 01:29:32, Serial0/2/0.12  
O IA      10.1.1.8/30 [110/192] via 10.1.1.2, 01:29:32, Serial0/2/0.12  
O E2      10.1.4.8/30 [110/20] via 10.1.1.2, 01:29:32, Serial0/2/0.12  
O E2      10.2.1.0/24 [110/20] via 10.1.1.2, 01:29:32, Serial0/2/0.12  
O E2      10.2.2.0/24 [110/20] via 10.1.1.2, 01:29:33, Serial0/2/0.12  
C          10.1.1.0/30 is directly connected, Serial0/2/0.12  
O E2      10.1.4.4/30 [110/20] via 10.1.1.2, 01:29:33, Serial0/2/0.12  
O IA      10.1.1.4/30 [110/128] via 10.1.1.2, 01:29:33, Serial0/2/0.12  
R1#
```

R1#show processes cpu

CPU utilization for five seconds: 1%/0%; one minute: 1%; five minutes: 1%

PID	Runtime (ms)	Invoked	uSecs	5Sec	1Min	5Min	TTY	Process
1	20	81	246	0.00%	0.00%	0.00%	0	Chunk
Manager								
2	4	1085	3	0.00%	0.04%	0.05%	0	Load Meter
3	1176	625	1881	0.15%	0.22%	0.21%	0	Exec
4	0	1	0	0.00%	0.00%	0.00%	0	EDDRI_MAIN
5	7316	640	11431	0.00%	0.15%	0.12%	0	Check
heaps								
6	0	1	0	0.00%	0.00%	0.00%	0	Pool
Manager								
7	0	2	0	0.00%	0.00%	0.00%	0	Timers
8	0	1	0	0.00%	0.00%	0.00%	0	License
Client N								

38	16	2186	7	0.00%	0.00%	0.00%	0 Net
Background							
39	0	2	0	0.00%	0.00%	0.00%	0 IDB Work
40	0	11	0	0.00%	0.00%	0.00%	0 Logger
41	0	5418	0	0.00%	0.00%	0.00%	0 TTY
Background							
42	16	5438	2	0.07%	0.02%	0.00%	0 Per-Second
Jobs							
43	0	363	0	0.00%	0.00%	0.00%	0 c2800
Periodic							
44	0	1	0	0.00%	0.00%	0.00%	0 Inode
Table Dest							
45	0	1	0	0.00%	0.00%	0.00%	0 IKE HA Mgr
46	0	1	0	0.00%	0.00%	0.00%	0 IPSEC HA
Mgr							
47	8	4	2000	0.00%	0.00%	0.00%	0 rf task
48	52	552	94	0.07%	0.00%	0.00%	0 Net Input
49	0	1087	0	0.00%	0.00%	0.00%	0 Compute
load avg							
50	2184	92	23739	0.47%	0.05%	0.00%	0 Per-minute
Jobs							
51	0	1	0	0.00%	0.00%	0.00%	0 AggMgr
Process							
52	0	1	0	0.00%	0.00%	0.00%	0 Token
Daemon							
53	0	1	0	0.00%	0.00%	0.00%	0 Transport
Port A							
54	0	1	0	0.00%	0.00%	0.00%	0
dev_device_inser							
55	0	1	0	0.00%	0.00%	0.00%	0
dev_device_remov							
56	0	1	0	0.00%	0.00%	0.00%	0
sal_dpc_process							
57	0	1	0	0.00%	0.00%	0.00%	0 ARL Table
Manage							
58	0	2	0	0.00%	0.00%	0.00%	0 ESWPPM
59	0	2	0	0.00%	0.00%	0.00%	0 Eswilp
Storm Con							
60	0	2	0	0.00%	0.00%	0.00%	0 ESWILPPM
61	0	2	0	0.00%	0.00%	0.00%	0 Eswilp
Storm Con							
62	16	21697	0	0.00%	0.01%	0.00%	0 Netclock
Backgro							
63	0	2	0	0.00%	0.00%	0.00%	0 SM Monitor
64	0	2	0	0.00%	0.00%	0.00%	0 Bryce I2C
CMD Qu							
65	272	4	68000	0.00%	0.00%	0.00%	0 USB
Startup							
66	0	907	0	0.00%	0.00%	0.00%	0 mxt5100
67	0	2	0	0.00%	0.00%	0.00%	0 VNM DSPRM
MAIN							
68	0	1	0	0.00%	0.00%	0.00%	0 DSPFARM
DSP READ							

97	0	2	0	0.00%	0.00%	0.00%	0	Dot11 aaa
proces								
98	0	91	0	0.00%	0.00%	0.00%	0	pmkid
99	0	2	0	0.00%	0.00%	0.00%	0	Dot11 auth
Dot1x								
100	0	1	0	0.00%	0.00%	0.00%	0	Dot11 Mac
Auth								
101	0	2	0	0.00%	0.00%	0.00%	0	AAA
Dictionary R								
102	0	2	0	0.00%	0.00%	0.00%	0	AAA Server
103	0	1	0	0.00%	0.00%	0.00%	0	AAA ACCT
Proc								
104	4	1	4000	0.00%	0.00%	0.00%	0	ACCT
Periodic Pr								
105	44	730	60	0.00%	0.00%	0.00%	0	CDP
Protocol								
106	0	2	0	0.00%	0.00%	0.00%	0	Ethernet
OAM Pro								
107	0	2	0	0.00%	0.00%	0.00%	0	CEF
switching ba								
108	0	2	0	0.00%	0.00%	0.00%	0	ADJ
resolve proc								
109	0	1	0	0.00%	0.00%	0.00%	0	IP ARP
Adjacency								
110	0	1	0	0.00%	0.00%	0.00%	0	IP ARP
Retry Age								
111	516	1757	293	0.00%	0.00%	0.00%	0	IP Input
112	0	1	0	0.00%	0.00%	0.00%	0	ICMP event
handl								
113	0	4	0	0.00%	0.00%	0.00%	0	TurboACL
114	0	2	0	0.00%	0.00%	0.00%	0	TurboACL
chunk								
115	0	1	0	0.00%	0.00%	0.00%	0	IPv6 Echo
event								
116	0	1	0	0.00%	0.00%	0.00%	0	LSP Tunnel
FRR								
117	0	1	0	0.00%	0.00%	0.00%	0	MPLS Auto-
Tunnel								
118	0	11	0	0.00%	0.00%	0.00%	0	MOP
Protocols								
119	4	3	1333	0.00%	0.00%	0.00%	0	PPP Hooks
121	0	1	0	0.00%	0.00%	0.00%	0	SSS
Manager								
122	0	1	0	0.00%	0.00%	0.00%	0	SSS
Feature Mana								
123	0	1	0	0.00%	0.00%	0.00%	0	SSS
Feature Time								
124	0	2	0	0.00%	0.00%	0.00%	0	Spanning
Tree								
125	0	1	0	0.00%	0.00%	0.00%	0	X.25
Encaps Mana								
126	0	4	0	0.00%	0.00%	0.00%	0	SSM
connection m								
127	0	1	0	0.00%	0.00%	0.00%	0	AC Switch

128	0	19	0	0.00%	0.00%	0.00%	0
Authentication P							
129	0	1	0	0.00%	0.00%	0.00%	0 Auth-proxy
AAA B							
130	104	2	52000	0.00%	0.00%	0.00%	0 EAPoUDP
Process							
131	0	2	0	0.00%	0.00%	0.00%	0 IP Host
Track Pr							
132	0	2	0	0.00%	0.00%	0.00%	0 KRB5 AAA
133	0	2	0	0.00%	0.00%	0.00%	0 Ethernet
LMI							
134	0	2	0	0.00%	0.00%	0.00%	0 PPP IP
Route							
135	0	2	0	0.00%	0.00%	0.00%	0 PPP IPCP
136	0	107	0	0.00%	0.00%	0.00%	0 IP
Background							
137	8	4	2000	0.00%	0.00%	0.00%	0 IP RIB
Update							
138	0	2	0	0.00%	0.00%	0.00%	0 Dot1x
Supplicant							
139	0	2	0	0.00%	0.00%	0.00%	0 Dot1x
Supplicant							
140	0	2	0	0.00%	0.00%	0.00%	0 Dot1x
Supplicant							
141	0	1	0	0.00%	0.00%	0.00%	0 Asy FS
Helper							
142	0	91	0	0.00%	0.00%	0.00%	0 Licensing
Auto U							
143	0	1	0	0.00%	0.00%	0.00%	0 Socket
Timers							
144	0	93	0	0.00%	0.00%	0.00%	0 CEF
background p							
145	16	8378	1	0.00%	0.00%	0.00%	0 CEF: IPv4
proces							
146	4	9	444	0.00%	0.00%	0.00%	0 ADJ
background							
147	0	2	0	0.00%	0.00%	0.00%	0 L2MM
148	0	1	0	0.00%	0.00%	0.00%	0 MRD
149	0	1	0	0.00%	0.00%	0.00%	0 IGMP SN
150	0	1	0	0.00%	0.00%	0.00%	0 L2X Data
Daemon							
151	4	184	21	0.00%	0.00%	0.00%	0 TCP Timer
152	0	1	0	0.00%	0.00%	0.00%	0 TCP
Protocols							
153	0	20	0	0.00%	0.00%	0.00%	0 HTTP CORE
154	0	1	0	0.00%	0.00%	0.00%	0 IP
Traceroute							
155	0	2	0	0.00%	0.00%	0.00%	0 RLM groups
Proce							
156	0	2	0	0.00%	0.00%	0.00%	0 PPPoE Flow
Contr							
157	0	1	0	0.00%	0.00%	0.00%	0 SNMP
Timers							

250	0	1	0	0.00%	0.00%	0.00%	0 UNICAST
REKEY AC							
251	0	5457	0	0.00%	0.00%	0.00%	0 Crypto
Device Up							
252	0	2	0	0.00%	0.00%	0.00%	0 Multi-ISA
Event							
253	0	1	0	0.00%	0.00%	0.00%	0 Multi-ISA
Cleanu							
254	0	1	0	0.00%	0.00%	0.00%	0 PM
Callback							
255	0	1	0	0.00%	0.00%	0.00%	0 Licensing
MIB pr							
256	0	27272	0	0.00%	0.01%	0.00%	0 Atheros
LED Ctro							
257	0	2	0	0.00%	0.00%	0.00%	0 Control-
plane ho							
258	0	1	0	0.00%	0.00%	0.00%	0 DATA
Transfer Pr							
259	0	1	0	0.00%	0.00%	0.00%	0 DATA
Collector							
260	0	2	0	0.00%	0.00%	0.00%	0 AAA SEND
STOP EV							
261	4	2	2000	0.00%	0.00%	0.00%	0 EEM ED
Resource							
262	0	2	0	0.00%	0.00%	0.00%	0 EEM ED
Routing							
263	0	3	0	0.00%	0.00%	0.00%	0 EEM ED
Track							
264	0	546	0	0.00%	0.00%	0.00%	0 RMON
Recycle Pro							
265	0	2	0	0.00%	0.00%	0.00%	0 RMON
Deferred Se							
266	0	1	0	0.00%	0.00%	0.00%	0 Syslog
Traps							
267	0	171	0	0.00%	0.00%	0.00%	0 Crypto
cTCP proc							
268	8	2	4000	0.00%	0.00%	0.00%	0 VLAN
Manager							
269	68	1165	58	0.00%	0.00%	0.00%	0 OSPFv3-6
Hello							
270	0	1	0	0.00%	0.00%	0.00%	0 chkpt
message ha							
271	0	5438	0	0.00%	0.00%	0.00%	0 trunk
conditioni							
272	0	1	0	0.00%	0.00%	0.00%	0 trunk
conditioni							
273	8	5459	1	0.00%	0.00%	0.00%	0 CME
Extension Mo							
274	0	1	0	0.00%	0.00%	0.00%	0 IP SLAs
Ethernet							
275	4	218	18	0.00%	0.00%	0.00%	0 EEM Server
276	4	2	2000	0.00%	0.00%	0.00%	0 EEM Policy
Direc							
277	0	3	0	0.00%	0.00%	0.00%	0 EEM ED CLI

R1#show interfaces

FastEthernet0/0 is administratively down, line protocol is down

Hardware is MV96340 Ethernet, address is 001d.70a0.c690 (bia 001d.70a0.c690)

MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
reliability 255/255, txload 1/255, rxload 1/255

Encapsulation ARPA, loopback not set

Keepalive set (10 sec)

Auto-duplex, Auto Speed, 100BaseTX/FX

ARP type: ARPA, ARP Timeout 04:00:00

Last input never, output never, output hang never

Last clearing of "show interface" counters never

Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0

Queueing strategy: fifo

Output queue: 0/40 (size/max)

5 minute input rate 0 bits/sec, 0 packets/sec

5 minute output rate 0 bits/sec, 0 packets/sec

0 packets input, 0 bytes

Received 0 broadcasts, 0 runts, 0 giants, 0 throttles

0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored

0 watchdog

0 input packets with dribble condition detected

0 packets output, 0 bytes, 0 underruns

0 output errors, 0 collisions, 0 interface resets

0 unknown protocol drops

0 babbles, 0 late collision, 0 deferred

0 lost carrier, 0 no carrier

0 output buffer failures, 0 output buffers swapped out

FastEthernet0/1 is administratively down, line protocol is down

Hardware is MV96340 Ethernet, address is 001d.70a0.c691 (bia 001d.70a0.c691)

MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
reliability 255/255, txload 1/255, rxload 1/255

Encapsulation ARPA, loopback not set

Keepalive set (10 sec)

Auto-duplex, Auto Speed, 100BaseTX/FX

```
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 0 interface resets
  0 unknown protocol drops
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier
  0 output buffer failures, 0 output buffers swapped out
Serial0/0/0 is administratively down, line protocol is down
  Hardware is GT96K Serial
  MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation HDLC, loopback not set
  Keepalive set (10 sec)
  CRC checking enabled
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 3 interface resets
    0 unknown protocol drops
    0 output buffer failures, 0 output buffers swapped out
    0 carrier transitions
    DCD=down DSR=down DTR=down RTS=down CTS=down

Serial0/0/1 is administratively down, line protocol is down
  Hardware is GT96K Serial
  MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation HDLC, loopback not set
  Keepalive set (10 sec)
  CRC checking enabled
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: weighted fair
```


Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/0/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 3 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=down DSR=down DTR=down RTS=down CTS=down

Serial0/1/0 is administratively down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input 01:31:13, output 01:31:13, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/1/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
5 packets input, 1026 bytes, 0 no buffer
Received 5 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
1 packets output, 24 bytes, 0 underruns
0 output errors, 0 collisions, 3 interface resets
3 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=down DSR=down DTR=up RTS=down CTS=down

Serial0/2/0 is up, line protocol is up
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY, loopback not set
Keepalive set (10 sec)
CRC checking enabled
LMI enq sent 547, LMI stat recvd 546, LMI upd recvd 0, DTE LMI up
LMI enq recvd 0, LMI stat sent 0, LMI upd sent 0
LMI DLCI 1023 LMI type is CISCO frame relay DTE
FR SVC disabled, LAPF state down

Broadcast queue 1/64, broadcasts sent/dropped 1477/0, interface
broadcasts 1387
Last input 00:00:00, output 00:00:00, output hang never
Last clearing of "show interface" counters 01:31:12
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/1/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
2778 packets input, 224048 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
2940 packets output, 234475 bytes, 0 underruns
0 output errors, 0 collisions, 2 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=up DSR=up DTR=up RTS=up CTS=up

Serial0/2/0.12 is up, line protocol is up
Hardware is GT96K Serial
Internet address is 10.1.1.1/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY
CRC checking enabled
Last clearing of "show interface" counters never

Serial0/3/0 is up, line protocol is up
Hardware is GT96K Serial
Internet address is 209.65.200.225/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input 00:00:02, output 00:00:06, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/1/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
908 packets input, 61699 bytes, 0 no buffer
Received 642 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
904 packets output, 61202 bytes, 0 underruns
0 output errors, 0 collisions, 5 interface resets
3 unknown protocol drops

0 output buffer failures, 0 output buffers swapped out
5 carrier transitions
DCD=up DSR=up DTR=up RTS=up CTS=up

NVIO is up, line protocol is up
Hardware is NVI
Interface is unnumbered. Using address of Serial0/2/0.12 (10.1.1.1)
MTU 1514 bytes, BW 56 Kbit/sec, DLY 5000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation UNKNOWN, loopback not set
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 0 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out

R1#

```
R1#show cdp neighbors
```

```
Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge  
S - Switch, H - Host, I - IGMP, r - Repeater
```

Device ID	Local Intrfce	Holdtme	Capability	Platform	Port
R2	Ser 0/2/0.12	140	R S I	2811	Ser
0/2/0.12					
R5	Ser 0/3/0	168	R S I	2811	Ser
0/3/0					

```
R1#
```

```
R1#show cdp neighbors detail
```

```
-----
```

```
Device ID: R2
```

```
Entry address(es):
```

```
  IP address: 10.1.1.2
```

```
  IPv6 address: 2026::12:2 (global unicast)
```

```
  IPv6 address: FE80::216:9DFF:FEFA:CAB0 (link-local)
```

```
Platform: Cisco 2811, Capabilities: Router Switch IGMP
```

```
Interface: Serial0/2/0.12, Port ID (outgoing port): Serial0/2/0.12
```

```
Holdtime : 133 sec
```

```
Version :
```

```
Cisco IOS Software, 2800 Software (C2800NM-ADVIPSERVICESK9-M), Version  
12.4(22)T2, RELEASE SOFTWARE (fc4)
```

```
Technical Support: http://www.cisco.com/techsupport
```

```
Copyright (c) 1986-2009 by Cisco Systems, Inc.
```

```
Compiled Fri 19-Jun-09 15:34 by prod_rel_team
```

```
advertisement version: 2
```

```
VTP Management Domain: ''
```

```
-----
```

```
Device ID: R5
```

```
Entry address(es):
```

```
  IP address: 209.65.200.226
```

```
Platform: Cisco 2811, Capabilities: Router Switch IGMP
```

```
Interface: Serial0/3/0, Port ID (outgoing port): Serial0/3/0
```

```
Holdtime : 161 sec
```

```
Version :
```

```
Cisco IOS Software, 2800 Software (C2800NM-ADVIPSERVICESK9-M), Version  
12.4(22)T2, RELEASE SOFTWARE (fc4)
```

```
Technical Support: http://www.cisco.com/techsupport
```

```
Copyright (c) 1986-2009 by Cisco Systems, Inc.
```

```
Compiled Fri 19-Jun-09 15:34 by prod_rel_team
```

```
advertisement version: 2
```

```
VTP Management Domain: ''
```

```
R1#
```

```
R1#show frame-relay map
Serial0/2/0.12 (up): point-to-point dlci, dlci 102(0x66,0x1860),
broadcast
                status defined, active
R1#
```

```
R1#show ip interface
FastEthernet0/0 is administratively down, line protocol is down
  Internet protocol processing disabled
FastEthernet0/1 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/0/0 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/0/1 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/1/0 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/2/0 is up, line protocol is up
  Internet protocol processing disabled
Serial0/2/0.12 is up, line protocol is up
  Internet address is 10.1.1.1/30
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is not set
```

```
Directed broadcast forwarding is disabled
Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
    224.0.0.5
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP fast switching on the same interface is enabled
IP Flow switching is disabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is enabled, interface in domain inside
BGP Policy Mapping is disabled
Input features: Stateful Inspection, Virtual Fragment Reassembly,
Virtual Fragment Reassembly After IPsec Decryption, MCI Check
Output features: NAT Inside, Stateful Inspection
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
Serial0/3/0 is up, line protocol is up
Internet address is 209.65.200.225/30
Broadcast address is 255.255.255.255
Address determined by non-volatile memory
MTU is 1500 bytes
Helper address is not set
Directed broadcast forwarding is disabled
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP fast switching on the same interface is enabled
IP Flow switching is disabled
```


IP CEF switching is enabled
IP CEF switching turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is enabled, interface in domain outside
BGP Policy Mapping is disabled
Input features: Stateful Inspection, Virtual Fragment Reassembly,
Virtual Fragment Reassembly After IPsec Decryption, NAT Outside, MCI
Check
Output features: CCE Output Classification, Post-routing NAT Outside,
Stateful Inspection
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
NVIO is up, line protocol is up
Interface is unnumbered. Using address of Serial0/2/0.12 (10.1.1.1)
Broadcast address is 255.255.255.255
MTU is 1514 bytes
Helper address is not set
Directed broadcast forwarding is disabled
Multicast reserved groups joined: 224.0.0.5
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is disabled
IP fast switching on the same interface is disabled
IP Flow switching is disabled
IP CEF switching is disabled
IP Null turbo vector
IP Null turbo vector
IP multicast fast switching is disabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled

```
Input features: MCI Check
Output features: Post-routing NAT NVI Output
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
R1#
```

```
R1#show ip cef
Prefix          Next Hop          Interface
0.0.0.0/0      no route
0.0.0.0/8      drop
0.0.0.0/32     receive
```

10.1.1.0/30	attached	Serial0/2/0.12
10.1.1.0/32	receive	Serial0/2/0.12
10.1.1.1/32	receive	Serial0/2/0.12
10.1.1.3/32	receive	Serial0/2/0.12
10.1.1.4/30	10.1.1.2	Serial0/2/0.12
10.1.1.8/30	10.1.1.2	Serial0/2/0.12
10.1.4.4/30	10.1.1.2	Serial0/2/0.12
10.1.4.8/30	10.1.1.2	Serial0/2/0.12
10.2.1.0/24	10.1.1.2	Serial0/2/0.12
10.2.2.0/24	10.1.1.2	Serial0/2/0.12
10.2.4.12/30	10.1.1.2	Serial0/2/0.12
127.0.0.0/8	drop	
209.65.200.224/30	attached	Serial0/3/0
209.65.200.224/32	receive	Serial0/3/0
209.65.200.225/32	receive	Serial0/3/0
209.65.200.227/32	receive	Serial0/3/0
209.65.200.240/29	209.65.200.226	Serial0/3/0
224.0.0.0/4	multicast	
224.0.0.0/24	receive	
240.0.0.0/4	drop	
255.255.255.255/32	receive	

R1#

R1#show tcp statistics

Rcvd: 190 Total, 0 no port

0 checksum error, 0 bad offset, 0 too short

94 packets (1846 bytes) in sequence

0 dup packets (0 bytes)

0 partially dup packets (0 bytes)

0 out-of-order packets (0 bytes)

0 packets (0 bytes) with data after window

0 packets after close

0 window probe packets, 0 window update packets

0 dup ack packets, 0 ack packets with unsend data

94 ack packets (1794 bytes)

Sent: 186 Total, 0 urgent packets

1 control packets (including 0 retransmitted)

93 data packets (1793 bytes)

0 data packets (0 bytes) retransmitted

0 data packets (0 bytes) fastretransmitted

92 ack only packets (91 delayed)

0 window probe packets, 0 window update packets

0 Connections initiated, 1 connections accepted, 1 connections established

0 Connections closed (including 0 dropped, 0 embryonic dropped)

0 Total rxmt timeout, 0 connections dropped in rxmt timeout

0 Keepalive timeout, 0 keepalive probe, 0 Connections dropped in keepalive

R1#

```
R1#show ip protocols
Routing Protocol is "ospf 1"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  Router ID 10.1.1.1
  It is an autonomous system boundary router
  Redistributing External Routes from,
    connected, includes subnets in redistribution
    static, includes subnets in redistribution
    bgp 65001, includes subnets in redistribution
  Number of areas in this router is 1. 1 normal 0 stub 0 nssa
  Maximum path: 4
  Routing for Networks:
    10.1.1.1 0.0.0.0 area 12
Reference bandwidth unit is 100 mbps
Routing Information Sources:
  Gateway         Distance      Last Update
  3.3.3.3          110           01:31:14
  2.2.2.2          110           01:31:14
Distance: (default is 110)
```

```
Routing Protocol is "bgp 65001"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  IGP synchronization is disabled
  Automatic route summarization is disabled
Neighbor(s):
  Address          FiltIn FiltOut DistIn DistOut Weight RouteMap
```

```
209.65.200.226
Maximum path: 1
Routing Information Sources:
  Gateway          Distance      Last Update
  209.65.200.226    20           01:30:58
Distance: external 20 internal 200 local 200
```

R1#

```
R1#show access-lists
Standard IP access list 10
 10 permit 10.0.0.0, wildcard bits 0.255.255.255 (59 matches)
```

```
Standard IP access list DENY_10
  10 deny 10.0.0.0, wildcard bits 0.255.255.255
  20 permit any
Standard IP access list DENY_ALL
  10 deny any
Standard IP access list PERMIT_10
  10 permit 10.0.0.0, wildcard bits 0.255.255.255
Standard IP access list PERMIT_ALL
  10 permit any
R1#
```

```
R1#show ip ospf neighbor
```

Neighbor ID	Pri	State	Dead Time	Address
Interface 2.2.2.2	0	FULL/ -	00:00:38	10.1.1.2

Serial0/2/0.12
R1#

```
R1#show ip ospf interface
NVI0 is up, line protocol is up
  Interface is unnumbered. Using address of Serial0/2/0.12 (10.1.1.1),
  Area 12
```


Process ID 1, Router ID 10.1.1.1, Network Type POINT_TO_POINT, Cost:
1785

Transmit Delay is 1 sec, State POINT_TO_POINT
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
oob-resync timeout 40

Hello due in 00:00:09

Supports Link-local Signaling (LLS)

Cisco NSF helper support enabled

IETF NSF helper support enabled

Index 2/2, flood queue length 0

Next 0x0(0)/0x0(0)

Last flood scan length is 0, maximum is 0

Last flood scan time is 0 msec, maximum is 0 msec

Neighbor Count is 0, Adjacent neighbor count is 0

Suppress hello for 0 neighbor(s)

Serial0/2/0.12 is up, line protocol is up

Internet Address 10.1.1.1/30, Area 12

Process ID 1, Router ID 10.1.1.1, Network Type POINT_TO_POINT, Cost: 64

Transmit Delay is 1 sec, State POINT_TO_POINT

Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
oob-resync timeout 40

Hello due in 00:00:08

Supports Link-local Signaling (LLS)

Cisco NSF helper support enabled

IETF NSF helper support enabled

Index 1/1, flood queue length 0

Next 0x0(0)/0x0(0)

Last flood scan length is 1, maximum is 1

Last flood scan time is 0 msec, maximum is 4 msec

Neighbor Count is 1, Adjacent neighbor count is 1

Adjacent with neighbor 2.2.2.2

Suppress hello for 0 neighbor(s)

R1#

R1#show ip ospf database

OSPF Router with ID (10.1.1.1) (Process ID 1)

Router Link States (Area 12)

Link ID count	ADV Router	Age	Seq#	Checksum	Link
2.2.2.2	2.2.2.2	1490	0x80000008	0x004127	2
10.1.1.1	10.1.1.1	1449	0x80000004	0x00A6C0	2

Summary Net Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
10.1.1.4	2.2.2.2	1490	0x80000003	0x00F7ED
10.1.1.8	2.2.2.2	1490	0x80000003	0x00524F

Summary ASB Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
3.3.3.3	2.2.2.2	1490	0x80000003	0x0033B2

Type-5 AS External Link States

Link ID	ADV Router	Age	Seq#	Checksum	Tag
10.1.4.4	3.3.3.3	1532	0x80000003	0x00A8C3	0
10.1.4.8	3.3.3.3	1532	0x80000003	0x0080E7	0
10.2.1.0	3.3.3.3	1532	0x80000003	0x00F777	0
10.2.2.0	3.3.3.3	1533	0x80000003	0x00EC81	0
10.2.4.12	3.3.3.3	1533	0x80000003	0x004C17	0
209.65.200.224	10.1.1.1	1712	0x80000003	0x004295	0
209.65.200.240	10.1.1.1	1450	0x80000003	0x002DC8	65002

R1#

R1#show ip route ospf

```
10.0.0.0/8 is variably subnetted, 8 subnets, 2 masks
O E2    10.2.4.12/30 [110/20] via 10.1.1.2, 01:31:53, Serial0/2/0.12
O IA    10.1.1.8/30 [110/192] via 10.1.1.2, 01:31:53, Serial0/2/0.12
O E2    10.1.4.8/30 [110/20] via 10.1.1.2, 01:31:53, Serial0/2/0.12
O E2    10.2.1.0/24 [110/20] via 10.1.1.2, 01:31:53, Serial0/2/0.12
O E2    10.2.2.0/24 [110/20] via 10.1.1.2, 01:31:53, Serial0/2/0.12
O E2    10.1.4.4/30 [110/20] via 10.1.1.2, 01:31:53, Serial0/2/0.12
O IA    10.1.1.4/30 [110/128] via 10.1.1.2, 01:31:53, Serial0/2/0.12
R1#
```

```
R1#show ip bgp neighbors
BGP neighbor is 209.65.200.226, remote AS 65002, external link
  BGP version 4, remote router ID 5.5.5.5
  BGP state = Established, up for 01:32:36
  Last read 00:00:08, last write 00:00:09, hold time is 180, keepalive
  interval is 60 seconds
  Neighbor capabilities:
    Route refresh: advertised and received(new)
    Address family IPv4 Unicast: advertised and received
  Message statistics:
    InQ depth is 0
```

OutQ depth is 0

	Sent	Rcvd
Opens:	1	1
Notifications:	0	0
Updates:	0	1
Keepalives:	93	93
Route Refresh:	0	0
Total:	94	95

Default minimum time between advertisement runs is 30 seconds

For address family: IPv4 Unicast
BGP table version 2, neighbor version 2/0
Output queue size : 0
Index 1, Offset 0, Mask 0x2
1 update-group member

	Sent	Rcvd
Prefix activity:	----	----
Prefixes Current:	0	1 (Consumes 52 bytes)
Prefixes Total:	0	1
Implicit Withdraw:	0	0
Explicit Withdraw:	0	0
Used as bestpath:	n/a	1
Used as multipath:	n/a	0

	Outbound	Inbound
Local Policy Denied Prefixes:	-----	-----
Bestpath from this peer:	1	n/a
Total:	1	0

Number of NLRIs in the update sent: max 0, min 0

Address tracking is enabled, the RIB does have a route to 209.65.200.226

Connections established 1; dropped 0

Last reset never

Transport(tcp) path-mtu-discovery is enabled

Connection state is ESTAB, I/O status: 1, unread input bytes: 0

Connection is ECN Disabled, Minimum incoming TTL 0, Outgoing TTL 1

Local host: 209.65.200.225, Local port: 179

Foreign host: 209.65.200.226, Foreign port: 60823

Connection tableid (VRF): 0

Enqueued packets for retransmit: 0, input: 0 mis-ordered: 0 (0 bytes)

Event Timers (current time is 0x559C44):

Timer	Starts	Wakeups	Next
Retrans	95	0	0x0
TimeWait	0	0	0x0
AckHold	94	92	0x0
SendWnd	0	0	0x0
KeepAlive	0	0	0x0
GiveUp	0	0	0x0
PmtuAger	0	0	0x0
DeadWait	0	0	0x0

Linger 0 0 0x0
ProcessQ 0 0 0x0

iss: 2346902628 snduna: 2346904441 sndnxt: 2346904441 sndwnd:
16042
irs: 534252401 rcvnxt: 534254267 rcvwnd: 15985 delrcwnd:
399

SRTT: 300 ms, RTTO: 303 ms, RTV: 3 ms, KRTT: 0 ms
minRTT: 20 ms, maxRTT: 364 ms, ACK hold: 200 ms
Status Flags: passive open, gen tcbs
Option Flags: nagle, path mtu capable
IP Precedence value : 6

Datagrams (max data segment is 1460 bytes):
Rcvd: 190 (out of order: 0), with data: 95, total data bytes: 1865
Sent: 188 (retransmit: 0, fastretransmit: 0, partialack: 0, Second
Congestion: 0), with data: 94, total data bytes: 1812
Packets received in fast path: 0, fast processed: 0, slow path: 0
fast lock acquisition failures: 0, slow path: 0

R1#

```
R1#show ip bgp summary
BGP router identifier 1.1.1.1, local AS number 65001
BGP table version is 2, main routing table version 2
1 network entries using 132 bytes of memory
1 path entries using 52 bytes of memory
2/1 BGP path/bestpath attribute entries using 296 bytes of memory
1 BGP AS-PATH entries using 24 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 504 total bytes of memory
BGP activity 1/0 prefixes, 1/0 paths, scan interval 60 secs

Neighbor      V    AS MsgRcvd MsgSent   TblVer  InQ  OutQ  Up/Down
State/PfxRcd
209.65.200.226 4 65002     95     94       2    0    0 01:32:45
1
R1#
```

```
R1#show ip bgp
BGP table version is 2, local router ID is 1.1.1.1
Status codes: s suppressed, d damped, h history, * valid, > best, i -
internal,
                r RIB-failure, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

   Network          Next Hop           Metric LocPrf Weight Path
*> 209.65.200.240/29
                        209.65.200.226           0              0 65002 i
R1#
```



```
R1#show ip route bgp
    209.65.200.0/24 is variably subnetted, 2 subnets, 2 masks
B       209.65.200.240/29 [20/0] via 209.65.200.226, 01:32:07
R1#
```

```
R1#show ip nat translations
```

```
R1#
```

```
R1#show ip nat statistics
Total active translations: 0 (0 static, 0 dynamic; 0 extended)
Peak translations: 2, occurred 01:11:34 ago
Outside interfaces:
  Serial0/3/0
Inside interfaces:
  Serial0/2/0.12
Hits: 117 Misses: 0
CEF Translated packets: 116, CEF Punted packets: 1
Expired translations: 13
Dynamic mappings:
-- Inside Source
  [Id: 1] access-list 10 interface Serial0/3/0 refcount 0
Appl doors: 0
Normal doors: 0
Queued Packets: 0
R1#
```