

```
R1#
R1#
R1#show running-config
Building configuration...
```

```
Current configuration : 2616 bytes
!
! No configuration change since last restart
!
version 12.4
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname R1
!
boot-start-marker
boot-end-marker
!
logging message-counter syslog
no logging console
enable secret 5 $1$aKZT$R06SAsRilNacGlsvRsdUg0
!
no aaa new-model
!
dot11 syslog
ip source-route
!
!
ip cef
!
!
ip multicast-routing
ipv6 unicast-routing
ipv6 cef
!
multilink bundle-name authenticated
!
!
!
!
!
!
!
!
!
!
!
!
!
!
!
!
```

```
!  
!  
!  
!  
!  
!  
voice-card 0  
!  
!  
!  
!  
!  
archive  
  log config  
  hidekeys  
!  
!  
!  
!  
!  
!  
!  
!  
!  
interface FastEthernet0/0  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface FastEthernet0/1  
  no ip address  
  shutdown  
  duplex auto  
  speed auto  
!  
interface Serial0/0/0  
  no ip address  
  shutdown  
  no fair-queue  
  clock rate 2000000  
!  
interface Serial0/0/1  
  no ip address  
  shutdown  
!  
interface Serial0/1/0  
  no ip address  
  shutdown  
  clock rate 2000000  
!  
interface Serial0/2/0  
  no ip address  
  encapsulation frame-relay
```

```
!  
interface Serial0/2/0.12 point-to-point  
 ip address 10.1.1.1 255.255.255.252  
 ip pim sparse-dense-mode  
 ip nat inside  
 ip virtual-reassembly  
 snmp trap link-status  
 ipv6 address 2026::12:1/122  
 ipv6 enable  
 ipv6 ospf 6 area 12  
 frame-relay interface-dlci 102  
!  
interface Serial0/3/0  
 ip address 209.65.200.225 255.255.255.252  
 ip nat outside  
 ip virtual-reassembly  
 clock rate 56000  
!  
router ospf 1  
 router-id 10.1.1.1  
 log-adjacency-changes  
 redistribute connected subnets  
 redistribute static subnets  
 redistribute bgp 65001 subnets  
 network 10.1.1.1 0.0.0.0 area 12  
!  
router bgp 65001  
 no synchronization  
 bgp router-id 1.1.1.1  
 bgp log-neighbor-changes  
 neighbor 209.65.200.226 remote-as 65002  
 no auto-summary  
!  
ip forward-protocol nd  
ip http server  
no ip http secure-server  
!  
!  
ip nat inside source list 10 interface Serial0/3/0 overload  
!  
ip access-list standard DENY_10  
 deny 10.0.0.0 0.255.255.255  
 permit any  
ip access-list standard DENY_ALL  
 deny any  
ip access-list standard PERMIT_10  
 permit 10.0.0.0 0.255.255.255  
ip access-list standard PERMIT_ALL  
 permit any  
!  
access-list 10 permit 10.0.0.0 0.255.255.255  
ipv6 router ospf 6  
 router-id 1.1.1.1  
 log-adjacency-changes
```

```
!  
!  
!  
!  
!  
!  
!  
!  
control-plane  
!  
!  
!  
ccm-manager fax protocol cisco  
!  
mgcp fax t38 ecm  
mgcp behavior g729-variants static-pt  
!  
!  
!  
!  
!  
line con 0  
  exec-timeout 0 0  
  logging synchronous  
line aux 0  
line vty 0 4  
  password cisco  
  login  
!  
scheduler allocate 20000 1000  
ntp master 5  
ntp peer 10.1.1.2  
ntp peer 10.1.4.6  
ntp peer 10.1.1.6  
ntp peer 10.1.4.10  
ntp peer 10.1.1.10  
ntp peer 10.2.4.13  
ntp peer 10.2.4.14  
end
```

R1#

```
R1#ping 209.65.200.241
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.241, timeout is 2 seconds:  
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 32/33/36 ms
```

```
R1#
```

```
R1#ping 209.65.200.226
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.226, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 32/32/36 ms
```

```
R1#
```

```
R1#ping 209.65.200.225
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.225, timeout is 2 seconds:  
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/65/68 ms  
R1#
```

```
R1#ping 10.1.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132  
ms
```

```
R1#
```



```
R1#ping 10.1.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/65/68 ms
```

```
R1#
```

```
R1#ping 10.1.1.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.5, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/65/68 ms
```

```
R1#
```

```
R1#ping 10.1.1.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.6, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132
```

```
ms
```

```
R1#
```

```
R1#ping 10.1.1.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.9, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/129/132
```

```
ms
```

```
R1#
```

```
R1#ping 10.1.1.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.10, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196  
ms
```

```
R1#
```

```
R1#ping 10.1.4.10
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 10.1.4.10, timeout is 2 seconds:  
!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/196/204  
ms  
R1#
```

```
R1#ping 10.1.4.9
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 10.1.4.9, timeout is 2 seconds:
```

```
!!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196  
ms  
R1#
```

```
R1#ping 10.1.4.6
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 10.1.4.6, timeout is 2 seconds:  
!!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196  
ms
```

R1#

R1#ping 10.1.4.5

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 10.1.4.5, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196
ms

R1#


```
R1#ping 10.2.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.1, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R1#
```

```
R1#ping 10.2.2.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/196/204  
ms
```

```
R1#
```

```
R1#ping 10.2.1.254
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.254, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R1#
```

```
R1#ping 10.2.4.14
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.14, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196  
ms
```

```
R1#
```

```
R1#ping 10.2.4.13
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.13, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196  
ms
```

```
R1#
```

```
R1#ping 10.2.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.2, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R1#
```

```
R1#ping 10.2.2.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/192/196  
ms
```

```
R1#
```

```
R1#ping 10.2.1.4
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.4, timeout is 2 seconds:
```

```
.....
```

```
Success rate is 0 percent (0/5)
```

```
R1#
```



```
R1#show ip interface brief
```

Interface	IP-Address	OK?	Method	Status
FastEthernet0/0	unassigned	YES	NVRAM	administratively
down down				
FastEthernet0/1	unassigned	YES	NVRAM	administratively
down down				
Serial0/0/0	unassigned	YES	NVRAM	administratively
down down				
Serial0/0/1	unassigned	YES	NVRAM	administratively
down down				
Serial0/1/0	unassigned	YES	NVRAM	administratively
down down				
Serial0/2/0	unassigned	YES	NVRAM	up
up				
Serial0/2/0.12	10.1.1.1	YES	NVRAM	up
up				
Serial0/3/0	209.65.200.225	YES	NVRAM	up
up				
NV10	unassigned	YES	unset	administratively
down down				

```
R1#
```

```
R1#show ip route
```

```
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2  
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS  
level-2  
ia - IS-IS inter area, * - candidate default, U - per-user static  
route  
o - ODR, P - periodic downloaded static route
```

```
Gateway of last resort is not set
```

```
209.65.200.0/24 is variably subnetted, 2 subnets, 2 masks  
B 209.65.200.240/29 [20/0] via 209.65.200.226, 00:56:25  
C 209.65.200.224/30 is directly connected, Serial0/3/0  
10.0.0.0/8 is variably subnetted, 7 subnets, 2 masks  
O E2 10.2.4.12/30 [110/20] via 10.1.1.2, 00:44:37, Serial0/2/0.12  
O IA 10.1.1.8/30 [110/192] via 10.1.1.2, 00:44:53, Serial0/2/0.12  
O E2 10.1.4.8/30 [110/20] via 10.1.1.2, 00:44:37, Serial0/2/0.12  
O E2 10.2.2.0/24 [110/20] via 10.1.1.2, 00:44:37, Serial0/2/0.12  
C 10.1.1.0/30 is directly connected, Serial0/2/0.12  
O E2 10.1.4.4/30 [110/20] via 10.1.1.2, 00:44:38, Serial0/2/0.12  
O IA 10.1.1.4/30 [110/128] via 10.1.1.2, 00:54:43, Serial0/2/0.12  
R1#
```

R1#show processes cpu

CPU utilization for five seconds: 1%/0%; one minute: 2%; five minutes: 2%

PID	Runtime (ms)	Invoked	uSecs	5Sec	1Min	5Min	TTY	Process
1	20	81	246	0.00%	0.00%	0.00%	0	Chunk
Manager								
2	0	692	0	0.07%	0.04%	0.05%	0	Load Meter
3	1148	627	1830	0.00%	0.18%	0.18%	0	Exec
4	0	1	0	0.00%	0.00%	0.00%	0	EDDRI_MAIN
5	4720	410	11512	0.00%	0.15%	0.12%	0	Check
heaps								
6	0	1	0	0.00%	0.00%	0.00%	0	Pool
Manager								
7	0	2	0	0.00%	0.00%	0.00%	0	Timers
8	0	1	0	0.00%	0.00%	0.00%	0	License
Client N								

38	28	1418	19	0.00%	0.00%	0.00%	0 Net
Background							
39	0	2	0	0.00%	0.00%	0.00%	0 IDB Work
40	0	23	0	0.00%	0.00%	0.00%	0 Logger
41	0	3451	0	0.00%	0.00%	0.00%	0 TTY
Background							
42	4	3471	1	0.00%	0.01%	0.00%	0 Per-Second
Jobs							
43	0	232	0	0.00%	0.00%	0.00%	0 c2800
Periodic							
44	0	1	0	0.00%	0.00%	0.00%	0 Inode
Table Dest							
45	0	1	0	0.00%	0.00%	0.00%	0 IKE HA Mgr
46	0	1	0	0.00%	0.00%	0.00%	0 IPSEC HA
Mgr							
47	4	4	1000	0.00%	0.00%	0.00%	0 rf task
48	40	352	113	0.07%	0.00%	0.00%	0 Net Input
49	0	693	0	0.00%	0.00%	0.00%	0 Compute
load avg							
50	1392	59	23593	0.00%	0.05%	0.00%	0 Per-minute
Jobs							
51	0	1	0	0.00%	0.00%	0.00%	0 AggMgr
Process							
52	4	1	4000	0.00%	0.00%	0.00%	0 Token
Daemon							
53	0	1	0	0.00%	0.00%	0.00%	0 Transport
Port A							
54	0	1	0	0.00%	0.00%	0.00%	0
dev_device_inser							
55	0	1	0	0.00%	0.00%	0.00%	0
dev_device_remov							
56	0	1	0	0.00%	0.00%	0.00%	0
sal_dpc_process							
57	0	1	0	0.00%	0.00%	0.00%	0 ARL Table
Manage							
58	0	2	0	0.00%	0.00%	0.00%	0 ESWPPM
59	0	2	0	0.00%	0.00%	0.00%	0 Eswilp
Storm Con							
60	0	2	0	0.00%	0.00%	0.00%	0 ESWILPPM
61	0	2	0	0.00%	0.00%	0.00%	0 Eswilp
Storm Con							
62	0	13828	0	0.00%	0.00%	0.00%	0 Netclock
Backgro							
63	0	2	0	0.00%	0.00%	0.00%	0 SM Monitor
64	0	2	0	0.00%	0.00%	0.00%	0 Bryce I2C
CMD Qu							
65	276	4	69000	0.00%	0.00%	0.00%	0 USB
Startup							
66	0	579	0	0.00%	0.00%	0.00%	0 mxt5100
67	4	2	2000	0.00%	0.00%	0.00%	0 VNM DSPRM
MAIN							
68	0	1	0	0.00%	0.00%	0.00%	0 DSPFARM
DSP READ							

187	704	232	3034	0.00%	0.01%	0.00%	0	BGP
Scanner								
188	0	6772	0	0.00%	0.00%	0.00%	0	FW DP
Inspect pr								
189	0	6772	0	0.00%	0.00%	0.00%	0	CCE DP
URLF cach								
190	0	2	0	0.00%	0.00%	0.00%	0	URL filter
proc								
191	0	1	0	0.00%	0.00%	0.00%	0	Select
Timers								
192	32	2	16000	0.00%	0.00%	0.00%	0	HTTP
Process								
193	0	2	0	0.00%	0.00%	0.00%	0	CIFS API
Process								
194	0	2	0	0.00%	0.00%	0.00%	0	CIFS Proxy
Proce								
195	4	3	1333	0.00%	0.00%	0.00%	0	Crypto HW
Proc								
196	0	141	0	0.00%	0.00%	0.00%	0	
CRM_CALL_UPDATE_								
197	116	2	58000	0.00%	0.00%	0.00%	0	
CCVPM_HDSPRM								
198	0	4	0	0.00%	0.00%	0.00%	0	HDA DSPRM
MAIN								
199	4	2	2000	0.00%	0.00%	0.00%	0	STUN_APP
200	0	1	0	0.00%	0.00%	0.00%	0	STUN_TEST
201	0	1	0	0.00%	0.00%	0.00%	0	BGP Event
202	0	2	0	0.00%	0.00%	0.00%	0	AAA Cached
Serve								
203	0	2	0	0.00%	0.00%	0.00%	0	ENABLE AAA
204	0	1	0	0.00%	0.00%	0.00%	0	EM
Background Pr								
205	0	1	0	0.00%	0.00%	0.00%	0	Key chain
liveke								
206	0	2	0	0.00%	0.00%	0.00%	0	LINE AAA
207	0	2	0	0.00%	0.00%	0.00%	0	LOCAL AAA
208	0	4	0	0.00%	0.00%	0.00%	0	MPLS Auto
Mesh P								
209	8	2	4000	0.00%	0.00%	0.00%	0	TPLUS
210	0	2	0	0.00%	0.00%	0.00%	0	VSP_MGR
211	0	1	0	0.00%	0.00%	0.00%	0	
FW_TEST_TRP								
212	0	1	0	0.00%	0.00%	0.00%	0	EPM MAIN
PROCESS								
213	0	3	0	0.00%	0.00%	0.00%	0	Crypto WUI
214	0	2	0	0.00%	0.00%	0.00%	0	Crypto
Support								
215	0	1	0	0.00%	0.00%	0.00%	0	IPSECv6 PS
Proc								
216	0	1	0	0.00%	0.00%	0.00%	0	CCVPM_HTSP
217	0	2	0	0.00%	0.00%	0.00%	0	
VPM_MWI_BACKGROU								
218	0	1	0	0.00%	0.00%	0.00%	0	CCVPM_R2

249	0	1	0	0.00%	0.00%	0.00%	0 UNICAST
REKEY							
250	0	1	0	0.00%	0.00%	0.00%	0 UNICAST
REKEY AC							
251	0	3489	0	0.00%	0.00%	0.00%	0 Crypto
Device Up							
252	0	2	0	0.00%	0.00%	0.00%	0 Multi-ISA
Event							
253	0	1	0	0.00%	0.00%	0.00%	0 Multi-ISA
Cleanu							
254	0	1	0	0.00%	0.00%	0.00%	0 PM
Callback							
255	0	1	0	0.00%	0.00%	0.00%	0 Licensing
MIB pr							
256	4	17437	0	0.00%	0.01%	0.00%	0 Atheros
LED Ctro							
257	0	2	0	0.00%	0.00%	0.00%	0 Control-
plane ho							
258	0	1	0	0.00%	0.00%	0.00%	0 DATA
Transfer Pr							
259	0	1	0	0.00%	0.00%	0.00%	0 DATA
Collector							
260	0	2	0	0.00%	0.00%	0.00%	0 AAA SEND
STOP EV							
261	4	2	2000	0.00%	0.00%	0.00%	0 EEM ED
Resource							
262	0	2	0	0.00%	0.00%	0.00%	0 EEM ED
Routing							
263	0	3	0	0.00%	0.00%	0.00%	0 EEM ED
Track							
264	0	349	0	0.00%	0.00%	0.00%	0 RMON
Recycle Pro							
265	0	2	0	0.00%	0.00%	0.00%	0 RMON
Deferred Se							
266	0	1	0	0.00%	0.00%	0.00%	0 Syslog
Traps							
267	0	110	0	0.00%	0.00%	0.00%	0 Crypto
cTCP proc							
268	8	2	4000	0.00%	0.00%	0.00%	0 VLAN
Manager							
269	48	741	64	0.00%	0.00%	0.00%	0 OSPFv3-6
Hello							
270	0	1	0	0.00%	0.00%	0.00%	0 chkpt
message ha							
271	0	3472	0	0.07%	0.00%	0.00%	0 trunk
conditioni							
272	0	1	0	0.00%	0.00%	0.00%	0 trunk
conditioni							
273	0	3492	0	0.00%	0.00%	0.00%	0 CME
Extension Mo							
274	0	1	0	0.00%	0.00%	0.00%	0 IP SLAs
Ethernet							
275	4	220	18	0.00%	0.00%	0.00%	0 EEM Server

276	0	2	0	0.00%	0.00%	0.00%	0	EEM Policy
Direc								
277	0	3	0	0.00%	0.00%	0.00%	0	EEM ED CLI
278	4	3	1333	0.00%	0.00%	0.00%	0	EEM ED
Counter								
279	0	3	0	0.00%	0.00%	0.00%	0	EM ED GOLD
280	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
Interface								
281	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
IOSWD								
282	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
Ipsla								
283	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
None								
284	0	2	0	0.00%	0.00%	0.00%	0	EEM ED Nf
285	0	3	0	0.00%	0.00%	0.00%	0	EEM ED OIR
286	0	3	0	0.00%	0.00%	0.00%	0	EEM ED RF
287	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
SNMP								
288	0	2	0	0.00%	0.00%	0.00%	0	EEM ED
SNMP Noti								
289	0	90	0	0.00%	0.00%	0.00%	0	EEM ED
Timer								
290	4	3	1333	0.00%	0.00%	0.00%	0	EEM ED
Test								
291	0	3	0	0.00%	0.00%	0.00%	0	EEM ED
Config								
292	0	3	0	0.00%	0.00%	0.00%	0	EEM ED Env
293	4	13	307	0.00%	0.00%	0.00%	0	Syslog
294	0	1	0	0.00%	0.00%	0.00%	0	VPDN Test
295	4	3	1333	0.00%	0.00%	0.00%	0	EEM ED RPC
296	0	2	0	0.00%	0.00%	0.00%	0	Key Proc
297	0	1	0	0.00%	0.00%	0.00%	0	tHUB
299	0	20	0	0.00%	0.00%	0.00%	0	IPv6 RIB
Event H								
300	4	1745	2	0.00%	0.00%	0.00%	0	CEF: IPv6
proces								
301	548	685	800	0.00%	0.00%	0.00%	0	FR LMI
302	8	65	123	0.00%	0.00%	0.00%	0	FR PVC
event man								
303	4	34842	0	0.07%	0.03%	0.02%	0	FR
Broadcast Out								
304	0	61	0	0.00%	0.00%	0.00%	0	FR ARP
305	0	59	0	0.00%	0.00%	0.00%	0	FR
FRAGMENTATION								
306	0	175	0	0.00%	0.00%	0.00%	0	FR TUNNEL
307	0	1	0	0.00%	0.00%	0.00%	0	FRF9
manager								
308	0	1	0	0.00%	0.00%	0.00%	0	FRF9 timed
event								
309	4	349	11	0.00%	0.00%	0.00%	0	compute
load per								
310	0	3482	0	0.00%	0.00%	0.00%	0	IGMP Input


```
R1#show interfaces
FastEthernet0/0 is administratively down, line protocol is down
  Hardware is MV96340 Ethernet, address is 001d.70a0.c690 (bia
001d.70a0.c690)
  MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto Speed, 100BaseTX/FX
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes
    Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 0 interface resets
    0 unknown protocol drops
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/1 is administratively down, line protocol is down
  Hardware is MV96340 Ethernet, address is 001d.70a0.c691 (bia
001d.70a0.c691)
  MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
```

```
Keepalive set (10 sec)
Auto-duplex, Auto Speed, 100BaseTX/FX
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 0 interface resets
  0 unknown protocol drops
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier
  0 output buffer failures, 0 output buffers swapped out
Serial0/0/0 is administratively down, line protocol is down
  Hardware is GT96K Serial
  MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation HDLC, loopback not set
  Keepalive set (10 sec)
  CRC checking enabled
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 3 interface resets
    0 unknown protocol drops
    0 output buffer failures, 0 output buffers swapped out
    0 carrier transitions
    DCD=down DSR=down DTR=down RTS=down CTS=down

Serial0/0/1 is administratively down, line protocol is down
  Hardware is GT96K Serial
  MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation HDLC, loopback not set
  Keepalive set (10 sec)
  CRC checking enabled
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
```


Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/0/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 3 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=down DSR=down DTR=down RTS=down CTS=down

Serial0/1/0 is administratively down, line protocol is down
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input 00:58:26, output 00:58:25, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/1/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
5 packets input, 1026 bytes, 0 no buffer
Received 5 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
1 packets output, 24 bytes, 0 underruns
0 output errors, 0 collisions, 3 interface resets
3 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=down DSR=down DTR=up RTS=down CTS=down

Serial0/2/0 is up, line protocol is up
Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY, loopback not set
Keepalive set (10 sec)
CRC checking enabled
LMI enq sent 343, LMI stat recvd 342, LMI upd recvd 0, DTE LMI up
LMI enq recvd 0, LMI stat sent 0, LMI upd sent 0

```
LMI DLCI 1023 LMI type is CISCO frame relay DTE
FR SVC disabled, LAPF state down
Broadcast queue 0/64, broadcasts sent/dropped 936/0, interface
broadcasts 886
Last input 00:00:02, output 00:00:02, output hang never
Last clearing of "show interface" counters 00:58:24
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
  Conversations 0/1/256 (active/max active/max total)
  Reserved Conversations 0/0 (allocated/max allocated)
  Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  1933 packets input, 154444 bytes, 0 no buffer
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
  1889 packets output, 149266 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 unknown protocol drops
  0 output buffer failures, 0 output buffers swapped out
  39 carrier transitions
  DCD=up DSR=up DTR=up RTS=up CTS=up
```

```
Serial0/2/0.12 is up, line protocol is up
Hardware is GT96K Serial
Internet address is 10.1.1.1/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY
CRC checking enabled
Last clearing of "show interface" counters never
```

```
Serial0/3/0 is up, line protocol is up
Hardware is GT96K Serial
Internet address is 209.65.200.225/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
CRC checking enabled
Last input 00:00:04, output 00:00:09, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
  Conversations 0/1/256 (active/max active/max total)
  Reserved Conversations 0/0 (allocated/max allocated)
  Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  574 packets input, 39050 bytes, 0 no buffer
  Received 412 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
  729 packets output, 50662 bytes, 0 underruns
```

0 output errors, 0 collisions, 5 interface resets
3 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
5 carrier transitions
DCD=up DSR=up DTR=up RTS=up CTS=up

NV10 is administratively down, line protocol is down
Hardware is NV1
MTU 1514 bytes, BW 56 Kbit/sec, DLY 5000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation UNKNOWN, loopback not set
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 0 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out

R1#

```
R1#show cdp neighbors
```

```
Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge  
S - Switch, H - Host, I - IGMP, r - Repeater
```

Device ID	Local Intrfce	Holdtme	Capability	Platform	Port
R2	Ser 0/2/0.12	127	R S I	2811	Ser
0/2/0.12					
R5	Ser 0/3/0	155	R S I	2811	Ser
0/3/0					

```
R1#
```

R1#show cdp neighbors detail

Device ID: R2

Entry address(es):

IP address: 10.1.1.2

IPv6 address: 2026::12:2 (global unicast)

IPv6 address: FE80::216:9DFF:FEFA:CAB0 (link-local)

Platform: Cisco 2811, Capabilities: Router Switch IGMP

Interface: Serial0/2/0.12, Port ID (outgoing port): Serial0/2/0.12

Holdtime : 179 sec

Version :

Cisco IOS Software, 2800 Software (C2800NM-ADVIPSERVICESK9-M), Version 12.4(22)T2, RELEASE SOFTWARE (fc4)

Technical Support: <http://www.cisco.com/techsupport>

Copyright (c) 1986-2009 by Cisco Systems, Inc.

Compiled Fri 19-Jun-09 15:34 by prod_rel_team

advertisement version: 2

VTP Management Domain: ''

Device ID: R5

Entry address(es):

IP address: 209.65.200.226

Platform: Cisco 2811, Capabilities: Router Switch IGMP

Interface: Serial0/3/0, Port ID (outgoing port): Serial0/3/0

Holdtime : 148 sec

Version :

Cisco IOS Software, 2800 Software (C2800NM-ADVIPSERVICESK9-M), Version 12.4(22)T2, RELEASE SOFTWARE (fc4)

Technical Support: <http://www.cisco.com/techsupport>

Copyright (c) 1986-2009 by Cisco Systems, Inc.

Compiled Fri 19-Jun-09 15:34 by prod_rel_team

advertisement version: 2

VTP Management Domain: ''

R1#

```
R1#show frame-relay map
Serial0/2/0.12 (up): point-to-point dlci, dlci 102(0x66,0x1860),
broadcast
                status defined, active
R1#
```

```
R1#show ip interface
FastEthernet0/0 is administratively down, line protocol is down
  Internet protocol processing disabled
FastEthernet0/1 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/0/0 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/0/1 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/1/0 is administratively down, line protocol is down
  Internet protocol processing disabled
Serial0/2/0 is up, line protocol is up
  Internet protocol processing disabled
Serial0/2/0.12 is up, line protocol is up
  Internet address is 10.1.1.1/30
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
```

```
Helper address is not set
Directed broadcast forwarding is disabled
Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
    224.0.0.5
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP fast switching on the same interface is enabled
IP Flow switching is disabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is enabled, interface in domain inside
BGP Policy Mapping is disabled
Input features: Stateful Inspection, Virtual Fragment Reassembly,
Virtual Fragment Reassembly After IPsec Decryption, MCI Check
Output features: NAT Inside, Stateful Inspection
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
Serial0/3/0 is up, line protocol is up
Internet address is 209.65.200.225/30
Broadcast address is 255.255.255.255
Address determined by non-volatile memory
MTU is 1500 bytes
Helper address is not set
Directed broadcast forwarding is disabled
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP fast switching on the same interface is enabled
```



```
IP Flow switching is disabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is enabled, interface in domain outside
BGP Policy Mapping is disabled
  Input features: Stateful Inspection, Virtual Fragment Reassembly,
Virtual Fragment Reassembly After IPsec Decryption, NAT Outside, MCI
Check
  Output features: CCE Output Classification, Post-routing NAT Outside,
Stateful Inspection
  WCCP Redirect outbound is disabled
  WCCP Redirect inbound is disabled
  WCCP Redirect exclude is disabled
NVIO is administratively down, line protocol is down
  Internet protocol processing disabled
R1#
```

```

R1#show ip cef
Prefix                Next Hop                Interface
0.0.0.0/0             no route
0.0.0.0/8             drop
0.0.0.0/32            receive
10.1.1.0/30           attached                Serial0/2/0.12
10.1.1.0/32           receive                Serial0/2/0.12
10.1.1.1/32           receive                Serial0/2/0.12
10.1.1.3/32           receive                Serial0/2/0.12
10.1.1.4/30           10.1.1.2               Serial0/2/0.12
10.1.1.8/30           10.1.1.2               Serial0/2/0.12
10.1.4.4/30           10.1.1.2               Serial0/2/0.12
10.1.4.8/30           10.1.1.2               Serial0/2/0.12
10.2.2.0/24           10.1.1.2               Serial0/2/0.12
10.2.4.12/30          10.1.1.2               Serial0/2/0.12
127.0.0.0/8           drop
209.65.200.224/30     attached                Serial0/3/0
209.65.200.224/32     receive                Serial0/3/0
209.65.200.225/32     receive                Serial0/3/0
209.65.200.227/32     receive                Serial0/3/0
209.65.200.240/29     209.65.200.226         Serial0/3/0
224.0.0.0/4           multicast
224.0.0.0/24          receive
240.0.0.0/4           drop
255.255.255.255/32    receive
R1#

```

R1#show tcp statistics

Rcvd: 124 Total, 0 no port

0 checksum error, 0 bad offset, 0 too short

61 packets (1219 bytes) in sequence

0 dup packets (0 bytes)

0 partially dup packets (0 bytes)

0 out-of-order packets (0 bytes)

0 packets (0 bytes) with data after window

0 packets after close

0 window probe packets, 0 window update packets

0 dup ack packets, 0 ack packets with unsend data

61 ack packets (1167 bytes)

Sent: 121 Total, 0 urgent packets

1 control packets (including 0 retransmitted)

60 data packets (1166 bytes)

0 data packets (0 bytes) retransmitted

0 data packets (0 bytes) fastretransmitted

60 ack only packets (60 delayed)

0 window probe packets, 0 window update packets

0 Connections initiated, 1 connections accepted, 1 connections established

0 Connections closed (including 0 dropped, 0 embryonic dropped)

0 Total rxmt timeout, 0 connections dropped in rxmt timeout

0 Keepalive timeout, 0 keepalive probe, 0 Connections dropped in keepalive

R1#

```
R1#show ip protocols
Routing Protocol is "ospf 1"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  Router ID 10.1.1.1
  It is an autonomous system boundary router
  Redistributing External Routes from,
    connected, includes subnets in redistribution
    static, includes subnets in redistribution
    bgp 65001, includes subnets in redistribution
```

Number of areas in this router is 1. 1 normal 0 stub 0 nssa

Maximum path: 4

Routing for Networks:

10.1.1.1 0.0.0.0 area 12

Reference bandwidth unit is 100 mbps

Routing Information Sources:

Gateway	Distance	Last Update
3.3.3.3	110	00:46:21
2.2.2.2	110	00:46:36

Distance: (default is 110)

Routing Protocol is "bgp 65001"

Outgoing update filter list for all interfaces is not set

Incoming update filter list for all interfaces is not set

IGP synchronization is disabled

Automatic route summarization is disabled

Neighbor(s):

Address	FiltIn	FiltOut	DistIn	DistOut	Weight	RouteMap
209.65.200.226						

Maximum path: 1

Routing Information Sources:

Gateway	Distance	Last Update
209.65.200.226	20	00:58:10

Distance: external 20 internal 200 local 200

R1#

```
R1#show access-lists
Standard IP access list 10
  10 permit 10.0.0.0, wildcard bits 0.255.255.255 (177 matches)
Standard IP access list DENY_10
  10 deny 10.0.0.0, wildcard bits 0.255.255.255
  20 permit any
Standard IP access list DENY_ALL
  10 deny any
Standard IP access list PERMIT_10
  10 permit 10.0.0.0, wildcard bits 0.255.255.255
Standard IP access list PERMIT_ALL
  10 permit any
R1#
```

```
R1#show ip ospf neighbor
```

Neighbor ID	Pri	State	Dead Time	Address
Interface				
2.2.2.2	0	FULL/ -	00:00:38	10.1.1.2
Serial0/2/0.12				

```
R1#
```

```
R1#show ip ospf interface
Serial0/2/0.12 is up, line protocol is up
  Internet Address 10.1.1.1/30, Area 12
  Process ID 1, Router ID 10.1.1.1, Network Type POINT_TO_POINT, Cost: 64
  Transmit Delay is 1 sec, State POINT_TO_POINT
  Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
    oob-resync timeout 40
    Hello due in 00:00:04
  Supports Link-local Signaling (LLS)
  Cisco NSF helper support enabled
  IETF NSF helper support enabled
  Index 1/1, flood queue length 0
  Next 0x0(0)/0x0(0)
  Last flood scan length is 2, maximum is 2
  Last flood scan time is 0 msec, maximum is 0 msec
  Neighbor Count is 1, Adjacent neighbor count is 1
    Adjacent with neighbor 2.2.2.2
  Suppress hello for 0 neighbor(s)
R1#
```


R1#show ip ospf database

OSPF Router with ID (10.1.1.1) (Process ID 1)

Router Link States (Area 12)

Link ID count	ADV Router	Age	Seq#	Checksum	Link
2.2.2.2	2.2.2.2	1592	0x80000009	0x003F28	2
10.1.1.1	10.1.1.1	1563	0x80000004	0x00A6C0	2

Summary Net Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
10.1.1.4	2.2.2.2	1592	0x80000002	0x00F9EC
10.1.1.8	2.2.2.2	813	0x80000002	0x00544E

Summary ASB Link States (Area 12)

Link ID	ADV Router	Age	Seq#	Checksum
3.3.3.3	2.2.2.2	813	0x80000002	0x0035B1

Type-5 AS External Link States

Link ID	ADV Router	Age	Seq#	Checksum	Tag
10.1.4.4	3.3.3.3	865	0x80000002	0x00AAC2	0
10.1.4.8	3.3.3.3	865	0x80000002	0x0082E6	0
10.2.2.0	3.3.3.3	865	0x80000002	0x00EE80	0
10.2.4.12	3.3.3.3	866	0x80000002	0x004E16	0
209.65.200.224	10.1.1.1	1565	0x80000002	0x004494	0
209.65.200.240	10.1.1.1	1565	0x80000002	0x002FC7	65002

R1#

```
R1#show ip route ospf
    10.0.0.0/8 is variably subnetted, 7 subnets, 2 masks
O E2   10.2.4.12/30 [110/20] via 10.1.1.2, 00:46:59, Serial0/2/0.12
O IA   10.1.1.8/30 [110/192] via 10.1.1.2, 00:47:15, Serial0/2/0.12
O E2   10.1.4.8/30 [110/20] via 10.1.1.2, 00:46:59, Serial0/2/0.12
O E2   10.2.2.0/24 [110/20] via 10.1.1.2, 00:46:59, Serial0/2/0.12
O E2   10.1.4.4/30 [110/20] via 10.1.1.2, 00:46:59, Serial0/2/0.12
O IA   10.1.1.4/30 [110/128] via 10.1.1.2, 00:57:04, Serial0/2/0.12
R1#
```

```
R1#show ip bgp neighbors
BGP neighbor is 209.65.200.226, remote AS 65002, external link
  BGP version 4, remote router ID 5.5.5.5
  BGP state = Established, up for 00:59:49
  Last read 00:00:32, last write 00:00:34, hold time is 180, keepalive
interval is 60 seconds
  Neighbor capabilities:
    Route refresh: advertised and received(new)
    Address family IPv4 Unicast: advertised and received
  Message statistics:
    InQ depth is 0
    OutQ depth is 0
```

Sent

Rcvd

```

Opens:                1          1
Notifications:       0          0
Updates:             0          1
Keepalives:         60         60
Route Refresh:      0          0
Total:              61         62

```

Default minimum time between advertisement runs is 30 seconds

```

For address family: IPv4 Unicast
BGP table version 2, neighbor version 2/0
Output queue size : 0
Index 1, Offset 0, Mask 0x2
1 update-group member

```

	Sent	Rcvd
Prefix activity:	----	----
Prefixes Current:	0	1 (Consumes 52 bytes)
Prefixes Total:	0	1
Implicit Withdraw:	0	0
Explicit Withdraw:	0	0
Used as bestpath:	n/a	1
Used as multipath:	n/a	0

	Outbound	Inbound
Local Policy Denied Prefixes:	-----	-----
Bestpath from this peer:	1	n/a
Total:	1	0

Number of NLRIs in the update sent: max 0, min 0

Address tracking is enabled, the RIB does have a route to 209.65.200.226

Connections established 1; dropped 0

Last reset never

Transport(tcp) path-mtu-discovery is enabled

Connection state is ESTAB, I/O status: 1, unread input bytes: 0

Connection is ECN Disabled, Minimum incoming TTL 0, Outgoing TTL 1

Local host: 209.65.200.225, Local port: 179

Foreign host: 209.65.200.226, Foreign port: 29689

Connection tableid (VRF): 0

Enqueued packets for retransmit: 0, input: 0 mis-ordered: 0 (0 bytes)

Event Timers (current time is 0x379CA8):

Timer	Starts	Wakeups	Next
Retrans	62	0	0x0
TimeWait	0	0	0x0
AckHold	62	61	0x0
SendWnd	0	0	0x0
KeepAlive	0	0	0x0
GiveUp	0	0	0x0
PmtuAger	0	0	0x0
DeadWait	0	0	0x0
Linger	0	0	0x0
ProcessQ	0	0	0x0

iss: 2998572375 snduna: 2998573561 sndnxt: 2998573561 sndwnd:
15199
irs: 808308797 rcvnxt: 808310036 rcvwnd: 15146 delrcvwnd:
1238

SRTT: 300 ms, RTTO: 303 ms, RTV: 3 ms, KRTT: 0 ms
minRTT: 16 ms, maxRTT: 300 ms, ACK hold: 200 ms
Status Flags: passive open, gen tcbs
Option Flags: nagle, path mtu capable
IP Precedence value : 6

Datagrams (max data segment is 1460 bytes):
Rcvd: 124 (out of order: 0), with data: 62, total data bytes: 1238
Sent: 123 (retransmit: 0, fastretransmit: 0, partialack: 0, Second
Congestion: 0), with data: 61, total data bytes: 1185
Packets received in fast path: 0, fast processed: 0, slow path: 0
fast lock acquisition failures: 0, slow path: 0

R1#

```

R1#show ip bgp summary
BGP router identifier 1.1.1.1, local AS number 65001
BGP table version is 2, main routing table version 2
1 network entries using 132 bytes of memory
1 path entries using 52 bytes of memory
2/1 BGP path/bestpath attribute entries using 296 bytes of memory
1 BGP AS-PATH entries using 24 bytes of memory
0 BGP route-map cache entries using 0 bytes of memory
0 BGP filter-list cache entries using 0 bytes of memory
BGP using 504 total bytes of memory
BGP activity 1/0 prefixes, 1/0 paths, scan interval 60 secs

Neighbor      V    AS MsgRcvd MsgSent   TblVer  InQ  OutQ  Up/Down
State/PfxRcd
209.65.200.226 4 65002      62     61       2    0    0 01:00:01
1
R1#

```

```
R1#show ip bgp
BGP table version is 2, local router ID is 1.1.1.1
Status codes: s suppressed, d damped, h history, * valid, > best, i -
internal,
                r RIB-failure, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete

   Network          Next Hop           Metric LocPrf Weight Path
*> 209.65.200.240/29
                209.65.200.226           0             0 65002 i
R1#
```

```
R1#show ip route bgp
    209.65.200.0/24 is variably subnetted, 2 subnets, 2 masks
B       209.65.200.240/29 [20/0] via 209.65.200.226, 00:59:23
R1#
```



```
R1#show ip nat translations
```

```
R1#
```

```
R1#show ip nat statistics
```

Total active translations: 0 (0 static, 0 dynamic; 0 extended)
Peak translations: 17, occurred 00:55:10 ago
Outside interfaces:
 Serial0/3/0
Inside interfaces:
 Serial0/2/0.12
Hits: 197 Misses: 0
CEF Translated packets: 40, CEF Punted packets: 157
Expired translations: 42
Dynamic mappings:
-- Inside Source
 [Id: 1] access-list 10 interface Serial0/3/0 refcount 0
Appl doors: 0
Normal doors: 0
Queued Packets: 0
R1#