

```

DSW2#
DSW2#show running-config
Building configuration...

Current configuration : 6019 bytes
!
! No configuration change since last restart
!
version 12.2
no service pad
service timestamps debug uptime
service timestamps log uptime
no service password-encryption
!
hostname DSW2
!
no logging console
!
no aaa new-model
ipv6 unicast-routing
ip subnet-zero
ip routing
!
ip multicast-routing
vtp domain netlearning
vtp mode transparent
!
!
crypto pki trustpoint TP-self-signed-4246780416
  enrollment selfsigned
  subject-name cn=IOS-Self-Signed-Certificate-4246780416
  revocation-check none
  rsakeypair TP-self-signed-4246780416
!
!
crypto pki certificate chain TP-self-signed-4246780416
  certificate self-signed 01
    3082023D 308201A6 A0030201 02020101 300D0609 2A864886 F70D0101 04050030
    31312F30 2D060355 04031326 494F532D 53656C66 2D536967 6E65642D 43657274
    69666963 6174652D 34323436 37383034 3136301E 170D3933 30333031 30303031
    30345A17 0D323030 31303130 30303030 305A3031 312F302D 06035504 03132649
    4F532D53 656C662D 5369676E 65642D43 65727469 66696361 74652D34 32343637
    38303431 3630819F 300D0609 2A864886 F70D0101 01050003 818D0030 81890281
    8100D699 D2A8BD0D A26CE645 B2CE1EC4 EF83204E CBA4D34A B03BC30C 7BF013B1
    5BDEC621 F3CE12CC BC929D9C 463A59DC D49CEF76 3D5193FD 7992F7FF 660F179F
    54CA6370 902081BB ABB71246 5DC79E39 D241B749 11CB4812 07CF1238 A25C59F6
    740464A7 6B3EAE02 6B6B0C13 9B534C70 85BD199E E52D4FB2 AB4C4B5F 678ECD24
    17B30203 010001A3 65306330 0F060355 1D130101 FF040530 030101FF 30100603
    551D1104 09300782 05445357 322E301F 0603551D 23041830 168014A7 8C27C43F
    00BEB401 3F63B68A 9CD582EF D7B15430 1D060355 1D0E0416 0414A78C 27C43F00
    BEB4013F 63B68A9C D582EFD7 B154300D 06092A86 4886F70D 01010405 00038181
    00B9A060 055A57EE 0EE7C450 128718FA 07A5DCE4 8EABE33F 56BA385F 8F9477E8
    191A361C EBEBF296 6A2E4637 11BB4D89 CDFA4DDB 7229B8F1 856DCE18 DF11CA57
    180C3686 28E9079C F004E71B A9F11040 7C952427 573ED2F5 AB38C4D9 768156A4

```

```
C597E2E3 B9D4C611 F902BEA8 A18209DD 239160AE E6AC24DE 41AD980B 261778F5
AA
quit
!
!
!
spanning-tree mode pvst
spanning-tree extend system-id
spanning-tree vlan 10,200 priority 8192
spanning-tree vlan 20 priority 4096
!
vlan internal allocation policy ascending
!
vlan 10,20,200
!
!
!
!
!
!
interface Tunnel67
no ip address
ipv6 address 2026::3:2/122
ipv6 enable
ipv6 rip RIPNG enable
tunnel source 10.2.4.14
tunnel destination 10.2.4.13
!
interface Port-channel12
no switchport
ip address 10.2.4.14 255.255.255.252
ip pim sparse-dense-mode
!
interface Port-channel23
switchport trunk encapsulation dot1q
switchport trunk allowed vlan 10,200
switchport mode trunk
!
interface Port-channel24
switchport trunk encapsulation dot1q
switchport trunk allowed vlan 20,200
switchport mode trunk
!
interface FastEthernet0/1
no switchport
ip address 10.1.4.10 255.255.255.252
ip pim sparse-dense-mode
!
interface FastEthernet0/2
switchport mode access
shutdown
!
interface FastEthernet0/3
switchport mode access
```

```
!  
interface FastEthernet0/4  
  switchport mode access  
  shutdown  
!  
interface FastEthernet0/5  
  switchport mode access  
  shutdown  
!  
interface FastEthernet0/6  
  switchport mode access  
  shutdown  
!  
interface FastEthernet0/7  
  switchport mode access  
  shutdown  
!  
interface FastEthernet0/8  
  switchport mode access  
  shutdown  
!  
interface FastEthernet0/9  
  switchport mode access  
  shutdown  
!  
interface FastEthernet0/10  
  switchport mode access  
  shutdown  
!  
interface FastEthernet0/11  
  switchport mode access  
  shutdown  
!  
interface FastEthernet0/12  
  switchport mode access  
  shutdown  
!  
interface FastEthernet0/13  
  switchport mode access  
  shutdown  
!  
interface FastEthernet0/14  
  switchport mode access  
  shutdown  
!  
interface FastEthernet0/15  
  switchport mode access  
!  
interface FastEthernet0/16  
  switchport trunk encapsulation dot1q  
  switchport trunk allowed vlan 20,200  
  switchport mode trunk  
  channel-group 24 mode desirable  
!
```

```
interface FastEthernet0/17
  switchport trunk encapsulation dot1q
  switchport trunk allowed vlan 20,200
  switchport mode trunk
  channel-group 24 mode desirable
!
interface FastEthernet0/18
  switchport trunk encapsulation dot1q
  switchport trunk allowed vlan 20,200
  switchport mode trunk
  channel-group 24 mode desirable
!
interface FastEthernet0/19
  switchport trunk encapsulation dot1q
  switchport trunk allowed vlan 10,200
  switchport mode trunk
  channel-group 23 mode active
!
interface FastEthernet0/20
  switchport trunk encapsulation dot1q
  switchport trunk allowed vlan 10,200
  switchport mode trunk
  channel-group 23 mode active
!
interface FastEthernet0/21
  switchport trunk encapsulation dot1q
  switchport trunk allowed vlan 10,200
  switchport mode trunk
  channel-group 23 mode active
!
interface FastEthernet0/22
  no switchport
  no ip address
  channel-group 12 mode on
!
interface FastEthernet0/23
  no switchport
  no ip address
  channel-group 12 mode on
!
interface FastEthernet0/24
  no switchport
  no ip address
  channel-group 12 mode on
!
interface GigabitEthernet0/1
  switchport mode dynamic desirable
  shutdown
!
interface GigabitEthernet0/2
  switchport mode dynamic desirable
  shutdown
!
interface Vlan1
```

```
no ip address
shutdown
!
interface Vlan10
 ip address 10.2.1.2 255.255.255.0
 ip helper-address 10.1.4.9
 ip pim sparse-dense-mode
 standby 10 ip 10.2.1.254
 standby 10 priority 20
!
interface Vlan20
 ip address 10.2.2.1 255.255.255.0
 ip pim sparse-dense-mode
!
interface Vlan200
 ip address 192.168.1.130 255.255.255.224
!
!
router eigrp 10
 metric weights 0 1 1 1 1 1
 no auto-summary
 network 10.1.4.10 0.0.0.0
 network 10.2.1.2 0.0.0.0
 network 10.2.2.1 0.0.0.0
 network 10.2.4.14 0.0.0.0
!
ip classless
ip http server
ip http secure-server
!
!
ip access-list standard DENY_10
 deny 10.0.0.0 0.255.255.255
 permit any
ip access-list standard DENY_ALL
 deny any
ip access-list standard PERMIT_10
 permit 10.0.0.0 0.255.255.255
ip access-list standard PERMIT_ALL
 permit any
!
ipv6 router rip RIPNG
!
!
control-plane
!
!
line con 0
 exec-timeout 0 0
 logging synchronous
line vty 0 4
 login
line vty 5 15
 login
```

```
!  
ntp clock-period 17179923  
ntp server 10.1.1.1  
end
```

```
DSW2#
```

```
DSW2#ping 209.65.200.241
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 209.65.200.241, timeout is 2 seconds:  
!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 224/227/232  
ms  
DSW2#
```

```
DSW2#ping 209.65.200.226
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.226, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 224/228/232  
ms
```

```
DSW2#
```

```
DSW2#ping 209.65.200.225
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.225, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/196/200  
ms
```

```
DSW2#
```



```
DSW2#ping 10.1.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196  
ms
```

```
DSW2#
```

```
DSW2#ping 10.1.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.2, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132  
ms
```

```
DSW2#
```

```
DSW2#ping 10.1.1.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.5, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/132  
ms
```

```
DSW2#
```

```
DSW2#ping 10.1.1.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.6, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/67/72 ms
```

```
DSW2#
```

```
DSW2#ping 10.1.1.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.9, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms
```

```
DSW2#
```

```
DSW2#ping 10.1.1.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.10, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.1.4.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.10, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.1.4.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.9, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.1.4.6
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.6, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/4/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.1.4.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.5, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
```

```
DSW2#
```



```
DSW2#ping 10.2.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/4/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.2.2.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.2, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/4/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.2.1.254
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.254, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/4/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.2.4.14
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.14, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.2.4.13
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.13, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/4/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.2.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/4 ms
```

```
DSW2#
```

```
DSW2#ping 10.2.2.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.1, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/1 ms
```

```
DSW2#
```

```
DSW2#ping 10.2.1.4
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.4, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/3/8 ms
```

```
DSW2#
```

```

DSW2#show ip interface brief
Interface          IP-Address      OK? Method Status
Protocol
Vlan1              unassigned     YES NVRAM  administratively down
down
Vlan10            10.2.1.2       YES NVRAM  up
up
Vlan20            10.2.2.1       YES NVRAM  up
up
Vlan200           192.168.1.130  YES NVRAM  up
up
FastEthernet0/1   10.1.4.10      YES NVRAM  up
up
FastEthernet0/2   unassigned     YES unset  administratively down
down
FastEthernet0/3   unassigned     YES unset  down
down
FastEthernet0/4   unassigned     YES unset  administratively down
down
FastEthernet0/5   unassigned     YES unset  administratively down
down

```

FastEthernet0/6 down	unassigned	YES unset	administratively down
FastEthernet0/7 down	unassigned	YES unset	administratively down
FastEthernet0/8 down	unassigned	YES unset	administratively down
FastEthernet0/9 down	unassigned	YES unset	administratively down
FastEthernet0/10 down	unassigned	YES unset	administratively down
FastEthernet0/11 down	unassigned	YES unset	administratively down
FastEthernet0/12 down	unassigned	YES unset	administratively down
FastEthernet0/13 down	unassigned	YES unset	administratively down
FastEthernet0/14 down	unassigned	YES unset	administratively down
FastEthernet0/15 down	unassigned	YES unset	down
FastEthernet0/16 up	unassigned	YES unset	up
FastEthernet0/17 up	unassigned	YES unset	up
FastEthernet0/18 up	unassigned	YES unset	up
FastEthernet0/19 up	unassigned	YES unset	up
FastEthernet0/20 up	unassigned	YES unset	up
FastEthernet0/21 up	unassigned	YES unset	up
FastEthernet0/22 up	unassigned	YES NVRAM	up
FastEthernet0/23 up	unassigned	YES NVRAM	up
FastEthernet0/24 up	unassigned	YES NVRAM	up
GigabitEthernet0/1 down	unassigned	YES unset	administratively down
GigabitEthernet0/2 down	unassigned	YES unset	administratively down
Port-channel12 up	10.2.4.14	YES NVRAM	up
Port-channel23 up	unassigned	YES unset	up
Port-channel24 up	unassigned	YES unset	up
Tunnel67 up	unassigned	YES NVRAM	up

DSW2#


```
DSW2#show ip route
```

```
Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP  
        D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
        N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
        E1 - OSPF external type 1, E2 - OSPF external type 2  
        i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS  
level-2  
        ia - IS-IS inter area, * - candidate default, U - per-user static  
route  
        o - ODR, P - periodic downloaded static route
```

```
Gateway of last resort is 10.1.4.9 to network 0.0.0.0
```

```
10.0.0.0/8 is variably subnetted, 6 subnets, 2 masks  
C       10.2.4.12/30 is directly connected, Port-channel12  
D EX    10.1.1.8/30 [170/1023] via 10.1.4.9, 00:58:19, FastEthernet0/1  
C       10.1.4.8/30 is directly connected, FastEthernet0/1  
C       10.2.1.0/24 is directly connected, Vlan10  
C       10.2.2.0/24 is directly connected, Vlan20  
D       10.1.4.4/30 [90/111] via 10.2.2.2, 01:01:35, Vlan20  
                [90/111] via 10.2.1.1, 01:01:35, Vlan10
```

```
192.168.1.0/27 is subnetted, 1 subnets
C      192.168.1.128 is directly connected, Vlan200
D*EX 0.0.0.0/0 [170/1023] via 10.1.4.9, 00:58:04, FastEthernet0/1
DSW2#
```

```
DSW2#show processes cpu
CPU utilization for five seconds: 1%/0%; one minute: 1%; five minutes: 1%
  PID Runtime(ms)   Invoked    uSecs   5Sec   1Min   5Min  TTY Process
   1         0         9         0  0.00%  0.00%  0.00%  0 Chunk
Manager
   2         0        751         0  0.00%  0.00%  0.00%  0 Load Meter
   3         8         35        228  0.00%  0.00%  0.00%  0 SpanTree
Helper
   4       3328        451       7379  0.31%  0.08%  0.06%  0 Check
heaps
   5         0         4         0  0.00%  0.00%  0.00%  0 Pool
Manager
   6         0         2         0  0.00%  0.00%  0.00%  0 Timers
```


99	0	1	0	0.00%	0.00%	0.00%	0	IP IRDP
100	0	49	0	0.00%	0.00%	0.00%	0	Cluster L2
101	0	377	0	0.00%	0.00%	0.00%	0	Cluster
RARP								
102	120	1040	115	0.00%	0.00%	0.00%	0	Cluster
Base								
103	0	1	0	0.00%	0.00%	0.00%	0	TCP Timer
104	0	1	0	0.00%	0.00%	0.00%	0	TCP
Protocols								
105	0	1	0	0.00%	0.00%	0.00%	0	Socket
Timers								
106	4	15	266	0.00%	0.00%	0.00%	0	HTTP CORE
107	0	1	0	0.00%	0.00%	0.00%	0	RARP Input
108	0	1	0	0.00%	0.00%	0.00%	0	802.1x
Critical								
109	8	30	266	0.00%	0.00%	0.00%	0	L2MM
110	40	316	126	0.00%	0.00%	0.00%	0	MRD
111	44	323	136	0.00%	0.00%	0.00%	0	IGMP SN
112	0	1	0	0.00%	0.00%	0.00%	0	IGMP QR
113	0	2	0	0.00%	0.00%	0.00%	0	L2TRACE
SERVER								
114	0	1	0	0.00%	0.00%	0.00%	0	Vegas wccp
manag								
115	4	4	1000	0.00%	0.00%	0.00%	0	Crypto ACL
116	16	78	205	0.00%	0.00%	0.00%	0	IP RIB
Update								
117	12	16	750	0.00%	0.00%	0.00%	0	DHCPD
Receive								
118	0	1	0	0.00%	0.00%	0.00%	0	Transport
Port A								
119	2112	15	140800	0.00%	0.15%	0.22%	0	crypto sw
pk pro								
120	0	2	0	0.00%	0.00%	0.00%	0	Crypto
Support								
121	0	2	0	0.00%	0.00%	0.00%	0	LOCAL AAA
122	0	2	0	0.00%	0.00%	0.00%	0	ENABLE AAA
123	0	2	0	0.00%	0.00%	0.00%	0	LINE AAA
125	0	2	0	0.00%	0.00%	0.00%	0	TPLUS
126	0	1	0	0.00%	0.00%	0.00%	0	CRYPTO QoS
proce								
127	0	1	0	0.00%	0.00%	0.00%	0	Crypto INT
128	0	4	0	0.00%	0.00%	0.00%	0	Crypto
IKMP								
129	100	191	523	0.00%	0.00%	0.00%	0	IPSEC key
engine								
130	0	1	0	0.00%	0.00%	0.00%	0	IPSEC
manual key								
131	0	1	0	0.00%	0.00%	0.00%	0	Crypto PAS
Proc								
132	4	12	333	0.00%	0.00%	0.00%	0	crypto
engine pr								
133	24	4	6000	0.00%	0.00%	0.00%	0	Crypto CA
134	0	1	0	0.00%	0.00%	0.00%	0	Crypto
PKI-CRL								

DSW2#show interfaces

```
Vlan1 is administratively down, line protocol is down
  Hardware is EtherSVI, address is 000b.fd20.ba00 (bia 000b.fd20.ba00)
  MTU 1500 bytes, BW 1000000 Kbit, DLY 10 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive not supported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 IP multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 1 interface resets
    0 output buffer failures, 0 output buffers swapped out
Vlan10 is up, line protocol is up
  Hardware is EtherSVI, address is 000b.fd20.ba00 (bia 000b.fd20.ba00)
  Internet address is 10.2.1.2/24
  MTU 1500 bytes, BW 1000000 Kbit, DLY 10 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive not supported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:00, output 00:00:02, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 6
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    2452 packets input, 193553 bytes, 0 no buffer
    Received 0 broadcasts (816 IP multicasts)
    0 runts, 0 giants, 0 throttles
```

```
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    2382 packets output, 163155 bytes, 0 underruns
    0 output errors, 0 interface resets
    0 output buffer failures, 0 output buffers swapped out
Vlan20 is up, line protocol is up
  Hardware is EtherSVI, address is 000b.fd20.ba00 (bia 000b.fd20.ba00)
  Internet address is 10.2.2.1/24
  MTU 1500 bytes, BW 1000000 Kbit, DLY 10 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive not supported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:01, output 00:00:03, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 6
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    984 packets input, 77950 bytes, 0 no buffer
    Received 0 broadcasts (818 IP multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    1068 packets output, 79885 bytes, 0 underruns
    0 output errors, 0 interface resets
    0 output buffer failures, 0 output buffers swapped out
Vlan200 is up, line protocol is up
  Hardware is EtherSVI, address is 000b.fd20.ba00 (bia 000b.fd20.ba00)
  Internet address is 192.168.1.130/27
  MTU 1500 bytes, BW 1000000 Kbit, DLY 10 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive not supported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output 01:02:07, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 6
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 IP multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    1 packets output, 60 bytes, 0 underruns
    0 output errors, 0 interface resets
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/1 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 000b.fd20.ba00 (bia
000b.fd20.ba00)
  Internet address is 10.1.4.10/30
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
```

```
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:03, output 00:00:02, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  5361 packets input, 437092 bytes, 0 no buffer
  Received 1096 broadcasts (831 IP multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 1093 multicast, 0 pause input
  0 input packets with dribble condition detected
  1713 packets output, 164003 bytes, 0 underruns
  0 output errors, 0 collisions, 3 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/2 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba02 (bia
000b.fd20.ba02)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/3 is down, line protocol is down (notconnect)
```

Hardware is Fast Ethernet, address is 000b.fd20.ba03 (bia 000b.fd20.ba03)
MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 0 multicast, 0 pause input
0 input packets with dribble condition detected
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 1 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/4 is administratively down, line protocol is down (disabled)

Hardware is Fast Ethernet, address is 000b.fd20.ba04 (bia 000b.fd20.ba04)
MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 0 multicast, 0 pause input
0 input packets with dribble condition detected
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 1 interface resets
0 babbles, 0 late collision, 0 deferred

```
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/5 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba05 (bia
000b.fd20.ba05)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/6 is administratively down, line protocol is down
(disabled)
```

```
  Hardware is Fast Ethernet, address is 000b.fd20.ba06 (bia
000b.fd20.ba06)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
```

```
0 input packets with dribble condition detected
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 1 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/7 is administratively down, line protocol is down
(disabled)
Hardware is Fast Ethernet, address is 000b.fd20.ba07 (bia
000b.fd20.ba07)
MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/8 is administratively down, line protocol is down
(disabled)
```

```
Hardware is Fast Ethernet, address is 000b.fd20.ba08 (bia
000b.fd20.ba08)
MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
```

```
Received 0 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 0 multicast, 0 pause input
0 input packets with dribble condition detected
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 1 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/9 is administratively down, line protocol is down
(disabled)
Hardware is Fast Ethernet, address is 000b.fd20.ba09 (bia
000b.fd20.ba09)
MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 0 multicast, 0 pause input
0 input packets with dribble condition detected
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 1 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/10 is administratively down, line protocol is down
(disabled)
Hardware is Fast Ethernet, address is 000b.fd20.ba0a (bia
000b.fd20.ba0a)
MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
```

```
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/11 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba0b (bia
000b.fd20.ba0b)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/12 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba0c (bia
000b.fd20.ba0c)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
```



```
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/13 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba0d (bia
000b.fd20.ba0d)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/14 is administratively down, line protocol is down
(disabled)
  Hardware is Fast Ethernet, address is 000b.fd20.ba0e (bia
000b.fd20.ba0e)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
```

```
Keepalive set (10 sec)
Auto-duplex, Auto-speed, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  0 packets input, 0 bytes, 0 no buffer
  Received 0 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 0 multicast, 0 pause input
  0 input packets with dribble condition detected
  0 packets output, 0 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/15 is down, line protocol is down (notconnect)
  Hardware is Fast Ethernet, address is 000b.fd20.ba0f (bia
000b.fd20.ba0f)
  MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Auto-duplex, Auto-speed, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    0 packets input, 0 bytes, 0 no buffer
    Received 0 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 0 multicast, 0 pause input
    0 input packets with dribble condition detected
    0 packets output, 0 bytes, 0 underruns
    0 output errors, 0 collisions, 1 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/16 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 000b.fd20.ba10 (bia
000b.fd20.ba10)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
```

```
    reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:05, output 00:00:02, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  717 packets input, 72694 bytes, 0 no buffer
  Received 338 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 338 multicast, 0 pause input
  0 input packets with dribble condition detected
  1805 packets output, 162591 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/17 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 000b.fd20.ba11 (bia
000b.fd20.ba11)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:07, output 00:00:03, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  3999 packets input, 319284 bytes, 0 no buffer
  Received 3204 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 3202 multicast, 0 pause input
  0 input packets with dribble condition detected
  733 packets output, 74020 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/18 is up, line protocol is up (connected)
```

```
Hardware is Fast Ethernet, address is 000b.fd20.ba12 (bia
000b.fd20.ba12)
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:10, output 00:00:05, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 1000 bits/sec, 1 packets/sec
  718 packets input, 72784 bytes, 0 no buffer
  Received 339 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 339 multicast, 0 pause input
  0 input packets with dribble condition detected
  2616 packets output, 208864 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/19 is up, line protocol is up (connected)
Hardware is Fast Ethernet, address is 000b.fd20.ba13 (bia
000b.fd20.ba13)
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:11, output 00:00:02, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 1000 bits/sec, 2 packets/sec
5 minute output rate 1000 bits/sec, 1 packets/sec
  7260 packets input, 578236 bytes, 0 no buffer
  Received 6819 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 6705 multicast, 0 pause input
  0 input packets with dribble condition detected
  3139 packets output, 263539 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
```

```
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/20 is up, line protocol is up (connected)
Hardware is Fast Ethernet, address is 000b.fd20.ba14 (bia
000b.fd20.ba14)
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:12, output 00:00:06, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  720 packets input, 78338 bytes, 0 no buffer
Received 340 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 340 multicast, 0 pause input
  0 input packets with dribble condition detected
  721 packets output, 77932 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/21 is up, line protocol is up (connected)
Hardware is Fast Ethernet, address is 000b.fd20.ba15 (bia
000b.fd20.ba15)
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
  reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:07, output 00:00:08, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  724 packets input, 78880 bytes, 0 no buffer
Received 340 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 340 multicast, 0 pause input
  0 input packets with dribble condition detected
  4359 packets output, 376566 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
```

```
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/22 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 000b.fd20.ba00 (bia
000b.fd20.ba00)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:21, output 00:00:07, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    3720 packets input, 447026 bytes, 0 no buffer
    Received 1099 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 1097 multicast, 0 pause input
    0 input packets with dribble condition detected
    3731 packets output, 444141 bytes, 0 underruns
    0 output errors, 0 collisions, 3 interface resets
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier, 0 PAUSE output
    0 output buffer failures, 0 output buffers swapped out
FastEthernet0/23 is up, line protocol is up (connected)
  Hardware is Fast Ethernet, address is 000b.fd20.ba00 (bia
000b.fd20.ba00)
  MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:22, output 00:00:08, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    450 packets input, 49610 bytes, 0 no buffer
    Received 65 broadcasts (0 multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog, 65 multicast, 0 pause input
    0 input packets with dribble condition detected
```

```
447 packets output, 51120 bytes, 0 underruns
0 output errors, 0 collisions, 3 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
FastEthernet0/24 is up, line protocol is up (connected)
Hardware is Fast Ethernet, address is 000b.fd20.ba00 (bia
000b.fd20.ba00)
MTU 1500 bytes, BW 100000 Kbit, DLY 100 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:24, output 00:00:00, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
445 packets input, 49020 bytes, 0 no buffer
Received 65 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 65 multicast, 0 pause input
0 input packets with dribble condition detected
448 packets output, 51184 bytes, 0 underruns
0 output errors, 0 collisions, 3 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
GigabitEthernet0/1 is administratively down, line protocol is down
(disabled)
Hardware is Gigabit Ethernet, address is 000b.fd20.ba19 (bia
000b.fd20.ba19)
MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive not set
Auto-duplex, Auto-speed, link type is auto, media type is unknown
input flow-control is off, output flow-control is off
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
```

```
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 0 multicast, 0 pause input
0 input packets with dribble condition detected
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 1 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
GigabitEthernet0/2 is administratively down, line protocol is down
(disabled)
Hardware is Gigabit Ethernet, address is 000b.fd20.bala (bia
000b.fd20.bala)
MTU 1500 bytes, BW 10000 Kbit, DLY 1000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive not set
Auto-duplex, Auto-speed, link type is auto, media type is unknown
input flow-control is off, output flow-control is off
ARP type: ARPA, ARP Timeout 04:00:00
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts (0 multicasts)
0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
0 watchdog, 0 multicast, 0 pause input
0 input packets with dribble condition detected
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 1 interface resets
0 babbles, 0 late collision, 0 deferred
0 lost carrier, 0 no carrier, 0 PAUSE output
0 output buffer failures, 0 output buffers swapped out
Port-channel12 is up, line protocol is up (connected)
Hardware is EtherChannel, address is 000b.fd20.ba00 (bia
000b.fd20.ba00)
Internet address is 10.2.4.14/30
MTU 1500 bytes, BW 300000 Kbit, DLY 100 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation ARPA, loopback not set
Keepalive set (10 sec)
Full-duplex, 100Mb/s, media type is 10/100BaseTX
input flow-control is off, output flow-control is unsupported
Members in this channel: Fa0/22 Fa0/23 Fa0/24
ARP type: ARPA, ARP Timeout 04:00:00
Last input 00:00:00, output 00:00:00, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
```



```
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  4618 packets input, 545888 bytes, 0 no buffer
  Received 1232 broadcasts (841 IP multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 1230 multicast, 0 pause input
  0 input packets with dribble condition detected
  4629 packets output, 546665 bytes, 0 underruns
  0 output errors, 0 collisions, 4 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
Port-channel23 is up, line protocol is up (connected)
  Hardware is EtherChannel, address is 000b.fd20.ba13 (bia
000b.fd20.ba13)
  MTU 1500 bytes, BW 300000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  Members in this channel: Fa0/19 Fa0/20 Fa0/21
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:00, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 1000 bits/sec, 1 packets/sec
  8704 packets input, 735010 bytes, 0 no buffer
  Received 7493 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 7378 multicast, 0 pause input
  0 input packets with dribble condition detected
  8211 packets output, 716741 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
Port-channel24 is up, line protocol is up (connected)
  Hardware is EtherChannel, address is 000b.fd20.ba11 (bia
000b.fd20.ba11)
  MTU 1500 bytes, BW 300000 Kbit, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, media type is 10/100BaseTX
  input flow-control is off, output flow-control is unsupported
  Members in this channel: Fa0/16 Fa0/17 Fa0/18
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:01, output 00:00:00, output hang never
```

```
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  5436 packets input, 465024 bytes, 0 no buffer
  Received 3875 broadcasts (0 multicasts)
  0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog, 3873 multicast, 0 pause input
  0 input packets with dribble condition detected
  5154 packets output, 445563 bytes, 0 underruns
  0 output errors, 0 collisions, 1 interface resets
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier, 0 PAUSE output
  0 output buffer failures, 0 output buffers swapped out
Tunnel67 is up, line protocol is up
  Hardware is Tunnel
  MTU 1514 bytes, BW 100 Kbit, DLY 50000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation TUNNEL, loopback not set
  Keepalive not set
  Tunnel source 10.2.4.14, destination 10.2.4.13
  Tunnel protocol/transport GRE/IP, key disabled, sequencing disabled
  Tunnel TTL 255
  Checksumming of packets disabled
  Last input 00:00:25, output 00:00:24, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/0 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 0 packets/sec
    2195 packets input, 273800 bytes, 0 no buffer
    Received 0 broadcasts (0 IP multicasts)
    0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
    2203 packets output, 269108 bytes, 0 underruns
    0 output errors, 0 collisions, 0 interface resets
    0 output buffer failures, 0 output buffers swapped out
DSW2#
```

DSW2#show interfaces counters errors

Port	Align-Err	FCS-Err	Xmit-Err	Rcv-Err	UnderSize
Fa0/1	0	0	0	0	0
Fa0/2	0	0	0	0	0
Fa0/3	0	0	0	0	0
Fa0/4	0	0	0	0	0
Fa0/5	0	0	0	0	0
Fa0/6	0	0	0	0	0
Fa0/7	0	0	0	0	0
Fa0/8	0	0	0	0	0
Fa0/9	0	0	0	0	0
Fa0/10	0	0	0	0	0
Fa0/11	0	0	0	0	0
Fa0/12	0	0	0	0	0
Fa0/13	0	0	0	0	0
Fa0/14	0	0	0	0	0
Fa0/15	0	0	0	0	0
Fa0/16	0	0	0	0	0
Fa0/17	0	0	0	0	0
Fa0/18	0	0	0	0	0
Fa0/19	0	0	0	0	0
Fa0/20	0	0	0	0	0
Fa0/21	0	0	0	0	0
Fa0/22	0	0	0	0	0
Fa0/23	0	0	0	0	0
Fa0/24	0	0	0	0	0
Gi0/1	0	0	0	0	0
Gi0/2	0	0	0	0	0
Po12	0	0	0	0	0

Po23	0	0	0	0	0
Po24	0	0	0	0	0

Port	Single-Col	Multi-Col	Late-Col	Excess-Col	Carri-Sen	Runts
Giants						
Fa0/1	0	0	0	0	0	0
0						
Fa0/2	0	0	0	0	0	0
0						
Fa0/3	0	0	0	0	0	0
0						
Fa0/4	0	0	0	0	0	0
0						
Fa0/5	0	0	0	0	0	0
0						
Fa0/6	0	0	0	0	0	0
0						
Fa0/7	0	0	0	0	0	0
0						
Fa0/8	0	0	0	0	0	0
0						
Fa0/9	0	0	0	0	0	0
0						
Fa0/10	0	0	0	0	0	0
0						
Fa0/11	0	0	0	0	0	0
0						
Fa0/12	0	0	0	0	0	0
0						
Fa0/13	0	0	0	0	0	0
0						
Fa0/14	0	0	0	0	0	0
0						
Fa0/15	0	0	0	0	0	0
0						
Fa0/16	0	0	0	0	0	0
0						
Fa0/17	0	0	0	0	0	0
0						
Fa0/18	0	0	0	0	0	0
0						
Fa0/19	0	0	0	0	0	0
0						
Fa0/20	0	0	0	0	0	0
0						
Fa0/21	0	0	0	0	0	0
0						
Fa0/22	0	0	0	0	0	0
0						
Fa0/23	0	0	0	0	0	0
0						
Fa0/24	0	0	0	0	0	0
0						

Gi0/1	0	0	0	0	0	0
0						
Gi0/2	0	0	0	0	0	0
0						
Po12	0	0	0	0	0	0
0						
Po23	0	0	0	0	0	0
0						
Po24	0	0	0	0	0	0
0						
DSW2#						

DSW2#show cdp neighbors

Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge
 S - Switch, H - Host, I - IGMP, r - Repeater, P - Phone

Device ID	Local Intrfce	Holdtme	Capability	Platform	Port
ID					

R4 0/1	Fas 0/1	133	R S I	1841	Fas
DSW1 0/24	Fas 0/24	134	R S I	WS-C3550-	Fas
DSW1 0/23	Fas 0/23	134	R S I	WS-C3550-	Fas
DSW1 0/22	Fas 0/22	134	R S I	WS-C3550-	Fas
ASW1 0/17	Fas 0/20	122	S I	WS-C2950-	Fas
ASW1 0/18	Fas 0/21	122	S I	WS-C2950-	Fas
ASW1 0/16	Fas 0/19	122	S I	WS-C2950-	Fas
ASW2 0/21	Fas 0/18	123	S I	WS-C2950-	Fas
ASW2 0/19	Fas 0/16	123	S I	WS-C2950-	Fas
ASW2 0/20	Fas 0/17	123	S I	WS-C2950-	Fas
DSW2#					

```
DSW2#show cdp neighbors detail
```

```
-----  
Device ID: R4  
Entry address(es):  
  IP address: 10.1.4.9  
Platform: Cisco 1841, Capabilities: Router Switch IGMP  
Interface: FastEthernet0/1, Port ID (outgoing port): FastEthernet0/1  
Holdtime : 125 sec
```

```
Version :  
Cisco IOS Software, 1841 Software (C1841-ADVIPSERVICESK9-M), Version  
12.4(25b), RELEASE SOFTWARE (fc1)  
Technical Support: http://www.cisco.com/techsupport  
Copyright (c) 1986-2009 by Cisco Systems, Inc.  
Compiled Wed 12-Aug-09 10:49 by prod_rel_team
```

```
advertisement version: 2  
VTP Management Domain: ''  
Duplex: full  
Management address(es):
```

```
-----  
Device ID: DSW1  
Entry address(es):  
  IP address: 10.2.4.13  
Platform: Cisco WS-C3550-24, Capabilities: Router Switch IGMP  
Interface: FastEthernet0/24, Port ID (outgoing port): FastEthernet0/24  
Holdtime : 125 sec
```

```
Version :  
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version  
12.2(44)SE6, RELEASE SOFTWARE (fc1)  
Copyright (c) 1986-2009 by Cisco Systems, Inc.  
Compiled Mon 09-Mar-09 20:28 by gereddy
```

```
advertisement version: 2  
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,  
value=00000000FFFFFFFFF0102250C0000000000000000DBDE36E00FF0000  
VTP Management Domain: 'netlearning'  
Duplex: full  
Management address(es):  
  IP address: 10.2.4.13
```

```
-----  
Device ID: DSW1  
Entry address(es):  
  IP address: 10.2.4.13  
Platform: Cisco WS-C3550-24, Capabilities: Router Switch IGMP  
Interface: FastEthernet0/23, Port ID (outgoing port): FastEthernet0/23  
Holdtime : 124 sec
```

Version :
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version
12.2(44)SE6, RELEASE SOFTWARE (fc1)
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Mon 09-Mar-09 20:28 by gereddy

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF0102250C0000000000000000DBDE36E00FF0000
VTP Management Domain: 'netlearning'
Duplex: full
Management address(es):
IP address: 10.2.4.13

Device ID: DSW1
Entry address(es):
IP address: 10.2.4.13
Platform: Cisco WS-C3550-24, Capabilities: Router Switch IGMP
Interface: FastEthernet0/22, Port ID (outgoing port): FastEthernet0/22
Holdtime : 123 sec

Version :
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version
12.2(44)SE6, RELEASE SOFTWARE (fc1)
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Mon 09-Mar-09 20:28 by gereddy

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF0102250C0000000000000000DBDE36E00FF0000
VTP Management Domain: 'netlearning'
Duplex: full
Management address(es):
IP address: 10.2.4.13

Device ID: ASW1
Entry address(es):
IP address: 192.168.1.131
Platform: cisco WS-C2950-24, Capabilities: Switch IGMP
Interface: FastEthernet0/20, Port ID (outgoing port): FastEthernet0/17
Holdtime : 172 sec

Version :
Cisco Internetwork Operating System Software
IOS (tm) C2950 Software (C2950-I6Q4L2-M), Version 12.1(22)EA4a, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2005 by cisco Systems, Inc.
Compiled Fri 16-Sep-05 10:46 by yenanh

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225020000000000000015FAAC46C0FF0000

VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
 IP address: 192.168.1.131

Device ID: ASW1
Entry address(es):
 IP address: 192.168.1.131
Platform: cisco WS-C2950-24, Capabilities: Switch IGMP
Interface: FastEthernet0/21, Port ID (outgoing port): FastEthernet0/18
Holdtime : 171 sec

Version :
Cisco Internetwork Operating System Software
IOS (tm) C2950 Software (C2950-I6Q4L2-M), Version 12.1(22)EA4a, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2005 by cisco Systems, Inc.
Compiled Fri 16-Sep-05 10:46 by yenanh

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225020000000000000015FAAC46C0FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
 IP address: 192.168.1.131

Device ID: ASW1
Entry address(es):
 IP address: 192.168.1.131
Platform: cisco WS-C2950-24, Capabilities: Switch IGMP
Interface: FastEthernet0/19, Port ID (outgoing port): FastEthernet0/16
Holdtime : 170 sec

Version :
Cisco Internetwork Operating System Software
IOS (tm) C2950 Software (C2950-I6Q4L2-M), Version 12.1(22)EA4a, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2005 by cisco Systems, Inc.
Compiled Fri 16-Sep-05 10:46 by yenanh

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225020000000000000015FAAC46C0FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
 IP address: 192.168.1.131

Device ID: ASW2
Entry address(es):
 IP address: 192.168.1.132
Platform: cisco WS-C2950-24, Capabilities: Switch IGMP
Interface: FastEthernet0/18, Port ID (outgoing port): FastEthernet0/21
Holdtime : 169 sec

Version :
Cisco Internetwork Operating System Software
IOS (tm) C2950 Software (C2950-I6Q4L2-M), Version 12.1(22)EA4a, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2005 by cisco Systems, Inc.
Compiled Fri 16-Sep-05 10:46 by yenanh

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225010000000000000015FAB82880FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
 IP address: 192.168.1.132

Device ID: ASW2
Entry address(es):
 IP address: 192.168.1.132
Platform: cisco WS-C2950-24, Capabilities: Switch IGMP
Interface: FastEthernet0/16, Port ID (outgoing port): FastEthernet0/19
Holdtime : 169 sec

Version :
Cisco Internetwork Operating System Software
IOS (tm) C2950 Software (C2950-I6Q4L2-M), Version 12.1(22)EA4a, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2005 by cisco Systems, Inc.
Compiled Fri 16-Sep-05 10:46 by yenanh

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225010000000000000015FAB82880FF0000
VTP Management Domain: 'netlearning'
Native VLAN: 1
Duplex: full
Management address(es):
 IP address: 192.168.1.132

Device ID: ASW2
Entry address(es):
 IP address: 192.168.1.132
Platform: cisco WS-C2950-24, Capabilities: Switch IGMP
Interface: FastEthernet0/17, Port ID (outgoing port): FastEthernet0/20

Holdtime : 167 sec

Version :

Cisco Internetwork Operating System Software
IOS (tm) C2950 Software (C2950-I6Q4L2-M), Version 12.1(22)EA4a, RELEASE
SOFTWARE (fc1)
Copyright (c) 1986-2005 by cisco Systems, Inc.
Compiled Fri 16-Sep-05 10:46 by yenanh

advertisement version: 2

Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010225010000000000000015FAB82880FF0000

VTP Management Domain: 'netlearning'

Native VLAN: 1

Duplex: full

Management address(es):

IP address: 192.168.1.132

DSW2#

```

DSW2#show arp
Protocol Address           Age (min)  Hardware Addr   Type   Interface
Internet 10.2.4.13             64         000d.bde3.6e00  ARPA   Port-
channel12
Internet 10.2.4.14             -          000b.fd20.ba00  ARPA   Port-
channel12
Internet 10.1.4.10             -          000b.fd20.ba00  ARPA
FastEthernet0/1
Internet 10.1.4.9              64         0019.5578.1cb3  ARPA
FastEthernet0/1
Internet 10.2.1.1              63         000d.bde3.6e00  ARPA   Vlan10
Internet 10.2.2.2              63         000d.bde3.6e00  ARPA   Vlan20
Internet 10.2.2.1              -          000b.fd20.ba00  ARPA   Vlan20
Internet 10.2.1.2              -          000b.fd20.ba00  ARPA   Vlan10
Internet 10.2.1.4              2          001c.238e.dbbc  ARPA   Vlan10
Internet 192.168.1.130        -          000b.fd20.ba00  ARPA   Vlan200
Internet 10.2.1.254           53         0000.0c07.ac0a  ARPA   Vlan10
DSW2#

```

```

DSW2#show ip arp
Protocol Address           Age (min)  Hardware Addr   Type   Interface
Internet 10.2.4.13             64      000d.bde3.6e00  ARPA   Port-
channel12
Internet 10.2.4.14             -       000b.fd20.ba00  ARPA   Port-
channel12
Internet 10.1.4.10             -       000b.fd20.ba00  ARPA
FastEthernet0/1
Internet 10.1.4.9              64      0019.5578.1cb3  ARPA
FastEthernet0/1
Internet 10.2.1.1              63      000d.bde3.6e00  ARPA   Vlan10
Internet 10.2.2.2              63      000d.bde3.6e00  ARPA   Vlan20
Internet 10.2.2.1              -       000b.fd20.ba00  ARPA   Vlan20
Internet 10.2.1.2              -       000b.fd20.ba00  ARPA   Vlan10
Internet 10.2.1.4              2       001c.238e.dbbc  ARPA   Vlan10
Internet 192.168.1.130        -       000b.fd20.ba00  ARPA   Vlan200
Internet 10.2.1.254           53      0000.0c07.ac0a  ARPA   Vlan10
DSW2#

```

```
DSW2#show ip interface
Vlan1 is administratively down, line protocol is down
  Internet protocol processing disabled
Vlan10 is up, line protocol is up
  Internet address is 10.2.1.2/24
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is 10.1.4.9
  Directed broadcast forwarding is disabled
  Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
  224.0.0.10
  Outgoing access list is not set
  Inbound access list is not set
  Proxy ARP is enabled
  Local Proxy ARP is disabled
  Security level is default
  Split horizon is enabled
  ICMP redirects are always sent
  ICMP unreachable are always sent
  ICMP mask replies are never sent
  IP fast switching is enabled
  IP CEF switching is enabled
  IP CEF switching turbo vector
  IP Null turbo vector
  IP multicast fast switching is enabled
  IP multicast distributed fast switching is disabled
  IP route-cache flags are Fast, CEF
  Router Discovery is disabled
  IP output packet accounting is disabled
  IP access violation accounting is disabled
  TCP/IP header compression is disabled
  RTP/IP header compression is disabled
  Probe proxy name replies are disabled
  Policy routing is disabled
  Network address translation is disabled
  BGP Policy Mapping is disabled
  WCCP Redirect outbound is disabled
  WCCP Redirect inbound is disabled
  WCCP Redirect exclude is disabled
Vlan20 is up, line protocol is up
  Internet address is 10.2.2.1/24
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is not set
  Directed broadcast forwarding is disabled
  Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
  224.0.0.10
  Outgoing access list is not set
  Inbound access list is not set
```

Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP Null turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Probe proxy name replies are disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
Vlan200 is up, line protocol is up
Internet address is 192.168.1.130/27
Broadcast address is 255.255.255.255
Address determined by non-volatile memory
MTU is 1500 bytes
Helper address is not set
Directed broadcast forwarding is disabled
Outgoing access list is not set
Inbound access list is not set
Proxy ARP is enabled
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP Null turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled

Probe proxy name replies are disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
FastEthernet0/1 is up, line protocol is up
 Internet address is 10.1.4.10/30
 Broadcast address is 255.255.255.255
 Address determined by non-volatile memory
 MTU is 1500 bytes
 Helper address is not set
 Directed broadcast forwarding is disabled
 Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
 224.0.0.10
 Outgoing access list is not set
 Inbound access list is not set
 Proxy ARP is enabled
 Local Proxy ARP is disabled
 Security level is default
 Split horizon is enabled
 ICMP redirects are always sent
 ICMP unreachable are always sent
 ICMP mask replies are never sent
 IP fast switching is enabled
 IP CEF switching is enabled
 IP CEF switching turbo vector
 IP Null turbo vector
 IP multicast fast switching is enabled
 IP multicast distributed fast switching is disabled
 IP route-cache flags are Fast, CEF
 Router Discovery is disabled
 IP output packet accounting is disabled
 IP access violation accounting is disabled
 TCP/IP header compression is disabled
 RTP/IP header compression is disabled
 Probe proxy name replies are disabled
 Policy routing is disabled
 Network address translation is disabled
 BGP Policy Mapping is disabled
 WCCP Redirect outbound is disabled
 WCCP Redirect inbound is disabled
 WCCP Redirect exclude is disabled
FastEthernet0/2 is administratively down, line protocol is down
 Inbound access list is not set
FastEthernet0/3 is down, line protocol is down
 Inbound access list is not set
FastEthernet0/4 is administratively down, line protocol is down
 Inbound access list is not set
FastEthernet0/5 is administratively down, line protocol is down
 Inbound access list is not set
FastEthernet0/6 is administratively down, line protocol is down


```
Inbound access list is not set
FastEthernet0/7 is administratively down, line protocol is down
  Inbound access list is not set
FastEthernet0/8 is administratively down, line protocol is down
  Inbound access list is not set
FastEthernet0/9 is administratively down, line protocol is down
  Inbound access list is not set
FastEthernet0/10 is administratively down, line protocol is down
  Inbound access list is not set
FastEthernet0/11 is administratively down, line protocol is down
  Inbound access list is not set
FastEthernet0/12 is administratively down, line protocol is down
  Inbound access list is not set
FastEthernet0/13 is administratively down, line protocol is down
  Inbound access list is not set
FastEthernet0/14 is administratively down, line protocol is down
  Inbound access list is not set
FastEthernet0/15 is down, line protocol is down
  Inbound access list is not set
FastEthernet0/16 is up, line protocol is up
  Inbound access list is not set
FastEthernet0/17 is up, line protocol is up
  Inbound access list is not set
FastEthernet0/18 is up, line protocol is up
  Inbound access list is not set
FastEthernet0/19 is up, line protocol is up
  Inbound access list is not set
FastEthernet0/20 is up, line protocol is up
  Inbound access list is not set
FastEthernet0/21 is up, line protocol is up
  Inbound access list is not set
FastEthernet0/22 is up, line protocol is up
  Internet protocol processing disabled
FastEthernet0/23 is up, line protocol is up
  Internet protocol processing disabled
FastEthernet0/24 is up, line protocol is up
  Internet protocol processing disabled
GigabitEthernet0/1 is administratively down, line protocol is down
  Inbound access list is not set
GigabitEthernet0/2 is administratively down, line protocol is down
  Inbound access list is not set
Port-channel12 is up, line protocol is up
  Internet address is 10.2.4.14/30
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is not set
  Directed broadcast forwarding is disabled
  Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
  224.0.0.13
    224.0.0.10
  Outgoing access list is not set
  Inbound access list is not set
  Proxy ARP is enabled
```

```
Local Proxy ARP is disabled
Security level is default
Split horizon is enabled
ICMP redirects are always sent
ICMP unreachable are always sent
ICMP mask replies are never sent
IP fast switching is enabled
IP CEF switching is enabled
IP CEF switching turbo vector
IP Null turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Probe proxy name replies are disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
Port-channel23 is up, line protocol is up
Port-channel24 is up, line protocol is up
Tunnel67 is up, line protocol is up
  Internet protocol processing disabled
DSW2#
```

```

DSW2#show ip cef
Prefix                Next Hop                Interface
0.0.0.0/0            10.1.4.9                FastEthernet0/1
0.0.0.0/32           receive
10.1.1.8/30          10.1.4.9                FastEthernet0/1
10.1.4.4/30          10.2.1.1                Vlan10
                    10.2.2.2                Vlan20
10.1.4.8/30          attached                FastEthernet0/1
10.1.4.8/32          receive                FastEthernet0/1
10.1.4.9/32          attached                FastEthernet0/1
10.1.4.10/32         receive                FastEthernet0/1
10.1.4.11/32         receive                FastEthernet0/1
10.2.1.0/24          attached                Vlan10
10.2.1.0/32          receive                Vlan10
10.2.1.1/32          attached                Vlan10
10.2.1.2/32          receive                Vlan10
10.2.1.4/32          attached                Vlan10
10.2.1.254/32        attached                Vlan10
10.2.1.255/32        receive                Vlan10
10.2.2.0/24          attached                Vlan20
10.2.2.0/32          receive                Vlan20
10.2.2.1/32          receive                Vlan20
10.2.2.2/32          attached                Vlan20
10.2.2.255/32        receive                Vlan20
10.2.4.12/30         attached                Port-channel12
10.2.4.12/32         receive                Port-channel12
10.2.4.13/32         attached                Port-channel12
10.2.4.14/32         receive                Port-channel12
10.2.4.15/32         receive                Port-channel12
192.168.1.128/27     attached                Vlan200
192.168.1.128/32     receive                Vlan200
192.168.1.130/32     receive                Vlan200
192.168.1.159/32     receive                Vlan200
224.0.0.0/4          multicast
224.0.0.0/24         receive
240.0.0.0/4          drop
255.255.255.255/32   receive
DSW2#

```

```
DSW2#show tcp statistics
Rcvd: 0 Total, 0 no port
      0 checksum error, 0 bad offset, 0 too short
      0 packets (0 bytes) in sequence
      0 dup packets (0 bytes)
      0 partially dup packets (0 bytes)
      0 out-of-order packets (0 bytes)
      0 packets (0 bytes) with data after window
      0 packets after close
      0 window probe packets, 0 window update packets
      0 dup ack packets, 0 ack packets with unsend data
      0 ack packets (0 bytes)
Sent: 0 Total, 0 urgent packets
      0 control packets (including 0 retransmitted)
      0 data packets (0 bytes)
      0 data packets (0 bytes) retransmitted
      0 data packets (0 bytes) fastretransmitted
      0 ack only packets (0 delayed)
      0 window probe packets, 0 window update packets
0 Connections initiated, 0 connections accepted, 0 connections
established
0 Connections closed (including 0 dropped, 0 embryonic dropped)
```

```
0 Total rxmt timeout, 0 connections dropped in rxmt timeout
0 Keepalive timeout, 0 keepalive probe, 0 Connections dropped in
keepalive
DSW2#
```

```
DSW2#show ip protocols
*** IP Routing is NSF aware ***
```

```
Routing Protocol is "eigrp 10"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  Default networks flagged in outgoing updates
  Default networks accepted from incoming updates
  Redistributing: eigrp 10
```

```
Address Family Protocol EIGRP-IPv4:(10)
  EIGRP metric weight K1=1, K2=1, K3=1, K4=1, K5=1
  EIGRP maximum hopcount 100
  EIGRP maximum metric variance 1
```

EIGRP NSF-aware route hold timer is 240
Topologies : 0(base)

Automatic network summarization is not in effect
Maximum path: 4

Routing for Networks:

10.1.4.10/32

10.2.1.2/32

10.2.2.1/32

10.2.4.14/32

Routing Information Sources:

Gateway	Distance	Last Update
10.2.4.13	90	01:00:34
10.1.4.9	90	01:00:34
10.2.1.1	90	01:00:34
10.2.2.2	90	01:00:34

Distance: internal 90 external 170

DSW2#

```
DSW2#show access-lists
Standard IP access list DENY_10
  10 deny 10.0.0.0, wildcard bits 0.255.255.255
  20 permit any
Standard IP access list DENY_ALL
  10 deny any
Standard IP access list PERMIT_10
  10 permit 10.0.0.0, wildcard bits 0.255.255.255
Standard IP access list PERMIT_ALL
  10 permit any
DSW2#
```

```
DSW2#show ip route eigrp
  10.0.0.0/8 is variably subnetted, 6 subnets, 2 masks
D EX 10.1.1.8/30 [170/1023] via 10.1.4.9, 01:01:04, FastEthernet0/1
D 10.1.4.4/30 [90/111] via 10.2.2.2, 01:04:20, Vlan20
  [90/111] via 10.2.1.1, 01:04:20, Vlan10
D*EX 0.0.0.0/0 [170/1023] via 10.1.4.9, 01:00:48, FastEthernet0/1
```



```
DSW2#show ip eigrp interfaces
EIGRP-IPv4:(10) interfaces for process 10
```

Pending Interface Routes	Peers	Xmit Queue Un/Reliable	Mean SRTT	Pacing Time Un/Reliable	Multicast Flow Timer
Fa0/1 0	1	0/0	1	0/1	50
Vl10 0	1	0/0	55	0/1	276
Vl20 0	1	0/0	35	0/1	176
Po12 0	1	0/0	1	0/1	50

```
DSW2#
```

```
DSW2#show vlan
```

VLAN Name	Status	Ports
-----	-----	-----
1 default	active	Fa0/2, Fa0/3, Fa0/4,
Fa0/5		Fa0/6, Fa0/7, Fa0/8,
Fa0/9		Fa0/10, Fa0/11, Fa0/12,
Fa0/13		Fa0/14, Fa0/15, Gi0/1,
Gi0/2		
10 VLAN0010	active	
20 VLAN0020	active	
200 VLAN0200	active	
1002 fddi-default	act/unsup	
1003 trcrf-default	act/unsup	
1004 fddinet-default	act/unsup	
1005 trbrf-default	act/unsup	

VLAN	Type	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Trans1	Trans2
1	enet	100001	1500	-	-	-	-	-	0	0
10	enet	100010	1500	-	-	-	-	-	0	0
20	enet	100020	1500	-	-	-	-	-	0	0
200	enet	100200	1500	-	-	-	-	-	0	0
1002	fddi	101002	1500	-	-	-	-	-	0	0
1003	trcrf	101003	4472	1005	3276	-	-	srb	0	0
1004	fdnet	101004	1500	-	-	-	ieee	-	0	0
1005	trbrf	101005	4472	-	-	15	ibm	-	0	0

VLAN	AREHops	STEHops	Backup	CRF
1003	7	7	off	

Remote SPAN VLANs

Primary	Secondary	Type	Ports

DSW2#

DSW2#show spanning-tree

VLAN0010

Spanning tree enabled protocol ieee

Root ID Priority 4106
 Address 000d.bde3.6e00
 Cost 18
 Port 66 (Port-channel23)
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec

Bridge ID Priority 8202 (priority 8192 sys-id-ext 10)
 Address 000b.fd20.ba00
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
 Aging Time 300

Interface	Role	Sts	Cost	Prio.Nbr	Type
Po23	Root	FWD	9	128.66	P2p

VLAN0020

Spanning tree enabled protocol ieee

Root ID Priority 4116
 Address 000b.fd20.ba00
 This bridge is the root
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec

Bridge ID Priority 4116 (priority 4096 sys-id-ext 20)
 Address 000b.fd20.ba00
 Hello Time 2 sec Max Age 20 sec Forward Delay 15 sec
 Aging Time 300

Interface	Role	Sts	Cost	Prio.Nbr	Type
Po24	Desg	FWD	9	128.67	P2p

VLAN0200

Spanning tree enabled protocol ieee

Root ID Priority 4296
 Address 000d.bde3.6e00
 Cost 18

```
Port          66 (Port-channel23)
Hello Time    2 sec  Max Age 20 sec  Forward Delay 15 sec
```

```
Bridge ID Priority    8392    (priority 8192 sys-id-ext 200)
Address       000b.fd20.ba00
Hello Time    2 sec  Max Age 20 sec  Forward Delay 15 sec
Aging Time    300
```

Interface	Role	Sts	Cost	Prio.Nbr	Type
Po23	Root	FWD	9	128.66	P2p
Po24	Altn	BLK	9	128.67	P2p

DSW2#

DSW2#show interfaces status

Port	Name	Status	Vlan	Duplex	Speed	Type
------	------	--------	------	--------	-------	------

Fa0/1	connected	routed	a-full	a-100
10/100BaseTX				
Fa0/2	disabled	1	auto	auto
10/100BaseTX				
Fa0/3	notconnect	1	auto	auto
10/100BaseTX				
Fa0/4	disabled	1	auto	auto
10/100BaseTX				
Fa0/5	disabled	1	auto	auto
10/100BaseTX				
Fa0/6	disabled	1	auto	auto
10/100BaseTX				
Fa0/7	disabled	1	auto	auto
10/100BaseTX				
Fa0/8	disabled	1	auto	auto
10/100BaseTX				
Fa0/9	disabled	1	auto	auto
10/100BaseTX				
Fa0/10	disabled	1	auto	auto
10/100BaseTX				
Fa0/11	disabled	1	auto	auto
10/100BaseTX				
Fa0/12	disabled	1	auto	auto
10/100BaseTX				
Fa0/13	disabled	1	auto	auto
10/100BaseTX				
Fa0/14	disabled	1	auto	auto
10/100BaseTX				
Fa0/15	notconnect	1	auto	auto
10/100BaseTX				
Fa0/16	connected	trunk	a-full	a-100
10/100BaseTX				
Fa0/17	connected	trunk	a-full	a-100
10/100BaseTX				
Fa0/18	connected	trunk	a-full	a-100
10/100BaseTX				
Fa0/19	connected	trunk	a-full	a-100
10/100BaseTX				
Fa0/20	connected	trunk	a-full	a-100
10/100BaseTX				
Fa0/21	connected	trunk	a-full	a-100
10/100BaseTX				
Fa0/22	connected	routed	a-full	a-100
10/100BaseTX				
Fa0/23	connected	routed	a-full	a-100
10/100BaseTX				
Fa0/24	connected	routed	a-full	a-100
10/100BaseTX				
Gi0/1	disabled	1	auto	auto
unknown				
Gi0/2	disabled	1	auto	auto
unknown				
Po12	connected	routed	a-full	a-100
Po23	connected	trunk	a-full	a-100

```
Po24          connected   trunk      a-full  a-100
DSW2#
```

```
DSW2#show interfaces switchport
```

```
Name: Fa0/2
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
```

Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/3
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/4
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none

Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/5
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/6
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off

Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/7
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/8
Switchport: Enabled

Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/9
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled

Appliance trust: none

Name: Fa0/10
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/11
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/12
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/13
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none

Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/14
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/15
Switchport: Enabled
Administrative Mode: static access
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: Off
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q

Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/16
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po24)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 20,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/17
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po24)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled

Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 20,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/18
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po24)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 20,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/19
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po23)

Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Fa0/20
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po23)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled

Appliance trust: none

Name: Fa0/21
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk (member of bundle Po23)
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Gi0/1
Switchport: Enabled
Administrative Mode: dynamic desirable
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled

Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Gi0/2
Switchport: Enabled
Administrative Mode: dynamic desirable
Operational Mode: down
Administrative Trunking Encapsulation: negotiate
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: ALL
Pruning VLANs Enabled: 2-1001
Capture Mode Disabled
Capture VLANs Allowed: ALL

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Po23
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none

Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 10,200
Pruning VLANs Enabled: 2-1001

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none

Name: Po24
Switchport: Enabled
Administrative Mode: trunk
Operational Mode: trunk
Administrative Trunking Encapsulation: dot1q
Operational Trunking Encapsulation: dot1q
Negotiation of Trunking: On
Access Mode VLAN: 1 (default)
Trunking Native Mode VLAN: 1 (default)
Administrative Native VLAN tagging: enabled
Voice VLAN: none
Administrative private-vlan host-association: none
Administrative private-vlan mapping: none
Administrative private-vlan trunk native VLAN: none
Administrative private-vlan trunk Native VLAN tagging: enabled
Administrative private-vlan trunk encapsulation: dot1q
Administrative private-vlan trunk normal VLANs: none
Administrative private-vlan trunk associations: none
Administrative private-vlan trunk mappings: none
Operational private-vlan: none
Trunking VLANs Enabled: 20,200
Pruning VLANs Enabled: 2-1001

Protected: false
Unknown unicast blocked: disabled
Unknown multicast blocked: disabled
Appliance trust: none
DSW2#

DSW2#show interfaces trunk

Port	Mode	Encapsulation	Status	Native vlan
Po23	on	802.1q	trunking	1
Po24	on	802.1q	trunking	1

Port	Vlans allowed on trunk
Po23	10,200
Po24	20,200

Port	Vlans allowed and active in management domain
Po23	10,200
Po24	20,200

Port	Vlans in spanning tree forwarding state and not pruned
Po23	10,200
Po24	20

DSW2#

```
DSW2#show vtp status
VTP Version                : running VTP2
Configuration Revision     : 0
Maximum VLANs supported locally : 1005
Number of existing VLANs   : 8
VTP Operating Mode        : Transparent
VTP Domain Name           : netlearning
VTP Pruning Mode          : Disabled
VTP V2 Mode                : Enabled
VTP Traps Generation      : Disabled
MD5 digest                 : 0x99 0xF7 0xCE 0x74 0x55 0xA6 0x6A 0xC7
Configuration last modified by 0.0.0.0 at 0-0-00 00:00:00
DSW2#
```

```
DSW2#show vtp password
VTP Password: cisco1
DSW2#
```

```
DSW2#show etherchannel detail
      Channel-group listing:
```

```
-----
Group: 12
```

```
-----
Group state = L3
Ports: 3    Maxports = 8
Port-channels: 1 Max Port-channels = 1
Protocol:    -
Minimum Links: 0
```

```
      Ports in the group:
```

```
-----
Port: Fa0/22
```

```
-----
Port state      = Up Mstr In-Bndl
Channel group   = 12          Mode = On          Gcchange = -
Port-channel    = Po12       GC   = -          Pseudo port-channel =
Po12
Port index      = 0          Load = 0x00          Protocol = -
```

```
Age of the port in the current state: 0d:01h:06m:45s
```

```
-----
Port: Fa0/23
```

```
-----
Port state      = Up Mstr In-Bndl
Channel group   = 12          Mode = On          Gcchange = -
Port-channel    = Po12       GC   = -          Pseudo port-channel =
Po12
Port index      = 0          Load = 0x00          Protocol = -
```

```
Age of the port in the current state: 0d:01h:06m:46s
```

```
-----
Port: Fa0/24
```

```
-----
Port state      = Up Mstr In-Bndl
Channel group   = 12          Mode = On          Gcchange = -
Port-channel    = Po12       GC   = -          Pseudo port-channel =
Po12
Port index      = 0          Load = 0x00          Protocol = -
```

```
Age of the port in the current state: 0d:01h:06m:46s
```

```
-----
      Port-channels in the group:
```

```
-----
Port-channel: Po12
```

```
-----
Age of the Port-channel   = 0d:01h:06m:53s
Logical slot/port        = 1/0          Number of ports = 3
```



```

GC = 0x00000000 HotStandBy port = null
Passive port list = Fa0/22 Fa0/23 Fa0/24
Port state = Port-channel L3-Ag Ag-Inuse
Protocol = -
Port security = Disabled

```

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/22	On	0
0	00	Fa0/23	On	0
0	00	Fa0/24	On	0

```

Time since last port bundled: 0d:01h:06m:46s Fa0/24
Time since last port Un-bundled: 0d:01h:06m:48s Fa0/24

```

Group: 23

```

-----
Group state = L2
Ports: 3 Maxports = 16
Port-channels: 1 Max Port-channels = 1
Protocol: LACP
Minimum Links: 0

```

Ports in the group:

Port: Fa0/19

```

-----
Port state = Up Mstr Assoc In-Bndl
Channel group = 23 Mode = Active Gcchange = -
Port-channel = Po23 GC = - Pseudo port-channel =
Po23
Port index = 0 Load = 0x00 Protocol = LACP

```

```

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast
LACPDUs.
A - Device is in active mode. P - Device is in passive
mode.

```

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number
Fa0/19	SA	bndl	32768	0x17	0x17	0x10

Partner's information:

Port	Flags	Priority	LACP port Dev ID	Admin Age	Oper key	Port Key	Port Number
Fa0/19	SA	bndl	32768	0x17	0x17	0x10	0x10

Fa0/19 SA 32768 0015.faac.46c0 8s 0x0 0x2 0x10
0x3D

Age of the port in the current state: 0d:01h:06m:42s

Port: Fa0/20

Port state = Up Mstr Assoc In-Bndl
Channel group = 23 Mode = Active Gcchange = -
Port-channel = Po23 GC = - Pseudo port-channel =
Po23
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast
LACPDUs.
A - Device is in active mode. P - Device is in passive
mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number
Fa0/20 0x3D	SA	bndl	32768	0x17	0x17	0x11

Partner's information:

Port	Flags	State	LACP port Priority	Dev ID	Age	Admin key	Oper Key	Port Number
Fa0/20 0x3D	SA		32768	0015.faac.46c0	0s	0x0	0x2	0x11

Age of the port in the current state: 0d:01h:06m:42s

Port: Fa0/21

Port state = Up Mstr Assoc In-Bndl
Channel group = 23 Mode = Active Gcchange = -
Port-channel = Po23 GC = - Pseudo port-channel =
Po23
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast
LACPDUs.
A - Device is in active mode. P - Device is in passive
mode.

Local information:

Port	Flags	State	LACP port	Admin	Oper	Port
Port	Flags	State	Priority	Key	Key	Number
Fa0/21	SA	bndl	32768	0x17	0x17	0x12

Partner's information:

Port	Flags	State	LACP port	Admin	Oper	Port		
Port	Flags	State	Priority	Dev ID	Age	key	Key	Number
Fa0/21	SA		32768	0015.faac.46c0	6s	0x0	0x2	0x12

Age of the port in the current state: 0d:01h:06m:43s

Port-channels in the group:

Port-channel: Po23 (Primary Aggregator)

Age of the Port-channel = 0d:01h:06m:58s
 Logical slot/port = 1/1 Number of ports = 3
 HotStandBy port = null
 Port state = Port-channel Ag-Inuse
 Protocol = LACP
 Port security = Disabled

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/19	Active	0
0	00	Fa0/20	Active	0
0	00	Fa0/21	Active	0

Time since last port bundled: 0d:01h:06m:44s Fa0/20

Group: 24

Group state = L2
 Ports: 3 Maxports = 8
 Port-channels: 1 Max Port-channels = 1
 Protocol: PAgP
 Minimum Links: 0

Ports in the group:

Port: Fa0/16

Port state = Up Mstr In-Bndl
Channel group = 24 Mode = Desirable-Sl Gcchange = 0
Port-channel = Po24 GC = 0x00180001 Pseudo port-channel = Po24
Port index = 0 Load = 0x00 Protocol = PAgP

Flags: S - Device is sending Slow hello. C - Device is in Consistent state.
A - Device is in Auto mode. P - Device learns on physical port.
d - PAgP is down.
Timers: H - Hello timer is running. Q - Quit timer is running.
S - Switching timer is running. I - Interface timer is running.

Local information:

Group	Port	Flags	State	Timers	Hello Interval	Partner Count	PAgP Priority	Learning Method
	Fa0/16	SC	U6/S7	H	30s	1	128	Any 32

Partner's information:

Group	Partner	Partner	Partner	Partner
Port	Name	Device ID	Port	Age Flags
Fa0/16	ASW2	0015.fab8.2880	Fa0/19	7s SC

10001

Age of the port in the current state: 0d:01h:06m:47s

Port: Fa0/17

Port state = Up Mstr In-Bndl
Channel group = 24 Mode = Desirable-Sl Gcchange = 0
Port-channel = Po24 GC = 0x00180001 Pseudo port-channel = Po24
Port index = 0 Load = 0x00 Protocol = PAgP

Flags: S - Device is sending Slow hello. C - Device is in Consistent state.
A - Device is in Auto mode. P - Device learns on physical port.
d - PAgP is down.
Timers: H - Hello timer is running. Q - Quit timer is running.
S - Switching timer is running. I - Interface timer is running.

Local information:

Group	Hello	Partner	PAgP	Learning
-------	-------	---------	------	----------

Port	Flags	State	Timers	Interval	Count	Priority	Method	
Fa0/17	SC	U6/S7	H	30s	1	128	Any	32

Partner's information:

Group	Partner	Partner	Partner	Partner
Port	Name	Device ID	Port	Age
Cap.				Flags
Fa0/17	ASW2	0015.fab8.2880	Fa0/20	8s
10001				SC

Age of the port in the current state: 0d:01h:06m:48s

Port: Fa0/18

Port state = Up Mstr In-Bndl
Channel group = 24 Mode = Desirable-Sl Gcchange = 0
Port-channel = Po24 GC = 0x00180001 Pseudo port-channel = Po24
Port index = 0 Load = 0x00 Protocol = PAgP

Flags: S - Device is sending Slow hello. C - Device is in Consistent state.
A - Device is in Auto mode. P - Device learns on physical port.
d - PAgP is down.
Timers: H - Hello timer is running. Q - Quit timer is running.
S - Switching timer is running. I - Interface timer is running.

Local information:

Group	Flags	State	Timers	Interval	Count	Priority	Method	
Fa0/18	SC	U6/S7	H	30s	1	128	Any	32

Partner's information:

Group	Partner	Partner	Partner	Partner
Port	Name	Device ID	Port	Age
Cap.				Flags
Fa0/18	ASW2	0015.fab8.2880	Fa0/21	15s
10001				SC

Age of the port in the current state: 0d:01h:06m:49s

Port-channels in the group:

Port-channel: Po24

Age of the Port-channel = 0d:01h:07m:03s
Logical slot/port = 1/2 Number of ports = 3
GC = 0x00180001 HotStandBy port = null
Port state = Port-channel Ag-Inuse
Protocol = PAgP
Port security = Disabled

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/16	Desirable-S1	0
0	00	Fa0/17	Desirable-S1	0
0	00	Fa0/18	Desirable-S1	0

Time since last port bundled: 0d:01h:06m:51s Fa0/18

DSW2#

```
DSW2#show standby
Vlan10 - Group 10
  State is Standby
    1 state change, last state change 01:05:58
  Virtual IP address is 10.2.1.254
  Active virtual MAC address is 0000.0c07.ac0a
    Local virtual MAC address is 0000.0c07.ac0a (v1 default)
  Hello time 3 sec, hold time 10 sec
    Next hello sent in 1.500 secs
  Preemption disabled
  Active router is 10.2.1.1, priority 110 (expires in 7.544 sec)
  Standby router is local
  Priority 20 (configured 20)
  IP redundancy name is "hsrp-Vl10-10" (default)
DSW2#
```

DSW2#show standby brief

P indicates configured to preempt.

Interface	Grp	Prio	P	State	Active	Standby	Virtual
Vl10	10	20		Standby	10.2.1.1	local	

IP
10.2.1.254
DSW2#

DSW2#show power inline

Available:360(w) Used:0(w) Remaining:360(w)

Interface	Admin	Oper	Power (Watts)	Device	Class	Max
Fa0/1	auto	off	0.0	n/a	n/a	15.4
Fa0/2	auto	off	0.0	n/a	n/a	15.4
Fa0/3	auto	off	0.0	n/a	n/a	15.4
Fa0/4	auto	off	0.0	n/a	n/a	15.4

Fa0/5	auto	off	0.0	n/a	n/a	15.4
Fa0/6	auto	off	0.0	n/a	n/a	15.4
Fa0/7	auto	off	0.0	n/a	n/a	15.4
Fa0/8	auto	off	0.0	n/a	n/a	15.4
Fa0/9	auto	off	0.0	n/a	n/a	15.4
Fa0/10	auto	off	0.0	n/a	n/a	15.4
Fa0/11	auto	off	0.0	n/a	n/a	15.4
Fa0/12	auto	off	0.0	n/a	n/a	15.4
Fa0/13	auto	off	0.0	n/a	n/a	15.4
Fa0/14	auto	off	0.0	n/a	n/a	15.4
Fa0/15	auto	off	0.0	n/a	n/a	15.4
Fa0/16	auto	off	0.0	n/a	n/a	15.4
Fa0/17	auto	off	0.0	n/a	n/a	15.4
Fa0/18	auto	off	0.0	n/a	n/a	15.4
Fa0/19	auto	off	0.0	n/a	n/a	15.4
Fa0/20	auto	off	0.0	n/a	n/a	15.4
Fa0/21	auto	off	0.0	n/a	n/a	15.4
Fa0/22	auto	off	0.0	n/a	n/a	15.4
Fa0/23	auto	off	0.0	n/a	n/a	15.4
Fa0/24	auto	off	0.0	n/a	n/a	15.4
DSW2#						

```
DSW2#show spanning-tree inconsistentports
```

Name	Interface	Inconsistency
------	-----------	---------------

Number of inconsistent ports (segments) in the system : 0

```
DSW2#
```

```
DSW2#show spanning-tree summary
```

```
Switch is in pvst mode
```

```
Root bridge for: VLAN0020
```

```
Extended system ID          is enabled
```

```
Portfast Default            is disabled
```

```
PortFast BPDU Guard Default is disabled
```

```
Portfast BPDU Filter Default is disabled
```

```
Loopguard Default          is disabled
EtherChannel misconfig guard is enabled
UplinkFast                 is disabled
BackboneFast               is disabled
Configured Pathcost method used is short
```

Name	Blocking	Listening	Learning	Forwarding	STP Active
VLAN0010	0	0	0	1	1
VLAN0020	0	0	0	1	1
VLAN0200	1	0	0	1	2
3 vlans	1	0	0	3	4

DSW2#

DSW2#show udld

Interface Fa0/1

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/2

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/3

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/4

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/5

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/6

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/7

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/8

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/9

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/10

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/11

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/12

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/13

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/14

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/15

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/16

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/17

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/18

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/19

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/20

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/21

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/22

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/23

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Fa0/24

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Gi0/1

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

Interface Gi0/2

Port enable administrative configuration setting: Disabled
Port enable operational state: Disabled
Current bidirectional state: Unknown

DSW2#

DSW2#show etherchannel summary

Flags: D - down P - bundled in port-channel
I - stand-alone s - suspended
H - Hot-standby (LACP only)
R - Layer3 S - Layer2
U - in use f - failed to allocate aggregator

M - not in use, minimum links not met
u - unsuitable for bundling
w - waiting to be aggregated
d - default port

Number of channel-groups in use: 3

Number of aggregators: 3

Group	Port-channel	Protocol	Ports		
12	Po12 (RU)	-	Fa0/22 (P)	Fa0/23 (P)	Fa0/24 (P)
23	Po23 (SU)	LACP	Fa0/19 (P)	Fa0/20 (P)	Fa0/21 (P)
24	Po24 (SU)	PAgP	Fa0/16 (P)	Fa0/17 (P)	Fa0/18 (P)

DSW2#

```
DSW2#show etherchannel protocol
      Channel-group listing:
```

```
-----
```

```
Group: 12
```

```
-----
```

```
Protocol: - (Mode ON)
```

```
Group: 23
```

```
-----
```

```
Protocol: LACP
```

```
Group: 24
```

```
-----
```

```
Protocol: PAgP
```

```
DSW2#
```



```
DSW2#show etherchannel port
      Channel-group listing:
      -----
```

```
Group: 12
-----
```

```
      Ports in the group:
      -----
```

```
Port: Fa0/22
-----
```

```
Port state      = Up Mstr In-Bndl
Channel group   = 12           Mode = On           Gchange = -
Port-channel    = Po12        GC   = -           Pseudo port-channel =
Po12
Port index      = 0           Load = 0x00        Protocol = -
```

```
Age of the port in the current state: 0d:01h:08m:04s
```

```
Port: Fa0/23
-----
```

```

Port state      = Up Mstr In-Bndl
Channel group  = 12          Mode = On          Gcchange = -
Port-channel   = Po12       GC   = -          Pseudo port-channel =
Po12
Port index     = 0          Load = 0x00          Protocol = -

```

Age of the port in the current state: 0d:01h:08m:04s

Port: Fa0/24

```

Port state      = Up Mstr In-Bndl
Channel group  = 12          Mode = On          Gcchange = -
Port-channel   = Po12       GC   = -          Pseudo port-channel =
Po12
Port index     = 0          Load = 0x00          Protocol = -

```

Age of the port in the current state: 0d:01h:08m:04s

Group: 23

Ports in the group:

Port: Fa0/19

```

Port state      = Up Mstr Assoc In-Bndl
Channel group  = 23          Mode = Active      Gcchange = -
Port-channel   = Po23       GC   = -          Pseudo port-channel =
Po23
Port index     = 0          Load = 0x00          Protocol = LACP

```

Flags: S - Device is sending Slow LACPDU's F - Device is sending fast LACPDU's.

 A - Device is in active mode. P - Device is in passive mode.

Local information:

Port	Flags	State	LACP port Priority	Admin Key	Oper Key	Port Number
Fa0/19	SA	bndl	32768	0x17	0x17	0x10
0x3D						

Partner's information:

Port	Flags	Priority	LACP port Dev ID	Admin Age	Oper key	Port Key	Port Number
State							

Fa0/19 SA 32768 0015.faac.46c0 4s 0x0 0x2 0x10
0x3D

Age of the port in the current state: 0d:01h:08m:00s

Port: Fa0/20

Port state = Up Mstr Assoc In-Bndl
Channel group = 23 Mode = Active Gcchange = -
Port-channel = Po23 GC = - Pseudo port-channel =
Po23
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast
LACPDUs.
A - Device is in active mode. P - Device is in passive
mode.

Local information:

Port	Flags	State	LACP port	Admin	Oper	Port
Port	Flags	State	Priority	Key	Key	Number
Fa0/20	SA	bndl	32768	0x17	0x17	0x11
0x3D						

Partner's information:

Port	Flags	State	LACP port	Admin	Oper	Port		
Port	Flags	State	Priority	Dev ID	Age	key	Key	Number
Fa0/20	SA		32768	0015.faac.46c0	24s	0x0	0x2	0x11
0x3D								

Age of the port in the current state: 0d:01h:07m:59s

Port: Fa0/21

Port state = Up Mstr Assoc In-Bndl
Channel group = 23 Mode = Active Gcchange = -
Port-channel = Po23 GC = - Pseudo port-channel =
Po23
Port index = 0 Load = 0x00 Protocol = LACP

Flags: S - Device is sending Slow LACPDUs F - Device is sending fast
LACPDUs.
A - Device is in active mode. P - Device is in passive
mode.

Local information:

Port	Flags	State	LACP port	Admin	Oper	Port
Port	Flags	State	Priority	Key	Key	Number
Fa0/21	SA	bndl	32768	0x17	0x17	0x12

Partner's information:

Port	Flags	State	LACP port	Admin	Oper	Port		
Port	Flags	State	Priority	Dev ID	Age	key	Key	Number
Fa0/21	SA		32768	0015.faac.46c0	3s	0x0	0x2	0x12

Age of the port in the current state: 0d:01h:08m:00s

Group: 24

Ports in the group:

Port: Fa0/16

Port state = Up Mstr In-Bndl
Channel group = 24 Mode = Desirable-Sl Gcchange = 0
Port-channel = Po24 GC = 0x00180001 Pseudo port-channel = Po24
Port index = 0 Load = 0x00 Protocol = PAgP

Flags: S - Device is sending Slow hello. C - Device is in Consistent state.
A - Device is in Auto mode. P - Device learns on physical port.
d - PAgP is down.
Timers: H - Hello timer is running. Q - Quit timer is running.
S - Switching timer is running. I - Interface timer is running.

Local information:

Group	Flags	State	Timers	Hello Interval	Partner Count	PAgP Priority	Learning Method
Fa0/16	SC	U6/S7	H	30s	1	128	Any 32

Partner's information:

Group	Partner Name	Partner Device ID	Partner Port	Partner Age	Partner Flags
-------	--------------	-------------------	--------------	-------------	---------------

Fa0/16 ASW2 0015.fab8.2880 Fa0/19 26s SC
10001

Age of the port in the current state: 0d:01h:08m:03s

Port: Fa0/17

Port state = Up Mstr In-Bndl
Channel group = 24 Mode = Desirable-S1 Gcchange = 0
Port-channel = Po24 GC = 0x00180001 Pseudo port-channel =
Po24
Port index = 0 Load = 0x00 Protocol = PAgP

Flags: S - Device is sending Slow hello. C - Device is in Consistent
state.

A - Device is in Auto mode. P - Device learns on physical
port.

d - PAgP is down.

Timers: H - Hello timer is running. Q - Quit timer is running.

S - Switching timer is running. I - Interface timer is
running.

Local information:

Group	Flags	State	Timers	Hello Interval	Partner Count	PAgP Priority	Learning Method
Fa0/17	SC	U6/S7	H	30s	1	128	Any 32

Partner's information:

Group	Partner Name	Partner Device ID	Partner Port	Partner Age	Partner Flags
Fa0/17 10001	ASW2	0015.fab8.2880	Fa0/20	25s	SC

Age of the port in the current state: 0d:01h:08m:04s

Port: Fa0/18

Port state = Up Mstr In-Bndl
Channel group = 24 Mode = Desirable-S1 Gcchange = 0
Port-channel = Po24 GC = 0x00180001 Pseudo port-channel =
Po24
Port index = 0 Load = 0x00 Protocol = PAgP

Flags: S - Device is sending Slow hello. C - Device is in Consistent
state.

A - Device is in Auto mode. P - Device learns on physical
port.

d - PAgP is down.
 Timers: H - Hello timer is running. Q - Quit timer is running.
 S - Switching timer is running. I - Interface timer is running.

Local information:

Group	Port	Flags	State	Timers	Hello Interval	Partner Count	PAgP Priority	Learning Method	
	Fa0/18	SC	U6/S7	H	30s	1	128	Any	32

Partner's information:

Group	Partner Port	Partner Name	Partner Device ID	Partner Port	Partner Age	Partner Flags
	Fa0/18	ASW2	0015.fab8.2880	Fa0/21	12s	SC
	10001					

Age of the port in the current state: 0d:01h:08m:06s

DSW2#

```
DSW2#show etherchannel load-balance
EtherChannel Load-Balancing Configuration:
    src-mac
```

```
EtherChannel Load-Balancing Addresses Used Per-Protocol:
Non-IP: Source MAC address
    IPv4: Source MAC address
```

```
DSW2#
```

```
DSW2#show etherchannel port-channel
    Channel-group listing:
```

Group: 12

Port-channels in the group:

Port-channel: Po12

Age of the Port-channel = 0d:01h:08m:33s
Logical slot/port = 1/0 Number of ports = 3
GC = 0x00000000 HotStandBy port = null
Passive port list = Fa0/22 Fa0/23 Fa0/24
Port state = Port-channel L3-Ag Ag-Inuse
Protocol = -
Port security = Disabled

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/22	On	0
0	00	Fa0/23	On	0
0	00	Fa0/24	On	0

Time since last port bundled: 0d:01h:08m:25s Fa0/24
Time since last port Un-bundled: 0d:01h:08m:27s Fa0/24

Group: 23

Port-channels in the group:

Port-channel: Po23 (Primary Aggregator)

Age of the Port-channel = 0d:01h:08m:34s
Logical slot/port = 1/1 Number of ports = 3
HotStandBy port = null
Port state = Port-channel Ag-Inuse
Protocol = LACP
Port security = Disabled

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/19	Active	0
0	00	Fa0/20	Active	0
0	00	Fa0/21	Active	0

Time since last port bundled: 0d:01h:08m:20s Fa0/20

Group: 24

Port-channels in the group:

Port-channel: Po24

Age of the Port-channel = 0d:01h:08m:34s
Logical slot/port = 1/2 Number of ports = 3
GC = 0x00180001 HotStandBy port = null
Port state = Port-channel Ag-Inuse
Protocol = PAgP
Port security = Disabled

Ports in the Port-channel:

Index	Load	Port	EC state	No of bits
0	00	Fa0/16	Desirable-S1	0
0	00	Fa0/17	Desirable-S1	0
0	00	Fa0/18	Desirable-S1	0

Time since last port bundled: 0d:01h:08m:22s Fa0/18

DSW2#

DSW2#show pagp neighbor

Flags: S - Device is sending Slow hello. C - Device is in Consistent state.

A - Device is in Auto mode. P - Device learns on physical port.

Channel group 24 neighbors

Group	Partner	Partner	Partner	Partner
Port	Name	Device ID	Port	Age Flags
Fa0/16 10001	ASW2	0015.fab8.2880	Fa0/19	1s SC
Fa0/17 10001	ASW2	0015.fab8.2880	Fa0/20	24s SC
Fa0/18 10001	ASW2	0015.fab8.2880	Fa0/21	10s SC

DSW2#

DSW2#show lacp neighbor

Flags: S - Device is requesting Slow LACPDUs

F - Device is requesting Fast LACPDUs

A - Device is in Active mode P - Device is in Passive mode

Channel group 23 neighbors

Partner's information:

Port	Flags	LACP port Priority	Dev ID	Age	Admin key	Oper Key	Port Number
Fa0/19 0x3D	SA	32768	0015.faac.46c0	19s	0x0	0x2	0x10
Fa0/20 0x3D	SA	32768	0015.faac.46c0	6s	0x0	0x2	0x11
Fa0/21 0x3D	SA	32768	0015.faac.46c0	14s	0x0	0x2	0x12

DSW2#

DSW2#show port-security

Secure Port	MaxSecureAddr	CurrentAddr	SecurityViolation	Security
Action	(Count)	(Count)	(Count)	

--

--
Total Addresses in System (excluding one mac per port) : 0
Max Addresses limit in System (excluding one mac per port) : 5120
DSW2#

```
DSW2#show port-security address
      Secure Mac Address Table
```

```
-----
```

Vlan	Mac Address	Type	Ports	Remaining Age (mins)
----	-----	----	----	-----

```
-----
```

```
Total Addresses in System (excluding one mac per port) : 0
Max Addresses limit in System (excluding one mac per port) : 5120
DSW2#
```

```
DSW2#
DSW2#show ipv6 interface brief
Vlan1 [administratively down/down]
      unassigned
```

Vlan10	[up/up]
unassigned	
Vlan20	[up/up]
unassigned	
Vlan200	[up/up]
unassigned	
FastEthernet0/1	[up/up]
unassigned	
FastEthernet0/2	[administratively down/down]
unassigned	
FastEthernet0/3	[down/down]
unassigned	
FastEthernet0/4	[administratively down/down]
unassigned	
FastEthernet0/5	[administratively down/down]
unassigned	
FastEthernet0/6	[administratively down/down]
unassigned	
FastEthernet0/7	[administratively down/down]
unassigned	
FastEthernet0/8	[administratively down/down]
unassigned	
FastEthernet0/9	[administratively down/down]
unassigned	
FastEthernet0/10	[administratively down/down]
unassigned	
FastEthernet0/11	[administratively down/down]
unassigned	
FastEthernet0/12	[administratively down/down]
unassigned	
FastEthernet0/13	[administratively down/down]
unassigned	
FastEthernet0/14	[administratively down/down]
unassigned	
FastEthernet0/15	[down/down]
unassigned	
FastEthernet0/16	[up/up]
unassigned	
FastEthernet0/17	[up/up]
unassigned	
FastEthernet0/18	[up/up]
unassigned	
FastEthernet0/19	[up/up]
unassigned	
FastEthernet0/20	[up/up]
unassigned	
FastEthernet0/21	[up/up]
unassigned	
FastEthernet0/22	[up/up]
unassigned	
FastEthernet0/23	[up/up]
unassigned	
FastEthernet0/24	[up/up]
unassigned	

```
GigabitEthernet0/1      [administratively down/down]
  unassigned
GigabitEthernet0/2      [administratively down/down]
  unassigned
Port-channel12          [up/up]
  unassigned
Port-channel23          [up/up]
  unassigned
Port-channel24          [up/up]
  unassigned
Tunnel67                [up/up]
  FE80::20B:FDFE:FE20:BA00
  2026::3:2
DSW2#
```

```
DSW2#ping ipv6 2026::12:1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::12:1, timeout is 2 seconds:
```

```
.....  
Success rate is 0 percent (0/5)  
DSW2#
```

```
DSW2#ping ipv6 2026::12:2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::12:2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 144/144/148
```

```
ms
```

```
DSW2#
```



```
DSW2#ping ipv6 2026::1:1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::1:1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 144/146/152  
ms
```

```
DSW2#
```

```
DSW2#ping ipv6 2026::1:2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::1:2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 80/80/80 ms
```

```
DSW2#
```

```
DSW2#ping ipv6 2026::3:1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::3:1, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 0/0/4 ms
```

```
DSW2#ping ipv6 2026::34:1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::34:1, timeout is 2 seconds:
```

```
!!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 80/80/84 ms
```

```
DSW2#ping ipv6 2026::34:2
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 2026::34:2, timeout is 2 seconds:  
!!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 0/3/4 ms  
DSW2#
```

```
DSW2#ping ipv6 2026::2:1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::2:1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 4/4/4 ms
```

```
DSW2#
```

```
DSW2#ping ipv6 2026::2:2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::2:2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 0/2/4 ms
```

```
DSW2#
```

```
DSW2#ping ipv6 2026::3:2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::3:2, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 0/0/0 ms
```

```
DSW2#
```

```
DSW2#show ipv6 route
```

```
IPv6 Routing Table - Default - 7 entries
```

```
Codes: C - Connected, L - Local, S - Static, U - Per-user Static route
```

```
       R - RIP, D - EIGRP, EX - EIGRP external
```

```
R    2026::1:0/122 [120/7]
```

```
     via FE80::20D:BDFF:FEE3:6E00, Tunnel67
```

```
R 2026::2:0/122 [120/2]
   via FE80::20D:BDFE:FEE3:6E00, Tunnel67
C 2026::3:0/122 [0/0]
   via Tunnel67, directly connected
L 2026::3:2/128 [0/0]
   via Tunnel67, receive
R 2026::12:0/122 [120/7]
   via FE80::20D:BDFE:FEE3:6E00, Tunnel67
R 2026::34:0/122 [120/7]
   via FE80::20D:BDFE:FEE3:6E00, Tunnel67
L FF00::/8 [0/0]
   via Null0, receive
DSW2#
```

```
DSW2#show ipv6 rip RIPNG
RIP process "RIPNG", port 521, multicast-group FF02::9, pid 171
  Administrative distance is 120. Maximum paths is 16
  Updates every 30 seconds, expire after 180
  Holddown lasts 0 seconds, garbage collect after 120
```



```
Split horizon is on; poison reverse is off
Default routes are not generated
Periodic updates 323, trigger updates 4
Interfaces:
  Tunnel67
Redistribution:
  None
DSW2#
```