

```
R4#
R4#show running-config
Building configuration...

Current configuration : 2828 bytes
!
! Last configuration change at 21:05:42 UTC Thu Jun 10 2010
! NVRAM config last updated at 21:05:44 UTC Thu Jun 10 2010
!
version 12.4
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname R4
!
boot-start-marker
boot system flash:c1841-advipservicesk9-mz.124-25b.bin
boot-end-marker
!
no logging console
enable secret 5 $1$/jV1$vYpms8yDHgGeGsdSbjts//
!
no aaa new-model
ip cef
!
!
no ip dhcp use vrf connected
ip dhcp excluded-address 10.2.1.1 10.2.1.3
ip dhcp excluded-address 10.2.1.254
!
ip dhcp pool VLAN10
    network 10.2.1.0 255.255.255.0
    default-router 10.2.1.254
    domain-name netlearning.com.mx
    dns-server 209.65.200.243
!
!
ip multicast-routing
ip auth-proxy max-nodata-conns 3
ip admission max-nodata-conns 3
!
ipv6 unicast-routing
!
!
!
!
ip ftp username netlearning
ip ftp password netpass
!
!
!
interface Tunnel134
```

```
no ip address
ipv6 address 2026::34:2/122
ipv6 enable
ipv6 ospf 6 area 34
tunnel source Serial0/1/0.34
tunnel destination 10.1.1.9
tunnel mode ipv6ip
!
interface Tunnel46
no ip address
ipv6 address 2026::2:1/122
ipv6 enable
ipv6 rip RIPNG enable
tunnel source 10.1.4.5
tunnel destination 10.1.4.6
!
interface FastEthernet0/0
ip address 10.1.4.5 255.255.255.252
ip pim sparse-dense-mode
duplex auto
speed auto
!
interface FastEthernet0/1
ip address 10.1.4.9 255.255.255.252
ip pim sparse-dense-mode
duplex auto
speed auto
!
interface Serial0/0/0
no ip address
clock rate 56000
!
interface Serial0/0/1
no ip address
clock rate 56000
!
interface Serial0/1/0
no ip address
encapsulation frame-relay
!
interface Serial0/1/0.34 point-to-point
ip address 10.1.1.10 255.255.255.252
ip pim sparse-dense-mode
frame-relay interface-dlci 403
!
router eigrp 10
 redistribute ospf 1 metric 10000 100 255 1 1500
 network 10.1.4.5 0.0.0.0
 network 10.1.4.9 0.0.0.0
 metric weights 0 1 1 1 1 1
 no auto-summary
 eigrp router-id 4.4.4.4
!
router ospf 1
```

```
router-id 4.4.4.4
log-adjacency-changes
area 34 nssa
redistribute eigrp 10 subnets
network 10.1.1.10 0.0.0.0 area 34
!
ip forward-protocol nd
ip route 0.0.0.0 0.0.0.0 192.168.20.1
!
!
ip http server
no ip http secure-server
!
ip access-list standard DENY_10
deny 10.0.0.0 0.255.255.255
permit any
ip access-list standard DENY_ALL
deny any
ip access-list standard PERMIT_10
permit 10.0.0.0 0.255.255.255
ip access-list standard PERMIT_ALL
permit any
!
ipv6 router ospf 6
router-id 4.4.4.4
log-adjacency-changes
redistribute connected
redistribute rip RIPNG
!
ipv6 router rip RIPNG
redistribute connected metric 5
redistribute ospf 6 metric 5
!
!
!
!
control-plane
!
!
!
line con 0
exec-timeout 0 0
line aux 0
line vty 0 4
exec-timeout 0 0
no login
!
scheduler allocate 20000 1000
ntp clock-period 17177683
ntp server 10.1.1.1
end
```

R4#

```
R4#ping 209.65.200.241
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.241, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 224/226/228  
ms
```

```
R4#
```

```
R4#ping 209.65.200.226
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.226, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 224/226/228  
ms
```

```
R4#
```

```
R4#ping 209.65.200.225
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 209.65.200.225, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/195/196  
ms
```

```
R4#
```

```
R4#ping 10.1.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 192/194/196
```

```
ms
```

```
R4#
```

```
R4#ping 10.1.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.2, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/129/132
```

```
ms
```

```
R4#
```

```
R4#ping 10.1.1.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.5, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/131/136
```

```
ms
```

R4#

R4#ping 10.1.1.6

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 10.1.1.6, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 64/65/68 ms

R4#

```
R4#ping 10.1.1.9
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.9, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 64/66/68 ms
```

```
R4#
```

```
R4#ping 10.1.1.10
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.1.10, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 128/130/136  
ms
```

```
R4#
```

R4#ping 10.1.4.10

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 10.1.4.10, timeout is 2 seconds:

!!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms

R4#

R4#ping 10.1.4.9

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 10.1.4.9, timeout is 2 seconds:

!!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/4 ms

R4#

R4#ping 10.1.4.6

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 10.1.4.6, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms

R4#

```
R4#ping 10.1.4.5
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.1.4.5, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/1 ms
```

```
R4#
```

```
R4#ping 10.2.1.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
```

```
R4#
```

```
R4#ping 10.2.2.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.2, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
```

```
R4#
```

```
R4#ping 10.2.1.254
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.254, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
```

```
R4#
```

```
R4#ping 10.2.4.14
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.14, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
```

```
R4#
```

```
R4#ping 10.2.4.13
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.4.13, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
```

```
R4#
```

```
R4#ping 10.2.1.2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
```

```
R4#
```

```
R4#ping 10.2.2.1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.2.1, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/2/4 ms
```

```
R4#
```

```
R4#ping 10.2.1.4
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 10.2.1.4, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 1/1/1 ms
```

```
R4#
```

```
R4#show ip interface brief
```

Interface	IP-Address	OK?	Method	Status
Protocol				
FastEthernet0/0	10.1.4.5	YES	NVRAM	up
up				
FastEthernet0/1	10.1.4.9	YES	NVRAM	up
up				
Serial0/0/0	unassigned	YES	NVRAM	down
down				
Serial0/0/1	unassigned	YES	NVRAM	down
down				
Serial0/1/0	unassigned	YES	NVRAM	up
up				
Serial0/1/0.34	10.1.1.10	YES	NVRAM	up
up				
Tunnel34	unassigned	YES	NVRAM	up
up				
Tunnel46	unassigned	YES	NVRAM	up
up				

R4#

R4#show ip route

Codes: C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS
level-2
ia - IS-IS inter area, * - candidate default, U - per-user static
route
o - ODR, P - periodic downloaded static route

Gateway of last resort is 10.1.1.9 to network 0.0.0.0

10.0.0.0/8 is variably subnetted, 6 subnets, 2 masks
D 10.2.4.12/30 [90/120] via 10.1.4.10, 00:38:52, FastEthernet0/1
[90/120] via 10.1.4.6, 00:38:52, FastEthernet0/0
C 10.1.1.8/30 is directly connected, Serial0/1/0.34

```

C      10.1.4.8/30 is directly connected, FastEthernet0/1
D      10.2.1.0/24 [90/111] via 10.1.4.10, 00:38:18, FastEthernet0/1
      [90/111] via 10.1.4.6, 00:38:18, FastEthernet0/0
D      10.2.2.0/24 [90/111] via 10.1.4.10, 00:38:20, FastEthernet0/1
      [90/111] via 10.1.4.6, 00:38:20, FastEthernet0/0
C      10.1.4.4/30 is directly connected, FastEthernet0/0
O*IA 0.0.0.0/0 [110/65] via 10.1.1.9, 00:34:46, Serial0/1/0.34
R4#

```

```

R4#show processes cpu
CPU utilization for five seconds: 1%/0%; one minute: 0%; five minutes: 0%
  PID Runtime(ms)   Invoked    uSecs   5Sec   1Min   5Min  TTY Process
    1         0         3         0  0.00%  0.00%  0.00%  0 Chunk
Manager
    2         0        494         0  0.00%  0.01%  0.00%  0 Load Meter
    3        24        494        48  0.00%  0.00%  0.00%  0 OSPF-1
Hello
    4       1560       248       6290  0.57%  0.07%  0.06%  0 Check
heaps

```


98	4	43	93	0.00%	0.00%	0.00%	0	Adj
Manager								
99	4	2	2000	0.00%	0.00%	0.00%	0	ATM OAM
Input								
100	0	2	0	0.00%	0.00%	0.00%	0	ATM OAM
TIMER								
101	0	10	0	0.00%	0.00%	0.00%	0	HTTP CORE
102	0	1	0	0.00%	0.00%	0.00%	0	RARP Input
103	0	1	0	0.00%	0.00%	0.00%	0	PAD InCall
104	0	2	0	0.00%	0.00%	0.00%	0	X.25
Background								
105	0	2	0	0.00%	0.00%	0.00%	0	PPP Bind
106	0	2	0	0.00%	0.00%	0.00%	0	PPP SSS
107	8	24697	0	0.08%	0.03%	0.02%	0	RBSCP
Background								
108	0	495	0	0.00%	0.00%	0.00%	0	L2F
management d								
109	0	1	0	0.00%	0.00%	0.00%	0	Inspect
Timer								
110	0	259	0	0.00%	0.00%	0.00%	0	OSPFv3-6
Hello								
111	0	9	0	0.00%	0.00%	0.00%	0	
Authentication P								
112	0	1	0	0.00%	0.00%	0.00%	0	Auth-proxy
AAA B								
113	0	1	0	0.00%	0.00%	0.00%	0	IPS Timer
114	0	2	0	0.00%	0.00%	0.00%	0	SDEE
Management								
115	0	1	0	0.00%	0.00%	0.00%	0	IPv6
Inspect Tim								
116	4	2	2000	0.00%	0.00%	0.00%	0	URL filter
proc								
117	0	3	0	0.00%	0.00%	0.00%	0	Crypto HW
Proc								
118	0	2	0	0.00%	0.00%	0.00%	0	ENABLE AAA
119	0	1	0	0.00%	0.00%	0.00%	0	EM
Background Pr								
120	0	1	0	0.00%	0.00%	0.00%	0	Key chain
liveke								
121	0	2	0	0.00%	0.00%	0.00%	0	LINE AAA
122	0	2	0	0.00%	0.00%	0.00%	0	LOCAL AAA
123	0	2	0	0.00%	0.00%	0.00%	0	TPLUS
124	0	2	0	0.00%	0.00%	0.00%	0	VSP_MGR
125	0	1	0	0.00%	0.00%	0.00%	0	encrypt
proc								
126	0	3	0	0.00%	0.00%	0.00%	0	Crypto WUI
127	0	2	0	0.00%	0.00%	0.00%	0	Crypto
Support								
128	0	1	0	0.00%	0.00%	0.00%	0	
RPMS_PROC_MAIN								
129	0	1	0	0.00%	0.00%	0.00%	0	crypto
engine pr								
130	32	4	8000	0.00%	0.00%	0.00%	0	Crypto CA


```
197          32          2522          12  0.00%  0.00%  0.00%  0 OSPF-1
Router
198          108          2205          48  0.00%  0.00%  0.00%  0 IP-EIGRP:
HELLO
R4#
```

```
R4#show interfaces
```

```
FastEthernet0/0 is up, line protocol is up
  Hardware is Gt96k FE, address is 0019.5578.1cb2 (bia 0019.5578.1cb2)
  Internet address is 10.1.4.5/30
  MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, 100BaseTX/FX
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:00, output 00:00:01, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
```

```
Queueing strategy: fifo
Output queue: 0/40 (size/max)
5 minute input rate 0 bits/sec, 1 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  5426 packets input, 566213 bytes
  Received 691 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
  0 watchdog
  0 input packets with dribble condition detected
  3457 packets output, 406086 bytes, 0 underruns
  0 output errors, 0 collisions, 4 interface resets
  0 unknown protocol drops
  0 babbles, 0 late collision, 0 deferred
  0 lost carrier, 0 no carrier
  0 output buffer failures, 0 output buffers swapped out
FastEthernet0/1 is up, line protocol is up
  Hardware is Gt96k FE, address is 0019.5578.1cb3 (bia 0019.5578.1cb3)
  Internet address is 10.1.4.9/30
  MTU 1500 bytes, BW 100000 Kbit/sec, DLY 100 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation ARPA, loopback not set
  Keepalive set (10 sec)
  Full-duplex, 100Mb/s, 100BaseTX/FX
  ARP type: ARPA, ARP Timeout 04:00:00
  Last input 00:00:02, output 00:00:00, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: fifo
  Output queue: 0/40 (size/max)
  5 minute input rate 0 bits/sec, 0 packets/sec
  5 minute output rate 0 bits/sec, 1 packets/sec
    882 packets input, 90041 bytes
    Received 659 broadcasts, 0 runts, 0 giants, 0 throttles
    0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored
    0 watchdog
    0 input packets with dribble condition detected
    3388 packets output, 264131 bytes, 0 underruns
    0 output errors, 0 collisions, 5 interface resets
    0 unknown protocol drops
    0 babbles, 0 late collision, 0 deferred
    0 lost carrier, 0 no carrier
    0 output buffer failures, 0 output buffers swapped out
Serial0/0/0 is down, line protocol is down
  Hardware is GT96K Serial
  MTU 1500 bytes, BW 128 Kbit/sec, DLY 20000 usec,
    reliability 255/255, txload 1/255, rxload 1/255
  Encapsulation HDLC, loopback not set
  Keepalive set (10 sec)
  Last input never, output never, output hang never
  Last clearing of "show interface" counters never
  Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
  Queueing strategy: weighted fair
  Output queue: 0/1000/64/0 (size/max total/threshold/drops)
    Conversations 0/0/32 (active/max active/max total)
```

Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 96 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 5 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=up DSR=up DTR=down RTS=down CTS=up

Serial0/0/1 is down, line protocol is down

Hardware is GT96K Serial
MTU 1500 bytes, BW 128 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation HDLC, loopback not set
Keepalive set (10 sec)
Last input never, output never, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/0/32 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 96 kilobits/sec
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
0 packets input, 0 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
0 packets output, 0 bytes, 0 underruns
0 output errors, 0 collisions, 5 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
0 carrier transitions
DCD=up DSR=up DTR=down RTS=down CTS=up

Serial0/1/0 is up, line protocol is up

Hardware is GT96K Serial
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY, loopback not set
Keepalive set (10 sec)
LMI enq sent 232, LMI stat recvd 233, LMI upd recvd 0, DTE LMI up
LMI enq recvd 0, LMI stat sent 0, LMI upd sent 0
LMI DLCI 1023 LMI type is CISCO frame relay DTE
FR SVC disabled, LAPF state down
Broadcast queue 0/64, broadcasts sent/dropped 404/0, interface
broadcasts 362
Last input 00:00:07, output 00:00:06, output hang never
Last clearing of "show interface" counters 00:41:29

Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 0
Queueing strategy: weighted fair
Output queue: 0/1000/64/0 (size/max total/threshold/drops)
Conversations 0/4/256 (active/max active/max total)
Reserved Conversations 0/0 (allocated/max allocated)
Available Bandwidth 1158 kilobits/sec
5 minute input rate 0 bits/sec, 1 packets/sec
5 minute output rate 0 bits/sec, 1 packets/sec
3491 packets input, 255121 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
3607 packets output, 261306 bytes, 0 underruns
0 output errors, 0 collisions, 5 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out
76 carrier transitions
DCD=up DSR=up DTR=up RTS=up CTS=up

Serial0/1/0.34 is up, line protocol is up

Hardware is GT96K Serial
Internet address is 10.1.1.10/30
MTU 1500 bytes, BW 1544 Kbit/sec, DLY 20000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation FRAME-RELAY
Last clearing of "show interface" counters never

Tunnel34 is up, line protocol is up

Hardware is Tunnel
MTU 1514 bytes, BW 9 Kbit/sec, DLY 500000 usec,
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation TUNNEL, loopback not set
Keepalive not set
Tunnel source 10.1.1.10 (Serial0/1/0.34), destination 10.1.1.9
Tunnel protocol/transport IPv6/IP
Tunnel TTL 255
Fast tunneling enabled

Tunnel transmit bandwidth 8000 (kbps)
Tunnel receive bandwidth 8000 (kbps)
Last input 00:33:49, output 00:00:00, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 4
Queueing strategy: fifo

Output queue: 0/0 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
56 packets input, 7516 bytes, 0 no buffer
Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
296 packets output, 29652 bytes, 0 underruns
0 output errors, 0 collisions, 0 interface resets
0 unknown protocol drops
0 output buffer failures, 0 output buffers swapped out

Tunnel46 is up, line protocol is up

Hardware is Tunnel
MTU 1514 bytes, BW 9 Kbit/sec, DLY 500000 usec,

```
reliability 255/255, txload 1/255, rxload 1/255
Encapsulation TUNNEL, loopback not set
Keepalive not set
Tunnel source 10.1.4.5, destination 10.1.4.6
Tunnel protocol/transport GRE/IP
  Key disabled, sequencing disabled
  Checksumming of packets disabled
Tunnel TTL 255
Fast tunneling enabled
Tunnel transmit bandwidth 8000 (kbps)
Tunnel receive bandwidth 8000 (kbps)
Last input 00:00:12, output 00:00:16, output hang never
Last clearing of "show interface" counters never
Input queue: 0/75/0/0 (size/max/drops/flushes); Total output drops: 24
Queueing strategy: fifo
Output queue: 0/0 (size/max)
5 minute input rate 0 bits/sec, 0 packets/sec
5 minute output rate 0 bits/sec, 0 packets/sec
  2135 packets input, 263820 bytes, 0 no buffer
  Received 0 broadcasts, 0 runts, 0 giants, 0 throttles
  0 input errors, 0 CRC, 0 frame, 0 overrun, 0 ignored, 0 abort
  2124 packets output, 262736 bytes, 0 underruns
  0 output errors, 0 collisions, 0 interface resets
  0 unknown protocol drops
  0 output buffer failures, 0 output buffers swapped out
```

R4#

```
R4#show cdp neighbors
```

```
Capability Codes: R - Router, T - Trans Bridge, B - Source Route Bridge  
S - Switch, H - Host, I - IGMP, r - Repeater
```

Device ID	Local Intrfce	Holdtme	Capability	Platform	Port
R3	Ser 0/1/0.34	136	R S I	2811	Ser
DSW1	Fas 0/0	151	R S I	WS-C3550-	Fas
DSW2	Fas 0/1	135	R S I	WS-C3550-	Fas

```
R4#
```

R4#show cdp neighbors detail

Device ID: R3
Entry address(es):
 IP address: 10.1.1.9
Platform: Cisco 2811, Capabilities: Router Switch IGMP
Interface: Serial0/1/0.34, Port ID (outgoing port): Serial0/2/0.34
Holdtime : 128 sec

Version :
Cisco IOS Software, 2800 Software (C2800NM-ADVIPSERVICESK9-M), Version
12.4(22)T2, RELEASE SOFTWARE (fc4)
Technical Support: <http://www.cisco.com/techsupport>
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Fri 19-Jun-09 15:34 by prod_rel_team

advertisement version: 2
VTP Management Domain: ''

Device ID: DSW1
Entry address(es):
 IP address: 10.1.4.6
Platform: Cisco WS-C3550-24, Capabilities: Router Switch IGMP
Interface: FastEthernet0/0, Port ID (outgoing port): FastEthernet0/1
Holdtime : 143 sec

Version :
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version
12.2(44)SE6, RELEASE SOFTWARE (fc1)
Copyright (c) 1986-2009 by Cisco Systems, Inc.
Compiled Mon 09-Mar-09 20:28 by gereddy

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFF010221FF0000000000000000DBDE36E00FF0000
VTP Management Domain: 'netlearning'
Duplex: full

Device ID: DSW2
Entry address(es):
 IP address: 10.1.4.10
Platform: Cisco WS-C3550-24-PWR, Capabilities: Router Switch IGMP
Interface: FastEthernet0/1, Port ID (outgoing port): FastEthernet0/1
Holdtime : 127 sec

Version :
Cisco IOS Software, C3550 Software (C3550-IPSERVICESK9-M), Version
12.2(44)SE6, RELEASE SOFTWARE (fc1)
Copyright (c) 1986-2009 by Cisco Systems, Inc.

Compiled Mon 09-Mar-09 20:28 by gereddy

advertisement version: 2
Protocol Hello: OUI=0x00000C, Protocol ID=0x0112; payload len=27,
value=00000000FFFFFFFFF010221FF0000000000000000BFD20BA0FF0000
VTP Management Domain: 'netlearning'
Duplex: full

R4#

R4#show frame-relay map
Serial0/1/0.34 (up): point-to-point dlci, dlci 403(0x193,0x6430),
broadcast
 status defined, active

R4#

```
R4#show ip interface
FastEthernet0/0 is up, line protocol is up
  Internet address is 10.1.4.5/30
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is not set
  Directed broadcast forwarding is disabled
  Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
  224.0.0.13
    224.0.0.10
  Outgoing access list is not set
  Inbound access list is not set
  Proxy ARP is enabled
  Local Proxy ARP is disabled
  Security level is default
  Split horizon is enabled
  ICMP redirects are always sent
  ICMP unreachable are always sent
  ICMP mask replies are never sent
  IP fast switching is enabled
  IP fast switching on the same interface is disabled
```

IP Flow switching is disabled
IP CEF switching is enabled
IP CEF Fast switching turbo vector
IP multicast fast switching is enabled
IP multicast distributed fast switching is disabled
IP route-cache flags are Fast, CEF
Router Discovery is disabled
IP output packet accounting is disabled
IP access violation accounting is disabled
TCP/IP header compression is disabled
RTP/IP header compression is disabled
Policy routing is disabled
Network address translation is disabled
BGP Policy Mapping is disabled
WCCP Redirect outbound is disabled
WCCP Redirect inbound is disabled
WCCP Redirect exclude is disabled
FastEthernet0/1 is up, line protocol is up
 Internet address is 10.1.4.9/30
 Broadcast address is 255.255.255.255
 Address determined by non-volatile memory
 MTU is 1500 bytes
 Helper address is not set
 Directed broadcast forwarding is disabled
 Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
224.0.0.13
 224.0.0.10
 Outgoing access list is not set
 Inbound access list is not set
 Proxy ARP is enabled
 Local Proxy ARP is disabled
 Security level is default
 Split horizon is enabled
 ICMP redirects are always sent
 ICMP unreachable are always sent
 ICMP mask replies are never sent
 IP fast switching is enabled
 IP fast switching on the same interface is disabled
 IP Flow switching is disabled
 IP CEF switching is enabled
 IP CEF Fast switching turbo vector
 IP multicast fast switching is enabled
 IP multicast distributed fast switching is disabled
 IP route-cache flags are Fast, CEF
 Router Discovery is disabled
 IP output packet accounting is disabled
 IP access violation accounting is disabled
 TCP/IP header compression is disabled
 RTP/IP header compression is disabled
 Policy routing is disabled
 Network address translation is disabled
 BGP Policy Mapping is disabled
 WCCP Redirect outbound is disabled
 WCCP Redirect inbound is disabled

```
WCCP Redirect exclude is disabled
Serial0/0/0 is down, line protocol is down
  Internet protocol processing disabled
Serial0/0/1 is down, line protocol is down
  Internet protocol processing disabled
Serial0/1/0 is up, line protocol is up
  Internet protocol processing disabled
Serial0/1/0.34 is up, line protocol is up
  Internet address is 10.1.1.10/30
  Broadcast address is 255.255.255.255
  Address determined by non-volatile memory
  MTU is 1500 bytes
  Helper address is not set
  Directed broadcast forwarding is disabled
  Multicast reserved groups joined: 224.0.0.1 224.0.0.2 224.0.0.22
  224.0.0.13
    224.0.0.5
  Outgoing access list is not set
  Inbound access list is not set
  Proxy ARP is enabled
  Local Proxy ARP is disabled
  Security level is default
  Split horizon is enabled
  ICMP redirects are always sent
  ICMP unreachable are always sent
  ICMP mask replies are never sent
  IP fast switching is enabled
  IP fast switching on the same interface is enabled
  IP Flow switching is disabled
  IP CEF switching is enabled
  IP CEF Fast switching turbo vector
  IP multicast fast switching is enabled
  IP multicast distributed fast switching is disabled
  IP route-cache flags are Fast, CEF
  Router Discovery is disabled
  IP output packet accounting is disabled
  IP access violation accounting is disabled
  TCP/IP header compression is disabled
  RTP/IP header compression is disabled
  Policy routing is disabled
  Network address translation is disabled
  BGP Policy Mapping is disabled
  WCCP Redirect outbound is disabled
  WCCP Redirect inbound is disabled
  WCCP Redirect exclude is disabled
Tunnel34 is up, line protocol is up
  Internet protocol processing disabled
Tunnel46 is up, line protocol is up
  Internet protocol processing disabled
R4#
```

R4#show ip cef

Prefix	Next Hop	Interface
0.0.0.0/0	10.1.1.9	Serial0/1/0.34
0.0.0.0/8	drop	
0.0.0.0/32	receive	
10.1.1.8/30	attached	Serial0/1/0.34
10.1.1.8/32	receive	
10.1.1.10/32	receive	
10.1.1.11/32	receive	
10.1.4.4/30	attached	FastEthernet0/0
10.1.4.4/32	receive	
10.1.4.5/32	receive	
10.1.4.6/32	10.1.4.6	FastEthernet0/0
10.1.4.7/32	receive	
10.1.4.8/30	attached	FastEthernet0/1
10.1.4.8/32	receive	
10.1.4.9/32	receive	
10.1.4.10/32	10.1.4.10	FastEthernet0/1
10.1.4.11/32	receive	
10.2.1.0/24	10.1.4.10	FastEthernet0/1
	10.1.4.6	FastEthernet0/0
10.2.2.0/24	10.1.4.10	FastEthernet0/1

```
10.2.4.12/30      10.1.4.6      FastEthernet0/0
                  10.1.4.10     FastEthernet0/1
                  10.1.4.6      FastEthernet0/0
127.0.0.0/8      drop
224.0.0.0/4      0.0.0.0
224.0.0.0/24     receive
240.0.0.0/4      drop
255.255.255.255/32 receive
R4#
```

```
R4#show tcp statistics
Rcvd: 0 Total, 0 no port
      0 checksum error, 0 bad offset, 0 too short
      0 packets (0 bytes) in sequence
      0 dup packets (0 bytes)
      0 partially dup packets (0 bytes)
      0 out-of-order packets (0 bytes)
      0 packets (0 bytes) with data after window
      0 packets after close
```

```
0 window probe packets, 0 window update packets
0 dup ack packets, 0 ack packets with unsend data
0 ack packets (0 bytes)
Sent: 0 Total, 0 urgent packets
0 control packets (including 0 retransmitted)
0 data packets (0 bytes)
0 data packets (0 bytes) retransmitted
0 data packets (0 bytes) fastretransmitted
0 ack only packets (0 delayed)
0 window probe packets, 0 window update packets
0 Connections initiated, 0 connections accepted, 0 connections
established
0 Connections closed (including 0 dropped, 0 embryonic dropped)
0 Total rxmt timeout, 0 connections dropped in rxmt timeout
0 Keepalive timeout, 0 keepalive probe, 0 Connections dropped in
keepalive
R4#
```

```
R4#show ip protocols
```

```
Routing Protocol is "eigrp 10"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  Default networks flagged in outgoing updates
  Default networks accepted from incoming updates
  EIGRP metric weight K1=1, K2=1, K3=1, K4=1, K5=1
  EIGRP maximum hopcount 100
  EIGRP maximum metric variance 1
  Redistributing: eigrp 10, ospf 1
  EIGRP NSF-aware route hold timer is 240s
  Automatic network summarization is not in effect
  Maximum path: 4
  Routing for Networks:
    10.1.4.5/32
    10.1.4.9/32
  Routing Information Sources:
    Gateway          Distance      Last Update
    10.1.4.10         90           00:39:53
    10.1.4.6          90           00:39:53
  Distance: internal 90 external 170
```

```
Routing Protocol is "ospf 1"
  Outgoing update filter list for all interfaces is not set
  Incoming update filter list for all interfaces is not set
  Router ID 4.4.4.4
  It is an autonomous system boundary router
  Redistributing External Routes from,
    eigrp 10, includes subnets in redistribution
  Number of areas in this router is 1. 0 normal 0 stub 1 nssa
  Maximum path: 4
  Routing for Networks:
    10.1.1.10 0.0.0.0 area 34
  Reference bandwidth unit is 100 mbps
  Routing Information Sources:
    Gateway          Distance      Last Update
    3.3.3.3           110          00:36:21
  Distance: (default is 110)
```

R4#

```
R4#show access-lists
Standard IP access list DENY_10
  10 deny 10.0.0.0, wildcard bits 0.255.255.255
  20 permit any
Standard IP access list DENY_ALL
  10 deny any
Standard IP access list PERMIT_10
  10 permit 10.0.0.0, wildcard bits 0.255.255.255
Standard IP access list PERMIT_ALL
  10 permit any
R4#
```

```
R4#show ip route eigrp
  10.0.0.0/8 is variably subnetted, 6 subnets, 2 masks
D    10.2.4.12/30 [90/120] via 10.1.4.10, 00:40:46, FastEthernet0/1
      [90/120] via 10.1.4.6, 00:40:46, FastEthernet0/0
D    10.2.1.0/24 [90/111] via 10.1.4.10, 00:40:12, FastEthernet0/1
      [90/111] via 10.1.4.6, 00:40:12, FastEthernet0/0
D    10.2.2.0/24 [90/111] via 10.1.4.10, 00:40:14, FastEthernet0/1
      [90/111] via 10.1.4.6, 00:40:14, FastEthernet0/0
R4#
```

R4#show ip eigrp neighbors

IP-EIGRP neighbors for process 10

H	Address	Interface	Hold Uptime	SRTT	RTO	Q
Seq			(sec)	(ms)		Cnt
Num						
1	10.1.4.10	Fa0/1	12 00:41:05	1	200	0
88						
0	10.1.4.6	Fa0/0	10 00:41:39	1	200	0
96						

R4#

R4#show ip eigrp interfaces

IP-EIGRP interfaces for process 10

Pending Interface Routes	Peers	Xmit Queue	Mean	Pacing Time	Multicast
		Un/Reliable	SRTT	Un/Reliable	Flow Timer
Fa0/0	1	0/0	1	0/1	50
0					
Fa0/1	1	0/0	1	0/1	50
0					

R4#

R4#show ip ospf neighbor

Neighbor ID	Pri	State	Dead Time	Address
Interface				
3.3.3.3	0	FULL/ -	00:00:39	10.1.1.9
Serial0/1/0.34				

R4#

```
R4#show ip ospf interface
Serial0/1/0.34 is up, line protocol is up
  Internet Address 10.1.1.10/30, Area 34
  Process ID 1, Router ID 4.4.4.4, Network Type POINT_TO_POINT, Cost: 64
  Transmit Delay is 1 sec, State POINT_TO_POINT
  Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
    oob-resync timeout 40
    Hello due in 00:00:01
  Supports Link-local Signaling (LLS)
  Index 1/1, flood queue length 0
  Next 0x0(0)/0x0(0)
  Last flood scan length is 5, maximum is 5
  Last flood scan time is 0 msec, maximum is 0 msec
  Neighbor Count is 1, Adjacent neighbor count is 1
    Adjacent with neighbor 3.3.3.3
  Suppress hello for 0 neighbor(s)
R4#
```

R4#show ip ospf database

OSPF Router with ID (4.4.4.4) (Process ID 1)

Router Link States (Area 34)

Link ID	ADV Router	Age	Seq#	Checksum	Link
count					
3.3.3.3	3.3.3.3	287	0x8000000E	0x00CE71	2
4.4.4.4	4.4.4.4	341	0x80000010	0x0067D2	2

Summary Net Link States (Area 34)

Link ID	ADV Router	Age	Seq#	Checksum
0.0.0.0	3.3.3.3	287	0x80000002	0x00DC4C

Type-7 AS External Link States (Area 34)

Link ID	ADV Router	Age	Seq#	Checksum	Tag
10.1.4.4	4.4.4.4	341	0x80000005	0x00F16A	0
10.1.4.8	4.4.4.4	341	0x80000005	0x00C98E	0

```
10.2.1.0      4.4.4.4      341      0x80000003 0x00451C 0
10.2.2.0      4.4.4.4      341      0x80000003 0x003A26 0
10.2.4.12     4.4.4.4      341      0x80000003 0x0099BB 0
R4#
```

```
R4#show ip route ospf
O*IA 0.0.0.0/0 [110/65] via 10.1.1.9, 00:37:33, Serial0/1/0.34
R4#
```

```
R4#show ip dhcp binding
```

```
Bindings from all pools not associated with VRF:
```

IP address	Client-ID/ Hardware address/ User name	Lease expiration	Type
10.2.1.4	0100.1c23.8edb.bc	Jun 08 2010 07:29 PM	

```
Automatic  
R4#
```

```
R4#show ip dhcp conflict
IP address      Detection method  Detection time    VRF
R4#
```

```
R4#show ip dhcp pool
```

```
Pool VLAN10 :
```

```
Utilization mark (high/low) : 100 / 0
```

```
Subnet size (first/next) : 0 / 0
```

```
Total addresses : 254
```

```
Leased addresses : 1
```

```
Pending event : none
```

```
1 subnet is currently in the pool :
```

Current index	IP address range	Leased
addresses		
10.2.1.5	10.2.1.1 - 10.2.1.254	1

```
R4#
```

```
R4#show ipv6 interface brief
```

```
FastEthernet0/0 [up/up]
```

```
FastEthernet0/1          [up/up]
Serial0/0/0              [down/down]
Serial0/0/1              [down/down]
Serial0/1/0              [up/up]
Serial0/1/0.34           [up/up]
Tunnel134                [up/up]
    FE80::A01:10A
    2026::34:2
Tunnel146                [up/up]
    FE80::219:55FF:FE78:1CB2
    2026::2:1
R4#
```

```
R4#ping ipv6 2026::12:1
```

```
Type escape sequence to abort.
```

Sending 5, 100-byte ICMP Echos to 2026::12:1, timeout is 2 seconds:

.....

Success rate is 0 percent (0/5)

R4#

R4#ping ipv6 2026::12:2

Type escape sequence to abort.

Sending 5, 100-byte ICMP Echos to 2026::12:2, timeout is 2 seconds:

!!!!

Success rate is 100 percent (5/5), round-trip min/avg/max = 140/140/144
ms

R4#

```
R4#ping ipv6 2026::1:1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::1:1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 140/142/144  
ms
```

```
R4#
```

```
R4#ping ipv6 2026::1:2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::1:2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 76/77/80 ms
```

```
R4#
```

```
R4#ping ipv6 2026::34:1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::34:1, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 76/77/80 ms
```

```
R4#
```

```
R4#ping ipv6 2026::34:2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::34:2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 0/0/0 ms
```

```
R4#
```

```
R4#ping ipv6 2026::2:1
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::2:1, timeout is 2 seconds:
```

```
!!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 0/0/0 ms
```

```
R4#
```

```
R4#ping ipv6 2026::2:2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::2:2, timeout is 2 seconds:  
!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 0/1/4 ms  
R4#
```

```
R4#ping ipv6 2026::3:1
```

```
Type escape sequence to abort.  
Sending 5, 100-byte ICMP Echos to 2026::3:1, timeout is 2 seconds:  
!!!!  
Success rate is 100 percent (5/5), round-trip min/avg/max = 0/1/4 ms  
R4#
```

```
R4#ping ipv6 2026::3:2
```

```
Type escape sequence to abort.
```

```
Sending 5, 100-byte ICMP Echos to 2026::3:2, timeout is 2 seconds:
```

```
!!!!
```

```
Success rate is 100 percent (5/5), round-trip min/avg/max = 0/2/4 ms
```

```
R4#
```

```
R4#show ipv6 route
IPv6 Routing Table - 9 entries
Codes: C - Connected, L - Local, S - Static, R - RIP, B - BGP
        U - Per-user Static route
        I1 - ISIS L1, I2 - ISIS L2, IA - ISIS interarea, IS - ISIS summary
        O - OSPF intra, OI - OSPF inter, OE1 - OSPF ext 1, OE2 - OSPF ext
          2
            ON1 - OSPF NSSA ext 1, ON2 - OSPF NSSA ext 2
OI 2026::1:0/122 [110/11175]
    via FE80::A01:109, Tunnel34
C  2026::2:0/122 [0/0]
    via ::, Tunnel46
L  2026::2:1/128 [0/0]
    via ::, Tunnel46
R  2026::3:0/122 [120/2]
    via FE80::20D:BDFE:FEE3:6E00, Tunnel46
OI 2026::12:0/122 [110/11239]
    via FE80::A01:109, Tunnel34
C  2026::34:0/122 [0/0]
    via ::, Tunnel34
L  2026::34:2/128 [0/0]
    via ::, Tunnel34
L  FE80::/10 [0/0]
    via ::, Null0
L  FF00::/8 [0/0]
    via ::, Null0
R4#
```

```
R4#show ipv6 ospf
Routing Process "ospfv3 6" with ID 4.4.4.4
It is an autonomous system boundary router
Redistributing External Routes from,
    connected
    rip
SPF schedule delay 5 secs, Hold time between two SPFs 10 secs
Minimum LSA interval 5 secs. Minimum LSA arrival 1 secs
LSA group pacing timer 240 secs
Interface flood pacing timer 33 msec
Retransmission pacing timer 66 msec
Number of external LSA 2. Checksum Sum 0x010531
Number of areas in this router is 1. 1 normal 0 stub 0 nssa
Reference bandwidth unit is 100 mbps
    Area 34
```

```
Number of interfaces in this area is 1
SPF algorithm executed 8 times
Number of LSA 8. Checksum Sum 0x03EAD5
Number of DCbitless LSA 0
Number of indication LSA 0
Number of DoNotAge LSA 0
Flood list length 0
```

R4#

```
R4#show ipv6 ospf interface
Tunnel34 is up, line protocol is up
  Link Local Address FE80::A01:10A, Interface ID 13
  Area 34, Process ID 6, Instance ID 0, Router ID 4.4.4.4
  Network Type POINT_TO_POINT, Cost: 11111
  Transmit Delay is 1 sec, State POINT_TO_POINT,
```

```
Timer intervals configured, Hello 10, Dead 40, Wait 40, Retransmit 5
  Hello due in 00:00:06
Index 1/1/1, flood queue length 0
Next 0x0(0)/0x0(0)/0x0(0)
Last flood scan length is 1, maximum is 2
Last flood scan time is 0 msec, maximum is 0 msec
Neighbor Count is 1, Adjacent neighbor count is 1
  Adjacent with neighbor 10.1.1.6
Suppress hello for 0 neighbor(s)
R4#
```

```
R4#show ipv6 ospf neighbor
```

Neighbor ID Interface	Pri	State	Dead Time	Interface ID
--------------------------	-----	-------	-----------	--------------

```
10.1.1.6          1    FULL/  -          00:00:31    18
Tunnel34
R4#
```

```
R4#show ipv6 rip RIPNG
RIP process "RIPNG", port 521, multicast-group FF02::9, pid 181
  Administrative distance is 120. Maximum paths is 16
  Updates every 30 seconds, expire after 180
  Holddown lasts 0 seconds, garbage collect after 120
  Split horizon is on; poison reverse is off
  Default routes are not generated
  Periodic updates 321, trigger updates 11
Interfaces:
  Tunnel46
Redistribution:
  Redistributing protocol connected with metric 5
```

```
    Redistributing protocol ospf 6 with metric 5
R4#
```

```
R4#
```